
Unified Form Language (UFL) Documentation

Release 2017.1.0

FEniCS Project

May 10, 2017

Contents

1 Documentation	3
------------------------	----------

Python Module Index	191
----------------------------	------------

The Unified Form Language (UFL) is a domain specific language for declaration of finite element discretizations of variational forms. More precisely, it defines a flexible interface for choosing finite element spaces and defining expressions for weak forms in a notation close to mathematical notation.

UFL is part of the FEniCS Project.

For more information, visit <http://www.fenicsproject.org>

CHAPTER 1

Documentation

Installation

UFL is normally installed as part of an installation of FEniCS. If you are using UFL as part of the FEniCS software suite, it is recommended that you follow the [installation instructions for FEniCS](#).

To install UFL itself, read on below for a list of requirements and installation instructions.

Requirements and dependencies

UFL requires Python version 2.7 or later and depends on the following Python packages:

- NumPy
- six

These packages will be automatically installed as part of the installation of UFL, if not already present on your system.

Installation instructions

To install UFL, download the source code from the [UFL Bitbucket repository](#), and run the following command:

```
pip install .
```

To install to a specific location, add the `--prefix` flag to the installation command:

```
pip install --prefix=<some directory> .
```

User manual

Introduction

The Unified Form Language (UFL) is a domain specific language for defining discrete variational forms and functionals in a notation close to pen-and-paper formulation.

UFL is part of the FEniCS Project and is usually used in combination with other components from this project to compute solutions to partial differential equations. The form compiler FFC uses UFL as its end-user interface, producing implementations of the UFC interface as output. See DOLFIN for more details about using UFL in an integrated problem solving environment.

This manual is intended for different audiences. If you are an end-user and all you want to do is to solve your PDEs with the FEniCS framework, you should read [Form language](#), and also [Example forms](#). These two sections explain how to use all operators available in the language and present a number of examples to illustrate the use of the form language in applications.

The remaining chapters contain more technical details intended for developers who need to understand what is happening behind the scenes and modify or extend UFL in the future.

[Internal representation details](#) describes the implementation of the language, in particular how expressions are represented internally by UFL. This can also be useful knowledge to understand error messages and debug errors in your form files.

[Algorithms](#) explains the many algorithms available to work with UFL expressions, mostly intended to aid developers of form compilers. The algorithms include helper functions for easy and efficient iteration over expression trees, formatting tools to present expressions as text or images of different kinds, utilities to analyse properties of expressions or checking their validity, automatic differentiation algorithms, as well as algorithms to work with the computational graphs of expressions.

Form language

UFL consists of a set of operators and atomic expressions that can be used to express variational forms and functionals. Below we will define all these operators and atomic expressions in detail.

UFL is built on top of the Python language, and any Python code is valid in the definition of a form. In particular, comments (lines starting with `#`) and functions (keyword `def`, see [user-defined](#) below) are useful in the definition of a form. However, it is usually a good idea to avoid using advanced Python features in the form definition, to stay close to the mathematical notation.

The entire form language can be imported in Python with the line

```
from ufl import *
```

which is assumed in all examples below and can be omitted in `.ufl` files. This can be useful for experimenting with the language in an interactive Python interpreter.

Forms and integrals

UFL is designed to express forms in the following generalized format:

$$a(\mathbf{v}; \mathbf{w}) = \sum_{k=1}^{n_c} \int_{\Omega_k} I_k^c(\mathbf{v}; \mathbf{w}) dx + \sum_{k=1}^{n_e} \int_{\partial\Omega_k} I_k^e(\mathbf{v}; \mathbf{w}) ds + \sum_{k=1}^{n_i} \int_{\Gamma_k} I_k^i(\mathbf{v}; \mathbf{w}) dS.$$

Here the form a depends on the *form arguments* $\mathbf{v} = (v_1, \dots, v_r)$ and the *form coefficients* $\mathbf{w} = (w_1, \dots, w_n)$, and its expression is a sum of integrals. Each term of a valid form expression must be a scalar-valued expression integrated exactly once. How to define form arguments and integrand expressions is detailed in the rest of this chapter.

Integrals are expressed through multiplication with a measure, representing an integral over either

- the interior of the domain Ω (`dx`, cell integral);
- the boundary $\partial\Omega$ of Ω (`ds`, exterior facet integral);
- the set of interior facets Γ (`dS`, interior facet integral).

(Note that newer versions of UFL support several other integral types currently not documented here). As a basic example, assume v is a scalar-valued expression and consider the integral of v over the interior of Ω . This may be expressed as:

```
a = v*dx
```

and the integral of v over $\partial\Omega$ is written as:

```
a = v*ds.
```

Alternatively, measures can be redefined to represent numbered subsets of a domain, such that a form evaluates to different expressions on different parts of the domain. If c , e_0 and e_1 are scalar-valued expressions, then:

```
a = c*dx + e0*ds(0) + e1*ds(1)
```

represents

$$a = \int_{\Omega} c dx + \int_{\partial\Omega_0} e_0 ds + \int_{\partial\Omega_1} e_1 ds,$$

where

$$\partial\Omega_0 \subset \partial\Omega, \quad \partial\Omega_1 \subset \partial\Omega.$$

Note: The domain Ω , its subdomains and boundaries are not known to UFL. These are defined in a problem solving environment such as DOLFIN, which uses UFL to specify forms.

Finite element spaces

Before defining forms which can be integrated, it is necessary to describe the finite element spaces over which the integration takes place. UFL can represent very flexible general hierarchies of mixed finite elements, and has predefined names for most common element families. A finite element space is defined by an element domain, shape functions and nodal variables. In UFL, the element domain is called a `Cell`.

Cells

A polygonal cell is defined by a shape name and a geometric dimension, written as:

```
cell = Cell(shape, gdim)
```

Valid shapes are “interval”, “triangle”, “tetrahedron”, “quadrilateral”, and “hexahedron”. Some examples:

```
# Regular triangle cell
cell = Cell("triangle")

# Triangle cell embedded in 3D space
cell = Cell("triangle", 3)
```

Objects for regular cells of all basic shapes are predefined:

```
# Predefined linear cells
cell = interval
cell = triangle
cell = tetrahedron
cell = quadrilateral
cell = hexahedron
```

In the rest of this document, a variable name `cell` will be used where any cell is a valid argument, to make the examples dimension-independent wherever possible. Using a variable `cell` to hold the cell type used in a form is highly recommended, since this makes most form definitions dimension-independent.

Element families

UFL predefines a set of names of known element families. When defining a finite element below, the argument `family` is a string and its possible values include

- "Lagrange" or "CG", representing standard scalar Lagrange finite elements (continuous piecewise polynomial functions);
- "Discontinuous Lagrange" or "DG", representing scalar discontinuous Lagrange finite elements (discontinuous piecewise polynomial functions);
- "Crouzeix–Raviart" or "CR", representing scalar Crouzeix–Raviart elements;
- "Brezzi–Douglas–Marini" or "BDM", representing vector-valued Brezzi–Douglas–Marini H(div) elements;
- "Brezzi–Douglas–Fortin–Marini" or "BDFM", representing vector-valued Brezzi–Douglas–Fortin–Marini H(div) elements;
- "Raviart–Thomas" or "RT", representing vector-valued Raviart–Thomas H(div) elements.
- "Nedelec 1st kind H(div)" or "N1div", representing vector-valued Nedelec H(div) elements (of the first kind).
- "Nedelec 2st kind H(div)" or "N2div", representing vector-valued Nedelec H(div) elements (of the second kind).
- "Nedelec 1st kind H(curl)" or "N1curl", representing vector-valued Nedelec H(curl) elements (of the first kind).
- "Nedelec 2st kind H(curl)" or "N2curl", representing vector-valued Nedelec H(curl) elements (of the second kind).
- "Bubble", representing bubble elements, useful for example to build the mini elements.
- "Quadrature" or "Q", representing artificial “finite elements” with degrees of freedom being function evaluations at quadrature points;
- "Boundary Quadrature" or "BQ", representing artificial “finite elements” with degrees of freedom being function evaluations at quadrature points on the boundary.

Note that new versions of UFL also support notation from the Periodic Table of Finite Elements, currently not documented here.

Basic elements

A `FiniteElement`, sometimes called a basic element, represents a finite element from some family on a given cell with a certain polynomial degree. Valid families and cells are explained above. The notation is

```
element = FiniteElement(family, cell, degree)
```

Some examples:

```
element = FiniteElement("Lagrange", interval, 3)
element = FiniteElement("DG", tetrahedron, 0)
element = FiniteElement("BDM", triangle, 1)
```

Vector elements

A `VectorElement` represents a combination of basic elements such that each component of a vector is represented by the basic element. The size is usually omitted, the default size equals the geometry dimension. The notation is

```
element = VectorElement(family, cell, degree[, size])
```

Some examples:

```
# A quadratic "P2" vector element on a triangle
element = VectorElement("CG", triangle, 2)
# A linear 3D vector element on a 1D interval
element = VectorElement("CG", interval, 1, size=3)
# A six-dimensional piecewise constant element on a tetrahedron
element = VectorElement("DG", tetrahedron, 0, size=6)
```

Tensor elements

A `TensorElement` represents a combination of basic elements such that each component of a tensor is represented by the basic element. The shape is usually omitted, the default shape is :math: (d, d) where :math: d is the geometric dimension. The notation is

```
element = TensorElement(family, cell, degree[, shape, symmetry])
```

Any shape tuple consisting of positive integers is valid, and the optional symmetry can either be set to `True` which means standard matrix symmetry (like $A_{ij} = A_{ji}$), or a dict like { (0,1):(1,0), (0,2):(2,0) } where the dict keys are index tuples that are represented by the corresponding dict value.

Examples:

```
element = TensorElement("CG", cell, 2)
element = TensorElement("DG", cell, 0, shape=(6,6))
element = TensorElement("DG", cell, 0, symmetry=True)
element = TensorElement("DG", cell, 0, symmetry={(0,0): (1,1)})
```

Mixed elements

A `MixedElement` represents an arbitrary combination of other elements. `VectorElement` and `TensorElement` are special cases of a `MixedElement` where all sub-elements are equal.

General notation for an arbitrary number of subelements:

```
element = MixedElement(element1, element2[, element3, ...])
```

Shorthand notation for two subelements:

```
element = element1 * element2
```

Note: The `*` operator is left-associative, such that:

```
element = element1 * element2 * element3
```

represents $(e_1 * e_2) * e_3$, i.e. this is a mixed element with two sub-elements $(e_1 * e_2)$ and e_3 .

See [Form arguments](#) for details on how defining functions on mixed spaces can differ from defining functions on other finite element spaces.

Examples:

```
# Taylor-Hood element
V = VectorElement("Lagrange", cell, 2)
P = FiniteElement("Lagrange", cell, 1)
TH = V * P

# A tensor-vector-scalar element
T = TensorElement("Lagrange", cell, 2, symmetry=True)
V = VectorElement("Lagrange", cell, 1)
P = FiniteElement("DG", cell, 0)
ME = MixedElement(T, V, P)
```

EnrichedElement

The data type `EnrichedElement` represents the vector sum of two (or more) finite elements.

Example: The Mini element can be constructed as

```
P1 = VectorElement("Lagrange", "triangle", 1)
B = VectorElement("Bubble", "triangle", 3)
Q = FiniteElement("Lagrange", "triangle", 1)

Mini = (P1 + B) * Q
```

Form arguments

Form arguments are divided in two groups, arguments and coefficients. An `Argument` represents an arbitrary basis function in a given discrete finite element space, while a `Coefficient` represents a function in a discrete finite element space that will be provided by the user at a later stage. The number of `Arguments` that occur in a `Form` equals the “arity” of the form.

Basis functions

The data type `Argument` represents a basis function on a given finite element. An `Argument` must be created for a previously declared finite element (simple or mixed):

```
v = Argument(element)
```

Note that more than one `Argument` can be declared for the same `FiniteElement`. Basis functions are associated with the arguments of a multilinear form in the order of declaration.

For a `MixedElement`, the function `Arguments` can be used to construct tuples of `Arguments`, as illustrated here for a mixed Taylor–Hood element:

```
v, q = Arguments(TH)
u, p = Arguments(TH)
```

For a `Argument` on a `MixedElement` (or `VectorElement` or `TensorElement`), the function `split` can be used to extract basis function values on subspaces, as illustrated here for a mixed Taylor–Hood element:

```
vq = Argument(TH)
v, q = split(up)
```

This is equivalent to the previous use of `Arguments`:

```
v, q = Arguments(TH)
```

For convenience, `TestFunction` and `TrialFunction` are special instances of `Argument` with the property that a `TestFunction` will always be the first argument in a form and `TrialFunction` will always be the second argument in a form (order of declaration does not matter). Their usage is otherwise the same as for `Argument`:

```
v = TestFunction(element)
u = TrialFunction(element)
v, q = TestFunctions(TH)
u, p = TrialFunctions(TH)
```

Meshes and function spaces

Note that newer versions of UFL introduce the concept of a `Mesh` and a `FunctionSpace`. These are currently not documented here.

Coefficient functions

The data type `Coefficient` represents a function belonging to a given finite element space, that is, a linear combination of basis functions of the finite element space. A `Coefficient` must be declared for a previously declared `FiniteElement`:

```
f = Coefficient(element)
```

Note that the order in which `Coefficients` are declared is important, directly reflected in the ordering they have among the arguments to each `Form` they are part of.

`Coefficient` is used to represent user-defined functions, including, e.g., source terms, body forces, variable coefficients and stabilization terms. UFL treats each `Coefficient` as a linear combination of unknown basis functions

with unknown coefficients, that is, UFL knows nothing about the concrete basis functions of the element and nothing about the value of the function.

Note: Note that more than one function can be declared for the same `FiniteElement`. The following example declares two `Arguments` and two `Coefficients` for the same `FiniteElement`:

```
v = Argument(element)
u = Argument(element)
f = Coefficient(element)
g = Coefficient(element)
```

For a `Coefficient` on a `MixedElement` (or `VectorElement` or `TensorElement`), the function `split` can be used to extract function values on subspaces, as illustrated here for a mixed Taylor–Hood element:

```
up = Coefficient(TH)
u, p = split(up)
```

There is a shorthand for this, whose use is similar to `Arguments`, called `Coefficients`:

```
u, p = Coefficients(TH)
```

Spatially constant (or discontinuous piecewise constant) functions can conveniently be represented by `Constant`, `VectorConstant`, and `TensorConstant`:

```
c0 = Constant(cell)
v0 = VectorConstant(cell)
t0 = TensorConstant(cell)
```

These three lines are equivalent with first defining DG0 elements and then defining a `Coefficient` on each, illustrated here:

```
DG0 = FiniteElement("Discontinuous Lagrange", cell, 0)
DG0v = VectorElement("Discontinuous Lagrange", cell, 0)
DG0t = TensorElement("Discontinuous Lagrange", cell, 0)

c1 = Coefficient(DG0)
v1 = Coefficient(DG0v)
t1 = Coefficient(DG0t)
```

Basic Datatypes

UFL expressions can depend on some other quantities in addition to the functions and basis functions described above.

Literals and geometric quantities

Some atomic quantities are derived from the cell. For example, the (global) spatial coordinates are available as a vector valued expression `SpatialCoordinate(cell)`:

```
# Linear form for a load vector with a sin(y) coefficient
v = TestFunction(element)
x = SpatialCoordinate(cell)
L = sin(x[1])*v*dx
```

Another quantity is the (outwards pointing) facet normal `FacetNormal(cell)`. The normal vector is only defined on the boundary, so it can't be used in a cell integral.

Example functional `M`, an integral of the normal component of a function `g` over the boundary:

```
n = FacetNormal(cell)
g = Coefficient(VectorElement("CG", cell, 1))
M = dot(n, g)*ds
```

Python scalars (`int`, `float`) can be used anywhere a scalar expression is allowed. Another literal constant type is `Identity` which represents an $n \times n$ unit matrix of given size n , as in this example:

```
# Geometric dimension
d = cell.geometric_dimension()

# d x d identity matrix
I = Identity(d)

# Kronecker delta
delta_ij = I[i, j]
```

Indexing and tensor components

UFL supports index notation, which is often a convenient way to express forms. The basic principle of index notation is that summation is implicit over indices repeated twice in each term of an expression. The following examples illustrate the index notation, assuming that each of the variables `i` and `j` has been declared as a free `Index`:

- $\mathbf{v}[i] * \mathbf{w}[i]: \sum_{i=0}^{n-1} v_i w_i = \mathbf{v} \cdot \mathbf{w}$
- $\mathbf{Dx}(\mathbf{v}, i) * \mathbf{Dx}(\mathbf{w}, i): \sum_{i=0}^{d-1} \frac{\partial v}{\partial x_i} \frac{\partial w}{\partial x_i} = \nabla \mathbf{v} \cdot \nabla \mathbf{w}$
- $\mathbf{Dx}(\mathbf{v}[i], i): \sum_{i=0}^{d-1} \frac{\partial v_i}{\partial x_i} = \nabla \cdot \mathbf{v}$
- $\mathbf{Dx}(\mathbf{v}[i], j) * \mathbf{Dx}(\mathbf{w}[i], j): \sum_{i=0}^{n-1} \sum_{j=0}^{d-1} \frac{\partial v_i}{\partial x_j} \frac{\partial w_i}{\partial x_j} = \nabla \mathbf{v} : \nabla \mathbf{w}$

Here we will try to very briefly summarize the basic concepts of tensor algebra and index notation, just enough to express the operators in UFL.

Assuming an Euclidean space in d dimensions with $1 \leq d \leq 3$, and a set of orthonormal basis vectors \mathbf{i}_i for $i \in 0, \dots, d - 1$, we can define the dot product of any two basis functions as

$$\mathbf{i}_i \cdot \mathbf{i}_j = \delta_{ij},$$

where δ_{ij} is the Kronecker delta

$$\delta_{ij} \equiv \begin{cases} 1, & i = j, \\ 0, & \text{otherwise.} \end{cases}$$

A rank 1 tensor (vector) quantity \mathbf{v} can be represented in terms of unit vectors and its scalar components in that basis. In tensor algebra it is common to assume implicit summation over indices repeated twice in a product:

$$\mathbf{v} = v_k \mathbf{i}_k \equiv \sum_k v_k \mathbf{i}_k.$$

Similarly, a rank two tensor (matrix) quantity \mathbf{A} can be represented in terms of unit matrices, that is outer products of unit vectors:

$$\mathbf{A} = A_{ij} \mathbf{i}_i \mathbf{i}_j \equiv \sum_i \sum_j A_{ij} \mathbf{i}_i \mathbf{i}_j.$$

This generalizes to tensors of arbitrary rank:

$$\begin{aligned}\mathcal{C} &= C_{\iota} \mathbf{i}_{\iota_0} \otimes \cdots \otimes \mathbf{i}_{\iota_{r-1}} \\ &\equiv \sum_{\iota_0} \cdots \sum_{\iota_{r-1}} C_{\iota} \mathbf{i}_{\iota_0} \otimes \cdots \otimes \mathbf{i}_{\iota_{r-1}},\end{aligned}$$

where \mathcal{C} is a rank r tensor and ι is a multi-index of length r .

When writing equations on paper, a mathematician can easily switch between the \mathbf{v} and v_i representations without stating it explicitly. This is possible because of flexible notation and conventions. In a programming language, we can't use the boldface notation which associates \mathbf{v} and v by convention, and we can't always interpret such conventions unambiguously. Therefore, UFL requires that an expression is explicitly mapped from its tensor representation (\mathbf{v} , \mathbf{A}) to its component representation (v_i , A_{ij}) and back. This is done using `Index` objects, the indexing operator ($\mathbf{v}[\mathbf{i}]$) and the function `as_tensor`. More details on these follow.

In the following descriptions of UFL operator syntax, i -l and p -s are assumed to be predefined indices, and unless otherwise specified the name \mathbf{v} refers to some vector valued expression, and the name \mathbf{A} refers to some matrix valued expression. The name C refers to a tensor expression of arbitrary rank.

Defining indices

A set of indices i , j , k , l and p , q , r , s are predefined, and these should be enough for many applications. Examples will usually use these objects instead of creating new ones to conserve space.

The data type `Index` represents an index used for subscripting derivatives or taking components of non-scalar expressions. To create indices you can either make a single one using `Index()` or make several at once conveniently using `indices(n)`:

```
i = Index()
j, k, l = indices(3)
```

Each of these represents an `index` range determined by the context; if used to subscript a tensor-valued expression, the range is given by the shape of the expression, and if used to subscript a derivative, the range is given by the dimension d of the underlying shape of the finite element space. As we shall see below, indices can be a powerful tool when used to define forms in tensor notation.

Note: Advanced usage

If using UFL inside DOLFIN or another larger programming environment, it is a good idea to define your indices explicitly just before your form uses them, to avoid name collisions. The definition of the predefined indices is simply:

```
i, j, k, l = indices(4)
p, q, r, s = indices(4)
```

Note: Advanced usage

Note that in the old FFC notation, the definition

```
i = Index(0)
```

meant that the value of the index remained constant. This does not mean the same in UFL, and this notation is only meant for internal usage. Fixed indices are simply integers instead:

```
i = 0
```

Taking components of tensors

Basic fixed indexing of a vector valued expression v or matrix valued expression A :

- $v[0]$: component access, representing the scalar value of the first component of v
- $A[0, 1]$: component access, representing the scalar value of the first row, second column of A

Basic indexing:

- $v[i]$: component access, representing the scalar value of some component of v
- $A[i, j]$: component access, representing the scalar value of some component i, j of A

More advanced indexing:

- $A[i, 0]$: component access, representing the scalar value of some component i of the first column of A
- $A[i, :]$: row access, representing some row i of A , i.e. $\text{rank}(A[i,:]) == 1$
- $A[:, j]$: column access, representing some column j of A , i.e. $\text{rank}(A[:,j]) == 1$
- $C[\dots, 0]$: subtensor access, representing the subtensor of A with the last axis fixed, e.g., $A[\dots, 0] == A[:, 0]$
- $C[j, \dots]$: subtensor access, representing the subtensor of A with the first axis fixed, e.g., $A[j, \dots] == A[j, :]$

Making tensors from components

If you have expressions for scalar components of a tensor and wish to convert them to a tensor, there are two ways to do it. If you have a single expression with free indices that should map to tensor axes, like mapping v_k to v or A_{ij} to A , the following examples show how this is done:

```
vk = Identity(cell.geometric_dimension())[0,k]
v = as_tensor(vk, (k,))

Aij = v[i]*u[j]
A = as_tensor(Aij, (i,j))
```

Here v will represent unit vector \mathbf{i}_0 , and A will represent the outer product of v and u .

If you have multiple expressions without indices, you can build tensors from them just as easily, as illustrated here:

```
v = as_vector([1.0, 2.0, 3.0])
A = as_matrix([[u[0], 0], [0, u[1]]])
B = as_matrix([[a+b for b in range(2)] for a in range(2)])
```

Here v , A and B will represent the expressions

$$\begin{aligned} \mathbf{v} &= \mathbf{i}_0 + 2\mathbf{i}_1 + 3\mathbf{i}_2, \\ \mathbf{A} &= \begin{bmatrix} u_0 & 0 \\ 0 & u_1 \end{bmatrix}, \\ \mathbf{B} &= \begin{bmatrix} 0 & 1 \\ 1 & 2 \end{bmatrix}. \end{aligned}$$

Note that the function `as_tensor` generalizes from vectors to tensors of arbitrary rank, while the alternative functions `as_vector` and `as_matrix` work the same way but are only for constructing vectors and matrices. They are included for readability and convenience.

Implicit summation

Implicit summation can occur in only a few situations. A product of two terms that shares the same free index is implicitly treated as a sum over that free index:

- $v[i] * v[i]: \sum_i v_i v_i$
- $A[i, j] * v[i] * v[j]: \sum_j (\sum_i A_{ij} v_i) v_j$

A tensor valued expression indexed twice with the same free index is treated as a sum over that free index:

- $A[i, i]: \sum_i A_{ii}$
- $C[i, j, j, i]: \sum_i \sum_j C_{ijji}$

The spatial derivative, in the direction of a free index, of an expression with the same free index, is treated as a sum over that free index:

- $v[i].dx(i): \sum_i \frac{d(v_i)}{dx_i}$
- $A[i, j].dx(i): \sum_i \frac{d(A_{ij})}{dx_i}$

Note that these examples are sometimes written $v_{i,i}$ and $A_{ij,i}$ in pen-and-paper index notation.

Basic algebraic operators

The basic algebraic operators `+`, `-`, `*`, `/` can be used freely on UFL expressions. They do have some requirements on their operands, summarized here:

Addition or subtraction, `a + b` or `a - b`:

- The operands `a` and `b` must have the same shape.
- The operands `a` and `b` must have the same set of free indices.

Division, `a / b`:

- The operand `b` must be a scalar expression.
- The operand `b` must have no free indices.
- The operand `a` can be non-scalar with free indices, in which division represents scalar division of all components with the scalar `b`.

Multiplication, `a * b`:

- The only non-scalar operations allowed is scalar-tensor, matrix-vector and matrix-matrix multiplication.
- If either of the operands have any free indices, both must be scalar.
- If any free indices are repeated, summation is implied.

Basic nonlinear functions

Some basic nonlinear functions are also available, their meaning mostly obvious.

- `abs(f)`: the absolute value of `f`.

- `sign(f)`: the sign of f (+1 or -1).
- `pow(f, g)` or `f**g`: f to the power g , f^g
- `sqrt(f)`: square root, \sqrt{f}
- `exp(f)`: exponential of f
- `ln(f)`: natural logarithm of f
- `cos(f)`: cosine of f
- `sin(f)`: sine of f
- `tan(f)`: tangent of f
- `cosh(f)`: hyperbolic cosine of f
- `sinh(f)`: hyperbolic sine of f
- `tanh(f)`: hyperbolic tangent of f
- `acos(f)`: inverse cosine of f
- `asin(f)`: inverse sine of f
- `atan(f)`: inverse tangent of f
- `atan2(f1, f2)`: inverse tangent of $(f1/f2)$
- `erf(f)`: error function of f , $\frac{2}{\sqrt{\pi}} \int_0^f \exp(-t^2) dt$
- `bessel_J(nu, f)`: Bessel function of the first kind, $J_\nu(f)$
- `bessel_Y(nu, f)`: Bessel function of the second kind, $Y_\nu(f)$
- `bessel_I(nu, f)`: Modified Bessel function of the first kind, $I_\nu(f)$
- `bessel_K(nu, f)`: Modified Bessel function of the second kind, $K_\nu(f)$

These functions do not accept non-scalar operands or operands with free indices or Argument dependencies.

Tensor algebra operators

`transpose`

The transpose of a matrix A can be written as:

```
AT = transpose(A)
AT = A.T
AT = as_matrix(A[i,j], (j,i))
```

The definition of the transpose is

$$\text{AT}[i, j] \leftrightarrow (A^\top)_{ij} = A_{ji}$$

For transposing higher order tensor expressions, index notation can be used:

```
AT = as_tensor(A[i,j,k,l], (l,k,j,i))
```

tr

The trace of a matrix A is the sum of the diagonal entries. This can be written as:

```
t = tr(A)
t = A[i,i]
```

The definition of the trace is

$$\text{tr}(A) \leftrightarrow \text{tr}A = A_{ii} = \sum_{i=0}^{n-1} A_{ii}.$$

dot

The dot product of two tensors a and b can be written:

```
# General tensors
f = dot(a, b)

# Vectors a and b
f = a[i]*b[i]

# Matrices a and b
f = as_matrix(a[i,k]*b[k,j], (i,j))
```

The definition of the dot product of unit vectors is (assuming an orthonormal basis for a Euclidean space):

$$\mathbf{i}_i \cdot \mathbf{i}_j = \delta_{ij}$$

where δ_{ij} is the Kronecker delta function. The dot product of higher order tensors follow from this, as illustrated with the following examples.

An example with two vectors

$$\mathbf{v} \cdot \mathbf{u} = (v_i \mathbf{i}_i) \cdot (u_j \mathbf{i}_j) = v_i u_j (\mathbf{i}_i \cdot \mathbf{i}_j) = v_i u_j \delta_{ij} = v_i u_i$$

An example with a tensor of rank two

$$\begin{aligned} \mathbf{A} \cdot \mathbf{B} &= (A_{ij} \mathbf{i}_i \mathbf{i}_j) \cdot (B_{kl} \mathbf{i}_k \mathbf{i}_l) \\ &= (A_{ij} B_{kl}) \mathbf{i}_i (\mathbf{i}_j \cdot \mathbf{i}_k) \mathbf{i}_l \\ &= (A_{ij} B_{kl} \delta_{jk}) \mathbf{i}_i \mathbf{i}_l \\ &= A_{ik} B_{kl} \mathbf{i}_i \mathbf{i}_l. \end{aligned}$$

This is the same as a matrix-matrix multiplication.

An example with a vector and a tensor of rank two

$$\begin{aligned} \mathbf{v} \cdot \mathbf{A} &= (v_j \mathbf{i}_j) \cdot (A_{kl} \mathbf{i}_k \mathbf{i}_l) \\ &= (v_j A_{kl}) (\mathbf{i}_j \cdot \mathbf{i}_k) \mathbf{i}_l \\ &= (v_j A_{kl} \delta_{jk}) \mathbf{i}_l \\ &= v_k A_{kl} \mathbf{i}_l \end{aligned}$$

This is the same as a vector-matrix multiplication.

This generalizes to tensors of arbitrary rank: the dot product applies to the last axis of a and the first axis of b. The tensor rank of the product is rank(a)+rank(b)-2.

inner

The inner product is a contraction over all axes of a and b , that is the sum of all component-wise products. The operands must have exactly the same dimensions. For two vectors it is equivalent to the dot product.

If \mathbf{A} and \mathbf{B} are rank two tensors and \mathcal{C} and \mathcal{D} are rank 3 tensors their inner products are

$$\mathbf{A} : \mathbf{B} = A_{ij}B_{ij}$$

$$\mathcal{C} : \mathcal{D} = C_{ijk}D_{ijk}$$

Using UFL notation, the following sets of declarations are equivalent:

```
# Vectors
f = dot(a, b)
f = inner(a, b)
f = a[i]*b[i]

# Matrices
f = inner(A, B)
f = A[i,j]*B[i,j]

# Rank 3 tensors
f = inner(C, D)
f = C[i,j,k]*D[i,j,k]
```

outer

The outer product of two tensors a and b can be written:

```
A = outer(a, b)
```

The general definition of the outer product of two tensors \mathcal{C} of rank r and \mathcal{D} of rank s is

$$\mathcal{C} \otimes \mathcal{D} = C_{t_0^a \dots t_{r-1}^a} D_{t_0^b \dots t_{s-1}^b} \mathbf{i}_{t_0^a} \otimes \dots \otimes \mathbf{i}_{t_{r-2}^a} \otimes \mathbf{i}_{t_1^b} \otimes \dots \otimes \mathbf{i}_{t_{s-1}^b}$$

Some examples with vectors and matrices are easier to understand:

$$\mathbf{v} \otimes \mathbf{u} = v_i u_j \mathbf{i}_i \mathbf{i}_j,$$

$$\mathbf{v} \otimes \mathbf{B} = v_i B_{kl} \mathbf{i}_i \mathbf{i}_k \mathbf{i}_l,$$

$$\mathbf{A} \otimes \mathbf{B} = A_{ij} B_{kl} \mathbf{i}_i \mathbf{i}_j \mathbf{i}_k \mathbf{i}_l.$$

The outer product of vectors is often written simply as

$$\mathbf{v} \otimes \mathbf{u} = \mathbf{v}\mathbf{u},$$

which is what we have done with $\mathbf{i}_i \mathbf{i}_j$ above.

The rank of the outer product is the sum of the ranks of the operands.

cross

The operator `cross` accepts as arguments two logically vector-valued expressions and returns a vector which is the cross product (vector product) of the two vectors:

$$\text{cross}(\mathbf{v}, \mathbf{w}) \leftrightarrow \mathbf{v} \times \mathbf{w} = (v_1 w_2 - v_2 w_1, v_2 w_0 - v_0 w_2, v_0 w_1 - v_1 w_0)$$

Note that this operator is only defined for vectors of length three.

det

The determinant of a matrix A can be written as

$$d = \det(A)$$

dev

The deviatoric part of matrix A can be written as

$$B = \text{dev}(A)$$

The definition is

$$\text{dev}A = A - \frac{\mathbf{A}_{ii}}{d}\mathbf{I}$$

where d is the rank of matrix A and \mathbf{I} is the identity matrix.

sym

The symmetric part of A can be written as

$$B = \text{sym}(A)$$

The definition is

$$\text{sym}A = \frac{1}{2}(A + A^T)$$

skew

The skew symmetric part of A can be written as

$$B = \text{skew}(A)$$

The definition is

$$\text{skew}A = \frac{1}{2}(A - A^T)$$

cofac

The cofactor of a matrix A can be written as

$$B = \text{cofac}(A)$$

The definition is

$$\text{cofac}A = \det(A)A^{-1}$$

The implementation of this is currently rather crude, with a hardcoded symbolic expression for the cofactor. Therefore, this is limited to 1x1, 2x2 and 3x3 matrices.

inv

The inverse of matrix A can be written as

```
Ainv = inv(A)
```

The implementation of this is currently rather crude, with a hardcoded symbolic expression for the inverse. Therefore, this is limited to 1x1, 2x2 and 3x3 matrices.

Differential Operators

Three different kinds of derivatives are currently supported: spatial derivatives, derivatives w.r.t. user defined variables, and derivatives of a form or functional w.r.t. a function.

Basic spatial derivatives

Spatial derivatives hold a special physical meaning in partial differential equations and there are several ways to express those. The basic way is:

```
# Derivative w.r.t. x_2
f = Dx(v, 2)
f = v.dx(2)
# Derivative w.r.t. x_i
g = Dx(v, i)
g = v.dx(i)
```

If v is a scalar expression, f here is the scalar derivative of v with respect to spatial direction z . If v has no free indices, g is the scalar derivative in spatial direction x_i , and g has the free index i . This can be expressed compactly as $v_{,i}$:

$$f = \frac{\partial v}{\partial x_2} = v_{,2},$$
$$g = \frac{\partial v}{\partial x_i} = v_{,i}.$$

If the expression to be differentiated w.r.t. x_i has i as a free-index, implicit summation is implied:

```
# Sum of derivatives w.r.t. x_i for all i
g = Dx(v[i], i)
g = v[i].dx(i)
```

Here g will represent the sum of derivatives w.r.t. x_i for all i , that is

$$g = \sum_i \frac{\partial v}{\partial x_i} = v_{i,i}.$$

Note: $v[i].dx(i)$ and $v_{i,i}$ with compact notation denote implicit summation.

Compound spatial derivatives

UFL implements several common differential operators. The notation is simple and their names should be self-explanatory:

```
Df = grad(f)
df = div(f)
cf = curl(v)
rf = rot(f)
```

The operand f can have no free indices.

Gradient

The gradient of a scalar u is defined as

$$\text{grad}(u) \equiv \nabla u = \sum_{k=0}^{d-1} \frac{\partial u}{\partial x_k} \mathbf{i}_k,$$

which is a vector of all spatial partial derivatives of u .

The gradient of a vector \mathbf{v} is defined as

$$\text{grad}(\mathbf{v}) \equiv \nabla \mathbf{v} = \frac{\partial v_i}{\partial x_j} \mathbf{i}_i \mathbf{i}_j,$$

which, written componentwise, reads

$$\mathbf{A} = \nabla \mathbf{v}, \quad A_{ij} = v_{i,j}$$

In general for a tensor \mathbf{A} of rank r the definition is

$$\text{grad}(\mathbf{A}) \equiv \nabla \mathbf{A} = \left(\frac{\partial}{\partial x_i} \right) (A_\iota \mathbf{i}_{\iota_0} \otimes \cdots \otimes \mathbf{i}_{\iota_{r-1}}) \otimes \mathbf{i}_i = \frac{\partial A_\iota}{\partial x_i} \mathbf{i}_{\iota_0} \otimes \cdots \otimes \mathbf{i}_{\iota_{r-1}} \otimes \mathbf{i}_i,$$

where ι is a multi-index of length r .

In UFL, the following pairs of declarations are equivalent:

```
Dfi = grad(f)[i]
Dfi = f.dx(i)

Dvi = grad(v)[i, j]
Dvi = v[i].dx(j)

DAi = grad(A)[..., i]
DAi = A.dx(i)
```

for a scalar expression f , a vector expression v , and a tensor expression A of arbitrary rank.

Divergence

The divergence of any nonscalar (vector or tensor) expression \mathbf{A} is defined as the contraction of the partial derivative over the last axis of the expression.

The divergence of a vector \mathbf{v} is defined as

$$\text{div}(\mathbf{v}) \equiv \nabla \cdot \mathbf{v} = \sum_{k=0}^{d-1} \frac{\partial v_i}{\partial x_i}$$

In UFL, the following declarations are equivalent:

```
dv = div(v)
dv = v[i].dx(i)

dA = div(A)
dA = A[..., i].dx(i)
```

for a vector expression v and a tensor expression A .

Curl and rot

The operator `curl` or `rot` accepts as argument a vector-valued expression and returns its curl

$$\text{curl}(\mathbf{v}) = \nabla \times \mathbf{v} = \left(\frac{\partial v_2}{\partial x_1} - \frac{\partial v_1}{\partial x_2}, \frac{\partial v_0}{\partial x_2} - \frac{\partial v_2}{\partial x_0}, \frac{\partial v_1}{\partial x_0} - \frac{\partial v_0}{\partial x_1} \right).$$

Note: The `curl` or `rot` operator is only defined for vectors of length three.

In UFL, the following declarations are equivalent:

```
omega = curl(v)
omega = rot(v)
```

Variable derivatives

UFL also supports differentiation with respect to user defined variables. A user defined variable can be any expression that is defined as a variable.

The notation is illustrated here:

```
# Define some arbitrary expression
u = Coefficient(element)
w = sin(u**2)

# Annotate expression w as a variable that can be used by "diff"
w = variable(w)

# This expression is a function of w
F = w**2

# The derivative of expression F w.r.t. the variable w
dF = diff(F, w) # == 2*w
```

Note that the variable w still represents the same expression.

This can be useful for example to implement material laws in hyperelasticity where the stress tensor is derived from a Helmholtz strain energy function.

Currently, UFL does not implement time in any particular way, but differentiation w.r.t. time can be done without this support through the use of a constant variable t :

```
t = variable(Constant(cell))
f = sin(x[0])**2 * cos(t)
dfdt = diff(f, t)
```

Functional derivatives

The third and final kind of derivative are derivatives of functionals or forms w.r.t. to a `Coefficient`. This is described in more detail in the section [AD](#) about form transformations.

DG operators

UFL provides operators for implementation of discontinuous Galerkin methods. These include the evaluation of the jump and average of a function (or in general an expression) over the interior facets (edges or faces) of a mesh.

Restriction: `v('+'')` and `v(''-')`

When integrating over interior facets (`*dS`), one may restrict expressions to the positive or negative side of the facet:

```
element = FiniteElement("Discontinuous Lagrange", tetrahedron, 0)

v = TestFunction(element)
u = TrialFunction(element)

f = Coefficient(element)

a = f('+'')*dot(grad(v)('+''), grad(u)(''-'))*dS
```

Restriction may be applied to functions of any finite element space but will only have effect when applied to expressions that are discontinuous across facets.

Jump: `jump(v)`

The operator `jump` may be used to express the jump of a function across a common facet of two cells. Two versions of the `jump` operator are provided.

If called with only one argument, then the `jump` operator evaluates to the difference between the restrictions of the given expression on the positive and negative sides of the facet:

$$\text{jump}(v) \leftrightarrow [[v]] = v^+ - v^-$$

If the expression `v` is scalar, then `jump(v)` will also be scalar, and if `v` is vector-valued, then `jump(v)` will also be vector-valued.

If called with two arguments, `jump(v, n)` evaluates to the jump in `v` weighted by `n`. Typically, `n` will be chosen to represent the unit outward normal of the facet (as seen from each of the two neighboring cells). If `v` is scalar, then `jump(v, n)` is given by

$$\text{jump}(v, n) \leftrightarrow [[v]]_n = v^+ n^+ + v^- n^-$$

If `v` is vector-valued, then `jump(v, n)` is given by

$$\text{jump}(v, n) \leftrightarrow [[v]]_n = v^+ \cdot n^+ + v^- \cdot n^-$$

Thus, if the expression `v` is scalar, then `jump(v, n)` will be vector-valued, and if `v` is vector-valued, then `jump(v, n)` will be scalar.

Average: avg (v)

The operator `avg` may be used to express the average of an expression across a common facet of two cells:

$$\text{avg}(v) \leftrightarrow [[v]] = \frac{1}{2}(v^+ + v^-)$$

The expression `avg (v)` has the same value shape as the expression `v`.

Conditional Operators

Conditional

UFL has limited support for branching, but for some PDEs it is needed. The expression `c` in:

```
c = conditional(condition, true_value, false_value)
```

evaluates to `true_value` at run-time if `condition` evaluates to true, or to `false_value` otherwise.

This corresponds to the C++ syntax (`condition ? true_value : false_value`), or the Python syntax (`true_value if condition else false_value`).

Conditions

- `eq(a, b)` must be used in place of the notation `a == b`
- `ne(a, b)` must be used in place of the notation `a != b`
- `le(a, b)` is equivalent to `a <= b`
- `ge(a, b)` is equivalent to `a >= b`
- `lt(a, b)` is equivalent to `a < b`
- `gt(a, b)` is equivalent to `a > b`

Note: Because of details in the way Python behaves, we cannot overload the `==` operator, hence these named operators.

User-defined operators

A user may define new operators, using standard Python syntax. As an example, consider the strain-rate operator ϵ of linear elasticity, defined by

$$\epsilon(v) = \frac{1}{2}(\nabla v + (\nabla v)^\top).$$

This operator can be implemented as a function using the Python `def` keyword:

```
def epsilon(v):
    return 0.5*(grad(v) + grad(v).T)
```

Alternatively, using the shorthand `lambda` notation, the strain operator may be defined as follows:

```
epsilon = lambda v: 0.5*(grad(v) + grad(v).T)
```

Form Transformations

When you have defined a `Form`, you can derive new related forms from it automatically. UFL defines a set of common form transformations described in this section.

Replacing arguments of a Form

The function `replace` lets you replace terminal objects with other values, using a mapping defined by a Python dictionary. This can be used for example to replace a `Coefficient` with a fixed value for optimized runtime evaluation.

Example:

```
f = Coefficient(element)
g = Coefficient(element)
c = Constant(cell)
a = f*g*v*dx
b = replace(a, { f: 3.14, g: c })
```

The replacement values must have the same basic properties as the original values, in particular value shape and free indices.

Action of a form on a function

The action of a bilinear form a is defined as

$$b(v; w) = a(v, w)$$

The action of a linear form L is defined as

$$f(w) = L(w)$$

This operation is implemented in UFL simply by replacing the rightmost basis function (trial function for a , test function for L) in a `Form`, and is used like this:

```
L = action(a, w)
f = action(L, w)
```

To give a concrete example, these declarations are equivalent:

```
a = inner(grad(u), grad(v)) * dx
L = action(a, w)

a = inner(grad(u), grad(v)) * dx
L = inner(grad(w), grad(v)) * dx
```

If a is a rank 2 form used to assemble the matrix A , L is a rank 1 form that can be used to assemble the vector $b = Ax$ directly. This can be used to define both the form of a matrix and the form of its action without code duplication, and for the action of a Jacobi matrix computed using derivative.

If L is a rank 1 form used to assemble the vector b , f is a functional that can be used to assemble the scalar value $f = b \cdot w$ directly. This operation is sometimes used in, e.g., error control with L being the residual equation and w

being the solution to the dual problem. (However, the discrete vector for the assembled residual equation will typically be available, so doing the dot product using linear algebra would be faster than using this feature.)

Energy norm of a bilinear form

The functional representing the energy norm $|v|_A = v^T A v$ of a matrix A assembled from a form a can be computed with:

```
f = energy_norm(a, w)
```

which is equivalent to:

```
f = action(action(a, w), w)
```

Adjoint of a bilinear form

The adjoint a' of a bilinear form a is defined as

$$a'(u, v) = a(v, u).$$

This operation is implemented in UFL simply by swapping test and trial functions in a `Form`, and is used like this:

```
aprime = adjoint(a)
```

Linear and bilinear parts of a form

Sometimes it is useful to write an equation on the format

$$a(v, u) - L(v) = 0.$$

Before assembly, we need to extract the forms corresponding to the left hand side and right hand side. This corresponds to extracting the bilinear and linear terms of the form respectively, or separating the terms that depend on both a test and a trial function on one side and the terms that depend on only a test function on the other.

This is easily done in UFL using `lhs` and `rhs`:

```
b = u*v*dx - f*v*dx
a, L = lhs(b), rhs(b)
```

Note that `rhs` multiplies the extracted terms by -1, corresponding to moving them from left to right, so this is equivalent to

```
a = u*v*dx
L = f*v*dx
```

As a slightly more complicated example, this formulation:

```
F = v*(u - w)*dx + k*dot(grad(v), grad(0.5*(w + u)))*dx
a, L = lhs(F), rhs(F)
```

is equivalent to

```
a = v*u*dx + k*dot(grad(v), 0.5*grad(u))*dx
L = v*w*dx - k*dot(grad(v), 0.5*grad(w))*dx
```

Automatic functional differentiation

UFL can compute derivatives of functionals or forms w.r.t. to a `Coefficient`. This functionality can be used for example to linearize your nonlinear residual equation automatically, or derive a linear system from a functional, or compute sensitivity vectors w.r.t. some coefficient.

A functional can be differentiated to obtain a linear form,

$$F(v; w) = \frac{d}{dw} f(v; w)$$

and a linear form can be differentiated to obtain the bilinear form corresponding to its Jacobi matrix.

Note: Note that by “linear form” we only mean a form that is linear in its test function, not in the function you differentiate with respect to.

$$J(v, u; w) = \frac{d}{dw} F(v; w).$$

The UFL code to express this is (for a simple functional $f(w) = \int_{\Omega} \frac{1}{2} w^2 dx$)

```
f = (w**2)/2 * dx
F = derivative(f, w, v)
J = derivative(F, w, u)
```

which is equivalent to

```
f = (w**2)/2 * dx
F = w*v*dx
J = u*v*dx
```

Assume in the following examples that

```
v = TestFunction(element)
u = TrialFunction(element)
w = Coefficient(element)
```

The stiffness matrix can be computed from the functional $\int_{\Omega} \nabla w : \nabla v dx$, by

```
f = inner(grad(w), grad(w))/2 * dx
F = derivative(f, w, v)
J = derivative(F, w, u)
```

which is equivalent to

```
f = inner(grad(w), grad(w))/2 * dx
F = inner(grad(w), grad(v)) * dx
J = inner(grad(u), grad(v)) * dx
```

Note that here the basis functions are provided explicitly, which is sometimes necessary, e.g., if part of the form is linearized manually as in

```

g = Coefficient(element)
f = inner(grad(w), grad(w)) * dx
F = derivative(f, w, v) + dot(w-g, v) * dx
J = derivative(F, w, u)

```

Derivatives can also be computed w.r.t. functions in mixed spaces. Consider this example, an implementation of the harmonic map equations using automatic differentiation:

```

X = VectorElement("Lagrange", cell, 1)
Y = FiniteElement("Lagrange", cell, 1)

x = Coefficient(X)
y = Coefficient(Y)

L = inner(grad(x), grad(x)) * dx + dot(x, x) * y * dx

F = derivative(L, (x,y))
J = derivative(F, (x,y))

```

Here L is defined as a functional with two coefficient functions x and y from separate finite element spaces. However, F and J become linear and bilinear forms respectively with basis functions defined on the mixed finite element

```
M = X + Y
```

There is a subtle difference between defining x and y separately and this alternative implementation (reusing the elements X, Y, M):

```

u = Coefficient(M)
x, y = split(u)

L = inner(grad(x), grad(x)) * dx + dot(x, x) * y * dx

F = derivative(L, u)
J = derivative(F, u)

```

The difference is that the forms here have *one* coefficient function u in the mixed space, and the forms above have *two* coefficient functions x and y .

Combining form transformations

Form transformations can be combined freely. Note that, to do this, derivatives are usually evaluated before applying (e.g.) the action of a form, because `derivative` changes the arity of the form:

```

element = FiniteElement("CG", cell, 1)
w = Coefficient(element)
f = w**4/4*dx(0) + inner(grad(w), grad(w)) * dx(1)
F = derivative(f, w)
J = derivative(F, w)
Ja = action(J, w)
Jp = adjoint(J)
Jpa = action(Jp, w)
g = Coefficient(element)
Jnorm = energy_norm(J, g)

```

Form files

UFL forms and elements can be collected in a *form file* with the extension `.ufl`. Form compilers will typically execute this file with the global UFL namespace available, and extract forms and elements that are defined after execution. The compilers do not compile all forms and elements that are defined in file, but only those that are “exported”. A finite element with the variable name `element` is exported by default, as are forms with the names `M`, `L`, and `a`. The default form names are intended for a functional, linear form, and bilinear form respectively.

To export multiple forms and elements or use other names, an explicit list with the forms and elements to export can be defined. Simply write

```
elements = [V, P, TH]
forms = [a, L, F, J, L2, H1]
```

at the end of the file to export the elements and forms held by these variables.

Example forms

The following examples illustrate basic usage of the form language for the definition of a collection of standard multilinear forms. We assume that `dx` has been declared as an integral over the interior of Ω and that both `i` and `j` have been declared as a free Index.

The examples presented below can all be found in the subdirectory `demo/` of the UFL source tree together with numerous other examples.

The mass matrix

As a first example, consider the bilinear form corresponding to a mass matrix,

$$a(v, u) = \int_{\Omega} v u \, dx,$$

which can be implemented in UFL as follows:

```
element = FiniteElement("Lagrange", triangle, 1)

v = TestFunction(element)
u = TrialFunction(element)

a = v*u*dx
```

This example is implemented in the file `Mass.ufl` in the collection of demonstration forms included with the UFL source distribution.

Poisson equation

The bilinear and linear forms form for Poisson’s equation,

$$\begin{aligned} a(v, u) &= \int_{\Omega} \nabla v \cdot \nabla u \, dx, \\ L(v; f) &= \int_{\Omega} v f \, dx, \end{aligned}$$

can be implemented as follows:

```

element = FiniteElement("Lagrange", triangle, 1)

v = TestFunction(element)
u = TrialFunction(element)
f = Coefficient(element)

a = dot(grad(v), grad(u)) * dx
L = v*f*dx

```

Alternatively, index notation can be used to express the scalar product like this:

```
a = Dx(v, i)*Dx(u, i)*dx
```

or like this:

```
a = v.dx(i)*u.dx(i)*dx
```

This example is implemented in the file `Poisson.ufl` in the collection of demonstration forms included with the UFL source distribution.

Vector-valued Poisson

The bilinear and linear forms for a system of (independent) Poisson equations,

$$a(v, u) = \int_{\Omega} \nabla v : \nabla u \, dx,$$

$$L(v; f) = \int_{\Omega} v \cdot f \, dx,$$

with v , u and f vector-valued can be implemented as follows:

```

element = VectorElement("Lagrange", triangle, 1)

v = TestFunction(element)
u = TrialFunction(element)
f = Coefficient(element)

a = inner(grad(v), grad(u)) * dx
L = dot(v, f) * dx

```

Alternatively, index notation may be used like this:

```
a = Dx(v[i], j)*Dx(u[i], j)*dx
L = v[i]*f[i]*dx
```

or like this:

```
a = v[i].dx(j)*u[i].dx(j)*dx
L = v[i]*f[i]*dx
```

This example is implemented in the file `PoissonSystem.ufl` in the collection of demonstration forms included with the UFL source distribution.

The strain-strain term of linear elasticity

The strain-strain term of linear elasticity,

$$a(v, u) = \int_{\Omega} \epsilon(v) : \epsilon(u) dx,$$

where

$$\epsilon(v) = \frac{1}{2}(\nabla v + (\nabla v)^T)$$

can be implemented as follows:

```
element = VectorElement("Lagrange", tetrahedron, 1)

v = TestFunction(element)
u = TrialFunction(element)

def epsilon(v):
    Dv = grad(v)
    return 0.5*(Dv + Dv.T)

a = inner(epsilon(v), epsilon(u))*dx
```

Alternatively, index notation can be used to define the form:

```
a = 0.25*(Dx(v[j], i) + Dx(v[i], j)) * \
(Dx(u[j], i) + Dx(u[i], j)) *dx
```

or like this:

```
a = 0.25*(v[j].dx(i) + v[i].dx(j)) * \
(u[j].dx(i) + u[i].dx(j)) *dx
```

This example is implemented in the file `Elasticity.ufl` in the collection of demonstration forms included with the UFL source distribution.

The nonlinear term of Navier–Stokes

The bilinear form for fixed-point iteration on the nonlinear term of the incompressible Navier–Stokes equations,

$$a(v, u; w) = \int_{\Omega} (w \cdot \nabla u) \cdot v dx,$$

with w the frozen velocity from a previous iteration, can be implemented as follows:

```
element = VectorElement("Lagrange", tetrahedron, 1)

v = TestFunction(element)
u = TrialFunction(element)
w = Coefficient(element)

a = dot(grad(u)*w, v)*dx
```

alternatively using index notation like this:

```
a = v[i]*w[j]*Dx(u[i], j)*dx
```

or like this:

```
a = v[i]*w[j]*u[i].dx(j)*dx
```

This example is implemented in the file `NavierStokes.ufl` in the collection of demonstration forms included with the UFL source distribution.

The heat equation

Discretizing the heat equation,

$$\dot{u} - \nabla \cdot (c \nabla u) = f,$$

in time using the dG(0) method (backward Euler), we obtain the following variational problem for the discrete solution $u_h = u_h(x, t)$: Find $u_h^n = u_h(\cdot, t_n)$ with $u_h^{n-1} = u_h(\cdot, t_{n-1})$ given such that

$$\frac{1}{k_n} \int_{\Omega} v (u_h^n - u_h^{n-1}) dx + \int_{\Omega} c \nabla v \cdot \nabla u_h^n dx = \int_{\Omega} v f^n dx$$

for all test functions v , where $k_n = t_n - t_{n-1}$ denotes the time step. In the example below, we implement this variational problem with piecewise linear test and trial functions, but other choices are possible (just choose another finite element).

Rewriting the variational problem in the standard form $a(v, u_h) = L(v)$ for all v , we obtain the following pair of bilinear and linear forms:

$$a(v, u_h^n; c, k) = \int_{\Omega} v u_h^n dx + k_n \int_{\Omega} c \nabla v \cdot \nabla u_h^n dx,$$

$$L(v; u_h^{n-1}, f, k) = \int_{\Omega} v u_h^{n-1} dx + k_n \int_{\Omega} v f^n dx,$$

which can be implemented as follows:

```
element = FiniteElement("Lagrange", triangle, 1)

v = TestFunction(element) # Test function
u1 = TrialFunction(element) # Value at t_n
u0 = Coefficient(element) # Value at t_{n-1}
c = Coefficient(element) # Heat conductivity
f = Coefficient(element) # Heat source
k = Constant("triangle") # Time step

a = v*u1*dx + k*c*dot(grad(v), grad(u1))*dx
L = v*u0*dx + k*v*f*dx
```

This example is implemented in the file `Heat.ufl` in the collection of demonstration forms included with the UFL source distribution.

Mixed formulation of Stokes

To solve Stokes' equations,

$$-\Delta u + \nabla p = f,$$

$$\nabla \cdot u = 0,$$

we write the variational problem in standard form $a(v, u) = L(v)$ for all v to obtain the following pair of bilinear and linear forms:

$$a((v, q), (u, p)) = \int_{\Omega} \nabla v : \nabla u - (\nabla \cdot v) p + q (\nabla \cdot u) dx,$$

$$L((v, q); f) = \int_{\Omega} v \cdot f dx.$$

Using a mixed formulation with Taylor-Hood elements, this can be implemented as follows:

```
cell = triangle
P2 = VectorElement("Lagrange", cell, 2)
P1 = FiniteElement("Lagrange", cell, 1)
TH = P2 * P1

(v, q) = TestFunctions(TH)
(u, p) = TrialFunctions(TH)

f = Coefficient(P2)

a = (inner(grad(v), grad(u)) - div(v)*p + q*div(u))*dx
L = dot(v, f)*dx
```

This example is implemented in the file `Stokes.ufl` in the collection of demonstration forms included with the UFL source distribution.

Mixed formulation of Poisson

We next consider the following formulation of Poisson's equation as a pair of first order equations for $\sigma \in H(\text{div})$ and $u \in L^2$:

$$\begin{aligned} \sigma + \nabla u &= 0, \\ \nabla \cdot \sigma &= f. \end{aligned}$$

We multiply the two equations by a pair of test functions τ and w and integrate by parts to obtain the following variational problem: Find $(\sigma, u) \in V = H(\text{div}) \times L^2$ such that

$$a((\tau, w), (\sigma, u)) = L((\tau, w)) \quad \forall (\tau, w) \in V,$$

where

$$a((\tau, w), (\sigma, u)) = \int_{\Omega} \tau \cdot \sigma - \nabla \cdot \tau u + w \nabla \cdot \sigma dx,$$

$$L((\tau, w); f) = \int_{\Omega} w \cdot f dx.$$

We may implement the corresponding forms in our form language using first order BDM $H(\text{div})$ -conforming elements for σ and piecewise constant L^2 -conforming elements for u as follows:

```
cell = triangle
BDM1 = FiniteElement("Brezzi-Douglas-Marini", cell, 1)
DG0 = FiniteElement("Discontinuous Lagrange", cell, 0)

element = BDM1 * DG0

(tau, w) = TestFunctions(element)
(sigma, u) = TrialFunctions(element)
```

```
f = Coefficient(DG0)
a = (dot(tau, sigma) - div(tau)*u + w*div(sigma))*dx
L = w*f*dx
```

This example is implemented in the file `MixedPoisson.ufl` in the collection of demonstration forms included with the UFL source distribution.

Poisson equation with DG elements

We consider again Poisson's equation, but now in an (interior penalty) discontinuous Galerkin formulation: Find $u \in V = L^2$ such that

$$a(v, u) = L(v) \quad \forall v \in V,$$

where

$$\begin{aligned} a(v, u; h) &= \int_{\Omega} \nabla v \cdot \nabla u \, dx \\ &\quad + \sum_S \int_S -\langle \nabla v \rangle \cdot [[u]]_n - [[v]]_n \cdot \langle \nabla u \rangle + (\alpha/h)[[v]]_n \cdot [[u]]_n \, dS \\ &\quad + \int_{\partial\Omega} -\nabla v \cdot [[u]]_n - [[v]]_n \cdot \nabla u + (\gamma/h)v u \, ds \\ L(v; f, g) &= \int_{\Omega} vf \, dx + \int_{\partial\Omega} vg \, ds. \end{aligned}$$

The corresponding finite element variational problem for discontinuous first order elements may be implemented as follows:

```
cell = triangle
DG1 = FiniteElement("Discontinuous Lagrange", cell, 1)

v = TestFunction(DG1)
u = TrialFunction(DG1)

f = Coefficient(DG1)
g = Coefficient(DG1)
h = 2.0*Circumradius(cell)
alpha = 1
gamma = 1

a = dot(grad(v), grad(u))*dx \
- dot(avg(grad(v)), jump(u))*ds \
- dot(jump(v), avg(grad(u)))*ds \
+ alpha/h(+)*dot(jump(v), jump(u))*ds \
- dot(grad(v), jump(u))*ds \
- dot(jump(v), grad(u))*ds \
+ gamma/h*v*u*ds
L = v*f*dx + v*g*ds
```

This example is implemented in the file `PoissonDG.ufl` in the collection of demonstration forms included with the UFL source distribution.

The Quadrature family

We consider here a nonlinear version of the Poisson's equation to illustrate the main point of the Quadrature finite element family. The strong equation looks as follows:

$$-\nabla \cdot (1 + u^2) \nabla u = f.$$

The linearised bilinear and linear forms for this equation,

$$\begin{aligned} a(v, u; u_0) &= \int_{\Omega} (1 + u_0^2) \nabla v \cdot \nabla u \, dx + \int_{\Omega} 2u_0 u \nabla v \cdot \nabla u_0 \, dx, \\ L(v; u_0, f) &= \int_{\Omega} v f \, dx - \int_{\Omega} (1 + u_0^2) \nabla v \cdot \nabla u_0 \, dx, \end{aligned}$$

can be implemented in a single form file as follows:

```
element = FiniteElement("Lagrange", triangle, 1)

v = TestFunction(element)
u = TrialFunction(element)
u0 = Coefficient(element)
f = Coefficient(element)

a = (1+u0**2)*dot(grad(v), grad(u)) *dx + 2*u0*u*dot(grad(v), grad(u0)) *dx
L = v*f*dx - (1+u0**2)*dot(grad(v), grad(u0)) *dx
```

Here, u_0 represents the solution from the previous Newton-Raphson iteration.

The above form will be denoted REF1 and serves as our reference implementation for linear elements. A similar form (REF2) using quadratic elements will serve as a reference for quadratic elements.

Now, assume that we want to treat the quantities $C = (1 + u_0^2)$ and $\sigma_0 = (1 + u_0^2) \nabla u_0$ as given functions (to be computed elsewhere). Substituting into the bilinear and linear forms, we obtain

$$\begin{aligned} a(v, u) &= \int_{\Omega} C \nabla v \cdot \nabla u \, dx + \int_{\Omega} 2u_0 u \nabla v \cdot \nabla u_0 \, dx, \\ L(v; \sigma_0, f) &= \int_{\Omega} v f \, dx - \int_{\Omega} \nabla v \cdot \sigma_0 \, dx. \end{aligned}$$

Then, two additional forms are created to compute the tangent C and the gradient of u_0 . This situation shows up in plasticity and other problems where certain quantities need to be computed elsewhere (in user-defined functions). The three forms using the standard `FiniteElement` (linear elements) can then be implemented as

```
# NonlinearPoisson.ufl
element = FiniteElement("Lagrange", triangle, 1)
DG = FiniteElement("Discontinuous Lagrange", triangle, 0)
sig = VectorElement("Discontinuous Lagrange", triangle, 0)

v     = TestFunction(element)
u     = TrialFunction(element)
u0    = Coefficient(element)
C     = Coefficient(DG)
sig0 = Coefficient(sig)
f     = Coefficient(element)

a = v.dx(i)*C*u.dx(i)*dx + v.dx(i)*2*u0*u*u0.dx(i)*dx
L = v*f*dx - dot(grad(v), sig0)*dx
```

and

```
# Tangent.ufl
element = FiniteElement("Lagrange", triangle, 1)
DG = FiniteElement("Discontinuous Lagrange", triangle, 0)

v = TestFunction(DG)
u = TrialFunction(DG)
u0= Coefficient(element)

a = v*u*dx
L = v*(1.0 + u0**2)*dx
```

and

```
# Gradient.ufl
element = FiniteElement("Lagrange", triangle, 1)
DG = VectorElement("Discontinuous Lagrange", triangle, 0)

v = TestFunction(DG)
u = TrialFunction(DG)
u0 = Coefficient(element)

a = dot(v, u)*dx
L = dot(v, (1.0 + u0**2)*grad(u0))*dx
```

The three forms can be implemented using the `QuadratureElement` in a similar fashion in which only the element declaration is different:

```
# QE1NonlinearPoisson.ufl
element = FiniteElement("Lagrange", triangle, 1)
QE = FiniteElement("Quadrature", triangle, 2)
sig = VectorElement("Quadrature", triangle, 2)
```

and

```
# QE1Tangent.ufl
element = FiniteElement("Lagrange", triangle, 1)
QE = FiniteElement("Quadrature", triangle, 2)
```

and

```
# QE1Gradient.ufl
element = FiniteElement("Lagrange", triangle, 1)
QE = VectorElement("Quadrature", triangle, 2)
```

Note that we use two points when declaring the `QuadratureElement`. This is because the RHS of `Tangent.form` is second order and therefore we need two points for exact integration. Due to consistency issues, when passing functions around between the forms, we also need to use two points when declaring the `QuadratureElement` in the other forms.

Typical values of the relative residual for each Newton iteration for all three approaches are shown in the table below. It is to be noted that the convergence rate is quadratic as it should be for all three methods.

Relative residuals for each approach for linear elements:

Iteration	REF1	FE1	QE1
1	6.3e-02	6.3e-02	6.3e-02
2	5.3e-04	5.3e-04	5.3e-04

3	$3.7\text{e-}08$	$3.7\text{e-}08$	$3.7\text{e-}08$
4	$2.9\text{e-}16$	$2.9\text{e-}16$	$2.5\text{e-}16$

However, if quadratic elements are used to interpolate the unknown field u , the order of all elements in the above forms is increased by 1. This influences the convergence rate as seen in the table below. Clearly, using the standard `FiniteElement` leads to a poor convergence whereas the `QuadratureElement` still leads to quadratic convergence.

Relative residuals for each approach for quadratic elements:

Iteration	REF2	FE2	QE2
1	$2.6\text{e-}01$	$3.9\text{e-}01$	$2.6\text{e-}01$
2	$1.1\text{e-}02$	$4.6\text{e-}02$	$1.1\text{e-}02$
3	$1.2\text{e-}05$	$1.1\text{e-}02$	$1.6\text{e-}05$
4	$1.1\text{e-}11$	$7.2\text{e-}04$	$9.1\text{e-}09$

More examples

Feel free to send additional demo form files for your favourite PDE to the UFL mailing list.

Internal representation details

This chapter explains how UFL forms and expressions are represented in detail. Most operations are mirrored by a representation class, e.g., `Sum` and `Product`, which are subclasses of `Expr`. You can import all of them from the submodule `ufl.classes` by

```
from ufl.classes import *
```

Structure of a form

Each `Form` owns multiple `Integral` instances, each associated with a different `Measure`. An `Integral` owns a `Measure` and an `Expr`, which represents the integrand expression. The `Expr` is the base class of all expressions. It has two direct subclasses `Terminal` and `Operator`.

Subclasses of `Terminal` represent atomic quantities which terminate the expression tree, e.g. they have no subexpressions. Subclasses of `Operator` represent operations on one or more other expressions, which may usually be `Expr` subclasses of arbitrary type. Different `Operators` may have restrictions on some properties of their arguments.

All the types mentioned here are conceptually immutable, i.e. they should never be modified over the course of their entire lifetime. When a modified expression, measure, integral, or form is needed, a new instance must be created, possibly sharing some data with the old one. Since the shared data is also immutable, sharing can cause no problems.

General properties of expressions

Any UFL expression has certain properties, defined by functions that every `Expr` subclass must implement. In the following, `u` represents an arbitrary UFL expression, i.e. an instance of an arbitrary `Expr` subclass.

operands

`u.operands()` returns a tuple with all the operands of `u`, which should all be `Expr` instances.

reconstruct

`u.reconstruct(operands)` returns a new `Expr` instance representing the same operation as `u` but with other operands. Terminal objects may simply return `self` since all `Expr` instances are immutable. An important invariant is that `u.reconstruct(u.operands()) == u`.

cell

`u.cell()` returns the first `Cell` instance found in `u`. It is currently assumed in UFL that no two different cells are used in a single form. Not all expression define a cell, in which case this returns `None` and `u` is spatially constant. Note that this property is used in some algorithms.

shape

`u.shape()` returns a tuple of integers, which is the tensor shape of `u`.

free_indices

`u.free_indices()` returns a tuple of `Index` objects, which are the unassigned, free indices of `u`.

index_dimensions

`u.index_dimensions()` returns a dict mapping from each `Index` instance in `u.free_indices()` to the integer dimension of the value space each index can range over.

str(u)

`str(u)` returns a human-readable string representation of `u`.

repr(u)

`repr(u)` returns a Python string representation of `u`, such that `eval(repr(u)) == u` holds in Python.

hash(u)

`hash(u)` returns a hash code for `u`, which is used extensively (indirectly) in algorithms whenever `u` is placed in a Python dict or set.

u == v

`u == v` returns true if and only if `u` and `v` represents the same expression in the exact same way. This is used extensively (indirectly) in algorithms whenever `u` is placed in a Python dict or set.

About other relational operators

In general, UFL expressions are not possible to fully evaluate since the cell and the values of form arguments are not available. Implementing relational operators for immediate evaluation is therefore impossible.

Overloading relational operators as a part of the form language is not possible either, since it interferes with the correct use of container types in Python like `dict` or `set`.

Elements

All finite element classes have a common base class `FiniteElementBase`. The class hierarchy looks like this:

TODO: Class figure. ... TODO: Describe all `FiniteElementBase` subclasses here.

Terminals

All `Terminal` subclasses have some non-`Expr` data attached to them. `ScalarValue` has a Python scalar, `Coefficient` has a `FiniteElement`, etc.

Therefore, a unified implementation of `reconstruct` is not possible, but since all `Expr` instances are immutable, `reconstruct` for terminals can simply return `self`. This feature and the immutability property is used extensively in algorithms.

Operators

All instances of `Operator` subclasses are fully specified by their type plus the tuple of `Expr` instances that are the operands. Their constructors should take these operands as the positional arguments, and only that. This way, a unified implementation of `reconstruct` is possible, by simply calling the constructor with new operands. This feature is used extensively in algorithms.

Extending UFL

Adding new types to the UFL class hierarchy must be done with care. If you can get away with implementing a new operator as a combination of existing ones, that is the easiest route. The reason is that only some of the properties of an operator is represented by the `Expr` subclass. Other properties are part of the various algorithms in UFL. One example is derivatives, which are defined in the differentiation algorithm, and how to render a type to the `LaTeX` or dot formats. These properties could be merged into the class hierarchy, but other properties like how to map a UFL type to some `ffc` or `dolfin` type cannot be part of UFL. So before adding a new class, consider that doing so may require changes in multiple algorithms and even other projects.

Algorithms

Algorithms to work with UFL forms and expressions can be found in the submodule `ufl.algorithms`. You can import all of them with the line

```
from ufl.algorithms import *
```

This chapter gives an overview of (most of) the implemented algorithms. The intended audience is primarily developers, but advanced users may find information here useful for debugging.

While domain specific languages introduce notation to express particular ideas more easily, which can reduce the probability of bugs in user code, they also add yet another layer of abstraction which can make debugging more difficult when the need arises. Many of the utilities described here can be useful in that regard.

Formatting expressions

Expressions can be formatted in various ways for inspection, which is particularly useful for debugging. We use the following as an example form for the formatting sections below:

```
element = FiniteElement("CG", triangle, 1)
v = TestFunction(element)
u = TrialFunction(element)
c = Coefficient(element)
f = Coefficient(element)
a = c*u*v*dx + f*v*ds
```

str

Compact, human readable pretty printing. Useful in interactive Python sessions. Example output of `str(a)`:

```
{ v_0 * v_1 * w_0 } * dx(<Mesh #1 with coordinates parameterized by <Lagrange vector
↪element of degree 1 on a triangle: 2 x <CG1 on a triangle>>>[everywhere], {})
+ { v_0 * w_1 } * ds(<Mesh #1 with coordinates parameterized by <Lagrange vector
↪element of degree 1 on a triangle: 2 x <CG1 on a triangle>>>[everywhere], {})
```

repr

Accurate description of an expression, with the property that `eval(repr(a)) == a`. Useful to see which representation types occur in an expression, especially if `str(a)` is ambiguous. Example output of `repr(a)`:

```
Form([Integral(Product(Argument(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle,
↪1, dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 0, None),
↪Product(Argument(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1, dim=2), -1),
↪FiniteElement('Lagrange', triangle, 1)), 1, None),
↪Coefficient(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1, dim=2), -1),
↪FiniteElement('Lagrange', triangle, 1))), 'cell', Mesh(VectorElement('Lagrange
↪', triangle, 1, dim=2), -1), 'everywhere', {}, None),
↪Integral(Product(Argument(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1,
↪dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 0, None),
↪Coefficient(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1, dim=2), -1),
↪FiniteElement('Lagrange', triangle, 1)), 1), 'exterior_facet', Mesh(VectorElement(
↪'Lagrange', triangle, 1, dim=2), -1), 'everywhere', {}, None]))])
```

Tree formatting

ASCII tree formatting, useful to inspect the tree structure of an expression in interactive Python sessions. Example output of `tree_format(a)`:

```
Form:
  Integral:
    integral type: cell
    subdomain id: everywhere
    integrand:
      Product
      (
        Argument(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1, dim=2), -1),
↪FiniteElement('Lagrange', triangle, 1)), 0, None)
```

```

Product
(
    Argument(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, dim=2), -  
→1), FiniteElement('Lagrange', triangle, 1)), 1, None)
    Coefficient(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, _  
→dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 0)
)
)
Integral:
integral type: exterior_facet
subdomain id: everywhere
integrand:
Product
(
    Argument(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, dim=2), -1), _  
→FiniteElement('Lagrange', triangle, 1)), 0, None)
    Coefficient(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, dim=2), -  
→1), FiniteElement('Lagrange', triangle, 1)), 1)
)

```

Inspecting and manipulating the expression tree

This subsection is mostly for form compiler developers and technically interested users.

Traversing expressions

`iter_expressions`

Example usage:

```
for e in iter_expressions(a):
    print str(e)
```

outputs:

```
v_0 * v_1 * w_0
v_0 * w_1
```

Transforming expressions

So far we presented algorithms meant to inspect expressions in various ways. Some recurring patterns occur when writing algorithms to modify expressions, either to apply mathematical transformations or to change their representation. Usually, different expression node types need different treatment.

To assist in such algorithms, UFL provides the `Transformer` class. This implements a variant of the Visitor pattern to enable easy definition of transformation rules for the types you wish to handle.

Shown here is maybe the simplest transformer possible:

```
class Printer(Transformer):
    def __init__(self):
        Transformer.__init__(self)
```

```

def expr(self, o, *operands):
    print "Visiting", str(o), "with operands:"
    print ", ".join(map(str,operands))
    return o

element = FiniteElement("CG", triangle, 1)
v = TestFunction(element)
u = TrialFunction(element)
a = u*v

p = Printer()
p.visit(a)

```

The call to `visit` will traverse `a` and call `Printer.expr` on all expression nodes in post-order, with the argument `operands` holding the return values from visits to the operands of `o`. The output is:

```

Visiting v_0 * v_1 with operands:
v_0, v_1

```

$(v_h^0)(v_h^1)$

Implementing `expr` above provides a default handler for any expression node type. For each subclass of `Expr` you can define a handler function to override the default by using the name of the type in underscore notation, e.g. `vector_constant` for `VectorConstant`. The constructor of `Transformer` and implementation of `Transformer.visit` handles the mapping from type to handler function automatically.

Here is a simple example to show how to override default behaviour:

```

from ufl.classes import *
class CoefficientReplacer(Transformer):
    def __init__(self):
        Transformer.__init__(self)

    expr = Transformer.reuse_if_possible
    terminal = Transformer.always_reuse

    def coefficient(self, o):
        return FloatValue(3.14)

element = FiniteElement("CG", triangle, 1)
v = TestFunction(element)
f = Coefficient(element)
a = f*v

r = CoefficientReplacer()
b = r.visit(a)
print b

```

which outputs

```
3.14 * v_0
```

The output of this code is the transformed expression `b == 3.14*v`. This code also demonstrates how to reuse existing handlers. The handler `Transformer.reuse_if_possible` will return the input object if the operands have not changed, and otherwise reconstruct a new instance of the same type but with the new transformed operands. The handler `Transformer.always_reuse` always reuses the instance without recursing into its children, usually applied to terminals. To set these defaults with less code, inherit `ReuseTransformer` instead of `Transformer`.

This ensures that the parts of the expression tree that are not changed by the transformation algorithms will always reuse the same instances.

We have already mentioned the difference between pre-traversal and post-traversal, and some times you need to combine the two. `Transformer` makes this easy by checking the number of arguments to your handler functions to see if they take transformed operands as input or not. If a handler function does not take more than a single argument in addition to `self`, its children are not visited automatically, and the handler function must call `visit` on its operands itself.

Here is an example of mixing pre- and post-traversal:

```
class Traverser(ReuseTransformer):
    def __init__(self):
        ReuseTransformer.__init__(self)

    def sum(self, o):
        operands = o.operands()
        newoperands = []
        for e in operands:
            newoperands.append( self.visit(e) )
        return sum(newoperands)

element = FiniteElement("CG", triangle, 1)
f = Coefficient(element)
g = Coefficient(element)
h = Coefficient(element)
a = f+g+h

r = Traverser()
b = r.visit(a)
print b
```

This code inherits the `ReuseTransformer` as explained above, so the default behaviour is to recurse into children first and then call `Transformer.reuse_if_possible` to reuse or reconstruct each expression node. Since `sum` only takes `self` and the expression node instance `o` as arguments, its children are not visited automatically, and `sum` explicitly calls `self.visit` to do this.

Automatic differentiation implementation

This subsection is mostly for form compiler developers and technically interested users.

First of all, we give a brief explanation of the algorithm. Recall that a `Coefficient` represents a sum of unknown coefficients multiplied with unknown basis functions in some finite element space.

$$w(x) = \sum_k w_k \phi_k(x)$$

Also recall that an `Argument` represents any (unknown) basis function in some finite element space.

$$v(x) = \phi_k(x), \quad \phi_k \in V_h.$$

A form $L(v; w)$ implemented in UFL is intended for discretization like

$$b_i = L(\phi_i; \sum_k w_k \phi_k), \quad \forall \phi_i \in V_h.$$

The Jacobi matrix A_{ij} of this vector can be obtained by differentiation of b_i w.r.t. w_j , which can be written

$$A_{ij} = \frac{db_i}{dw_j} = a(\phi_i, \phi_j; \sum_k w_k \phi_k), \quad \forall \phi_i \in V_h, \quad \forall \phi_j \in V_h,$$

for some form a . In UFL, the form a can be obtained by differentiating L . To manage this, we note that as long as the domain Ω is independent of w_j , \int_{Ω} commutes with $\frac{d}{dw_j}$, and we can differentiate the integrand expression instead, e.g.,

$$L(v; w) = \int_{\Omega} I_c(v; w) dx + \int_{\partial\Omega} I_e(v; w) ds,$$

$$\frac{d}{dw_j} L(v; w) = \int_{\Omega} \frac{dI_c}{dw_j} dx + \int_{\partial\Omega} \frac{dI_e}{dw_j} ds.$$

In addition, we need that

$$\frac{dw}{dw_j} = \phi_j, \quad \forall \phi_j \in V_h,$$

which in UFL can be represented as

$$w = \text{Coefficient(element)},$$

$$v = \text{Argument(element)},$$

$$\frac{dw}{dw_j} = v,$$

since w represents the sum and v represents any and all basis functions in V_h .

Other operators have well defined derivatives, and by repeatedly applying the chain rule we can differentiate the integrand automatically.

Computational graphs

This section is for form compiler developers and is probably of no interest to end-users.

An expression tree can be seen as a directed acyclic graph (DAG). To aid in the implementation of form compilers, UFL includes tools to build a linearized¹ computational graph from the abstract expression tree.


A graph can be partitioned into subgraphs based on dependencies of subexpressions, such that a quadrature based compiler can easily place subexpressions inside the right sets of loops.

The computational graph

Consider the expression

$$f = (a + b) * (c + d)$$

where a, b, c, d are arbitrary scalar expressions. The *expression tree* for f looks like this:



In UFL f is represented like this expression tree. If a, b, c, d are all distinct Coefficient instances, the UFL representation will look like this:

¹ Linearized as in a linear datastructure, do not confuse this with automatic differentiation.

```
Coefficient Coefficient Coefficient Coefficient
  \   /     \   /
    Sum     Sum
      \       /
      --- Product ---
```

If we instead have the expression

$$f = (a + b) * (a - b)$$

the tree will in fact look like this, with the functions a and b only represented once:

```
Coefficient      Coefficient
|      \   /      |
|      Sum     Product -- IntValue(-1)
|      |       |
|      Product  |
|      |       |
|----- Sum -----|
```

The expression tree is a directed acyclic graph (DAG) where the vertices are Expr instances and each edge represents a direct dependency between two vertices, i.e. that one vertex is among the operands of another. A graph can also be represented in a linearized data structure, consisting of an array of vertices and an array of edges. This representation is convenient for many algorithms. An example to illustrate this graph representation follows:

```
G = V, E
V = [a, b, a+b, c, d, c+d, (a+b)*(c+d)]
E = [(6,2), (6,5), (5,3), (5,4), (2,0), (2,1)]
```

In the following, this representation of an expression will be called the *computational graph*. To construct this graph from a UFL expression, simply do

```
G = Graph(expression)
V, E = G
```

The Graph class can build some useful data structures for use in algorithms:

```
Vin = G.Vin() # Vin[i] = list of vertex indices j such that there is an edge from ↵ V[j] to V[i]
Vout = G.Vout() # Vout[i] = list of vertex indices j such that there is an edge from ↵ V[i] to V[j]
Ein = G.Ein() # Ein[i] = list of edge indices j such that E[j] is an edge to V[i], ↵ e.g. E[j][1] == i
Eout = G.Eout() # Eout[i] = list of edge indices j such that E[j] is an edge from ↵ V[i], e.g. E[j][0] == i
```

The ordering of the vertices in the graph can in principle be arbitrary, but here they are ordered such that

$$v_i \prec v_j, \quad \forall j > i,$$

where $a \prec b$ means that a does not depend on b directly or indirectly.

Another property of the computational graph built by UFL is that no identical expression is assigned to more than one vertex. This is achieved efficiently by inserting expressions in a dict (a hash map) during graph building.

In principle, correct code can be generated for an expression from its computational graph simply by iterating over the vertices and generating code for each one separately. However, we can do better than that.

Partitioning the graph

To help generate better code efficiently, we can partition vertices by their dependencies, which allows us to, e.g., place expressions outside the quadrature loop if they don't depend (directly or indirectly) on the spatial coordinates. This is done simply by

```
P = partition(G)
```

Commandline utilities

See installed version: `ufl-analyse`

Run

```
# ufl-version
```

to see the currently installed version of UFL printed to the terminal.

Validation and debugging: `ufl-analyse`

The command `ufl-analyse` loads all forms found in a `.ufl` file, tries to discover any errors in them, and prints various kinds of information about each form. Basic usage is

```
# ufl-analyse myform.ufl
```

For more information, type

```
# ufl-analyse --help
```

Note: This script is not well maintained, you will likely get more useful information from your form compiler.

Formatting and visualization: `ufl-convert`

The command `ufl-convert` loads all forms found in a `.ufl` file, compiles them into a different form or extracts some information from them, and writes the result in a suitable file format.

To try this tool, go to the `demo/` directory of the UFL source tree. Some of the features to try are basic printing of `str` and `repr` string representations of each form:

```
# ufl-convert --format=str stiffness.ufl
# ufl-convert --format=repr stiffness.ufl
```

compilation of forms to mathematical notation in LaTeX:

```
# ufl-convert --filetype=pdf --format=tex --show=1 stiffness.ufl
```

LaTeX output of forms after processing with UFL compiler utilities:

```
# ufl-convert -tpdf -ftex -s1 --compile=1 stiffness.ufl
```

and visualization of expression trees using graphviz via compilation of forms to the dot format:

```
# ufl-convert -tpdf -fdot -sl stiffness.ufl
```

Type `ufl-convert --help` for more details.

ufl package

Subpackages

ufl.algorithms package

Submodules

ufl.algorithms.ad module

Front-end for AD routines.

```
ufl.algorithms.ad.expand_derivatives(form, **kwargs)
```

Expand all derivatives of expr.

In the returned expression g which is mathematically equivalent to expr, there are no VariableDerivative or CoefficientDerivative objects left, and Grad objects have been propagated to Terminal nodes.

ufl.algorithms.analysis module

Utility algorithms for inspection of and information extraction from UFL objects in various ways.

```
ufl.algorithms.analysis.extract_arguments(a)
```

Build a sorted list of all arguments in a, which can be a Form, Integral or Expr.

```
ufl.algorithms.analysis.extract_arguments_and_coefficients(a)
```

Build two sorted lists of all arguments and coefficients in a, which can be a Form, Integral or Expr.

```
ufl.algorithms.analysis.extract_coefficients(a)
```

Build a sorted list of all coefficients in a, which can be a Form, Integral or Expr.

```
ufl.algorithms.analysis.extract_elements(form)
```

Build sorted tuple of all elements used in form.

```
ufl.algorithms.analysis.extract_sub_elements(elements)
```

Build sorted tuple of all sub elements (including parent element).

```
ufl.algorithms.analysis.extract_type(a, ufl_type)
```

Build a set of all objects of class `ufl_type` found in a. The argument a can be a Form, Integral or Expr.

```
ufl.algorithms.analysis.extract_unique_elements(form)
```

Build sorted tuple of all unique elements used in form.

```
ufl.algorithms.analysis.has_exact_type(a, ufl_type)
```

Return if an object of class `ufl_type` can be found in a. The argument a can be a Form, Integral or Expr.

```
ufl.algorithms.analysis.has_type(a, ufl_type)
```

Return if an object of class `ufl_type` can be found in a. The argument a can be a Form, Integral or Expr.

`ufl.algorithms.analysis.sort_elements(elements)`

Sort elements so that any sub elements appear before the corresponding mixed elements. This is useful when sub elements need to be defined before the corresponding mixed elements.

The ordering is based on sorting a directed acyclic graph.

`ufl.algorithms.analysis.unique_tuple(objects)`

Return tuple of unique objects, preserving initial ordering.

ufl.algorithms.apply_algebra_lowering module

Algorithm for expanding compound expressions into equivalent representations using basic operators.

`class ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra`

Bases: `ufl.corealg.multifunction.MultiFunction`

Expands high level compound operators (e.g. inner) to equivalent representations using basic operators (e.g. index notation).

`alternative_dot(o, a, b)`

`alternative_inner(o, a, b)`

`cofactor(o, A)`

`cross(o, a, b)`

`curl(o, a)`

`determinant(o, A)`

`deviatoric(o, A)`

`div(o, a)`

`dot(o, a, b)`

`expr(o, *ops)`

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

`inner(o, a, b)`

`inverse(o, A)`

`nabla_div(o, a)`

`nabla_grad(o, a)`

`outer(o, a, b)`

`skew(o, A)`

`sym(o, A)`

`trace(o, A)`

`transposed(o, A)`

```
ufl.algorithms.apply_algebra_lowering.apply_algebra_lowering(expr)
    Expands high level compound operators (e.g. inner) to equivalent representations using basic operators (e.g. index notation).
```

ufl.algorithms.apply_derivatives module

This module contains the apply_derivatives algorithm which computes the derivatives of a form of expression.

```
class ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher
```

Bases: *ufl.corealg.multifunction.MultiFunction*

```
coefficient_derivative(o,f,dummy_w,dummy_v,dummy_cd)
```

```
derivative(o)
```

```
expr(o,*ops)
```

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

```
grad(o,f)
```

```
indexed(o,Ap,ii)
```

```
reference_grad(o,f)
```

```
terminal(o)
```

```
variable_derivative(o,f,dummy_v)
```

```
class ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset(coefficients,
    arguments, coefficient_derivatives)
```

Bases: *ufl.algorithms.apply_derivatives.GenericDerivativeRuleset*

Apply AFD (Automatic Functional Differentiation) to expression.

Implements rules for the Gateaux derivative $D_w[v](\dots)$ defined as

$$D_w[v](e) = d/d\tau e(w+\tau v)|_{\tau=0}$$

```
argument(o)
```

Return a zero with the right shape for terminals independent of differentiation variable.

```
cell_avg(o,fp)
```

```
coefficient(o)
```

```
facet_avg(o,fp)
```

```
geometric_quantity(o)
```

Return a zero with the right shape for terminals independent of differentiation variable.

```
grad(g)
```

```
reference_grad(o)
```

```
reference_value(o)
```

```
class ufl.algorithms.apply_derivatives.GenericDerivativeRuleset(var_shape)
```

Bases: *ufl.corealg.multifunction.MultiFunction*

`abs` (*o, df*)
`acos` (*o, fp*)
`asin` (*o, fp*)
`atan` (*o, fp*)
`atan_2` (*o, fp, gp*)
`bessel_i` (*o, nup, fp*)
`bessel_j` (*o, nup, fp*)
`bessel_k` (*o, nup, fp*)
`bessel_y` (*o, nup, fp*)
`binary_condition` (*o, dl, dr*)
`cell_avg` (*o*)
`component_tensor` (*o, Ap, ii*)
`conditional` (*o, unused_dc, dt, df*)
`constant_value` (*o*)
 Return a zero with the right shape for terminals independent of differentiation variable.
`cos` (*o, fp*)
`cosh` (*o, fp*)
`derivative` (*o*)
`division` (*o, fp, gp*)
`erf` (*o, fp*)
`exp` (*o, fp*)
`expr` (*o*)
`facet_avg` (*o*)
`fixme` (*o*)
`form_argument` (*o*)
`geometric_quantity` (*o*)
`grad` (*o*)
`independent_operator` (*o*)
 Return a zero with the right shape and indices for operators independent of differentiation variable.
`independent_terminal` (*o*)
 Return a zero with the right shape for terminals independent of differentiation variable.
`index_sum` (*o, Ap, i*)
`indexed` (*o, Ap, ii*)
`label` (*o*)
 Labels and indices are not differentiable. It's convenient to return the non-differentiated object.
`list_tensor` (*o, *dops*)
`ln` (*o, fp*)

```
math_function(o, df)
max_value(o, df, dg)
min_value(o, df, dg)
multi_index(o)
    Labels and indices are not differentiable. It's convenient to return the non-differentiated object.

non_differentiable_terminal(o)
    Labels and indices are not differentiable. It's convenient to return the non-differentiated object.

not_condition(o, c)

override(o)

power(o, fp, gp)

product(o, da, db)

restricted(o, fp)

sin(o, fp)

sinh(o, fp)

sqrt(o, fp)

sum(o, da, db)

tan(o, fp)

tanh(o, fp)

unexpected(o)

variable(o, df, unused_l)

class ufl.algorithms.apply_derivatives.GradRuleset(geometric_dimension)
Bases: ufl.algorithms.apply\_derivatives.GenericDerivativeRuleset

argument(o)

cell_avg(o)
    Return a zero with the right shape and indices for operators independent of differentiation variable.

cell_coordinate(o)
     $dX/dx = \text{inv}(dx/dX) = \text{inv}(J) = K$ 

coefficient(o)

facet_avg(o)
    Return a zero with the right shape and indices for operators independent of differentiation variable.

geometric_quantity(o)
    Default for geometric quantities is  $dg/dx = 0$  if piecewise constant, otherwise keep  $\text{Grad}(g)$ . Override for specific types if other behaviour is needed.

grad(o)
    Represent  $\text{grad}(\text{grad}(f))$  as  $\text{Grad}(\text{Grad}(f))$ .

jacobian_inverse(o)

reference_grad(o)

reference_value(o)
```

```

spatial_coordinate(o)
dx/dx = I

class ufl.algorithms.apply_derivatives.ReferenceGradRuleset(topological_dimension)
Bases: ufl.algorithms.apply_derivatives.GenericDerivativeRuleset

argument(o)

cell_avg(o)
Return a zero with the right shape and indices for operators independent of differentiation variable.

cell_coordinate(o)
dX/dX = I

coefficient(o)

facet_avg(o)
Return a zero with the right shape and indices for operators independent of differentiation variable.

geometric_quantity(o)
dg/dX = 0 if piecewise constant, otherwise ReferenceGrad(g)

grad(o)

reference_grad(o)
Represent ref_grad(ref_grad(f)) as RefGrad(RefGrad(f)).

reference_value(o)

spatial_coordinate(o)
dx/dX = J

class ufl.algorithms.apply_derivatives.VariableRuleset(var)
Bases: ufl.algorithms.apply_derivatives.GenericDerivativeRuleset

argument(o)
Return a zero with the right shape for terminals independent of differentiation variable.

cell_avg(o)
Return a zero with the right shape and indices for operators independent of differentiation variable.

coefficient(o)
df/dv = Id if v is f else 0.

Note that if v = variable(f), df/dv is still 0, but if v == f, i.e. isinstance(v, Coefficient) == True, then df/dv
== df/f = Id.

facet_avg(o)
Return a zero with the right shape and indices for operators independent of differentiation variable.

geometric_quantity(o)
Return a zero with the right shape for terminals independent of differentiation variable.

grad(o)
Variable derivative of a gradient of a terminal must be 0.

reference_grad(o)
Variable derivative of a gradient of a terminal must be 0.

reference_value(o)

variable(o, df, l)

ufl.algorithms.apply_derivatives.apply_derivatives(expression)

```

ufl.algorithms.apply_function_pullbacks module

Algorithm for replacing gradients in an expression with reference gradients and coordinate mappings.

class ufl.algorithms.apply_function_pullbacks.FunctionPullbackApplier

Bases: *ufl.corealg.multifunction.MultiFunction*

expr (*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

form_argument (*o*)

terminal (*t*)

ufl.algorithms.apply_function_pullbacks.apply_function_pullbacks (*expr*)

Change representation of coefficients and arguments in expression by applying Piola mappings where applicable and representing all form arguments in reference value.

@param expr: An Expr.

ufl.algorithms.apply_function_pullbacks.apply_single_function_pullbacks (*g*)

ufl.algorithms.apply_function_pullbacks.create_nested_lists (*shape*)

ufl.algorithms.apply_function_pullbacks.reshape_to_nested_list (*components*,
shape)

ufl.algorithms.apply_function_pullbacks.sub_elements_with_mappings (*element*)

Return an ordered list of the largest subelements that have a defined mapping.

ufl.algorithms.apply_geometry_lowering module

Algorithm for lowering abstractions of geometric types.

This means replacing high-level types with expressions of mostly the Jacobian and reference cell data.

class ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier (*preserve_types=()*)

Bases: *ufl.corealg.multifunction.MultiFunction*

cell_coordinate (*o*)

cell_normal (*o*)

cell_volume (*o*)

circumradius (*o*)

expr (*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

facet_area (*o*)

```

facet_cell_coordinate(o)
facet_jacobian(o)
facet_jacobian_determinant(o)
facet_jacobian_inverse(o)
facet_normal(o)
jacobian(o)
jacobian_determinant(o)
jacobian_inverse(o)
max_cell_edge_length(o)
max_facet_edge_length(o)
min_cell_edge_length(o)
min_facet_edge_length(o)
spatial_coordinate(o)
terminal(t)

ufl.algorithms.apply_geometry_lowering.apply_geometry_lowering(form,      pre-
                                                               serve_types=())

```

Change GeometricQuantity objects in expression to the lowest level GeometricQuantity objects.

Assumes the expression is preprocessed or at least that derivatives have been expanded.

@param form: An Expr or Form.

ufl.algorithms.apply_integral_scaling module

Algorithm for replacing gradients in an expression with reference gradients and coordinate mappings.

```

ufl.algorithms.apply_integral_scaling.apply_integral_scaling(form)
    Multiply integrands by a factor to scale the integral to reference frame.

```

```

ufl.algorithms.apply_integral_scaling.compute_integrand_scaling_factor(integral)
    Change integrand geometry to the right representations.

```

ufl.algorithms.apply_restrictions module

This module contains the apply_restrictions algorithm which propagates restrictions in a form towards the terminals.

```

class ufl.algorithms.apply_restrictions.DefaultRestrictionApplier(side=None)
    Bases: ufl.corealg.multifunction.MultiFunction

```

derivative(o)

facet_area(o)

Restrict a continuous quantity to default side if no current restriction is set.

facet_jacobian(o)

Restrict a continuous quantity to default side if no current restriction is set.

facet_jacobian_determinant(o)

Restrict a continuous quantity to default side if no current restriction is set.

facet_jacobian_inverse(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

facet_origin(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

max_facet_edge_length(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

min_facet_edge_length(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

operator(*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

restricted(*o*)**spatial_coordinate**(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

terminal(*o*)

class ufl.algorithms.apply_restrictions.**RestrictionPropagator**(*side=None*)
Bases: *ufl.corealg.multifunction.MultiFunction*

argument(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

cell_avg(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

coefficient(*o*)

Allow coefficients to be unrestricted (apply default if so) if the values are fully continuous across the facet.

constant_value(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

facet_avg(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

facet_coordinate(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

facet_normal(*o*)**geometric_cell_quantity**(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

geometric_facet_quantity(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

grad(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

label(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

multi_index(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

operator (*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

quadrature_weight (*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

reference_cell_volume (*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

reference_facet_volume (*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

reference_value (*o*)

Reference value of something follows same restriction rule as the underlying object.

restricted (*o*)

When hitting a restricted quantity, visit child with a separate restriction algorithm.

terminal (*o*)**variable** (*o*, *op*, *label*)

Strip variable.

`ufl.algorithms.apply_restrictions.apply_default_restrictions(expression)`

Some terminals can be restricted from either side.

This applies a default restriction to such terminals if unrestricted.

`ufl.algorithms.apply_restrictions.apply_restrictions(expression)`

Propagate restriction nodes to wrap differential terminals directly.

ufl.algorithms.change_to_reference module

Algorithm for replacing gradients in an expression with reference gradients and coordinate mappings.

`class ufl.algorithms.change_to_reference.NEWChangeToReferenceGrad`

Bases: `ufl.corealg.multifunction.MultiFunction`

cell_avg (*o*, **dummy_ops*)**coefficient_derivative** (*o*, **dummy_ops*)**expr** (*o*, **ops*)**facet_avg** (*o*, **dummy_ops*)**form_argument** (*t*)**geometric_quantity** (*t*)**grad** (*o*, **dummy_ops*)

Store modifier state.

reference_grad (*o*, **dummy_ops*)**restricted** (*o*, **dummy_ops*)

Store modifier state.

terminal(*o*)**class** ufl.algorithms.change_to_reference.**OLDChangeToReferenceGrad**
Bases: *ufl.corealg.multifunction.MultiFunction***coefficient_derivative**(*o*)**expr**(*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

grad(*o*)**reference_grad**(*o*)**terminal**(*o*)

```
ufl.algorithms.change_to_reference.change_integrand_geometry_representation(integrand,  
scale,  
in-  
te-  
gral_type)
```

Change integrand geometry to the right representations.

ufl.algorithms.change_to_reference.change_to_reference_grad(*e*)

Change Grad objects in expression to products of JacobianInverse and ReferenceGrad.

Assumes the expression is preprocessed or at least that derivatives have been expanded.

@param *e*: An Expr or Form.

ufl.algorithms.check_arities module

class ufl.algorithms.check_arities.**ArityChecker**(*arguments*)Bases: *ufl.corealg.multifunction.MultiFunction***argument**(*o*)**cell_avg**(*o*, *a*)**component_tensor**(*o*, *a*, *i*)**conditional**(*o*, *c*, *a*, *b*)**division**(*o*, *a*, *b*)**dot**(*o*, *a*, *b*)**expr**(*o*)**facet_avg**(*o*, *a*)**grad**(*o*, *a*)**index_sum**(*o*, *a*, *i*)**indexed**(*o*, *a*, *i*)**inner**(*o*, *a*, *b*)

```

linear_indexed_type(o, a, i)
linear_operator(o, a)
list_tensor(o, *ops)
negative_restricted(o, a)
nonlinear_operator(o)
outer(o, a, b)
positive_restricted(o, a)
product(o, a, b)
reference_grad(o, a)
reference_value(o, a)
sum(o, a, b)
terminal(o)
variable(o, f, l)

exception ufl.algorithms.check_arities.ArityMismatch
    Bases: ufl.log.UFLEException

ufl.algorithms.check_arities.check_form_arity(form, arguments)
ufl.algorithms.check_arities.check_integrand_arity(expr, arguments)

```

ufl.algorithms.check_restrictions module

Algorithms related to restrictions.

```

class ufl.algorithms.check_restrictions.RestrictionChecker(require_restriction)
    Bases: ufl.corealg.multifunction.MultiFunction

    expr(o)
    facet_normal(o)
    form_argument(o)
    restricted(o)

ufl.algorithms.check_restrictions.check_restrictions(expression, require_restriction)

```

re-

Check that types that must be restricted are restricted in expression.

ufl.algorithms.checks module

Functions to check the validity of forms.

```

ufl.algorithms.checks.validate_form(form)

```

Performs all implemented validations on a form. Raises exception if something fails.

ufl.algorithms.compute_form_data module

This module provides the compute_form_data function which form compilers will typically call prior to code generation to preprocess/simplify a raw input form given by a user.

```
ufl.algorithms.compute_form_data.attach_estimated_degrees(form)
```

Attach estimated polynomial degree to a form's integrals.

Parameters `form` – The `Form` to inspect.

Returns A new Form with estimate degrees attached.

```
ufl.algorithms.compute_form_data.compute_form_data(form,
                                                    do_apply_function_pullbacks=False,
                                                    do_apply_integral_scaling=False,
                                                    do_apply_geometry_lowering=False,
                                                    preserve_geometry_types=(),
                                                    do_apply_default_restrictions=True,
                                                    do_apply_restrictions=True,
                                                    do_estimate_degrees=True)
```

ufl.algorithms.domain_analysis module

Algorithms for building canonical data structure for integrals over subdomains.

```
class ufl.algorithms.domain_analysis.ExprTupleKey(x)
```

Bases: object

`x`

```
class ufl.algorithms.domain_analysis.IntegralData(domain, integral_type, subdomain_id,
                                                    integrals, metadata)
```

Bases: object

Utility class with the members (`domain`, `integral_type`, `subdomain_id`, `integrals`, `metadata`)

where `metadata` is an empty dictionary that may be used for associating metadata with each object.

`domain`

`enabled_coefficients`

`integral_coefficients`

`integral_type`

`integrals`

`metadata`

`subdomain_id`

```
ufl.algorithms.domain_analysis.accumulate_integrands_with_same_metadata(integrals)
```

Taking input on the form: `integrals = [integral0, integral1, ...]`

Return result on the form:

```
integrands_by_id = [(integrand0, metadata0), (integrand1, metadata1), ...]
```

where `integrand0 < integrand1` by the canonical ufl expression ordering criteria.

```
ufl.algorithms.domain_analysis.build_integral_data(integrals)
```

Build integral data given a list of integrals.

Parameters `integrals` – An iterable of `Integral` objects.

Returns A tuple of `IntegralData` objects.

The integrals you pass in here must have been rearranged and gathered (removing the “everywhere” subdomain_id). To do this, you should call `group_form_integrals()`.

```
ufl.algorithms.domain_analysis.dicts_lt(a, b)
```

```
ufl.algorithms.domain_analysis.group_form_integrals(form, domains)
```

Group integrals by domain and type, performing canonical simplification.

Parameters

- `form` – the `Form` to group the integrals of.
- `domains` – an iterable of `Domains`.

Returns A new `Form` with gathered integrands.

```
ufl.algorithms.domain_analysis.group_integrals_by_domain_and_type(integrals,
                                                               domains)
```

Input: `integrals`: list of `Integral` objects `domains`: list of `AbstractDomain` objects from the parent `Form`

Output: `integrals_by_domain_and_type`: dict: (domain, integral_type) -> list(`Integral`)

```
ufl.algorithms.domain_analysis.integral_subdomain_ids(integral)
```

Get a tuple of integer subdomains or a valid string subdomain from integral.

```
ufl.algorithms.domain_analysis.rearrange_integrals_by_single_subdomains(integrals)
```

Rearrange integrals over multiple subdomains to single subdomain integrals.

Input: `integrals`: list(`Integral`)

Output: `integrals`: dict: subdomain_id -> list(`Integral`) (reconstructed with single subdomain_id)

```
ufl.algorithms.domain_analysis.reconstruct_form_from_integral_data(integral_data)
```

ufl.algorithms.elementtransformations module

This module provides helper functions to - FFC/DOLFIN adaptive chain, - UFL algorithms taking care of underspecified DOLFIN expressions.

```
ufl.algorithms.elementtransformations.increase_order(element)
```

Return element of same family, but a polynomial degree higher.

```
ufl.algorithms.elementtransformations.tear(element)
```

For a finite element, return the corresponding discontinuous element.

ufl.algorithms.estimate_degrees module

Algorithms for estimating polynomial degrees of expressions.

```
class ufl.algorithms.estimate_degrees.IrreducibleInt
```

Bases: int

Degree type used by quadrilaterals.

Unlike int, values of this type are not decremented by `_reduce_degree`.

```
class ufl.algorithms.estimate_degrees.SumDegreeEstimator(default_degree,           ele-
                                                               ment_replace_map)
```

Bases: *ufl.corealg.multifunction.MultiFunction*

This algorithm is exact for a few operators and heuristic for many.

abs (*v, a*)

This is a heuristic, correct if there is no

argument (*v*)

A form argument provides a degree depending on the element, or the default degree if the element has no degree.

atan_2 (*v, a, b*)

Using the heuristic $\text{degree}(\text{atan2}(\text{const}, \text{const})) == 0$ $\text{degree}(\text{atan2}(a, b)) == \max(\text{degree}(a), \text{degree}(b)) + 2$ which can be wildly inaccurate but at least gives a somewhat high integration degree.

bessel_function (*v, nu, x*)

Using the heuristic $\text{degree}(\text{bessel_}*(\text{const})) == 0$ $\text{degree}(\text{bessel_}*(x)) == \text{degree}(x) + 2$ which can be wildly inaccurate but at least gives a somewhat high integration degree.

cell_avg (*v, a*)

Cell average of a function is always cellwise constant.

cell_coordinate (*v*)

A coordinate provides one additional degree.

coefficient (*v*)

A form argument provides a degree depending on the element, or the default degree if the element has no degree.

cofactor (*v, *args*)

component_tensor (*v, A, ii*)

compound_derivative (*v, *args*)

compound_tensor_operator (*v, *args*)

condition (*v, *args*)

conditional (*v, c, t, f*)

Degree of condition does not influence degree of values which conditional takes. So heuristically taking max of true degree and false degree. This will be exact in cells where condition takes single value. For improving accuracy of quadrature near condition transition surface quadrature order must be adjusted manually.

constant_value (*v*)

Constant values are constant.

cross (*v, *ops*)

curl (*v, f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

derivative (*v, *args*)

determinant (*v, *args*)

deviatoric (*v, *args*)

div (*v, f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

division(*v*, **ops*)

Using the sum here is a heuristic. Consider e.g. $(x+1)/(x-1)$.

dot(*v*, **ops*)**expr**(*v*, **ops*)

For most operators we take the max degree of its operands.

facet_avg(*v*, *a*)

Facet average of a function is always cellwise constant.

geometric_quantity(*v*)

Some geometric quantities are cellwise constant. Others are nonpolynomial and thus hard to estimate.

grad(*v,f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

index_sum(*v*, *A*, *ii*)**indexed**(*v*, *A*, *ii*)**inner**(*v*, **ops*)**inverse**(*v*, **args*)**label**(*v*)**list_tensor**(*v*, **ops*)**math_function**(*v*, *a*)

Using the heuristic $\text{degree}(\sin(\text{const})) == 0$ $\text{degree}(\sin(a)) == \text{degree}(a)+2$ which can be wildly inaccurate but at least gives a somewhat high integration degree.

max_value(*v*, *l*, *r*)

Same as conditional.

min_value(*v*, *l*, *r*)

Same as conditional.

multi_index(*v*)**nabla_div**(*v,f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

nabla_grad(*v,f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

negative_restricted(*v*, *a*)**outer**(*v*, **ops*)**positive_restricted**(*v*, *a*)**power**(*v*, *a*, *b*)

If *b* is an integer: $\text{degree}(a^{**}b) == \text{degree}(a)*b$ otherwise use the heuristic $\text{degree}(a^{**}b) == \text{degree}(a)*2$

product(*v*, **ops*)**reference_curl**(*v,f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

reference_div(*v,f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

reference_grad(*v,f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

reference_value(*rv,f*)

skew(*v, *args*)

spatial_coordinate(*v*)

A coordinate provides additional degrees depending on coordinate field of domain.

sum(*v, *ops*)

sym(*v, *args*)

trace(*v, *args*)

transposed(*v,A*)

variable(*v, e, l*)

variable_derivative(*v, *args*)

```
ufl.algorithms.estimate_degrees.estimate_total_polynomial_degree(e, de-fault_degree=1, element_replace_map={})
```

Estimate total polynomial degree of integrand.

NB! Although some compound types are supported here, some derivatives and compounds must be preprocessed prior to degree estimation. In generic code, this algorithm should only be applied after preprocessing.

For coefficients defined on an element with unspecified degree (None), the degree is set to the given default degree.

ufl.algorithms.expand_compounds module

Algorithm for expanding compound expressions into equivalent representations using basic operators.

```
ufl.algorithms.expand_compounds.expand_compounds(e)
```

ufl.algorithms.expand_indices module

This module defines expression transformation utilities, for expanding free indices in expressions to explicit fixed indices only.

```
class ufl.algorithms.expand_indices.IndexExpander
    Bases: ufl.algorithms.transformer.ReuseTransformer
```

...

component()

Return current component tuple.

component_tensor(*x*)

conditional(*x*)

```

division(x)
form_argument(x)
grad(x)
index_sum(x)
indexed(x)
list_tensor(x)
multi_index(x)
scalar_value(x)
terminal(x)
zero(x)
ufl.algorithms.expand_indices.expand_indices(e)
ufl.algorithms.expand_indices.purge_list_tensors(expr)
    Get rid of all ListTensor instances by expanding expressions to use their components directly. Will usually
    increase the size of the expression.

```

ufl.algorithms.formdata module

FormData class easy for collecting of various data about a form.

```
class ufl.algorithms.formdata.ExprData
```

Bases: object

Class collecting various information extracted from a Expr by calling preprocess.

```
class ufl.algorithms.formdata.FormData
```

Bases: object

Class collecting various information extracted from a Form by calling preprocess.

ufl.algorithms.formfiles module

A collection of utility algorithms for handling UFL files.

```
class ufl.algorithms.formfiles.FileData
```

Bases: object

```
ufl.algorithms.formfiles.execute_ufl_code(uflcode, filename)
```

```
ufl.algorithms.formfiles.interpret_ufl_namespace(namespace)
```

Takes a namespace dict from an executed ufl file and converts it to a FileData object.

```
ufl.algorithms.formfiles.load_forms(filename)
```

Return a list of all forms in a file.

```
ufl.algorithms.formfiles.load_ufl_file(filename)
```

Load a .ufl file with elements, coefficients and forms.

```
ufl.algorithms.formfiles.read_lines_decoded(fn)
```

```
ufl.algorithms.formfiles.read_ufl_file(filename)
```

Read a .ufl file, handling file extension, file existence, and #include replacement.

```
ufl.algorithms.formfiles.replace_include_statements(lines)
Replace '#include foo.ufl' statements with contents of foo.ufl.
```

ufl.algorithms.formsplitter module

Extract part of a form in a mixed FunctionSpace.

```
class ufl.algorithms.formsplitter.FormSplitter
```

Bases: *ufl.corealg.multifunction.MultiFunction*

argument (*obj*)

expr (*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

multi_index (*obj*)

split (*form*, *ix*, *iy*=0)

```
ufl.algorithms.formsplitter.block_split(form, ix, iy=0)
```

ufl.algorithms.formtransformations module

This module defines utilities for transforming complete Forms into new related Forms.

```
class ufl.algorithms.formtransformations.PartExtractor(arguments)
```

Bases: *ufl.algorithms.transformer.Transformer*

PartExtractor extracts those parts of a form that contain the given argument(s).

argument (*x*)

Return itself unless itself provides too much.

cell_avg (*x*, *arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

component_tensor (*x*)

Return parts of expression belonging to this indexed expression.

division (*x*)

Return parts_of_numerator/denominator.

dot (*x*, **ops*)

Note: Product is a visit-children-first handler. ops are the visited factors.

expr (*x*)

The default is a nonlinear operator not accepting any Arguments among its children.

facet_avg (*x*, *arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

grad (*x*, *arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

index_sum(*x*)

Return parts of expression belonging to this indexed expression.

indexed(*x*)

Return parts of expression belonging to this indexed expression.

inner(*x, *ops*)

Note: Product is a visit-children-first handler. ops are the visited factors.

linear_indexed_type(*x*)

Return parts of expression belonging to this indexed expression.

linear_operator(*x, arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

list_tensor(*x, *ops*)**negative_restricted**(*x, arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

outer(*x, *ops*)

Note: Product is a visit-children-first handler. ops are the visited factors.

positive_restricted(*x, arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

product(*x, *ops*)

Note: Product is a visit-children-first handler. ops are the visited factors.

sum(*x*)

Return the terms that might eventually yield the correct parts(!)

The logic required for sums is a bit elaborate:

A sum may contain terms providing different arguments. We should return (a sum of) a suitable subset of these terms. Those should all provide the same arguments.

For each term in a sum, there are 2 simple possibilities:

1a) The relevant part of the term is zero -> skip. 1b) The term provides more arguments than we want -> skip

2) If all terms fall into the above category, we can just return zero.

Any remaining terms may provide exactly the arguments we want, or fewer. This is where things start getting interesting.

3) Bottom-line: if there are terms with providing different arguments – provide terms that contain the most arguments. If there are terms providing different sets of same size -> throw error (e.g. Argument(-1) + Argument(-2))

terminal(*x*)

The default is a nonlinear operator not accepting any Arguments among its children.

variable(*x*)

Return relevant parts of this variable.

ufl.algorithms.formtransformations.**compute_energy_norm**(*form, coefficient*)

Compute the a-norm of a Coefficient given a form a.

This works simply by replacing the two Arguments with a Coefficient on the same function space (element). The Form returned will thus be a functional with no Arguments, and one additional Coefficient at the end if no coefficient has been provided.

`ufl.algorithms.formtransformations.compute_form_action(form, coefficient)`

Compute the action of a form on a Coefficient.

This works simply by replacing the last Argument with a Coefficient on the same function space (element). The form returned will thus have one Argument less and one additional Coefficient at the end if no Coefficient has been provided.

`ufl.algorithms.formtransformations.compute_form_adjoint(form, re-ordered_arguments=None)`

Compute the adjoint of a bilinear form.

This works simply by swapping the number and part of the two arguments, but keeping their elements and places in the integrand expressions.

`ufl.algorithms.formtransformations.compute_form_arities(form)`

Return set of arities of terms present in form.

`ufl.algorithms.formtransformations.compute_form_functional(form)`

Compute the functional part of a form, that is the terms independent of Arguments.

(Used for testing, not sure if it's useful for anything?)

`ufl.algorithms.formtransformations.compute_form_lhs(form)`

Compute the left hand side of a form.

Example:

$a = u*v*dx + f*v*dx \quad a = \text{lhs}(a) \rightarrow u*v*dx$

`ufl.algorithms.formtransformations.compute_form_rhs(form)`

Compute the right hand side of a form.

Example:

$a = u*v*dx + f*v*dx \quad L = \text{rhs}(a) \rightarrow -f*v*dx$

`ufl.algorithms.formtransformations.compute_form_with_arity(form, arity, arguments=None)`

Compute parts of form of given arity.

`ufl.algorithms.formtransformations.zero_expr(e)`

ufl.algorithms.map_integrands module

Basic algorithms for applying functions to subexpressions.

`ufl.algorithms.map_integrands.map_integrand_dags(function, form, only_integral_type=None, compress=True)`

`ufl.algorithms.map_integrands.map_integrands(function, form, only_integral_type=None)`
Apply transform(expression) to each integrand expression in form, or to form if it is an Expr.

ufl.algorithms.multipfunction module

ufl.algorithms.renumbering module

Algorithms for renumbering of counted objects, currently variables and indices.

```

class ufl.algorithms.renumbering.IndexRenumberingTransformer
    Bases: ufl.algorithms.renumbering.VariableRenumberingTransformer

    This is a poorly designed algorithm. It is used in some tests, please do not use for anything else.

    index(o)
    multi_index(o)
    zero(o)

class ufl.algorithms.renumbering.VariableRenumberingTransformer
    Bases: ufl.algorithms.transformer.ReuseTransformer

    variable(o)

ufl.algorithms.renumbering.renumber_indices(expr)

```

ufl.algorithms.replace module

Algorithm for replacing terminals in an expression.

```

class ufl.algorithms.replace.Replacer(mapping)
    Bases: ufl.corealg.multifunction.MultiFunction

    coefficient_derivative(o)
    expr(o, *ops)
        Reuse object if operands are the same objects.

        Use in your own subclass by setting e.g.

```

```
expr = MultiFunction.reuse_if_un触ed
```

as a default rule.

```
terminal(o)
```

```
ufl.algorithms.replace.replace(e, mapping)
    Replace terminal objects in expression.

    @param e: An Expr or Form.

    @param mapping: A dict with from:to replacements to perform.
```

ufl.algorithms.signature module

Signature computation for forms.

```

ufl.algorithms.signature.compute_expression_hashdata(expression,           termi-
                                                 nal_hashdata)
ufl.algorithms.signature.compute_expression_signature(expr, renumbering)
ufl.algorithms.signature.compute_form_signature(form, renumbering)
ufl.algorithms.signature.compute_multiindex_hashdata(expr, index_numbering)
ufl.algorithms.signature.compute_terminal_hashdata(expressions, renumbering)

```

ufl.algorithms.transformer module

This module defines the Transformer base class and some basic specializations to further base other algorithms upon, as well as some utilities for easier application of such algorithms.

class ufl.algorithms.transformer.CopyTransformer (variable_cache=None)

Bases: *ufl.algorithms.transformer.Transformer*

expr (o, *operands)

Always reconstruct expr.

terminal (o)

Always reuse Expr (ignore children)

variable (o)

class ufl.algorithms.transformer.ReuseTransformer (variable_cache=None)

Bases: *ufl.algorithms.transformer.Transformer*

expr (o, *ops)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

expr = MultiFunction.reuse_if_untouched

as a default rule.

terminal (o)

Always reuse Expr (ignore children)

variable (o)

class ufl.algorithms.transformer.Transformer (variable_cache=None)

Bases: object

Base class for a visitor-like algorithm design pattern used to transform expression trees from one representation to another.

always_reconstruct (o, *operands)

Always reconstruct expr.

expr (o)

Trigger error.

print_visit_stack ()

reconstruct_variable (o)

reuse (o)

Always reuse Expr (ignore children)

reuse_if_possible (o, *ops)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

expr = MultiFunction.reuse_if_untouched

as a default rule.

reuse_if_untouched (o, *ops)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```

expr = MultiFunction.reuse_if_unouched
      as a default rule.

reuse_variable(o)
terminal(o)
      Always reuse Expr (ignore children)

undefined(o)
      Trigger error.

visit(o)

class ufl.algorithms.transformer.VariableStripper
      Bases: ufl.algorithms.transformer.ReuseTransformer

variable(o)

ufl.algorithms.transformer.apply_transformer(e, transformer, integral_type=None)
      Apply transformer.visit(expression) to each integrand expression in form, or to form if it is an Expr.

ufl.algorithms.transformer.is_post_handler(function)
      Is this a handler that expects transformed children as input?

ufl.algorithms.transformer.strip_variables(e)
      Replace all Variable instances with the expression they represent.

ufl.algorithms.transformer.ufl2ufl(e)
      Convert an UFL expression to a new UFL expression, with no changes. This is used for testing that objects in the expression behave as expected.

ufl.algorithms.transformer.ufl2uflcopy(e)
      Convert an UFL expression to a new UFL expression. All nonterminal object instances are replaced with identical copies, while terminal objects are kept. This is used for testing that objects in the expression behave as expected.

```

ufl.algorithms.traversal module

This module contains algorithms for traversing expression trees in different ways.

```
ufl.algorithms.traversal.iter_expressions(a)
      Utility function to handle Form, Integral and any Expr the same way when inspecting expressions. Returns an iterable over Expr instances: - a is an Expr: (a,) - a is an Integral: the integrand expression of a - a is a Form: all integrand expressions of all integrals
```

Module contents

This module collects algorithms and utility functions operating on UFL objects.

```
ufl.algorithms.estimate_total_polynomial_degree(e, default_degree=1, element_replace_map={})
      Estimate total polynomial degree of integrand.
```

NB! Although some compound types are supported here, some derivatives and compounds must be preprocessed prior to degree estimation. In generic code, this algorithm should only be applied after preprocessing.

For coefficients defined on an element with unspecified degree (None), the degree is set to the given default degree.

`ufl.algorithms.sort_elements(elements)`

Sort elements so that any sub elements appear before the corresponding mixed elements. This is useful when sub elements need to be defined before the corresponding mixed elements.

The ordering is based on sorting a directed acyclic graph.

```
ufl.algorithms.compute_form_data(form,
                                  do_apply_function_pullbacks=False,
                                  do_apply_integral_scaling=False,
                                  do_apply_geometry_lowering=False,
                                  preserve_geometry_types=(),
                                  do_apply_default_restrictions=True,
                                  do_apply_restrictions=True, do_estimate_degrees=True)
```

`ufl.algorithms.purge_list_tensors(expr)`

Get rid of all ListTensor instances by expanding expressions to use their components directly. Will usually increase the size of the expression.

`ufl.algorithms.apply_transformer(e, transformer, integral_type=None)`

Apply transformer.visit(expression) to each integrand expression in form, or to form if it is an Expr.

`class ufl.algorithms.ReuseTransformer(variable_cache=None)`

Bases: `ufl.algorithms.transformer.Transformer`

`expr(o, *ops)`

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

`expr = MultiFunction.reuse_if_untouched`

as a default rule.

`terminal(o)`

Always reuse Expr (ignore children)

`variable(o)`

`ufl.algorithms.load_ufl_file(filename)`

Load a .ufl file with elements, coefficients and forms.

`class ufl.algorithms.Transformer(variable_cache=None)`

Bases: `object`

Base class for a visitor-like algorithm design pattern used to transform expression trees from one representation to another.

`always_reconstruct(o, *operands)`

Always reconstruct expr.

`expr(o)`

Trigger error.

`print_visit_stack()`

`reconstruct_variable(o)`

`reuse(o)`

Always reuse Expr (ignore children)

`reuse_if_possible(o, *ops)`

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

`expr = MultiFunction.reuse_if_untouched`

as a default rule.

reuse_if_unouched(*o*, **ops*)
Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

reuse_variable(*o*)
terminal(*o*)
Always reuse Expr (ignore children)

undefined(*o*)
Trigger error.

visit(*o*)

class ufl.algorithms.MultiFunction
Bases: object

Base class for collections of non-recursive expression node handlers.

Subclass this (remember to call the `__init__` method of this class), and implement handler functions for each Expr type, using the lower case handler name of the type (`exprtype._ufl_handler_name_`).

This class is optimized for efficient type based dispatch in the `__call__` operator via typecode based lookup of the handler function bound to the algorithm object. Of course Python's function call overhead still applies.

expr(*o*, **args*)
Trigger error for types with missing handlers.

reuse_if_unouched(*o*, **ops*)
Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

undefined(*o*, **args*)
Trigger error for types with missing handlers.

ufl.algorithms.extract_unique_elements(*form*)
Build sorted tuple of all unique elements used in form.

ufl.algorithms.extract_type(*a*, *ufl_type*)
Build a set of all objects of class *ufl_type* found in *a*. The argument *a* can be a Form, Integral or Expr.

ufl.algorithms.extract_elements(*form*)
Build sorted tuple of all elements used in form.

ufl.algorithms.extract_sub_elements(*elements*)
Build sorted tuple of all sub elements (including parent element).

ufl.algorithms.expand_indices(*e*)

ufl.algorithms.replace(*e*, *mapping*)
Replace terminal objects in expression.

@param e: An Expr or Form.

@param mapping: A dict with from:to replacements to perform.

`ufl.algorithms.expand_derivatives (form, **kwargs)`
Expand all derivatives of expr.

In the returned expression g which is mathematically equivalent to expr, there are no VariableDerivative or CoefficientDerivative objects left, and Grad objects have been propagated to Terminal nodes.

`ufl.algorithms.extract_coefficients (a)`
Build a sorted list of all coefficients in a, which can be a Form, Integral or Expr.

`ufl.algorithms.strip_variables (e)`
Replace all Variable instances with the expression they represent.

`ufl.algorithms.post_traversal (expr)`
Yield o for each node o in *expr*, child before parent.

`ufl.algorithms.change_to_reference_grad (e)`
Change Grad objects in expression to products of JacobianInverse and ReferenceGrad.

Assumes the expression is preprocessed or at least that derivatives have been expanded.

@param e: An Expr or Form.

`ufl.algorithms.expand_compounds (e)`

`ufl.algorithms.validate_form (form)`
Performs all implemented validations on a form. Raises exception if something fails.

`ufl.algorithms.uf2late (expression)`

Generate LaTeX code for a UFL expression or form (wrapper for form2latex and expression2latex).

class ufl.algorithms.FormSplitter
Bases: `ufl.corealg.multifunction.MultiFunction`

argument (obj)

expr (o, *ops)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_un触ed
```

as a default rule.

multi_index (obj)

split (form, ix, iy=0)

`ufl.algorithms.extract_arguments (a)`

Build a sorted list of all arguments in a, which can be a Form, Integral or Expr.

`ufl.algorithms.compute_form_adjoint (form, reordered_arguments=None)`
Compute the adjoint of a bilinear form.

This works simply by swapping the number and part of the two arguments, but keeping their elements and places in the integrand expressions.

`ufl.algorithms.compute_form_action (form, coefficient)`
Compute the action of a form on a Coefficient.

This works simply by replacing the last Argument with a Coefficient on the same function space (element). The form returned will thus have one Argument less and one additional Coefficient at the end if no Coefficient has been provided.

`ufl.algorithms.compute_energy_norm(form, coefficient)`

Compute the a-norm of a Coefficient given a form a.

This works simply by replacing the two Arguments with a Coefficient on the same function space (element). The Form returned will thus be a functional with no Arguments, and one additional Coefficient at the end if no coefficient has been provided.

`ufl.algorithms.compute_form_lhs(form)`

Compute the left hand side of a form.

Example:

$a = u*v*dx + f*v*dx \quad a = \text{lhs}(a) \rightarrow u*v*dx$

`ufl.algorithms.compute_form_rhs(form)`

Compute the right hand side of a form.

Example:

$a = u*v*dx + f*v*dx \quad L = \text{rhs}(a) \rightarrow -f*v*dx$

`ufl.algorithms.compute_form_functional(form)`

Compute the functional part of a form, that is the terms independent of Arguments.

(Used for testing, not sure if it's useful for anything?)

`ufl.algorithms.compute_form_signature(form, renumbering)`

`ufl.algorithms.tree_format(expression, indentation=0, parentheses=True)`

ufl.core package

Submodules

ufl.core.compute_expr_hash module

Non-recursive traversal-based hash computation algorithm.

Fast iteration over nodes in an Expr DAG to compute memorized hashes for all unique nodes.

`ufl.core.compute_expr_hash.compute_expr_hash(expr)`

Compute hashes of `expr` and all its nodes efficiently, without using Python recursion.

ufl.core.expr module

This module defines the `Expr` class, the superclass for all expression tree node types in UFL.

NB! A note about other operators not implemented here:

More operators (special functions) on `Expr` instances are defined in `exprooperators.py`, as well as the transpose `A.T` and spatial derivative `a.dx(i)`. This is to avoid circular dependencies between `Expr` and its subclasses.

`class ufl.core.expr.Expr`

Bases: `object`

Base class for all UFL expression types.

Instance properties Every `Expr` instance will have certain properties. The most important ones are `ufl_operands`, `ufl_shape`, `ufl_free_indices`, and `ufl_index_dimensions` properties. Expressions are immutable and hashable.

Type traits The `Expr` API defines a number of type traits that each subclass needs to provide. Most of these are specified indirectly via the arguments to the `ufl_type` class decorator, allowing UFL to do some consistency checks and automate most of the traits for most types. Type traits are accessed via a class or instance object of the form `obj._ufl_traitname_`. See the source code for description of each type trait.

Operators Some Python special functions are implemented in this class, some are implemented in subclasses, and some are attached to this class in the `ufl_type` class decorator.

Defining subclasses To define a new expression class, inherit from either `Terminal` or `Operator`, and apply the `ufl_type` class decorator with suitable arguments. See the docstring of `ufl_type` for details on its arguments. Looking at existing classes similar to the one you wish to add is a good idea. Looking through the comments in the `Expr` class and `ufl_type` to understand all the properties that may need to be specified is also a good idea. Note that many algorithms in UFL and form compilers will need handlers implemented for each new type:::

```
@ufl_type()
class MyOperator(Operator):
    pass
```

Type collections All `Expr` subclasses are collected by `ufl_type` in global variables available via `Expr`.

Profiling Object creation statistics can be collected by doing

```
Expr.ufl_enable_profiling()
# ... run some code
initstats, delstats = Expr.ufl_disable_profiling()
```

Giving a list of creation and deletion counts for each typecode.

T

Transpose a rank-2 tensor expression. For more general transpose operations of higher order tensor expressions, use indexing and `Tensor`.

`dx(*ii)`

Return the partial derivative with respect to spatial variable number ii .

`evaluate(x, mapping, component, index_values)`

Evaluate expression at given coordinate with given values for terminals.

`geometric_dimension()`

Return the geometric dimension this expression lives in.

`static ufl_disable_profiling()`

Turn off the object counting mechanism. Return object init and del counts.

`ufl_domain()`

Return the single unique domain this expression is defined on, or throw an error.

`ufl_domains()`

Return all domains this expression is defined on.

`static ufl_enable_profiling()`

Turn on the object counting mechanism and reset counts to zero.

```
ufl.core.expr.ufl_err_str(expr)
```

`ufl.core.multiindex` module

This module defines the single index types and some internal index utilities.

```

class ufl.core.multiindex.FixedIndex (value)
    Bases: ufl.core.multiindex.IndexBase

    UFL value: An index with a specific value assigned.

class ufl.core.multiindex.Index (count=None)
    Bases: ufl.core.multiindex.IndexBase

    UFL value: An index with no value assigned.

    Used to represent free indices in Einstein indexing notation.

count ()

class ufl.core.multiindex.IndexBase
    Bases: object

    Base class for all indices.

class ufl.core.multiindex.MultiIndex (indices)
    Bases: ufl.core.terminal.Terminal

    Represents a sequence of indices, either fixed or free.

evaluate (x, mapping, component, index_values)
    Evaluate index.

indices ()
    Return tuple of indices.

is_cellwise_constant ()
    Always True.

ufl_domains ()
    Return tuple of domains related to this terminal object.

ufl_free_indices
    This shall not be used.

ufl_index_dimensions
    This shall not be used.

ufl_shape
    This shall not be used.

ufl.core.multiindex.as_multi_index (ii, shape=None)
    Return a MultiIndex version of ii.

ufl.core.multiindex.indices (n)
    UFL value: Return a tuple of n new Index objects.

```

ufl.core.operator module

```

class ufl.core.operator.Operator (operands=None)
    Bases: ufl.core.expr.Expr

    Base class for all operators, i.e. non-terminal expression types.

ufl_operands

```

ufl.core.terminal module

This module defines the `Terminal` class, the superclass for all types that are terminal nodes in an expression tree.

class ufl.core.terminal.FormArgument
Bases: `ufl.core.terminal.Terminal`

An abstract class for a form argument.

class ufl.core.terminal.Terminal
Bases: `ufl.core.expr.Expr`

A terminal node in the UFL expression tree.

evaluate (*x, mapping, component, index_values, derivatives=()*)
Get *self* from *mapping* and return the component asked for.

ufl_domains()
Return tuple of domains related to this terminal object.

ufl_free_indices = ()
ufl_index_dimensions = ()
ufl_operands = ()

ufl.core.ufl_id module

Utilites for types with a globally counted unique id attached to each object.

ufl.core.ufl_id.attach_ufl_id(*cls*)
Equip class with `.ufl_id()` and handle bookkeeping.

Usage:

1.Apply to class:

```
@attach_ufl_id  
class MyClass(object):
```

2.If `__slots__` is defined, include `_ufl_id` attribute:

```
__slots__ = ("_ufl_id",)
```

3.Add keyword argument to constructor:

```
def __init__(self, *args, ufl_id=None):
```

4.Call `self._init_ufl_id` with `ufl_id` and assign to `._ufl_id` attribute:

```
self._ufl_id = self._init_ufl_id(ufl_id)
```

Result:

`MyClass().ufl_id()` returns unique value for each constructed object.

ufl.core.ufl_type module

`ufl.core.ufl_type.attach_implementations_of_indexing_interface(cls, in-herit_shape_from_operand, in-herit_indices_from_operand)`

`ufl.core.ufl_type.attach_operators_from_hash_data(cls)`
Class decorator to attach `__hash__`, `__eq__` and `__ne__` implementations.

These are implemented in terms of a `._ufl_hash_data()` method on the class, which should return a tuple or hashable and comparable data.

`ufl.core.ufl_type.check_abstract_trait_consistency(cls)`
Check that the first base classes up to `Expr` are other UFL types.

`ufl.core.ufl_type.check_has_slots(cls)`
Check if type has `__slots__` unless it is marked as exception with `_ufl_noslots_`.

`ufl.core.ufl_type.check_implements_required_methods(cls)`
Check if type implements the required methods.

`ufl.core.ufl_type.check_implements_required_properties(cls)`
Check if type implements the required properties.

`ufl.core.ufl_type.check_is_terminal_consistency(cls)`
Check for consistency in `is_terminal` trait among superclasses.

`ufl.core.ufl_type.check_type_traits_consistency(cls)`
Execute a variety of consistency checks on the ufl type traits.

`ufl.core.ufl_type.determine_num_ops(cls, num_ops, unop, binop, rbinop)`
Determine number of operands for this type.

`ufl.core.ufl_type.get_base_attr(cls, name)`
Return first non-`None` attribute of given name among base classes.

`ufl.core.ufl_type.set_trait(cls, basename, value, inherit=False)`
Assign a trait to class with namespaces `_ufl_basename_` applied.

If trait value is `None`, optionally inherit it from the closest base class that has it.

`ufl.core.ufl_type.ufl_type(is_abstract=False, is_terminal=None, is_scalar=False, is_index_free=False, is_shaping=False, is_literal=False, is_terminal_modifier=False, is_in_reference_frame=False, is_restriction=False, is_evaluation=False, is_differential=None, use_default_hash=True, num_ops=None, inherit_shape_from_operand=None, in-herit_indices_from_operand=None, wraps_type=None, unop=None, binop=None, rbinop=None)`

This decorator is to be applied to every subclass in the UFL `Expr` hierarchy.

This decorator contains a number of checks that are intended to enforce uniform behaviour across UFL types.

The rationale behind the checks and the meaning of the optional arguments should be sufficiently documented in the source code below.

`ufl.core.ufl_type.update_global_expr_attributes(cls)`
Update global `Expr` attributes, mainly by adding `cls` to global collections of ufl types.

Module contents

ufl.corealg package

Submodules

ufl.corealg.map_dag module

Basic algorithms for applying functions to subexpressions.

`ufl.corealg.map_dag.map_expr_dag(function, expression, compress=True)`

Apply a function to each subexpression node in an expression DAG.

If `compress` is `True` (default) the output object from the function is cached in a `dict` and reused such that the resulting expression DAG does not contain duplicate objects.

Return the result of the final function call.

`ufl.corealg.map_dag.map_expr_dags(function, expressions, compress=True)`

Apply a function to each subexpression node in an expression DAG.

If `compress` is `True` (default) the output object from the function is cached in a `dict` and reused such that the resulting expression DAG does not contain duplicate objects.

Return a list with the result of the final function call for each expression.

ufl.corealg.multipfunction module

Base class for multifunctions with UFL Expr type dispatch.

`class ufl.corealg.multipfunction.MultiFunction`

Bases: `object`

Base class for collections of non-recursive expression node handlers.

Subclass this (remember to call the `__init__` method of this class), and implement handler functions for each `Expr` type, using the lower case handler name of the type (`exprtype._ufl_handler_name_`).

This class is optimized for efficient type based dispatch in the `__call__` operator via typecode based lookup of the handler function bound to the algorithm object. Of course Python's function call overhead still applies.

`expr(o, *args)`

Trigger error for types with missing handlers.

`reuse_if_un触ed(o, *ops)`

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_un触ed
```

as a default rule.

`undefined(o, *args)`

Trigger error for types with missing handlers.

`ufl.corealg.multipfunction.get_num_args(function)`

Return the number of arguments accepted by `function`.

`ufl.corealg.multifunction.memoized_handler(handler)`
Function decorator to memoize MultiFunction handlers.

ufl.corealg.traversal module

Various expression traversal utilities.

The algorithms here are non-recursive, which is faster than recursion by a factor of 10 or so because of the function call overhead.

`ufl.corealg.traversal.cutoff_post_traversal(expr, cutofftypes)`
Yield \circ for each node \circ in $expr$, child before parent, but skipping subtrees of the cutofftypes.

`ufl.corealg.traversal.cutoff_unique_post_traversal(expr, cutofftypes, visited=None)`
Yield \circ for each node \circ in $expr$, child before parent.

Never visit a node twice.

`ufl.corealg.traversal.post_traversal(expr)`
Yield \circ for each node \circ in $expr$, child before parent.

`ufl.corealg.traversal.pre_traversal(expr)`
Yield \circ for each tree node \circ in $expr$, parent before child.

`ufl.corealg.traversal.traverse_terminals(expr)`
Iterate over all terminal objects in $expr$, including duplicates.

`ufl.corealg.traversal.traverse_unique_terminals(expr, visited=None)`
Iterate over all terminal objects in $expr$, not including duplicates.

`ufl.corealg.traversal.unique_post_traversal(expr, visited=None)`
Yield \circ for each node \circ in $expr$, child before parent.

Never visit a node twice.

`ufl.corealg.traversal.unique_pre_traversal(expr, visited=None)`
Yield \circ for each tree node \circ in $expr$, parent before child.

This version only visits each node once.

Module contents

ufl.finiteelement package

Submodules

ufl.finiteelement.brokenelement module

`class ufl.finiteelement.brokenelement.BrokenElement(element)`
Bases: `ufl.finiteelement.finiteelementbase.FiniteElementBase`

The discontinuous version of an existing Finite Element space.

`mapping()`

`reconstruct(**kwargs)`

`shortstr()`

Format as string for pretty printing.

ufl.finiteelement.elementlist module

This module provides an extensive list of predefined finite element families. Users or, more likely, form compilers, may register new elements by calling the function `register_element`.

```
ufl.finiteelement.elementlist.canonical_element_description(family, cell, order,
                                                               form_degree)
```

Given basic element information, return corresponding element information on canonical form.

Input: family, cell, (polynomial) order, form_degree Output: family (canonical), short_name (for printing), order, value shape, reference value shape, sobolev_space.

This is used by the `FiniteElement` constructor to verify input data against the element list and aliases defined in ufl.

```
ufl.finiteelement.elementlist.feec_element(family, n, r, k)
```

Finite element exterior calculus notation n = topological dimension of domain r = polynomial order k = form_degree

```
ufl.finiteelement.elementlist.register_alias(alias, to)
```

```
ufl.finiteelement.elementlist.register_element(family, short_name, value_rank,
                                                sobolev_space, mapping, degree_range,
                                                cellnames)
```

Register new finite element family.

```
ufl.finiteelement.elementlist.register_element2(family, value_rank, sobolev_space,
                                                mapping, degree_range, cellnames)
```

Register new finite element family.

```
ufl.finiteelement.elementlist.show_elements()
```

Shows all registered elements.

ufl.finiteelement.enrichedelement module

This module defines the UFL finite element classes.

```
class ufl.finiteelement.enrichedelement.EnrichedElement(*elements)
```

Bases: `ufl.finiteelement.enrichedelement.EnrichedElementBase`

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Dual basis is a concatenation of subelements dual bases; primal basis is a concatenation of subelements primal bases; resulting element is not nodal even when subelements are. Structured basis may be exploited in form compilers.

```
is_cellwise_constant()
```

Return whether the basis functions of this element is spatially constant over each cell.

```
shortstr()
```

Format as string for pretty printing.

```
class ufl.finiteelement.enrichedelement.EnrichedElementBase(*elements)
```

Bases: `ufl.finiteelement.finiteelementbase.FiniteElementBase`

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

```

mapping()
reconstruct(**kwargs)
sobolev_space()
    Return the underlying Sobolev space.

class ufl.finiteelement.enrichedelement.NodalEnrichedElement(*elements)
    Bases: ufl.finiteelement.enrichedelement.EnrichedElementBase

```

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Primal basis is reorthogonalized to dual basis which is a concatenation of subelements dual bases; resulting element is nodal.

```

is_cellwise_constant()
    Return whether the basis functions of this element is spatially constant over each cell.

shortstr()
    Format as string for pretty printing.

```

ufl.finiteelement.facetelement module

```

ufl.finiteelement.facetelement.FacetElement(element)
    Constructs the restriction of a finite element to the facets of the cell.

```

ufl.finiteelement.finiteelement module

This module defines the UFL finite element classes.

```

class ufl.finiteelement.finiteelement.FiniteElement(family, cell=None, degree=None, form_degree=None, quad_scheme=None, variant=None)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase

```

The basic finite element class for all simple finite elements.

```

mapping()
reconstruct(family=None, cell=None, degree=None)
    Construct a new FiniteElement object with some properties replaced with new values.

shortstr()
    Format as string for pretty printing.

sobolev_space()
    Return the underlying Sobolev space.

variant()

```

ufl.finiteelement.finiteelementbase module

This module defines the UFL finite element classes.

```
class ufl.finiteelement.finiteelementbase.FiniteElementBase(family,      cell,      de-
                                                               gree,      quad_scheme,
                                                               value_shape,      refer-
                                                               ence_value_shape)
```

Bases: object

Base class for all finite elements.

cell()
Return cell of finite element.

degree(component=None)
Return polynomial degree of finite element.

extract_component(i)
Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component(i)
Recursively extract reference component index relative to a (simple) element and that element for given reference value component index.

extract_subelement_component(i)
Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component(i)
Extract direct subelement index and subelement relative reference component index for a given reference component index.

family()
Return finite element family.

is_cellwise_constant(component=None)
Return whether the basis functions of this element is spatially constant over each cell.

mapping()
Not implemented.

num_sub_elements()
Return number of sub-elements.

quadrature_scheme()
Return quadrature scheme of finite element.

reference_value_shape()
Return the shape of the value space on the reference cell.

reference_value_size()
Return the integer product of the reference value shape.

sub_elements()
Return list of sub-elements.

symmetry()
Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

value_shape()
Return the shape of the value space on the global domain.

value_size()
Return the integer product of the value shape.

ufl.finiteelement.hdivcurl module

```
class ufl.finiteelement.hdivcurl.HCurlElement (element)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
    A curl-conforming version of an outer product element, assuming this makes mathematical sense.

    mapping ()
    reconstruct (**kwargs)
    shortstr ()
        Format as string for pretty printing.
    sobolev_space ()
        Return the underlying Sobolev space.

class ufl.finiteelement.hdivcurl.HDivElement (element)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
    A div-conforming version of an outer product element, assuming this makes mathematical sense.

    mapping ()
    reconstruct (**kwargs)
    shortstr ()
        Format as string for pretty printing.
    sobolev_space ()
        Return the underlying Sobolev space.
```

ufl.finiteelement.interiorelement module

```
ufl.finiteelement.interiorelement.InteriorElement (element)
    Constructs the restriction of a finite element to the interior of the cell.
```

ufl.finiteelement.mixedelement module

This module defines the UFL finite element classes.

```
class ufl.finiteelement.mixedelement.MixedElement (*elements, **kwargs)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
    A finite element composed of a nested hierarchy of mixed or simple elements.

    degree (component=None)
        Return polynomial degree of finite element.

    extract_component (i)
        Recursively extract component index relative to a (simple) element and that element for given value component index.

    extract_reference_component (i)
        Recursively extract reference_component index relative to a (simple) element and that element for given value reference_component index.

    extract_subelement_component (i)
        Extract direct subelement index and subelement relative component index for a given component index.
```

```
extract_subelement_reference_component(i)
    Extract direct subelement index and subelement relative reference_component index for a given reference_component index.

is_cellwise_constant(component=None)
    Return whether the basis functions of this element is spatially constant over each cell.

mapping()
num_sub_elements()
    Return number of sub elements.

reconstruct(**kwargs)
reconstruct_from_elements(*elements)
    Reconstruct a mixed element from new subelements.

shortstr()
    Format as string for pretty printing.

sub_elements()
    Return list of sub elements.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.finiteelement.mixedelement.TensorElement(family, cell=None, degree=None, shape=None, symmetry=None, quad_scheme=None)
Bases: ufl.finiteelement.mixedelement.MixedElement

A special case of a mixed finite element where all elements are equal.

extract_subelement_component(i)
    Extract direct subelement index and subelement relative component index for a given component index.

flattened_sub_element_mapping()
mapping()
reconstruct(**kwargs)
shortstr()
    Format as string for pretty printing.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.finiteelement.mixedelement.VectorElement(family, cell=None, degree=None, dim=None, form_degree=None, quad_scheme=None)
Bases: ufl.finiteelement.mixedelement.MixedElement

A special case of a mixed finite element where all elements are equal.

reconstruct(**kwargs)
shortstr()
    Format as string for pretty printing.
```

ufl.finiteelement.restrictedelement module

This module defines the UFL finite element classes.

```
class ufl.finiteelement.restrictedelement.RestrictedElement(element, restriction_domain)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase

Represents the restriction of a finite element to a type of cell entity.

is_cellwise_constant()
    Return whether the basis functions of this element is spatially constant over each cell.

mapping()
num_restricted_sub_elements()
    Return number of restricted sub elements.

num_sub_elements()
    Return number of sub elements.

reconstruct(**kwargs)
restricted_sub_elements()
    Return list of restricted sub elements.

restriction_domain()
    Return the domain onto which the element is restricted.

shortstr()
    Format as string for pretty printing.

sub_element()
    Return the element which is restricted.

sub_elements()
    Return list of sub elements.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.
```

ufl.finiteelement.tensorproductelement module

This module defines the UFL finite element classes.

```
class ufl.finiteelement.tensorproductelement.TensorProductElement(*elements, **kwargs)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
```

The tensor product of d element spaces:

$$V = V_1 \otimes V_2 \otimes \dots \otimes V_d$$

Given bases $\{\phi_{j_i}\}$ of the spaces V_i for $i = 1, \dots, d$, $\{\phi_{j_1} \otimes \phi_{j_2} \otimes \dots \otimes \phi_{j_d}\}$ forms a basis for V .

```
mapping()
num_sub_elements()
    Return number of subelements.

reconstruct(cell=None)
```

```
shortstr()
    Short pretty-print.

sobolev_space()
    Return the underlying Sobolev space of the TensorProductElement.

sub_elements()
    Return subelements (factors).
```

Module contents

This module defines the UFL finite element classes.

ufl.formatting package

Submodules

ufl.formatting.graph module

Algorithms for working with linearized computational graphs.

```
class ufl.formatting.graph.Graph(expression)
    Graph class which computes connectivity on demand.

    E()
    Ein()
    Eout()
    V()
    Vin()
    Vout()

class ufl.formatting.graph.HeapItem(incoming, outgoing, i)
    Bases: object

class ufl.formatting.graph.StringDependencyDefiner(argument_deps=None, coefficient_deps=None)
    Bases: ufl.corealg.multifunction.MultiFunction

    Given an expr, returns a frozenset of its dependencies.
```

Possible dependency values are: “c” - depends on runtime information like the cell, local<->global coordinate mappings, facet normals, or coefficients “x” - depends on local coordinates “v%d” % i - depends on argument i, for i in [0,rank)

```
argument(x)
coefficient(x)
expr(o)
facet_normal(o)
geometric_quantity(x)
spatial_derivative(o)
```

```
ufl.formatting.graph.build_graph(expr)
```

Build a linearized graph from an UFL Expr.

Returns $G = (V, E)$, with V being a list of graph nodes (Expr objects) in post traversal ordering and E being a list of edges. Each edge is represented as a (i, j) tuple where i and j are vertex indices into V .

```
ufl.formatting.graph.depth_first_ordering(G)
```

```
ufl.formatting.graph.extract_incoming_edges(G)
```

Build lists of incoming edges to each vertex in a linearized graph.

```
ufl.formatting.graph.extract_incoming_vertex_connections(G)
```

Build lists of vertices in incoming and outgoing edges to and from each vertex in a linearized graph.

Returns lists V_{in} and V_{out} .

```
ufl.formatting.graph.extract_outgoing_edges(G)
```

Build list of outgoing edges from each vertex in a linearized graph.

```
ufl.formatting.graph.extract_outgoing_vertex_connections(G)
```

Build lists of vertices in incoming and outgoing edges to and from each vertex in a linearized graph.

Returns lists V_{in} and V_{out} .

```
ufl.formatting.graph.len_items(sequence)
```

```
ufl.formatting.graph.lists(n)
```

```
ufl.formatting.graph.partition(G, criteria=<function string_set_criteria>)
```

```
ufl.formatting.graph.string_set_criteria(v, keys)
```

ufl.formatting.latextools module

This module defines basic utilities for stitching together LaTeX documents.

```
ufl.formatting.latextools.align(lines)
```

```
ufl.formatting.latextools.document(title, sections)
```

```
ufl.formatting.latextools.itemize(items)
```

```
ufl.formatting.latextools.section(s)
```

```
ufl.formatting.latextools.subsection(s)
```

```
ufl.formatting.latextools.subsubsection(s)
```

```
ufl.formatting.latextools.testdocument()
```

```
ufl.formatting.latextools.verbatim(string)
```

ufl.formatting.printing module

A collection of utility algorithms for printing of UFL objects, mostly intended for debugging purposes.

```
ufl.formatting.printing.form_info(form)
```

```
ufl.formatting.printing.integral_info(integral)
```

```
ufl.formatting.printing.tree_format(expression, indentation=0, parentheses=True)
```

ufl.formatting.ufl2dot module

A collection of utility algorithms for printing of UFL objects in the DOT graph visualization language, mostly intended for debugging purposes.

```
class ufl.formatting.ufl2dot.CompactLabeller(function_mapping=None)
    Bases: ufl.formatting.ufl2dot.ReprLabeller

    cell_avg(e)
    component_tensor(e)
    curl(e)
    determinant(e)
    dev(e)
    diff(e)
    div(e)
    division(e)
    dot(e)
    facet_avg(e)
    form_argument(e)
    geometric_quantity(e)
    grad(e)
    identity(e)
    index_sum(e)
    indexed(e)
    inner(e)
    math_function(e)
    multi_index(e)
    nabla_div(e)
    nabla_grad(e)
    negative_restricted(e)
    outer(e)
    positive_restricted(e)
    power(e)
    product(e)
    scalar_value(e)
    skew(e)
    sum(e)
    trace(e)
    transposed(e)
```

```

zero (e)
class ufl.formatting.ufl2dot.FancyLabeller (function_mapping=None)
    Bases: ufl.formatting.ufl2dot.CompactLabeller

class ufl.formatting.ufl2dot.ReprLabeller
    Bases: ufl.corealg.multifunction.MultiFunction

operator (e)
terminal (e)

ufl.formatting.ufl2dot.build_entities (e, nodes, edges, nodeoffset, prefix='', labeller=None)
ufl.formatting.ufl2dot.format_entities (nodes, edges)
ufl.formatting.ufl2dot.ufl2dot (expression, formname='a', nodeoffset=0, begin=True, end=True, labeling='repr', object_names=None)

```

ufl.formatting.ufl2latex module

This module defines expression transformation utilities, either converting UFL expressions to new UFL expressions or converting UFL expressions to other representations.

```

class ufl.formatting.ufl2latex.Expression2LatexHandler (argument_names=None, coefficient_names=None)
    Bases: ufl.corealg.multifunction.MultiFunction

abs (o, a)
acos (o, f)
and_condition (o, a, b)
argument (o)
asin (o, f)
atan (o, f)
atan2 (o, f1, f2)
bessel_K (o, nu, f)
bessel_i (o, nu, f)
bessel_j (o, nu, f)
bessel_y (o, nu, f)
cell_avg (o, f)
coefficient (o)
coefficient_derivative (o, f, w, v)
cofactor (o, A)
component_tensor (o, *ops)
conditional (o, c, t, f)
constant (o)
cos (o, f)
cosh (o, f)

```

```
cross(o, a, b)
curl(o, f)
determinant(o, A)
deviatoric(o, A)
div(o, f)
division(o, a, b)
dot(o, a, b)
eq(o, a, b)
erf(o, f)
exp(o, f)
expr(o)
facet_normal(o)
ge(o, a, b)
grad(o, f)
gt(o, a, b)
identity(o)
index_sum(o, f, i)
indexed(o, a, b)
inner(o, a, b)
inverse(o, A)
le(o, a, b)
list_tensor(o)
ln(o, f)
lt(o, a, b)
max_value(o, a, b)
min_value(o, a, b)
multi_index(o)
nabla_div(o, f)
nabla_grad(o, f)
ne(o, a, b)
negative_restricted(o, f)
not_condition(o, a)
or_condition(o, a, b)
outer(o, a, b)
permutation_symbol(o)
positive_restricted(o, f)
```

```

power(o, a, b)
product(o, *ops)
scalar_value(o)
sin(o,f)
sinh(o,f)
skew(o, A)
sqrt(o,f)
sum(o, *ops)
sym(o, A)
tan(o,f)
tanh(o,f)
trace(o, A)
transposed(o, a)
variable(o)
variable_derivative(o,f, v)
zero(o)

ufl.formatting.ufl2latex.bfname(i,p)
ufl.formatting.ufl2latex.build_precedence_map()
ufl.formatting.ufl2latex.cfname(i)
ufl.formatting.ufl2latex.code2latex(G, partitions, formdata)
    TODO: Document me

ufl.formatting.ufl2latex.dependency_sorting(deplist, rank)
ufl.formatting.ufl2latex.deps2latex(deps)
ufl.formatting.ufl2latex.element2latex(element)
ufl.formatting.ufl2latex.expression2latex(expression, argument_names=None, coefficient_names=None)
ufl.formatting.ufl2latex.form2code2latex(formdata)
ufl.formatting.ufl2latex.form2latex(form, formdata)
ufl.formatting.ufl2latex.format_index(ii)
ufl.formatting.ufl2latex.format_multi_index(ii, formatstring='%'s')
ufl.formatting.ufl2latex.formdata2latex(formdata)
ufl.formatting.ufl2latex.forms2latexdocument(forms, uffilename, compile=False)
    Render forms from a .ufl file as a LaTeX document.

ufl.formatting.ufl2latex.integrand2code(integrand, formdata)
ufl.formatting.ufl2latex.par(s, condition=True)
ufl.formatting.ufl2latex.ufl2latex(expression)
    Generate LaTeX code for a UFL expression or form (wrapper for form2latex and expression2latex).

```

Module contents

ufl.utils package

Submodules

ufl.utils.counted module

Utilites for types with a global unique counter attached to each object.

class ufl.utils.counted.ExampleCounted (count=None)

Bases: object

An example class for classes of objects identified by a global counter.

Mimic this class to create globally counted objects within a single type.

count ()

ufl.utils.counted.counted_init (self, count=None, countedclass=None)

Initialize a counted object, see ExampleCounted below for how to use.

ufl.utils.derivativetuples module

This module contains a collection of utilities for representing partial derivatives as integer tuples.

ufl.utils.derivativetuples.compute_derivative_tuples (n, gdim)

Compute the list of all derivative tuples for derivatives of given total order n and given geometric dimension gdim. This function returns two lists. The first is a list of tuples, where each tuple of length n specifies the coordinate directions of the n derivatives. The second is a corresponding list of tuples, where each tuple of length gdim specifies the number of derivatives in each direction. Both lists have length gdim^n and are ordered as expected by the UFC function tabulate_basis_derivatives.

Example: If n = 2 and gdim = 3, then the nice tuples are

```
(0, 0) <-> (2, 0, 0) <-> d^2/dxdx (0, 1) <-> (1, 1, 0) <-> d^2/dxdy (0, 2) <-> (1, 0, 1) <-> d^2/dxdz  
(1, 0) <-> (1, 1, 0) <-> d^2/dydx (1, 1) <-> (0, 2, 0) <-> d^2/dydy (1, 2) <-> (0, 1, 1) <-> d^2/dydz  
(2, 0) <-> (1, 0, 1) <-> d^2/dzdx (2, 1) <-> (0, 1, 1) <-> d^2/dzdy (2, 2) <-> (0, 0, 2) <-> d^2/dzdz
```

ufl.utils.derivativetuples.derivative_counts_to_listing (derivative_counts)

Convert a derivative count tuple to a derivative listing tuple.

The derivative $d^3 / dy^2 dz$ is represented in counting form as (0, 2, 1) meaning (dx^0, dy^2, dz^1) and in listing form as (1, 1, 2) meaning (dy, dy, dz).

ufl.utils.derivativetuples.derivative_listing_to_counts (derivatives, gdim)

Convert a derivative listing tuple to a derivative count tuple.

The derivative $d^3 / dy^2 dz$ is represented in counting form as (0, 2, 1) meaning (dx^0, dy^2, dz^1) and in listing form as (1, 1, 2) meaning (dy, dy, dz).

ufl.utils.dicts module

Various dict manipulation utilities.

class ufl.utils.dicts.EmptyDictType

Bases: dict

```
update(*args, **kwargs)
ufl.utils dicts.dict_sum(items)
    Construct a dict, in between dict(items) and sum(items), by accumulating items for each key.

ufl.utils dicts.mergedicts(dicts)
ufl.utils dicts.mergedicts2(d1, d2)
ufl.utils dicts.slice_dict(dictionary, keys, default=None)
ufl.utils dicts.some_key(a_dict)
    Return an arbitrary key from a dictionary.

ufl.utils dicts.split_dict(d, criteria)
    Split a dict d into two dicts based on a criteria on the keys.

ufl.utils dicts.subdict(superdict, keys)
```

ufl.utils.formatting module

Various string formatting utilities.

```
ufl.utils.formatting.camel2underscore(name)
    Convert a CamelCaps string to underscore_syntax.

ufl.utils.formatting.dstr(d, colszie=80)
    Pretty-print dictionary of key-value pairs.

ufl.utils.formatting.estr(elements)
    Format list of elements for printing.

ufl.utils.formatting.istr(o)
    Format object as string, inserting ? for None.

ufl.utils.formatting.lstr(l)
    Pretty-print list or tuple, invoking str() on items instead of repr() like str() does.

ufl.utils.formatting.sstr(s)
    Pretty-print set.

ufl.utils.formatting.tstr(t, colszie=80)
    Pretty-print list of tuples of key-value pairs.
```

ufl.utils.indexflattening module

This module contains a collection of utilities for mapping between multiindices and a flattened index space.

```
ufl.utils.indexflattening.flatten_multiindex(ii, strides)
    Return the flat index corresponding to the given multiindex.

ufl.utils.indexflattening.shape_to_strides(sh)
    Return a tuple of strides given a shape tuple.

ufl.utils.indexflattening.unflatten_index(i, strides)
    Return the multiindex corresponding to the given flat index.
```

ufl.utils.py23 module

Python 2/3 compatibility utilities.

`ufl.utils.py23.as_bytes(s)`

Return s if bytes, or encode unicode string to bytes using utf-8.

`ufl.utils.py23.as_native_str(s)`

Return s as bytes string, encoded using utf-8 if necessary.

`ufl.utils.py23.as_native_strings(stringlist)`

`ufl.utils.py23.as_unicode(s)`

Return s if unicode string, or decode bytes to unicode string using utf-8.

ufl.utils.sequences module

Various sequence manipulation utilities.

`ufl.utils.sequences.and_tuples(seqa, seqb)`

Return ‘and’ of all pairs in two sequences of same length.

`ufl.utils.sequences.iter_tree(tree)`

Iterate over all nodes in a tree represented by lists of lists of leaves.

`ufl.utils.sequences.or_tuples(seqa, seqb)`

Return ‘or’ of all pairs in two sequences of same length.

`ufl.utils.sequences.product(sequence)`

Return the product of all elements in a sequence.

`ufl.utils.sequences.recursive_chain(lists)`

`ufl.utils.sequences.unzip(seq)`

Inverse operation of zip: unzip(zip(a, b)) == (a, b)

`ufl.utils.sequences.xor(a, b)`

ufl.utils.sorting module

Utilites for sorting.

`ufl.utils.sorting.canonicalize_metadata(metadata)`

Assuming metadata to be a dict with string keys and builtin python types as values.

Transform dict to a tuple of (key, value) item tuples ordered by key, with dict, list and tuple values converted the same way recursively. Lists and tuples are converted to tuples. Other values are converted using str(). This is such that the end result can be hashed and sorted using regular <, because python 3 doesn’t allow e.g. (3 < “auto”) which occurs regularly in metadata.

`ufl.utils.sorting.sorted_by_count(seq)`

Sort a sequence by the item.count().

`ufl.utils.sorting.sorted_by_key(mapping)`

Sort dict items by key, allowing different key types.

`ufl.utils.sorting.sorted_by_tuple_key(mapping)`

Sort dict items by tuple valued keys, allowing different types as items of the key tuples.

```
ufl.utils.sorting.sorted_by_ufl_id(seq)
    Sort a sequence by the item.ufl_id().

ufl.utils.sorting.topological_sorting(nodes, edges)
    Return a topologically sorted list of the nodes

    Implemented algorithm from Wikipedia :P
    <http://en.wikipedia.org/wiki/Topological\_sorting>
    No error for cyclic edges...
```

ufl.utils.stacks module

Various utility data structures.

```
class ufl.utils.stacks.Stack(*args)
    Bases: list

    A stack datastructure.

    peek()
    push(v)

class ufl.utils.stacks.StackDict(*args, **kwargs)
    Bases: dict

    A dict that can be changed incrementally with ‘d.push(k,v)’ and have changes rolled back with ‘k,v = d.pop()’.

    pop()
    push(k, v)
```

ufl.utils.ufltypedicts module

Various utility data structures.

```
class ufl.utils.ufltypedicts.UFLTypeDefaultDict(default)
    Bases: dict

class ufl.utils.ufltypedicts.UFLTypeDict
    Bases: dict
```

Module contents

Submodules

ufl.algebra module

Basic algebra operations.

```
class ufl.algebra.Abs(a)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
```

```
ufl_shape

class ufl.algebra.Division(a, b)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)

    ufl_free_indices

    ufl_index_dimensions

    ufl_shape = ()

class ufl.algebra.Power(a, b)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)

    ufl_free_indices

    ufl_index_dimensions

    ufl_shape = ()

class ufl.algebra.Product(a, b)
    Bases: ufl.core.operator.Operator

    The product of two or more UFL objects.

    evaluate(x, mapping, component, index_values)

    ufl_free_indices

    ufl_index_dimensions

    ufl_shape = ()

class ufl.algebra.Sum(a, b)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)

    ufl_free_indices

    ufl_index_dimensions

    ufl_shape
```

ufl.argument module

This module defines the class Argument and a number of related classes (functions), including TestFunction and TrialFunction.

```
class ufl.argument.Argument(function_space, number, part=None)
    Bases: ufl.core.terminal.FormArgument

    UFL value: Representation of an argument to a form.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    number()
        Return the Argument number.

    part()
```

ufl_domain()
 Deprecated, please use .ufl_function_space().ufl_domain() instead.

ufl_domains()
 Deprecated, please use .ufl_function_space().ufl_domains() instead.

ufl_element()
 Deprecated, please use .ufl_function_space().ufl_element() instead.

ufl_function_space()
 Get the function space of this Argument.

ufl_shape
 Return the associated UFL shape.

`ufl.argument.Arguments(function_space, number)`

UFL value: Create an Argument in a mixed space, and return a tuple with the function components corresponding to the subelements.

`ufl.argument.TestFunction(function_space, part=None)`

UFL value: Create a test function argument to a form.

`ufl.argument.TestFunctions(function_space)`

UFL value: Create a TestFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

`ufl.argument.TrialFunction(function_space, part=None)`

UFL value: Create a trial function argument to a form.

`ufl.argument.TrialFunctions(function_space)`

UFL value: Create a TrialFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

ufl.assertions module

This module provides assertion functions used by the UFL implementation.

`ufl.assertions.expecting_expr(v)`

`ufl.assertions.expecting_instance(v, c)`

`ufl.assertions.expecting_python_scalar(v)`

`ufl.assertions.expecting_terminal(v)`

`ufl.assertions.expecting_true_ufl_scalar(v)`

`ufl.assertions.ufl_assert(condition, *message)`

Assert that condition is true and otherwise issue an error with given message.

ufl.cell module

Types for representing a cell.

class ufl.cell.AbstractCell(*topological_dimension*, *geometric_dimension*)
 Bases: object

Representation of an abstract finite element cell with only the dimensions known.

geometric_dimension()
 Return the dimension of the space this cell is embedded in.

```
has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

topological_dimension()
    Return the dimension of the topology of this cell.

class ufl.cell.Cell(cellname, geometric_dimension=None)
    Bases: ufl.cell.AbstractCell

    Representation of a named finite element cell with known structure.

cellname()
    Return the cellname of the cell.

has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

num_edges()
    The number of cell edges.

num_facet_edges()
    The number of facet edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct(geometric_dimension=None)

class ufl.cell.TensorProductCell(*cells, **kwargs)
    Bases: ufl.cell.AbstractCell

cellname()
    Return the cellname of the cell.

has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

num_edges()
    The number of cell edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct(geometric_dimension=None)

sub_cells()
    Return list of cell factors.

ufl.cell.as_cell(cell)
    Convert any valid object to a Cell or return cell if it is already a Cell.
```

Allows an already valid cell, a known cellname string, or a tuple of cells for a product cell.

`ufl.cell.hypercube(topological_dimension, geometric_dimension=None)`
Return a hypercube cell of given dimension.

`ufl.cell.simplex(topological_dimension, geometric_dimension=None)`
Return a simplex cell of given dimension.

ufl.checks module

Utility functions for checking properties of expressions.

`ufl.checks.is_cellwise_constant(expr)`
Return whether expression is constant over a single cell.

`ufl.checks.is_globally_constant(expr)`
Check if an expression is globally constant, which includes spatially independent constant coefficients that are not known before assembly time.

`ufl.checks.is_python_scalar(expression)`
Return True iff expression is of a Python scalar type.

`ufl.checks.is_scalar_constant_expression(expr)`
Check if an expression is a globally constant scalar expression.

`ufl.checks.is_true_ufl_scalar(expression)`
Return True iff expression is scalar-valued, with no free indices.

`ufl.checks.is_ufl_scalar(expression)`
Return True iff expression is scalar-valued, but possibly containing free indices.

ufl.classes module

This file is useful for external code like tests and form compilers, since it enables the syntax “from ufl.classes import CellFacetooBar” for getting implementation details not exposed through the default ufl namespace. It also contains functionality used by algorithms for dealing with groups of classes, and for mapping types to different handler functions.

class `ufl.classes.Expr`

Bases: `object`

Base class for all UFL expression types.

Instance properties Every `Expr` instance will have certain properties. The most important ones are `ufl_operands`, `ufl_shape`, `ufl_free_indices`, and `ufl_index_dimensions` properties. Expressions are immutable and hashable.

Type traits The `Expr` API defines a number of type traits that each subclass needs to provide. Most of these are specified indirectly via the arguments to the `ufl_type` class decorator, allowing UFL to do some consistency checks and automate most of the traits for most types. Type traits are accessed via a class or instance object of the form `obj._ufl_traitname_`. See the source code for description of each type trait.

Operators Some Python special functions are implemented in this class, some are implemented in subclasses, and some are attached to this class in the `ufl_type` class decorator.

Defining subclasses To define a new expression class, inherit from either `Terminal` or `Operator`, and apply the `ufl_type` class decorator with suitable arguments. See the docstring of `ufl_type` for details on its arguments. Looking at existing classes similar to the one you wish to add is a good idea. Looking

through the comments in the `Expr` class and `ufl_type` to understand all the properties that may need to be specified is also a good idea. Note that many algorithms in UFL and form compilers will need handlers implemented for each new type:::

```
@ufl_type()
class MyOperator(Operator):
    pass
```

Type collections All `Expr` subclasses are collected by `ufl_type` in global variables available via `Expr`.

Profiling Object creation statistics can be collected by doing

```
Expr.ufl_enable_profiling()
# ... run some code
initstats, delstats = Expr.ufl_disable_profiling()
```

Giving a list of creation and deletion counts for each typecode.

T

Transpose a rank-2 tensor expression. For more general transpose operations of higher order tensor expressions, use indexing and `Tensor`.

dx (*ii)

Return the partial derivative with respect to spatial variable number *ii*.

evaluate (x, mapping, component, index_values)

Evaluate expression at given coordinate with given values for terminals.

geometric_dimension ()

Return the geometric dimension this expression lives in.

static ufl_disable_profiling ()

Turn off the object counting mechanism. Return object init and del counts.

ufl_domain ()

Return the single unique domain this expression is defined on, or throw an error.

ufl_domains ()

Return all domains this expression is defined on.

static ufl_enable_profiling ()

Turn on the object counting mechanism and reset counts to zero.

class ufl.classes.Terminal

Bases: `ufl.core.expr.Expr`

A terminal node in the UFL expression tree.

evaluate (x, mapping, component, index_values, derivatives=())

Get *self* from *mapping* and return the component asked for.

ufl_domains ()

Return tuple of domains related to this terminal object.

ufl_free_indices = ()

ufl_index_dimensions = ()

ufl_operands = ()

class ufl.classes.FormArgument

Bases: `ufl.core.terminal.Terminal`

An abstract class for a form argument.

```

class ufl.classes.GeometricQuantity(domain)
    Bases: ufl.core.terminal.Terminal

        is_cellwise_constant()
            Return whether this expression is spatially constant over each cell (or over each facet for facet quantities).

        ufl_domains()

        ufl_shape = ()

class ufl.classes.GeometricCellQuantity(domain)
    Bases: ufl.geometry.GeometricQuantity

class ufl.classes.GeometricFacetQuantity(domain)
    Bases: ufl.geometry.GeometricQuantity

class ufl.classes.SpatialCoordinate(domain)
    Bases: ufl.geometry.GeometricCellQuantity

        UFL geometry representation: The coordinate in a domain.

        In the context of expression integration, represents the domain coordinate of each quadrature point.

        In the context of expression evaluation in a point, represents the value of that point.

        evaluate(x, mapping, component, index_values)
            Return the value of the coordinate.

        is_cellwise_constant()
            Return whether this expression is spatially constant over each cell.

        name = 'x'

        ufl_shape
            Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.classes.CellCoordinate(domain)
    Bases: ufl.geometry.GeometricCellQuantity

        UFL geometry representation: The coordinate in a reference cell.

        In the context of expression integration, represents the reference cell coordinate of each quadrature point.

        In the context of expression evaluation in a point in a cell, represents that point in the reference coordinate system of the cell.

        is_cellwise_constant()
            Return whether this expression is spatially constant over each cell.

        name = 'X'

        ufl_shape

class ufl.classes.FacetCoordinate(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

        UFL geometry representation: The coordinate in a reference cell of a facet.

        In the context of expression integration over a facet, represents the reference facet coordinate of each quadrature point.

        In the context of expression evaluation in a point on a facet, represents that point in the reference coordinate system of the facet.

        is_cellwise_constant()
            Return whether this expression is spatially constant over each cell.

```

```
name = 'Xf'  
  
ufl_shape  
  
class ufl.classes.CellOrigin(domain)  
    Bases: ufl.geometry.GeometricCellQuantity  
  
    UFC geometry representation: The spatial coordinate corresponding to origin of a reference cell.  
  
    is_cellwise_constant()  
  
    name = 'x0'  
  
    ufl_shape  
  
class ufl.classes.FacetOrigin(domain)  
    Bases: ufl.geometry.GeometricFacetQuantity  
  
    UFC geometry representation: The spatial coordinate corresponding to origin of a reference facet.  
  
    name = 'x0f'  
  
    ufl_shape  
  
class ufl.classes.CellFacetOrigin(domain)  
    Bases: ufl.geometry.GeometricFacetQuantity  
  
    UFC geometry representation: The reference cell coordinate corresponding to origin of a reference facet.  
  
    name = 'X0f'  
  
    ufl_shape  
  
class ufl.classes.Jacobian(domain)  
    Bases: ufl.geometry.GeometricCellQuantity  
  
    UFC geometry representation: The Jacobian of the mapping from reference cell to spatial coordinates.
```

$$J_{ij} = \frac{dx_i}{dX_j}$$

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

name = 'J'**ufl_shape**

Return the number of coordinates defined (i.e. the geometric dimension of the domain).

```
class ufl.classes.FacetJacobian(domain)
```

Bases: ufl.geometry.GeometricFacetQuantity

UFC geometry representation: The Jacobian of the mapping from reference facet to spatial coordinates.

$$FJ_{ij} = dx_i/dX_f_j$$

The FacetJacobian is the product of the Jacobian and CellFacetJacobian:

$$FJ = dx/dX_f = dx/dX dX/dX_f = J * CFJ$$

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

name = 'FJ'**ufl_shape**

```

class ufl.classes.CellFacetJacobian (domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The Jacobian of the mapping from reference facet to reference cell coordinates.

    CFJ_ij = dX_i/dXf_j

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = 'CFJ'

    ufl_shape

class ufl.classes.CellEdgeVectors (domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The vectors between reference cell vertices for each edge in cell.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = 'CEV'

    ufl_shape

class ufl.classes.FacetEdgeVectors (domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The vectors between reference cell vertices for each edge in current facet.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = 'FEV'

    ufl_shape

class ufl.classes.JacobianDeterminant (domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The determinant of the Jacobian.

    Represents the signed determinant of a square Jacobian or the pseudo-determinant of a non-square Jacobian.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = 'detJ'

class ufl.classes.FacetJacobainDeterminant (domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The pseudo-determinant of the FacetJacobian.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = 'detFJ'

class ufl.classes.CellFacetJacobainDeterminant (domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The pseudo-determinant of the CellFacetJacobian.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

```

```
name = 'detCFJ'

class ufl.classes.JacobianInverse(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFC geometry representation: The inverse of the Jacobian.
    Represents the inverse of a square Jacobian or the pseudo-inverse of a non-square Jacobian.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'K'

    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.classes.FacetJacobainInverse(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
    UFC geometry representation: The pseudo-inverse of the FacetJacobian.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'FK'

    ufl_shape

class ufl.classes.CellFacetJacobainInverse(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
    UFC geometry representation: The pseudo-inverse of the CellFacetJacobian.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'CFK'

    ufl_shape

class ufl.classes.FacetNormal(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
    UFC geometry representation: The outwards pointing normal vector of the current facet.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'n'

    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.classes.CellNormal(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFC geometry representation: The upwards pointing normal vector of the current manifold cell.

    name = 'cell_normal'

    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.classes.ReferenceNormal(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The outwards pointing normal vector of the current facet on the reference cell

name = ‘reference_normal’

ufl_shape

class ufl.classes.ReferenceCellVolume (domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The volume of the reference cell.

name = ‘reference_cell_volume’

class ufl.classes.ReferenceFacetVolume (domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The volume of the reference cell of the current facet.

name = ‘reference_facet_volume’

class ufl.classes.CellVolume (domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The volume of the cell.

name = ‘volume’

class ufl.classes.Circumradius (domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The circumradius of the cell.

name = ‘circumradius’

class ufl.classes.FacetArea (domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The area of the facet.

name = ‘facetarea’

class ufl.classes.MinCellEdgeLength (domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The minimum edge length of the cell.

name = ‘mincelledgelength’

class ufl.classes.MaxCellEdgeLength (domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The maximum edge length of the cell.

name = ‘maxcelledgelength’

class ufl.classes.MinFacetEdgeLength (domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The minimum edge length of the facet.

name = ‘minfacetedgelenhgt’

class ufl.classes.MaxFacetEdgeLength (domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The maximum edge length of the facet.

name = ‘maxfacetedgelenhgt’

```
class ufl.classes.CellOrientation (domain)
Bases: ufl.geometry.GeometricCellQuantity

UFL geometry representation: The orientation (+1/-1) of the current cell.

For non-manifold cells (tdim == gdim), this equals the sign of the Jacobian determinant, i.e. +1 if the physical
cell is oriented the same way as the reference cell and -1 otherwise.

For manifold cells of tdim==gdim-1 this is input data belonging to the mesh, used to distinguish between the
sides of the manifold.

    name = 'cell_orientation'

class ufl.classes.FacetOrientation (domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The orientation (+1/-1) of the current facet relative to the reference cell.

    name = 'facet_orientation'

class ufl.classes.QuadratureWeight (domain)
Bases: ufl.geometry.GeometricQuantity

UFL geometry representation: The current quadrature weight.

Only used inside a quadrature context.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'weight'

class ufl.classes.Operator (operands=None)
Bases: ufl.core.expr.Expr

Base class for all operators, i.e. non-terminal expression types.

    ufl_operands

class ufl.classes.MultiIndex (indices)
Bases: ufl.core.terminal.Terminal

Represents a sequence of indices, either fixed or free.

    evaluate (x, mapping, component, index_values)
        Evaluate index.

    indices()
        Return tuple of indices.

    is_cellwise_constant()
        Always True.

    ufl_domains()
        Return tuple of domains related to this terminal object.

    ufl_free_indices
        This shall not be used.

    ufl_index_dimensions
        This shall not be used.

    ufl_shape
        This shall not be used.
```

```

class ufl.classes.ConstantValue
    Bases: ufl.core.terminal.Terminal

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    ufl_domains()
        Return tuple of domains related to this terminal object.

class ufl.classes.Zero(shape=(), free_indices=(), index_dimensions=None)
    Bases: ufl.constantvalue.ConstantValue

    UFL literal type: Representation of a zero valued expression.

    evaluate(x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.ScalarValue(value)
    Bases: ufl.constantvalue.ConstantValue

    A constant scalar value.

    evaluate(x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()
    value()

class ufl.classes.FloatValue(value)
    Bases: ufl.constantvalue.ScalarValue

    UFL literal type: Representation of a constant scalar floating point value.

class ufl.classes.IntValue(value)
    Bases: ufl.constantvalue.ScalarValue

    UFL literal type: Representation of a constant scalar integer value.

class ufl.classes.Identity(dim)
    Bases: ufl.constantvalue.ConstantValue

    UFL literal type: Representation of an identity matrix.

    evaluate(x, mapping, component, index_values)
        Evaluates the identity matrix on the given components.

    ufl_shape

class ufl.classes.PermutationSymbol(dim)
    Bases: ufl.constantvalue.ConstantValue

    UFL literal type: Representation of a permutation symbol.

    This is also known as the Levi-Civita symbol, antisymmetric symbol, or alternating symbol.

    evaluate(x, mapping, component, index_values)
        Evaluates the permutation symbol.

    ufl_shape

```

```
class ufl.classes.Indexed(expression, multiindex)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values, derivatives=())
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = ()

class ufl.classes.ListTensor(*expressions)
    Bases: ufl.core.operator.Operator

    UFL operator type: Wraps a list of expressions into a tensor valued expression of one higher rank.

    evaluate(x, mapping, component, index_values, derivatives=())
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.ComponentTensor(expression, indices)
    Bases: ufl.core.operator.Operator

    UFL operator type: Maps the free indices of a scalar valued expression to tensor axes.

    evaluate(x, mapping, component, index_values)
    indices()
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.Argument(function_space, number, part=None)
    Bases: ufl.core.terminal.FormArgument

    UFL value: Representation of an argument to a form.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    number()
        Return the Argument number.

    part()
    ufl_domain()
        Deprecated, please use .ufl_function_space().ufl_domain() instead.

    ufl_domains()
        Deprecated, please use .ufl_function_space().ufl_domains() instead.

    ufl_element()
        Deprecated, please use .ufl_function_space().ufl_element() instead.

    ufl_function_space()
        Get the function space of this Argument.

    ufl_shape
        Return the associated UFL shape.
```

```
class ufl.classes.Coefficient (function_space, count=None)
Bases: ufl.core.terminal.FormArgument

UFL form argument type: Representation of a form coefficient.

count ()
is_cellwise_constant ()
    Return whether this expression is spatially constant over each cell.

ufl_domain ()
    Shortcut to get the domain of the function space of this coefficient.

ufl_domains ()
    Return tuple of domains related to this terminal object.

ufl_element ()
    Shortcut to get the finite element of the function space of this coefficient.

ufl_function_space ()
    Get the function space of this coefficient.

ufl_shape
    Return the associated UFL shape.
```

```
class ufl.classes.Label (count=None)
Bases: ufl.core.terminal.Terminal

count ()
is_cellwise_constant ()
ufl_domains ()
    Return tuple of domains related to this terminal object.

ufl_free_indices
ufl_index_dimensions
ufl_shape
```

```
class ufl.classes.Variable (expression, label=None)
Bases: ufl.core.operator.Operator
```

A Variable is a representative for another expression.

It will be used by the end-user mainly for defining a quantity to differentiate w.r.t. using diff. Example:

```
e = <...>
e = variable(e)
f = exp(e**2)
df = diff(f, e)
```

```
evaluate (x, mapping, component, index_values)
```

```
expression ()
```

```
label ()
```

```
ufl_domains ()
```

```
ufl_free_indices = ()
```

```
ufl_index_dimensions = ()
```

```
ufl_shape
```

```
class ufl.classes.Sum(a, b)
    Bases: ufl.core.operator.Operator
    evaluate(x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.Product(a, b)
    Bases: ufl.core.operator.Operator
    The product of two or more UFL objects.
    evaluate(x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = ()

class ufl.classes.Division(a, b)
    Bases: ufl.core.operator.Operator
    evaluate(x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = ()

class ufl.classes.Power(a, b)
    Bases: ufl.core.operator.Operator
    evaluate(x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = ()

class ufl.classes.Abs(a)
    Bases: ufl.core.operator.Operator
    evaluate(x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.CompoundTensorOperator(operands)
    Bases: ufl.core.operator.Operator

class ufl.classes.Transposed(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

```
class ufl.classes.Outer(a, b)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.Inner(a, b)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape = ()

class ufl.classes.Dot(a, b)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.Cross(a, b)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape = (3,)

class ufl.classes.Trace(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape = ()

class ufl.classes.Determinant(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices = ()
        ufl_index_dimensions = ()
        ufl_shape = ()

class ufl.classes.Inverse(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices = ()
        ufl_index_dimensions = ()
        ufl_shape

class ufl.classes.Cofactor(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices = ()
        ufl_index_dimensions = ()
```

```
ufl_shape

class ufl.classes.Deviatoric(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.Skew(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.Sym(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.IndexSum(summand, index)
    Bases: ufl.core.operator.Operator

    dimension()
    evaluate(x, mapping, component, index_values)
    index()
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.Restricted(f)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
    side()
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.PositiveRestricted(f)
    Bases: ufl.restriction.Restricted

class ufl.classes.NegativeRestricted(f)
    Bases: ufl.restriction.Restricted

class ufl.classes.CellAvg(f)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
    Performs an approximate symbolic evaluation, since we dont have a cell.
```

```

 =()
 =()


class ufl.classes.FacetAvg(f)
    Bases: ufl.core.operator.Operator

        evaluate(x, mapping, component, index_values)
            Performs an approximate symbolic evaluation, since we dont have a cell.

 =()
 =()


class ufl.classes.ExprList(*operands)
    Bases: ufl.core.operator.Operator

List of Expr objects. For internal use, never to be created by end users.

()
()





class ufl.classes.ExprMapping(*operands)
    Bases: ufl.core.operator.Operator

Mapping of Expr objects. For internal use, never to be created by end users.

()
()
()




class ufl.classes.Derivative(operands)
    Bases: ufl.core.operator.Operator

Base class for all derivative types.

class ufl.classes.CoefficientDerivative(integrand, coefficients, arguments, coefficient_derivatives)
    Bases: ufl.differentiation.Derivative

Derivative of the integrand of a form w.r.t. the degrees of freedom in a discrete Coefficient.





class ufl.classes.VariableDerivative(f, v)
    Bases: ufl.differentiation.Derivative

```

```
ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.CompoundDerivative(operands)
    Bases: ufl.differentiation.Derivative
        Base class for all compound derivative types.

class ufl.classes.Grad(f)
    Bases: ufl.differentiation.CompoundDerivative
        evaluate(x, mapping, component, index_values, derivatives=())
            Get child from mapping and return the component asked for.
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.ReferenceGrad(f)
    Bases: ufl.differentiation.CompoundDerivative
        evaluate(x, mapping, component, index_values, derivatives=())
            Get child from mapping and return the component asked for.
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.Div(f)
    Bases: ufl.differentiation.CompoundDerivative
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.ReferenceDiv(f)
    Bases: ufl.differentiation.CompoundDerivative
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.NablaGrad(f)
    Bases: ufl.differentiation.CompoundDerivative
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.NablaDiv(f)
    Bases: ufl.differentiation.CompoundDerivative
        ufl_free_indices
        ufl_index_dimensions
```

```

ufl_shape

class ufl.classes.Curl(f)
    Bases: ufl.differentiation.CompoundDerivative
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.ReferenceCurl(f)
    Bases: ufl.differentiation.CompoundDerivative
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.classes.Condition(operands)
    Bases: ufl.core.operator.Operator
        ufl_free_indices = ()
        ufl_index_dimensions = ()
        ufl_shape = ()

class ufl.classes.BinaryCondition(name, left, right)
    Bases: ufl.conditional.Condition

class ufl.classes.EQ(left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

class ufl.classes.NE(left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

class ufl.classes.LE(left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

class ufl.classes.GE(left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

class ufl.classes.LT(left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

class ufl.classes.GT(left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

class ufl.classes.AndCondition(left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

```

```
class ufl.classes.OrCondition (left, right)
    Bases: ufl.conditional.BinaryCondition
    evaluate (x, mapping, component, index_values)

class ufl.classes.NotCondition (condition)
    Bases: ufl.conditional.Condition
    evaluate (x, mapping, component, index_values)

class ufl.classes.Conditional (condition, true_value, false_value)
    Bases: ufl.core.operator.Operator
    evaluate (x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.classes.MinValue (left, right)
    Bases: ufl.core.operator.Operator
    UFC operator: Take the minimum of two values.
    evaluate (x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.classes.MaxValue (left, right)
    Bases: ufl.core.operator.Operator
    UFC operator: Take the maximum of two values.
    evaluate (x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.classes.MathFunction (name, argument)
    Bases: ufl.core.operator.Operator
    Base class for all unary scalar math functions.
    evaluate (x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.classes.Sqrt (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Exp (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Ln (argument)
    Bases: ufl.mathfunctions.MathFunction
```

```

evaluate (x, mapping, component, index_values)
class ufl.classes.Cos (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Sin (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Tan (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Cosh (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Sinh (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Tanh (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Acos (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Asin (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Atan (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Atan2 (arg1, arg2)
    Bases: ufl.core.operator.Operator
    evaluate (x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.classes.Erf (argument)
    Bases: ufl.mathfunctions.MathFunction
    evaluate (x, mapping, component, index_values)

class ufl.classes.BesselFunction (name, classname, nu, argument)
    Bases: ufl.core.operator.Operator
    Base class for all bessel functions
    evaluate (x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.classes.BesselJ (nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.classes.BesselY (nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.classes.BesselI (nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

```

```
class ufl.classes.BesselK(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.classes.ReferenceValue(f)
    Bases: ufl.core.operator.Operator
    Representation of the reference cell value of a form argument.

    evaluate(x, mapping, component, index_values, derivatives=())
        Get child from mapping and return the component asked for.

    ufl_free_indices =()
    ufl_index_dimensions =()
    ufl_shape

class ufl.classes.AbstractCell(topological_dimension, geometric_dimension)
    Bases: object
    Representation of an abstract finite element cell with only the dimensions known.

    geometric_dimension()
        Return the dimension of the space this cell is embedded in.

    has_simplex_facets()
        Return True if all the facets of this cell are simplex cells.

    is_simplex()
        Return True if this is a simplex cell.

    topological_dimension()
        Return the dimension of the topology of this cell.

class ufl.classes.Cell(cellname, geometric_dimension=None)
    Bases: ufl.cell.AbstractCell
    Representation of a named finite element cell with known structure.

    cellname()
        Return the cellname of the cell.

    has_simplex_facets()
        Return True if all the facets of this cell are simplex cells.

    is_simplex()
        Return True if this is a simplex cell.

    num_edges()
        The number of cell edges.

    num_facet_edges()
        The number of facet edges.

    num_facets()
        The number of cell facets.

    num_vertices()
        The number of cell vertices.

    reconstruct(geometric_dimension=None)

class ufl.classes.TensorProductCell(*cells, **kwargs)
    Bases: ufl.cell.AbstractCell
```

cellname()
 Return the cellname of the cell.

has_simplex_facets()
 Return True if all the facets of this cell are simplex cells.

is_simplex()
 Return True if this is a simplex cell.

num_edges()
 The number of cell edges.

num_facets()
 The number of cell facets.

num_vertices()
 The number of cell vertices.

reconstruct(*geometric_dimension=None*)

sub_cells()
 Return list of cell factors.

class ufl.classes.FiniteElementBase(*family, cell, degree, quad_scheme, value_shape, reference_value_shape*)
 Bases: object
 Base class for all finite elements.

cell()
 Return cell of finite element.

degree(*component=None*)
 Return polynomial degree of finite element.

extract_component(*i*)
 Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component(*i*)
 Recursively extract reference component index relative to a (simple) element and that element for given reference value component index.

extract_subelement_component(*i*)
 Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component(*i*)
 Extract direct subelement index and subelement relative reference component index for a given reference component index.

family()
 Return finite element family.

is_cellwise_constant(*component=None*)
 Return whether the basis functions of this element is spatially constant over each cell.

mapping()
 Not implemented.

num_sub_elements()
 Return number of sub-elements.

quadrature_scheme()
 Return quadrature scheme of finite element.

reference_value_shape()
Return the shape of the value space on the reference cell.

reference_value_size()
Return the integer product of the reference value shape.

sub_elements()
Return list of sub-elements.

symmetry()
Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

value_shape()
Return the shape of the value space on the global domain.

value_size()
Return the integer product of the value shape.

class ufl.classes.FiniteElement(family, cell=None, degree=None, form_degree=None, quad_scheme=None, variant=None)
Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*
The basic finite element class for all simple finite elements.

mapping()

reconstruct(family=None, cell=None, degree=None)
Construct a new FiniteElement object with some properties replaced with new values.

shortstr()
Format as string for pretty printing.

sobolev_space()
Return the underlying Sobolev space.

variant()

class ufl.classes.MixedElement(*elements, **kwargs)
Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*
A finite element composed of a nested hierarchy of mixed or simple elements.

degree(component=None)
Return polynomial degree of finite element.

extract_component(i)
Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component(i)
Recursively extract reference_component index relative to a (simple) element and that element for given value reference_component index.

extract_subelement_component(i)
Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component(i)
Extract direct subelement index and subelement relative reference_component index for a given reference_component index.

is_cellwise_constant(component=None)
Return whether the basis functions of this element is spatially constant over each cell.

mapping()

```

num_sub_elements()
    Return number of sub elements.

reconstruct(**kwargs)

reconstruct_from_elements(*elements)
    Reconstruct a mixed element from new subelements.

shortstr()
    Format as string for pretty printing.

sub_elements()
    Return list of sub elements.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.classes.VectorElement(family, cell=None, degree=None, dim=None, form_degree=None, quad_scheme=None)
Bases: ufl.finiteelement.mixedelement.MixedElement
A special case of a mixed finite element where all elements are equal.

reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.

class ufl.classes.TensorElement(family, cell=None, degree=None, shape=None, symmetry=None, quad_scheme=None)
Bases: ufl.finiteelement.mixedelement.MixedElement
A special case of a mixed finite element where all elements are equal.

extract_subelement_component(i)
    Extract direct subelement index and subelement relative component index for a given component index.

flattened_sub_element_mapping()

mapping()

reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.classes.EnrichedElement(*elements)
Bases: ufl.finiteelement.enrichedelement.EnrichedElementBase
The vector sum of several finite element spaces:


$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$


Dual basis is a concatenation of subelements dual bases; primal basis is a concatenation of subelements primal bases; resulting element is not nodal even when subelements are. Structured basis may be exploited in form compilers.

is_cellwise_constant()
    Return whether the basis functions of this element is spatially constant over each cell.

```

shortstr()

Format as string for pretty printing.

class ufl.classes.NodalEnrichedElement (*elements)

Bases: *ufl.finiteelement.enrichedelement.EnrichedElementBase*

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Primal basis is reorthogonalized to dual basis which is a concatenation of subelements dual bases; resulting element is nodal.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

shortstr()

Format as string for pretty printing.

class ufl.classes.RestrictedElement (element, restriction_domain)

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

Represents the restriction of a finite element to a type of cell entity.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

mapping()
num_restricted_sub_elements()

Return number of restricted sub elements.

num_sub_elements()

Return number of sub elements.

reconstruct (kwargs)**
restricted_sub_elements()

Return list of restricted sub elements.

restriction_domain()

Return the domain onto which the element is restricted.

shortstr()

Format as string for pretty printing.

sub_element()

Return the element which is restricted.

sub_elements()

Return list of sub elements.

symmetry()

Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

class ufl.classes.TensorProductElement (*elements, **kwargs)

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

The tensor product of d element spaces:

$$V = V_1 \otimes V_2 \otimes \dots \otimes V_d$$

Given bases $\{\phi_{j_i}\}$ of the spaces V_i for $i = 1, \dots, d$, $\{\phi_{j_1} \otimes \phi_{j_2} \otimes \dots \otimes \phi_{j_d}\}$ forms a basis for V .

```

mapping()
num_sub_elements()
    Return number of subelements.

reconstruct(cell=None)

shortstr()
    Short pretty-print.

sobolev_space()
    Return the underlying Sobolev space of the TensorProductElement.

sub_elements()
    Return subelements (factors).

class ufl.classes.HDivElement(element)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
    A div-conforming version of an outer product element, assuming this makes mathematical sense.

mapping()
reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.

sobolev_space()
    Return the underlying Sobolev space.

class ufl.classes.HCurlElement(element)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
    A curl-conforming version of an outer product element, assuming this makes mathematical sense.

mapping()
reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.

sobolev_space()
    Return the underlying Sobolev space.

class ufl.classes.BrokenElement(element)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
    The discontinuous version of an existing Finite Element space.

mapping()
reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.

ufl.classes.FacetElement(element)
    Constructs the restriction of a finite element to the facets of the cell.

ufl.classes.InteriorElement(element)
    Constructs the restriction of a finite element to the interior of the cell.

class ufl.classes.AbstractDomain(topological_dimension, geometric_dimension)
    Bases: object

```

Symbolic representation of a geometric domain with only a geometric and topological dimension.

geometric_dimension()

Return the dimension of the space this domain is embedded in.

topological_dimension()

Return the dimension of the topology of this domain.

class ufl.classes.Mesh (coordinate_element, ufl_id=None, cargo=None)

Bases: *ufl.domain.AbstractDomain*

Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cargo()

Return carried object that will not be used by UFL.

ufl_cell()

ufl_coordinate_element()

ufl_id()

Return the ufl_id of this object.

class ufl.classes.MeshView (mesh, topological_dimension, ufl_id=None)

Bases: *ufl.domain.AbstractDomain*

Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cell()

ufl_id()

Return the ufl_id of this object.

ufl_mesh()

class ufl.classes.TensorProductMesh (meshes, ufl_id=None)

Bases: *ufl.domain.AbstractDomain*

Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cell()

ufl_coordinate_element()

ufl_id()

Return the ufl_id of this object.

class ufl.classes.AbstractFunctionSpace

Bases: object

ufl_sub_spaces()

class ufl.classes.FunctionSpace (domain, element)

Bases: *ufl.functionspace.AbstractFunctionSpace*

ufl_domain()

Return ufl domain.

ufl_domains()

Return ufl domains.

```

ufl_element()
    Return ufl element.

ufl_sub_spaces()
    Return ufl sub spaces.

class ufl.classes.MixedFunctionSpace (*function_spaces)
    Bases: ufl.functionspace.AbstractFunctionSpace

ufl_domain()
    Return ufl domain.

ufl_domains()
    Return ufl domains.

ufl_element()
    Return ufl element.

ufl_sub_spaces()
    Return ufl sub spaces.

class ufl.classes.TensorProductFunctionSpace (*function_spaces)
    Bases: ufl.functionspace.AbstractFunctionSpace

ufl_sub_spaces()

class ufl.classes.IndexBase
    Bases: object

    Base class for all indices.

class ufl.classes.FixedIndex (value)
    Bases: ufl.core.multiindex.IndexBase

    UFL value: An index with a specific value assigned.

class ufl.classes.Index (count=None)
    Bases: ufl.core.multiindex.IndexBase

    UFL value: An index with no value assigned.

    Used to represent free indices in Einstein indexing notation.

count()

ufl.classes.TestFunction (function_space, part=None)
    UFL value: Create a test function argument to a form.

ufl.classes.TrialFunction (function_space, part=None)
    UFL value: Create a trial function argument to a form.

ufl.classes.TestFunctions (function_space)
    UFL value: Create a TestFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

ufl.classes.TrialFunctions (function_space)
    UFL value: Create a TrialFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

class ufl.classes.Measure (integral_type, domain=None, subdomain_id='everywhere', meta-data=None, subdomain_data=None)
    Bases: object

integral_type()
    Return the domain type.

```

Valid domain types are “cell”, “exterior_facet”, “interior_facet”, etc.

metadata()

Return the integral metadata. This data is not interpreted by UFL. It is passed to the form compiler which can ignore it or use it to compile each integral of a form in a different way.

reconstruct (*integral_type=None*, *subdomain_id=None*, *domain=None*, *metadata=None*, *subdomain_main_data=None*)

Construct a new Measure object with some properties replaced with new values.

Example: <dm = Measure instance> b = dm.reconstruct(subdomain_id=2) c = dm.reconstruct(metadata={“quadrature_degree”: 3})

Used by the call operator, so this is equivalent: b = dm(2) c = dm(0, {“quadrature_degree”: 3})

subdomain_data()

Return the integral subdomain_data. This data is not interpreted by UFL. Its intension is to give a context in which the domain id is interpreted.

subdomain_id()

Return the domain id of this measure (integer).

ufl_domain()

Return the domain associated with this measure.

This may be None or a Domain object.

class ufl.classes.MeasureSum (*measures)

Bases: object

Represents a sum of measures.

This is a notational intermediate object to translate the notation

f*(ds(1)+ds(3))

into

f*ds(1) + f*ds(3)

class ufl.classes.MeasureProduct (*measures)

Bases: object

Represents a product of measures.

This is a notational intermediate object to handle the notation

f*(dm1*dm2)

This is work in progress and not functional. It needs support in other parts of ufl and the rest of the code generation chain.

sub_measures()

Return submeasures.

class ufl.classes.Integral (*integrand*, *integral_type*, *domain*, *subdomain_id*, *metadata*, *subdomain_main_data*)

Bases: object

An integral over a single domain.

integral_type()

Return the domain type of this integral.

integrand()

Return the integrand expression, which is an Expr instance.

metadata()
 Return the compiler metadata this integral has been annotated with.

reconstruct (integrand=None, integral_type=None, domain=None, subdomain_id=None, meta-data=None, subdomain_data=None)
 Construct a new Integral object with some properties replaced with new values.

Example: <a = Integral instance> b = a.reconstruct(expand_compounds(a.integrand())) c = a.reconstruct(metadata={'quadrature_degree':2})

subdomain_data()
 Return the domain data of this integral.

subdomain_id()
 Return the subdomain id of this integral.

ufl_domain()
 Return the integration domain of this integral.

class ufl.classes.Form(integrals)
 Bases: object

Description of a weak form consisting of a sum of integrals over subdomains.

arguments()
 Return all Argument objects found in form.

coefficient_numbering()
 Return a contiguous numbering of coefficients in a mapping {coefficient:number}.

coefficients()
 Return all Coefficient objects found in form.

domain_numbering()
 Return a contiguous numbering of domains in a mapping {domain:number}.

empty()
 Returns whether the form has no integrals.

equals(other)
 Evaluate `bool(lhs_form == rhs_form)`.

geometric_dimension()
 Return the geometric dimension shared by all domains and functions in this form.

integrals()
 Return a sequence of all integrals in form.

integrals_by_type(integral_type)
 Return a sequence of all integrals with a particular domain type.

max_subdomain_ids()
 Returns a mapping on the form {domain:{integral_type:max_subdomain_id}}.

signature()
 Signature for use with jit cache (independent of incidental numbering of indices etc.)

subdomain_data()
 Returns a mapping on the form {domain:{integral_type: subdomain_data}}.

ufl_cell()
 Return the single cell this form is defined on, fails if multiple cells are found.

```
ufl_domain()
    Return the single geometric integration domain occurring in the form.

    Fails if multiple domains are found.

    NB! This does not include domains of coefficients defined on other meshes, look at form data for that
    additional information.

ufl_domains()
    Return the geometric integration domains occurring in the form.

    NB! This does not include domains of coefficients defined on other meshes.

    The return type is a tuple even if only a single domain exists.

x_repr_latex_()
x_repr_png_()

class ufl.classes.Equation(lhs, rhs)
Bases: object

This class is used to represent equations expressed by the “==” operator. Examples include a == L and F == 0
where a, L and F are Form objects.
```

ufl.coefficient module

This module defines the Coefficient class and a number of related classes, including Constant.

```
class ufl.coefficient.Coefficient(function_space, count=None)
Bases: ufl.core.terminal.FormArgument

UFL form argument type: Representation of a form coefficient.

count()
is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

ufl_domain()
    Shortcut to get the domain of the function space of this coefficient.

ufl_domains()
    Return tuple of domains related to this terminal object.

ufl_element()
    Shortcut to get the finite element of the function space of this coefficient.

ufl_function_space()
    Get the function space of this coefficient.

ufl_shape
    Return the associated UFL shape.

ufl.coefficient.Coefficients(function_space)
    UFL value: Create a Coefficient in a mixed space, and return a tuple with the function components corresponding
    to the subelements.

ufl.coefficient.Constant(domain, count=None)
    UFL value: Represents a globally constant scalar valued coefficient.

ufl.coefficient.TensorConstant(domain, shape=None, symmetry=None, count=None)
    UFL value: Represents a globally constant tensor valued coefficient.
```

`ufl.coefficient.VectorConstant (domain, dim=None, count=None)`
 UFL value: Represents a globally constant vector valued coefficient.

ufl.compound_expressions module

Functions implementing compound expressions as equivalent representations using basic operators.

```
ufl.compound_expressions.adj_expr(A)
ufl.compound_expressions.adj_expr_2x2(A)
ufl.compound_expressions.adj_expr_3x3(A)
ufl.compound_expressions.adj_expr_4x4(A)
ufl.compound_expressions.codeterminant_expr_nxn(A, rows, cols)
ufl.compound_expressions.cofactor_expr(A)
ufl.compound_expressions.cofactor_expr_2x2(A)
ufl.compound_expressions.cofactor_expr_3x3(A)
ufl.compound_expressions.cofactor_expr_4x4(A)
ufl.compound_expressions.cross_expr(a, b)
ufl.compound_expressions.determinant_expr(A)
  Compute the (pseudo-)determinant of A.

ufl.compound_expressions.determinant_expr_2x2(B)
ufl.compound_expressions.determinant_expr_3x3(A)
ufl.compound_expressions.deviatoric_expr(A)
ufl.compound_expressions.deviatoric_expr_2x2(A)
ufl.compound_expressions.deviatoric_expr_3x3(A)
ufl.compound_expressions.generic_pseudo_determinant_expr(A)
  Compute the pseudo-determinant of A: sqrt(det(A.T*A)).

ufl.compound_expressions.generic_pseudo_inverse_expr(A)
  Compute the Penrose-Moore pseudo-inverse of A: (A.T*A)^-1 * A.T.

ufl.compound_expressions.inverse_expr(A)
  Compute the inverse of A.

ufl.compound_expressions.old_determinant_expr_3x3(A)
ufl.compound_expressions.pseudo_determinant_expr(A)
  Compute the pseudo-determinant of A.

ufl.compound_expressions.pseudo_inverse_expr(A)
  Compute the Penrose-Moore pseudo-inverse of A: (A.T*A)^-1 * A.T.
```

ufl.conditional module

This module defines classes for conditional expressions.

```
class ufl.conditional.AndCondition(left, right)
  Bases: ufl.conditional.BinaryCondition
```

```
evaluate (x, mapping, component, index_values)  
class ufl.conditional.BinaryCondition (name, left, right)  
    Bases: ufl.conditional.Condition  
class ufl.conditional.Condition (operands)  
    Bases: ufl.core.operator.Operator  
        ufl_free_indices = ()  
        ufl_index_dimensions = ()  
        ufl_shape = ()  
class ufl.conditional.Conditional (condition, true_value, false_value)  
    Bases: ufl.core.operator.Operator  
        evaluate (x, mapping, component, index_values)  
        ufl_free_indices  
        ufl_index_dimensions  
        ufl_shape  
class ufl.conditional.EQ (left, right)  
    Bases: ufl.conditional.BinaryCondition  
        evaluate (x, mapping, component, index_values)  
class ufl.conditional.GE (left, right)  
    Bases: ufl.conditional.BinaryCondition  
        evaluate (x, mapping, component, index_values)  
class ufl.conditional.GT (left, right)  
    Bases: ufl.conditional.BinaryCondition  
        evaluate (x, mapping, component, index_values)  
class ufl.conditional.LE (left, right)  
    Bases: ufl.conditional.BinaryCondition  
        evaluate (x, mapping, component, index_values)  
class ufl.conditional.LT (left, right)  
    Bases: ufl.conditional.BinaryCondition  
        evaluate (x, mapping, component, index_values)  
class ufl.conditional.MaxValue (left, right)  
    Bases: ufl.core.operator.Operator  
    UFL operator: Take the maximum of two values.  
        evaluate (x, mapping, component, index_values)  
        ufl_free_indices = ()  
        ufl_index_dimensions = ()  
        ufl_shape = ()  
class ufl.conditional.MinValue (left, right)  
    Bases: ufl.core.operator.Operator  
    UFL operator: Take the minimum of two values.
```

```

evaluate (x, mapping, component, index_values)
 = ()
 = ()
 = ()

class ufl.conditional.NE (left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

class ufl.conditional.NotCondition (condition)
    Bases: ufl.conditional.Condition
        evaluate (x, mapping, component, index_values)

class ufl.conditional.OrCondition (left, right)
    Bases: ufl.conditional.BinaryCondition
        evaluate (x, mapping, component, index_values)

```

ufl.constantvalue module

This module defines classes representing constant values.

```

class ufl.constantvalue.ConstantValue
    Bases: ufl.core.terminal.Terminal
        is_cellwise_constant ()
            Return whether this expression is spatially constant over each cell.

        ufl_domains ()
            Return tuple of domains related to this terminal object.

class ufl.constantvalue.FloatValue (value)
    Bases: ufl.constantvalue.ScalarValue
        UFL literal type: Representation of a constant scalar floating point value.

class ufl.constantvalue.Identity (dim)
    Bases: ufl.constantvalue.ConstantValue
        UFL literal type: Representation of an identity matrix.

        evaluate (x, mapping, component, index_values)
            Evaluates the identity matrix on the given components.

        ufl_shape

class ufl.constantvalue.IntValue (value)
    Bases: ufl.constantvalue.ScalarValue
        UFL literal type: Representation of a constant scalar integer value.

class ufl.constantvalue.PermutationSymbol (dim)
    Bases: ufl.constantvalue.ConstantValue
        UFL literal type: Representation of a permutation symbol.

        This is also known as the Levi-Civita symbol, antisymmetric symbol, or alternating symbol.

        evaluate (x, mapping, component, index_values)
            Evaluates the permutation symbol.

```

```
ufl_shape
class ufl.constantvalue.ScalarValue (value)
    Bases: ufl.constantvalue.ConstantValue
    A constant scalar value.
    evaluate (x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()
    value ()

class ufl.constantvalue.Zero (shape=(), free_indices=(), index_dimensions=None)
    Bases: ufl.constantvalue.ConstantValue
    UFL literal type: Representation of a zero valued expression.
    evaluate (x, mapping, component, index_values)
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
ufl.constantvalue.as_ufl (expression)
    Converts expression to an Expr if possible.
ufl.constantvalue.format_float (x)
    Format float value based on global UFL precision.
ufl.constantvalue.zero (*shape)
    UFL literal constant: Return a zero tensor with the given shape.
```

ufl.differentiation module

Differential operators.

```
class ufl.differentiation.CoefficientDerivative (integrand, coefficients, arguments, coefficient_derivatives)
    Bases: ufl.differentiation.Derivative
    Derivative of the integrand of a form w.r.t. the degrees of freedom in a discrete Coefficient.
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
class ufl.differentiation.CompoundDerivative (operands)
    Bases: ufl.differentiation.Derivative
    Base class for all compound derivative types.
class ufl.differentiation.Curl (f)
    Bases: ufl.differentiation.CompoundDerivative
    ufl_free_indices
    ufl_index_dimensions
```

```



class ufl.differentiation.Derivative(operands)
    Bases: ufl.core.operator.Operator

    Base class for all derivative types.

class ufl.differentiation.Div(f)
    Bases: ufl.differentiation.CompoundDerivative

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.Grad(f)
    Bases: ufl.differentiation.CompoundDerivative

    evaluate (x, mapping, component, index_values, derivatives=())
        Get child from mapping and return the component asked for.

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.NablaDiv(f)
    Bases: ufl.differentiation.CompoundDerivative

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.NablaGrad(f)
    Bases: ufl.differentiation.CompoundDerivative

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.ReferenceCurl(f)
    Bases: ufl.differentiation.CompoundDerivative

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.ReferenceDiv(f)
    Bases: ufl.differentiation.CompoundDerivative

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.ReferenceGrad(f)
    Bases: ufl.differentiation.CompoundDerivative

```

```
evaluate(x, mapping, component, index_values, derivatives=())
    Get child from mapping and return the component asked for.

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.differentiation.VariableDerivative(f, v)
    Bases: ufl.differentiation.Derivative

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

ufl.domain module

Types for representing a geometric domain.

```
class ufl.domain.AbstractDomain(topological_dimension, geometric_dimension)
    Bases: object

    Symbolic representation of a geometric domain with only a geometric and topological dimension.

    geometric_dimension()
        Return the dimension of the space this domain is embedded in.

    topological_dimension()
        Return the dimension of the topology of this domain.

class ufl.domain.Mesh(coordinate_element, ufl_id=None, cargo=None)
    Bases: ufl.domain.AbstractDomain

    Symbolic representation of a mesh.

    is_piecewise_linear_simplex_domain()
    ufl_cargo()
        Return carried object that will not be used by UFL.

    ufl_cell()
    ufl_coordinate_element()
    ufl_id()
        Return the ufl_id of this object.

class ufl.domain.MeshView(mesh, topological_dimension, ufl_id=None)
    Bases: ufl.domain.AbstractDomain

    Symbolic representation of a mesh.

    is_piecewise_linear_simplex_domain()
    ufl_cell()
    ufl_id()
        Return the ufl_id of this object.

    ufl_mesh()
```

```

class ufl.domain.TensorProductMesh (meshes, ufl_id=None)
    Bases: ufl.domain.AbstractDomain

    Symbolic representation of a mesh.

        is_piecewise_linear_simplex_domain()

        ufl_cell()

        ufl_coordinate_element()

        ufl_id()
            Return the ufl_id of this object.

affine_mesh (cell, ufl_id=None)
    Create a Mesh over a given cell type with an affine geometric parameterization.

as_domain (domain)
    Convert any valid object to an AbstractDomain type.

default_domain (cell)
    Create a singular default Mesh from a cell, always returning the same Mesh object for the same cell.

extract_domains (expr)
    Return all domains expression is defined on.

extract_unique_domain (expr)
    Return the single unique domain expression is defined on or throw an error.

find_geometric_dimension (expr)
    Find the geometric dimension of an expression.

join_domains (domains)
    Take a list of domains and return a tuple with only unique domain objects.

    Checks that domains with the same id are compatible.

sort_domains (domains)
    Sort domains in a canonical ordering.

```

ufl.equation module

The Equation class, used to express equations like $a == L$.

```

class ufl.equation.Equation (lhs, rhs)
    Bases: object

```

This class is used to represent equations expressed by the “ $==$ ” operator. Examples include $a == L$ and $F == 0$ where a , L and F are Form objects.

ufl.exprcontainers module

This module defines special types for representing mapping of expressions to expressions.

```

class ufl.exprcontainers.ExprList (*operands)
    Bases: ufl.core.operator.Operator

    List of Expr objects. For internal use, never to be created by end users.

        free_indices()

        index_dimensions()

```

```
ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.exprcontainers.ExprMapping(*operands)
Bases: ufl.core.operator.Operator

    Mapping of Expr objects. For internal use, never to be created by end users.

    free_indices()
    index_dimensions()
    ufl_domains()
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

ufl.exprequals module

```
ufl.exprequals.expr_equals(self, other)
    Checks whether the two expressions are represented the exact same way. This does not check if the expressions
    are mathematically equal or equivalent! Used by sets and dicts.

ufl.exprequals.measure_collisions>equals_func)
ufl.exprequals.nonrecursive_expr_equals(self, other)
    Checks whether the two expressions are represented the exact same way. This does not check if the expressions
    are mathematically equal or equivalent! Used by sets and dicts.

ufl.exprequals.print_collisions()
ufl.exprequals.recursive_expr_equals(self, other)
    Checks whether the two expressions are represented the exact same way. This does not check if the expressions
    are mathematically equal or equivalent! Used by sets and dicts.
```

ufl.exprooperators module

This module attaches special functions to Expr. This way we avoid circular dependencies between e.g. Sum and its superclass Expr.

```
ufl.exprooperators.analyse_key(ii, rank)
    Takes something the user might input as an index tuple inside [], which could include complete slices (:) and
    ellipsis (...), and returns tuples of actual UFL index objects.

    The return value is a tuple (indices, axis_indices), each being a tuple of IndexBase instances.

    The return value ‘indices’ corresponds to all input objects of these types: - Index - FixedIndex - int => Wrapped
    in FixedIndex

    The return value ‘axis_indices’ corresponds to all input objects of these types: - Complete slice (:) => Replaced
    by a single new index - Ellipsis (...) => Replaced by multiple new indices
```

ufl.form module

The Form class.

class ufl.form.Form(*integrals*)

Bases: object

Description of a weak form consisting of a sum of integrals over subdomains.

arguments()

Return all Argument objects found in form.

coefficient_numbering()

Return a contiguous numbering of coefficients in a mapping {coefficient: number}.

coefficients()

Return all Coefficient objects found in form.

domain_numbering()

Return a contiguous numbering of domains in a mapping {domain: number}.

empty()

Returns whether the form has no integrals.

equals(*other*)

Evaluate bool(lhs_form == rhs_form).

geometric_dimension()

Return the geometric dimension shared by all domains and functions in this form.

integrals()

Return a sequence of all integrals in form.

integrals_by_type(*integral_type*)

Return a sequence of all integrals with a particular domain type.

max_subdomain_ids()

Returns a mapping on the form {domain: {integral_type: max_subdomain_id}}.

signature()

Signature for use with jit cache (independent of incidental numbering of indices etc.)

subdomain_data()

Returns a mapping on the form {domain: {integral_type: subdomain_data}}.

ufl_cell()

Return the single cell this form is defined on, fails if multiple cells are found.

ufl_domain()

Return the single geometric integration domain occurring in the form.

Fails if multiple domains are found.

NB! This does not include domains of coefficients defined on other meshes, look at form data for that additional information.

ufl_domains()

Return the geometric integration domains occurring in the form.

NB! This does not include domains of coefficients defined on other meshes.

The return type is a tuple even if only a single domain exists.

x_repr_latex_()

```
x_repr_png_()
ufl.form.as_form(form)
    Convert to form if not a form, otherwise return form.

ufl.form.replace_integral_domains(form, common_domain)
    Given a form and a domain, assign a common integration domain to all integrals.

Does not modify the input form (Form should always be immutable). This is to support ill formed forms with no domain specified, sometimes occurring in pydolfin, e.g. assemble(1*dx, mesh=mesh).
```

ufl.formoperators module

Various high level ways to transform a complete Form into a new Form.

```
ufl.formoperators.action(form, coefficient=None)
    UFL form operator: Given a bilinear form, return a linear form with an additional coefficient, representing the action of the form on the coefficient. This can be used for matrix-free methods.
```

```
ufl.formoperators.adjoint(form, reordered_arguments=None)
    UFL form operator: Given a combined bilinear form, compute the adjoint form by changing the ordering (count) of the test and trial functions.
```

By default, new `Argument` objects will be created with opposite ordering. However, if the adjoint form is to be added to other forms later, their arguments must match. In that case, the user must provide a tuple `*reordered_arguments*=(u2,v2)`.

```
ufl.formoperators.block_split(form, ix, iy=0)
    UFL form operator: Given a linear or bilinear form on a mixed space, extract the block corresponding to the indices ix, iy.
```

Example:

```
a = inner(grad(u), grad(v))*dx + div(u)*q*dx + div(v)*p*dx
a = block_split(a, 0, 0) -> inner(grad(u),
grad(v))*dx
```

```
ufl.formoperators.derivative(form, coefficient, argument=None, coefficient_derivatives=None)
    UFL form operator: Compute the Gateaux derivative of form w.r.t. coefficient in direction of argument.
```

If the argument is omitted, a new `Argument` is created in the same space as the coefficient, with argument number one higher than the highest one in the form.

The resulting form has one additional `Argument` in the same finite element space as the coefficient.

A tuple of `Coefficient`s may be provided in place of a single `Coefficient`, in which case the new `Argument` argument is based on a `MixedElement` created from this tuple.

An indexed `Coefficient` from a mixed space may be provided, in which case the argument should be in the corresponding subspace of the coefficient space.

If provided, `coefficient_derivatives` should be a mapping from `Coefficient` instances to their derivatives w.r.t. `coefficient`.

```
ufl.formoperators.energy_norm(form, coefficient=None)
    UFL form operator: Given a bilinear form a and a coefficient f, return the functional a(f, f).
```

```
ufl.formoperators.functional(form)
    UFL form operator: Extract the functional part of form.
```

```
ufl.formoperators.lhs(form)
    UFL form operator: Given a combined bilinear and linear form, extract the left hand side (bilinear form part).
```

Example:

```
a = u*v*dx + f*v*dx
a = lhs(a) -> u*v*dx
```

`ufl.formoperators.rhs (form)`

UFL form operator: Given a combined bilinear and linear form, extract the right hand side (negated linear form part).

Example:

```
a = u*v*dx + f*v*dx
L = rhs(a) -> -f*v*dx
```

`ufl.formoperators.sensitivity_rhs (a, u, L, v)`

UFL form operator: Compute the right hand side for a sensitivity calculation system.

The derivation behind this computation is as follows. Assume a, L to be bilinear and linear forms corresponding to the assembled linear system

$$Ax = b.$$

Where x is the vector of the discrete function corresponding to u . Let v be some scalar variable this equation depends on. Then we can write

$$\begin{aligned} 0 &= \frac{d}{dv}(Ax - b) = \frac{dA}{dv}x + A\frac{dx}{dv} - \frac{db}{dv}, \\ A\frac{dx}{dv} &= \frac{db}{dv} - \frac{dA}{dv}x, \end{aligned}$$

and solve this system for $\frac{dx}{dv}$, using the same bilinear form a and matrix A from the original system. Assume the forms are written

```
v = variable(v_expression)
L = IL(v)*dx
a = Ia(v)*dx
```

where IL and Ia are integrand expressions. Define a Coefficient u representing the solution to the equations. Then we can compute $\frac{db}{dv}$ and $\frac{dA}{dv}$ from the forms

```
da = diff(a, v)
dL = diff(L, v)
```

and the action of da on u by

```
dau = action(da, u)
```

In total, we can build the right hand side of the system to compute $\frac{du}{dv}$ with the single line

```
dL = diff(L, v) - action(diff(a, v), u)
```

or, using this function,

```
dL = sensitivity_rhs(a, u, L, v)
```

`ufl.formoperators.set_list_item (li, i, v)`

`ufl.formoperators.system (form)`

UFL form operator: Split a form into the left hand side and right hand side, see `lhs` and `rhs`.

`ufl.formoperators.zero_lists (shape)`

ufl.functionspace module

Types for representing function spaces.

```
class ufl.functionspace.AbstractFunctionSpace
    Bases: object

    ufl_sub_spaces()

class ufl.functionspace.FunctionSpace(domain, element)
    Bases: ufl.functionspace.AbstractFunctionSpace

    ufl_domain()
        Return ufl domain.

    ufl_domains()
        Return ufl domains.

    ufl_element()
        Return ufl element.

    ufl_sub_spaces()
        Return ufl sub spaces.

class ufl.functionspace.MixedFunctionSpace(*function_spaces)
    Bases: ufl.functionspace.AbstractFunctionSpace

    ufl_domain()
        Return ufl domain.

    ufl_domains()
        Return ufl domains.

    ufl_element()
        Return ufl element.

    ufl_sub_spaces()
        Return ufl sub spaces.

class ufl.functionspace.TensorProductFunctionSpace(*function_spaces)
    Bases: ufl.functionspace.AbstractFunctionSpace

    ufl_sub_spaces()
```

ufl.geometry module

Types for representing symbolic expressions for geometric quantities.

```
class ufl.geometry.CellCoordinate(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFC geometry representation: The coordinate in a reference cell.

    In the context of expression integration, represents the reference cell coordinate of each quadrature point.

    In the context of expression evaluation in a point in a cell, represents that point in the reference coordinate system of the cell.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'X'
```

```
ufl_shape

class ufl.geometry.CellEdgeVectors (domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The vectors between reference cell vertices for each edge in cell.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = ‘CEV’

    ufl_shape

class ufl.geometry.CellFacetJacobian (domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The Jacobian of the mapping from reference facet to reference cell coordinates.

    CFJ_ij = dX_i/dXf_j

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = ‘CFJ’

    ufl_shape

class ufl.geometry.CellFacetJacobianDeterminant (domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The pseudo-determinant of the CellFacetJacobian.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = ‘detCFJ’

class ufl.geometry.CellFacetJacobianInverse (domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The pseudo-inverse of the CellFacetJacobian.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = ‘CFK’

    ufl_shape

class ufl.geometry.CellFacetOrigin (domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The reference cell coordinate corresponding to origin of a reference facet.

    name = ‘X0f’

    ufl_shape

class ufl.geometry.CellNormal (domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The upwards pointing normal vector of the current manifold cell.

    name = ‘cell_normal’

    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).
```

```
class ufl.geometry.CellOrientation(domain)
Bases: ufl.geometry.GeometricCellQuantity

UFL geometry representation: The orientation (+1/-1) of the current cell.

For non-manifold cells (tdim == gdim), this equals the sign of the Jacobian determinant, i.e. +1 if the physical
cell is oriented the same way as the reference cell and -1 otherwise.

For manifold cells of tdim==gdim-1 this is input data belonging to the mesh, used to distinguish between the
sides of the manifold.

name = 'cell_orientation'

class ufl.geometry.CellOrigin(domain)
Bases: ufl.geometry.GeometricCellQuantity

UFL geometry representation: The spatial coordinate corresponding to origin of a reference cell.

is_cellwise_constant()
name = 'x0'
ufl_shape

class ufl.geometry.CellVolume(domain)
Bases: ufl.geometry.GeometricCellQuantity

UFL geometry representation: The volume of the cell.

name = 'volume'

class ufl.geometry.Circumradius(domain)
Bases: ufl.geometry.GeometricCellQuantity

UFL geometry representation: The circumradius of the cell.

name = 'circumradius'

class ufl.geometry.FacetArea(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The area of the facet.

name = 'facetarea'

class ufl.geometry.FacetCoordinate(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The coordinate in a reference cell of a facet.

In the context of expression integration over a facet, represents the reference facet coordinate of each quadrature
point.

In the context of expression evaluation in a point on a facet, represents that point in the reference coordinate
system of the facet.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'Xf'
ufl_shape

class ufl.geometry.FacetEdgeVectors(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The vectors between reference cell vertices for each edge in current facet.
```

```

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'FEV'
ufl_shape

class ufl.geometry.FacetJacobian(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The Jacobian of the mapping from reference facet to spatial coordinates.

         $F_{ij} = dx_i/dXf_j$ 

    The FacetJacobian is the product of the Jacobian and CellFacetJacobian:

         $FJ = dx/dXf = dx/dX dX/dXf = J * CFJ$ 

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'FJ'
ufl_shape

class ufl.geometry.FacetJacobianDeterminant(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The pseudo-determinant of the FacetJacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'detFJ'

class ufl.geometry.FacetJacobainInverse(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The pseudo-inverse of the FacetJacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'FK'
ufl_shape

class ufl.geometry.FacetNormal(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The outwards pointing normal vector of the current facet.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'n'
ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.geometry.FacetOrientation(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The orientation (+1/-1) of the current facet relative to the reference cell.

name = 'facet_orientation'

```

```
class ufl.geometry.FacetOrigin(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
    UFL geometry representation: The spatial coordinate corresponding to origin of a reference facet.

    name = 'x0f'
    ufl_shape

class ufl.geometry.GeometricCellQuantity(domain)
    Bases: ufl.geometry.GeometricQuantity

class ufl.geometry.GeometricFacetQuantity(domain)
    Bases: ufl.geometry.GeometricQuantity

class ufl.geometry.GeometricQuantity(domain)
    Bases: ufl.core.terminal.Terminal

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell (or over each facet for facet quantities).

    ufl_domains()
    ufl_shape = 0

class ufl.geometry.Jacobian(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFL geometry representation: The Jacobian of the mapping from reference cell to spatial coordinates.


$$J_{ij} = \frac{dx_i}{dX_j}$$


    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'J'
    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.geometry.JacobianDeterminant(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFL geometry representation: The determinant of the Jacobian.

    Represents the signed determinant of a square Jacobian or the pseudo-determinant of a non-square Jacobian.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'detJ'

class ufl.geometry.JacobianInverse(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFL geometry representation: The inverse of the Jacobian.

    Represents the inverse of a square Jacobian or the pseudo-inverse of a non-square Jacobian.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'K'
```

ufl_shape

Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.geometry.MaxCellEdgeLength (domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The maximum edge length of the cell.

name = ‘maxcelledgeLength’

class ufl.geometry.MaxFacetEdgeLength (domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The maximum edge length of the facet.

name = ‘maxfacetedgedlength’

class ufl.geometry.MinCellEdgeLength (domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The minimum edge length of the cell.

name = ‘mincelledgeLength’

class ufl.geometry.MinFacetEdgeLength (domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The minimum edge length of the facet.

name = ‘minfacetedgedlength’

class ufl.geometry.QuadratureWeight (domain)

Bases: *ufl.geometry.GeometricQuantity*

UFL geometry representation: The current quadrature weight.

Only used inside a quadrature context.

is_cellwise_constant ()

Return whether this expression is spatially constant over each cell.

name = ‘weight’

class ufl.geometry.ReferenceCellVolume (domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The volume of the reference cell.

name = ‘reference_cell_volume’

class ufl.geometry.ReferenceFacetVolume (domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The volume of the reference cell of the current facet.

name = ‘reference_facet_volume’

class ufl.geometry.ReferenceNormal (domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The outwards pointing normal vector of the current facet on the reference cell

name = ‘reference_normal’

ufl_shape

```
class ufl.geometry.SpatialCoordinate(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The coordinate in a domain.

    In the context of expression integration, represents the domain coordinate of each quadrature point.

    In the context of expression evaluation in a point, represents the value of that point.

    evaluate (x, mapping, component, index_values)
        Return the value of the coordinate.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    name = 'x'

    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).
```

ufl.index_combination_utils module

Utilities for analysing and manipulating free index tuples

```
ufl.index_combination_utils.create_slice_indices(component, shape, fi)
```

```
ufl.index_combination_utils.merge_nonoverlapping_indices(a, b)
```

Merge non-overlapping free indices into one representation.

Example: $C[i,j,r,s] = \text{outer}(A[i,s], B[j,r])$ A, B $\rightarrow (i,j,r,s)$, (idim,jdim,rdim,sdim)

```
ufl.index_combination_utils.merge_overlapping_indices(afi, afid, bfi, bfid)
```

Merge overlapping free indices into one free and one repeated representation.

Example: $C[j,r] := A[i,j,k] * B[i,r,k]$ A, B $\rightarrow (j,r)$, (jdim,rdim), (i,k), (idim,kdim)

```
ufl.index_combination_utils.merge_unique_indices(afi, afid, bfi, bfid)
```

Merge two pairs of (index ids, index dimensions) sequences into one pair without duplicates.

The id tuples afi, bfi are assumed already sorted by id. Given a list of (id, dim) tuples already sorted by id, return a unique list with duplicates removed. Also checks that the dimensions of duplicates are matching.

```
ufl.index_combination_utils.remove_indices(fi, fid, rfi)
```

```
ufl.index_combination_utils.unique_sorted_indices(indices)
```

Given a list of (id, dim) tuples already sorted by id, return a unique list with duplicates removed. Also checks that the dimensions of duplicates are matching.

ufl.indexed module

This module defines the Indexed class.

```
class ufl.indexed.Indexed(expression, multiindex)
    Bases: ufl.core.operator.Operator

    evaluate (x, mapping, component, index_values, derivatives=())
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = ()
```

ufl.indexsum module

This module defines the IndexSum class.

```
class ufl.indexsum.IndexSum (summand, index)
    Bases: ufl.core.operator.Operator
        dimension ()
        evaluate (x, mapping, component, index_values)
        index ()
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape
```

ufl.integral module

The Integral class.

```
class ufl.integral.Integral (integrand, integral_type, domain, subdomain_id, metadata, subdomain_data)
    Bases: object
    An integral over a single domain.
    integral_type ()
        Return the domain type of this integral.
    integrand ()
        Return the integrand expression, which is an Expr instance.
    metadata ()
        Return the compiler metadata this integral has been annotated with.
    reconstruct (integrand=None, integral_type=None, domain=None, subdomain_id=None, metadata=None, subdomain_data=None)
        Construct a new Integral object with some properties replaced with new values.
    Example: <a = Integral instance> b = a.reconstruct(expand_compounds(a.integrand()))
    c = a.reconstruct(metadata={'quadrature_degree':2})
    subdomain_data ()
        Return the domain data of this integral.
    subdomain_id ()
        Return the subdomain id of this integral.
    ufl_domain ()
        Return the integration domain of this integral.
```

ufl.log module

This module provides functions used by the UFL implementation to output messages. These may be redirected by the user of UFL.

```
class ufl.log.Logger (name, exception_type=<type 'exceptions.Exception'>)
```

```
add_indent (increment=1)
    Add to indentation level.

add_logfile (filename=None, mode='a', level=10)
    Add a log file.

begin (*message)
    Begin task: write message and increase indentation level.

debug (*message)
    Write debug message.

deprecate (*message)
    Write deprecation message.

end ()
    End task: write a newline and decrease indentation level.

error (*message)
    Write error message and raise an exception.

get_handler ()
    Get handler for logging.

get_logfile_handler (filename)
    Gets the handler to the file identified by the given file name.

get_logger ()
    Return message logger.

info (*message)
    Write info message.

info_blue (*message)
    Write info message in blue.

info_green (*message)
    Write info message in green.

info_red (*message)
    Write info message in red.

log (level, *message)
    Write a log message on given log level.

pop_level ()
    Pop log level from the level stack, reverting to before the last push_level.

push_level (level)
    Push a log level on the level stack.

set_handler (handler)
    Replace handler for logging. To add additional handlers instead of replacing the existing one, use log.get_logger().addHandler(myhandler). See the logging module for more details.

set_indent (level)
    Set indentation level.

set_level (level)
    Set log level.

set_prefix (prefix)
    Set prefix for log messages.
```

```
warning(*message)
    Write warning message.

warning_blue(*message)
    Write warning message in blue.

warning_green(*message)
    Write warning message in green.

warning_red(*message)
    Write warning message in red.
```

ufl.mathfunctions module

This module provides basic mathematical functions.

```
class ufl.mathfunctions.Acos(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Asin(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Atan(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Atan2(arg1, arg2)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.mathfunctions.BesselFunction(name, classname, nu, argument)
    Bases: ufl.core.operator.Operator

    Base class for all bessel functions

    evaluate(x, mapping, component, index_values)
    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.mathfunctions.BesselI(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.mathfunctions.BesselJ(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.mathfunctions.BesselK(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.mathfunctions.BesselY(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.mathfunctions.Cos(argument)
    Bases: ufl.mathfunctions.MathFunction
```

```

class ufl.mathfunctions.Cosh (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Erf (argument)
    Bases: ufl.mathfunctions.MathFunction
        evaluate (x, mapping, component, index_values)

class ufl.mathfunctions.Exp (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Ln (argument)
    Bases: ufl.mathfunctions.MathFunction
        evaluate (x, mapping, component, index_values)

class ufl.mathfunctions.MathFunction (name, argument)
    Bases: ufl.core.operator.Operator
        Base class for all unary scalar math functions.

        evaluate (x, mapping, component, index_values)
        ufl_free_indices = ()
        ufl_index_dimensions = ()
        ufl_shape = ()

class ufl.mathfunctions.Sin (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Sinh (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Sqrt (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Tan (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Tanh (argument)
    Bases: ufl.mathfunctions.MathFunction

```

ufl.measure module

The Measure class.

```

class ufl.measure.Measure (integral_type, domain=None, subdomain_id='everywhere', metadata=None, subdomain_data=None)
    Bases: object

    integral_type ()
        Return the domain type.

        Valid domain types are “cell”, “exterior_facet”, “interior_facet”, etc.

    metadata ()
        Return the integral metadata. This data is not interpreted by UFL. It is passed to the form compiler which can ignore it or use it to compile each integral of a form in a different way.

    reconstruct (integral_type=None, subdomain_id=None, domain=None, metadata=None, subdomain_main_data=None)
        Construct a new Measure object with some properties replaced with new values.

```

Example: <dm = Measure instance> b = dm.reconstruct(subdomain_id=2) c = dm.reconstruct(metadata={ “quadrature_degree”: 3 })

Used by the call operator, so this is equivalent: b = dm(2) c = dm(0, { “quadrature_degree”: 3 })

subdomain_data()

Return the integral subdomain_data. This data is not interpreted by UFL. Its intension is to give a context in which the domain id is interpreted.

subdomain_id()

Return the domain id of this measure (integer).

ufl_domain()

Return the domain associated with this measure.

This may be None or a Domain object.

class ufl.measure.MeasureProduct (*measures)

Bases: object

Represents a product of measures.

This is a notational intermediate object to handle the notation

f*(dm1*dm2)

This is work in progress and not functional. It needs support in other parts of ufl and the rest of the code generation chain.

sub_measures()

Return submeasures.

class ufl.measure.MeasureSum (*measures)

Bases: object

Represents a sum of measures.

This is a notational intermediate object to translate the notation

f*(ds(1)+ds(3))

into

f*ds(1) + f*ds(3)

ufl.measure.as_integral_type (integral_type)

Map short name to long name and require a valid one.

ufl.measure.integral_types()

Return a tuple of all domain type strings.

ufl.measure.measure_names()

Return a tuple of all measure name strings.

ufl.measure.register_integral_type (integral_type, measure_name)

ufl.objects module

Utility objects for pretty syntax in user code.

ufl.operators module

This module extends the form language with free function operators, which are either already available as member functions on UFL objects or defined as compound operators involving basic operations on the UFL objects.

`ufl.operators.And(left, right)`

UFL operator: A boolean expression (left and right) for use with `conditional`.

`ufl.operators.Dn(f)`

UFL operator: Take the directional derivative of f in the facet normal direction, $Dn(f) := \text{dot}(\text{grad}(f), n)$.

`ufl.operatorsDt(f)`

UFL operator: <Not implemented yet!> The partial derivative of f with respect to time.

`ufl.operators.Dx(f, *i)`

UFL operator: Take the partial derivative of f with respect to spatial variable number i . Equivalent to $f \cdot dx(*i)$.

`ufl.operators.Max(x, y)`

UFL operator: Take the maximum of x and y .

`ufl.operators.Min(x, y)`

UFL operator: Take the minimum of x and y .

`ufl.operators.Not(condition)`

UFL operator: A boolean expression (not condition) for use with `conditional`.

`ufl.operators.Or(left, right)`

UFL operator: A boolean expression (left or right) for use with `conditional`.

`ufl.operators.acos(f)`

UFL operator: Take the inverse cosine of f .

`ufl.operators.asin(f)`

UFL operator: Take the inverse sine of f .

`ufl.operators.atan(f)`

UFL operator: Take the inverse tangent of f .

`ufl.operators.atan_2(f1, f2)`

UFL operator: Take the inverse tangent with two the arguments $f1$ and $f2$.

`ufl.operators.avg(v)`

UFL operator: Take the average of v across a facet.

`ufl.operators.bessel_I(nu, f)`

UFL operator: regular modified cylindrical Bessel function.

`ufl.operators.bessel_J(nu, f)`

UFL operator: cylindrical Bessel function of the first kind.

`ufl.operators.bessel_K(nu, f)`

UFL operator: irregular modified cylindrical Bessel function.

`ufl.operators.bessel_Y(nu, f)`

UFL operator: cylindrical Bessel function of the second kind.

`ufl.operators.cell_avg(f)`

UFL operator: Take the average of v over a cell.

`ufl.operators.cofac(A)`

UFL operator: Take the cofactor of A .

`ufl.operators.conditional`(*condition*, *true_value*, *false_value*)
 UFL operator: A conditional expression, taking the value of *true_value* when *condition* evaluates to `true` and *false_value* otherwise.

`ufl.operators.contraction`(*a*, *a_axes*, *b*, *b_axes*)
 UFL operator: Take the contraction of *a* and *b* over given axes.

`ufl.operators.cos`(*f*)
 UFL operator: Take the cosine of *f*.

`ufl.operators.cosh`(*f*)
 UFL operator: Take the hyperbolic cosine of *f*.

`ufl.operators.cross`(*a*, *b*)
 UFL operator: Take the cross product of *a* and *b*.

`ufl.operators.curl`(*f*)
 UFL operator: Take the curl of *f*.

`ufl.operators.det`(*A*)
 UFL operator: Take the determinant of *A*.

`ufl.operators.dev`(*A*)
 UFL operator: Take the deviatoric part of *A*.

`ufl.operators.diag`(*A*)
 UFL operator: Take the diagonal part of rank 2 tensor *A* or make a diagonal rank 2 tensor from a rank 1 tensor.
 Always returns a rank 2 tensor. See also `diag_vector`.

`ufl.operators.diag_vector`(*A*)
 UFL operator: Take the diagonal part of rank 2 tensor *A* and return as a vector.
 See also `diag`.

`ufl.operators.diff`(*f*, *v*)
 UFL operator: Take the derivative of *f* with respect to the variable *v*.
 If *f* is a form, `diff` is applied to each integrand.

`ufl.operators.div`(*f*)
 UFL operator: Take the divergence of *f*.
 This operator follows the div convention where

$$\text{div}(\mathbf{v}) = \mathbf{v}[i].\text{dx}(i)$$

$$\text{div}(\mathbf{T})[:] = \mathbf{T}[:,i].\text{dx}(i)$$
 for vector expressions *v*, and arbitrary rank tensor expressions *T*.

See also: `nabla_div()`

`ufl.operators.dot`(*a*, *b*)
 UFL operator: Take the dot product of *a* and *b*.

`ufl.operators.elem_div`(*A*, *B*)
 UFL operator: Take the elementwise division of tensors *A* and *B* with the same shape.

`ufl.operators.elem_mult`(*A*, *B*)
 UFL operator: Take the elementwise multiplication of tensors *A* and *B* with the same shape.

`ufl.operators.elem_op`(*op*, **args*)
 UFL operator: Take the elementwise application of operator *op* on scalar values from one or more tensor arguments.

`ufl.operators.elem_op_items(op_ind, indices, *args)`

`ufl.operators.elem_pow(A, B)`

UFL operator: Take the elementwise power of tensors A and B with the same shape.

`ufl.operators.eq(left, right)`

UFL operator: A boolean expression ($\text{left} == \text{right}$) for use with conditional.

`ufl.operators.erf(f)`

UFL operator: Take the error function of f .

`ufl.operators.exp(f)`

UFL operator: Take the exponential of f .

`ufl.operators.exterior_derivative(f)`

UFL operator: Take the exterior derivative of f .

The exterior derivative uses the element family to determine whether `id`, `grad`, `curl` or `div` should be used.

Note that this uses the `grad` and `div` operators, as opposed to `nabla_grad` and `nabla_div`.

`ufl.operators.facet_avg(f)`

UFL operator: Take the average of v over a facet.

`ufl.operators.ge(left, right)`

UFL operator: A boolean expression ($\text{left} \geq \text{right}$) for use with conditional.

`ufl.operators.grad(f)`

UFL operator: Take the gradient of f .

This operator follows the grad convention where

$$\text{grad}(s)[i] = s.\text{dx}(i)$$

$$\text{grad}(v)[i,j] = v[i].\text{dx}(j)$$

$$\text{grad}(T)[:,i] = T[:,i].\text{dx}(i)$$

for scalar expressions s , vector expressions v , and arbitrary rank tensor expressions T .

See also: [`nabla_grad\(\)`](#)

`ufl.operators.gt(left, right)`

UFL operator: A boolean expression ($\text{left} > \text{right}$) for use with conditional.

`ufl.operators.inner(a, b)`

UFL operator: Take the inner product of a and b .

`ufl.operators.inv(A)`

UFL operator: Take the inverse of A .

`ufl.operators.jump(v, n=None)`

UFL operator: Take the jump of v across a facet.

`ufl.operators.le(left, right)`

UFL operator: A boolean expression ($\text{left} \leq \text{right}$) for use with conditional.

`ufl.operators.ln(f)`

UFL operator: Take the natural logarithm of f .

`ufl.operators.lt(left, right)`

UFL operator: A boolean expression ($\text{left} < \text{right}$) for use with conditional.

`ufl.operators.max_value(x, y)`

UFL operator: Take the maximum of x and y .

`ufl.operators.min_value(x, y)`
 UFL operator: Take the minimum of x and y .

`ufl.operators.nabla_div(f)`
 UFL operator: Take the divergence of f .

This operator follows the div convention where

$$\text{nabla_div}(\mathbf{v}) = \mathbf{v}[i].\text{dx}(i)$$

$$\text{nabla_div}(\mathbf{T})[:, :] = \mathbf{T}[i, :].\text{dx}(i)$$

for vector expressions \mathbf{v} , and arbitrary rank tensor expressions \mathbf{T} .

See also: [div\(\)](#)

`ufl.operators.nabla_grad(f)`
 UFL operator: Take the gradient of f .

This operator follows the grad convention where

$$\text{nabla_grad}(\mathbf{s})[i] = \mathbf{s}.\text{dx}(i)$$

$$\text{nabla_grad}(\mathbf{v})[i,j] = \mathbf{v}[j].\text{dx}(i)$$

$$\text{nabla_grad}(\mathbf{T})[i, :] = \mathbf{T}[:, i].\text{dx}(i)$$

for scalar expressions \mathbf{s} , vector expressions \mathbf{v} , and arbitrary rank tensor expressions \mathbf{T} .

See also: [grad\(\)](#)

`ufl.operators.ne(left, right)`

UFL operator: A boolean expression ($\text{left} != \text{right}$) for use with `conditional`.

`ufl.operators.outer(*operands)`

UFL operator: Take the outer product of two or more operands.

`ufl.operators.perp(v)`

UFL operator: Take the perp of v , i.e. $(-v_1, +v_0)$.

`ufl.operators.rank(f)`

UFL operator: The rank of f .

`ufl.operators.rot(f)`

UFL operator: Take the curl of f .

`ufl.operators.shape(f)`

UFL operator: The shape of f .

`ufl.operators.sign(x)`

UFL operator: Take the sign (+1 or -1) of x .

`ufl.operators.sin(f)`

UFL operator: Take the sine of f .

`ufl.operators.sinh(f)`

UFL operator: Take the hyperbolic sine of f .

`ufl.operators.skew(A)`

UFL operator: Take the skew symmetric part of A .

`ufl.operators.sqrt(f)`

UFL operator: Take the square root of f .

`ufl.operators.sym(A)`

UFL operator: Take the symmetric part of A .

`ufl.operators.tan(f)`

UFL operator: Take the tangent of f .

`ufl.operators.tanh(f)`

UFL operator: Take the hyperbolic tangent of f .

`ufl.operators.tr(A)`

UFL operator: Take the trace of A .

`ufl.operators.transpose(A)`

UFL operator: Take the transposed of tensor A .

`ufl.operators.variable(e)`

UFL operator: Define a variable representing the given expression, see also `diff()`.

ufl.permutation module

This module provides utility functions for computing permutations and generating index lists.

`ufl.permutation.build_component_numbering(shape, symmetry)`

Build a numbering of components within the given value shape, taking into consideration a symmetry mapping which leaves the mapping noncontiguous. Returns a dict { component -> numbering } and an ordered list of components [numbering -> component]. The dict contains all components while the list only contains the ones not mapped by the symmetry mapping.

`ufl.permutation.compute_indices(shape)`

Compute all index combinations for given shape

`ufl.permutation.compute_indices2(shape)`

Compute all index combinations for given shape

`ufl.permutation.compute_order_tuples(k, n)`

Compute all tuples of n integers such that the sum is k

`ufl.permutation.compute_permutation_pairs(j, k)`

Compute all permutations of $j + k$ elements from $(0, j + k)$ in rising order within $(0, j)$ and $(j, j + k)$ respectively.

`ufl.permutation.compute_permutations(k, n, skip=None)`

Compute all permutations of k elements from $(0, n)$ in rising order. Any elements that are contained in the list `skip` are not included.

`ufl.permutation.compute_sign(permuation)`

Compute sign by sorting.

ufl.precedence module

Precedence handling.

`ufl.precedence.assign_precedences(precedence_list)`

Given a precedence list, assign ints to class._precedence.

`ufl.precedence.build_precedence_list()`

`ufl.precedence.build_precedence_mapping(precedence_list)`

Given a precedence list, build a dict with class->int mappings. Utility function used by some external code.

`ufl.precedence.parstr(child, parent, pre='(', post=')', format=<type 'str'>)`

ufl.protocols module

```
ufl.protocols.id_or_none(obj)
    Returns None if the object is None, obj.ufl_id() if available, or id(obj) if not.

This allows external libraries to implement an alternative to id(obj) in the ufl_id() function, such that ufl can identify objects as the same without knowing about their types.

ufl.protocols.metadata_equal(a, b)
ufl.protocols.metadata_hashdata(md)
```

ufl.referencevalue module

Representation of the reference value of a function.

```
class ufl.referencevalue.ReferenceValue(f)
    Bases: ufl.core.operator.Operator

    Representation of the reference cell value of a form argument.

    evaluate(x, mapping, component, index_values, derivatives=())
        Get child from mapping and return the component asked for.

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape
```

ufl.restriction module

Restriction operations.

```
class ufl.restriction.CellAvg(f)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Performs an approximate symbolic evaluation, since we dont have a cell.

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape

class ufl.restriction.FacetAvg(f)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Performs an approximate symbolic evaluation, since we dont have a cell.

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape

class ufl.restriction.NegativeRestricted(f)
    Bases: ufl.restriction.Restricted

class ufl.restriction.PositiveRestricted(f)
    Bases: ufl.restriction.Restricted
```

```
class ufl.restriction.Restricted(f)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)

    side()

    ufl_free_indices

    ufl_index_dimensions

    ufl_shape
```

ufl.sobolevspaces module

This module defines a symbolic heirarchy of Sobolev spaces to enable symbolic reasoning about the spaces in which finite elements lie.

```
class ufl.sobolevspaces.DirectionalsobolevSpace(orders)
    Bases: ufl.sobolevspaces.SobolevSpace

    Symbolic representation of a Sobolev space with varying smoothness in different spatial directions.

class ufl.sobolevspaces.SobolevSpace(name, parents=None)
    Bases: object

    Symbolic representation of a Sobolev space. This implements a subset of the methods of a Python set so that finite elements and other Sobolev spaces can be tested for inclusion.
```

ufl.sorting module

This module contains a sorting rule for expr objects that is more robust w.r.t. argument numbering than using repr.

```
ufl.sorting.cmp_expr(a, b)
    Replacement for cmp(a, b), removed in Python 3, for Expr objects.

ufl.sorting.sorted_expr(sequence)
    Return a canonically sorted list of Expr objects in sequence.

ufl.sorting.sorted_expr_sum(seq)
```

ufl.split_functions module

Algorithm for splitting a Coefficient or Argument into subfunctions.

```
ufl.split_functions.split(v)
    UFL operator: If v is a Coefficient or Argument in a mixed space, returns a tuple with the function components corresponding to the subelements.
```

ufl.tensoralgebra module

Compound tensor algebra operations.

```
class ufl.tensoralgebra.Cofactor(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices = ()
```

```
ufl_index_dimensions = ()  
ufl_shape  
class ufl.tensoralgebra.CompoundTensorOperator (operands)  
    Bases: ufl.core.operator.Operator  
class ufl.tensoralgebra.Cross (a, b)  
    Bases: ufl.tensoralgebra.CompoundTensorOperator  
        ufl_free_indices  
        ufl_index_dimensions  
        ufl_shape = (3,)  
class ufl.tensoralgebra.Determinant (A)  
    Bases: ufl.tensoralgebra.CompoundTensorOperator  
        ufl_free_indices = ()  
        ufl_index_dimensions = ()  
        ufl_shape = ()  
class ufl.tensoralgebra.Deviatoric (A)  
    Bases: ufl.tensoralgebra.CompoundTensorOperator  
        ufl_free_indices  
        ufl_index_dimensions  
        ufl_shape  
class ufl.tensoralgebra.Dot (a, b)  
    Bases: ufl.tensoralgebra.CompoundTensorOperator  
        ufl_free_indices  
        ufl_index_dimensions  
        ufl_shape  
class ufl.tensoralgebra.Inner (a, b)  
    Bases: ufl.tensoralgebra.CompoundTensorOperator  
        ufl_free_indices  
        ufl_index_dimensions  
        ufl_shape = ()  
class ufl.tensoralgebra.Inverse (A)  
    Bases: ufl.tensoralgebra.CompoundTensorOperator  
        ufl_free_indices = ()  
        ufl_index_dimensions = ()  
        ufl_shape  
class ufl.tensoralgebra.Outer (a, b)  
    Bases: ufl.tensoralgebra.CompoundTensorOperator  
        ufl_free_indices  
        ufl_index_dimensions  
        ufl_shape
```

```
class ufl.tensoralgebra.Skew(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.tensoralgebra.Sym(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape

class ufl.tensoralgebra.Trace(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape = ()

class ufl.tensoralgebra.Transposed(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator
        ufl_free_indices
        ufl_index_dimensions
        ufl_shape
```

ufl.tensors module

Classes used to group scalar expressions into expressions with rank > 0.

```
class ufl.tensors.ComponentTensor(expression, indices)
    Bases: ufl.core.operator.Operator
```

UFL operator type: Maps the free indices of a scalar valued expression to tensor axes.

```
    evaluate(x, mapping, component, index_values)
    indices()
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

```
class ufl.tensors.ListTensor(*expressions)
    Bases: ufl.core.operator.Operator
```

UFL operator type: Wraps a list of expressions into a tensor valued expression of one higher rank.

```
    evaluate(x, mapping, component, index_values, derivatives=())
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

`ufl.tensors.as_matrix(expressions, indices=None)`
 UFL operator: As `as_tensor()`, but limited to rank 2 tensors.

`ufl.tensors.as_scalar(expression)`
 Given a scalar or tensor valued expression A, returns either of the tuples:

```
(a,b) = (A, ())
(a,b) = (A[indices], indices)
```

such that a is always a scalar valued expression.

`ufl.tensors.as_scalars(*expressions)`
 Given multiple scalar or tensor valued expressions A, returns either of the tuples:

```
(a,b) = (A, ())
(a,b) = ([A[0][indices], ..., A[-1][indices]], indices)
```

such that a is always a list of scalar valued expressions.

`ufl.tensors.as_tensor(expressions, indices=None)`
 UFL operator: Make a tensor valued expression.

This works in two different ways, by using indices or lists.

1) Returns A such that $A[\text{indices}] = \text{expressions}$. If indices are provided, expressions must be a scalar valued expression with all the provided indices among its free indices. This operator will then map each of these indices to a tensor axis, thereby making a tensor valued expression from a scalar valued expression with free indices.

2) Returns A such that $A[k, \dots] = \text{expressions}^*[k]$. If no indices are provided, *expressions must be a list or tuple of expressions. The expressions can also consist of recursively nested lists to build higher rank tensors.

`ufl.tensors.as_vector(expressions, index=None)`
 UFL operator: As `as_tensor()`, but limited to rank 1 tensors.

`ufl.tensors.dyad(d, *iota)`
 TODO: Develop this concept, can e.g. write $A[i,j]*\text{dyad}(j,i)$ for the transpose.

`ufl.tensors.from_numpy_to_lists(expressions)`

`ufl.tensors.numpy2nestedlists(arr)`

`ufl.tensors.relabel(A, indexmap)`

UFL operator: Relabel free indices of A with new indices, using the given mapping.

`ufl.tensors.unit_indexed_tensor(shape, component)`

`ufl.tensors.unit_list(i, n)`

`ufl.tensors.unit_list2(i, j, n)`

`ufl.tensors.unit_matrices(d)`

UFL value: A tuple of constant unit matrices in all directions with dimension d .

`ufl.tensors.unit_matrix(i, j, d)`

UFL value: A constant unit matrix in direction $i, *j*$ with dimension d .

`ufl.tensors.unit_vector(i, d)`

UFL value: A constant unit vector in direction i with dimension d .

`ufl.tensors.unit_vectors(d)`

UFL value: A tuple of constant unit vectors in all directions with dimension d .

`ufl.tensors.unwrap_list_tensor(lt)`

ufl.variable module

Defines the Variable and Label classes, used to label expressions as variables for differentiation.

```
class ufl.variable.Label(count=None)
    Bases: ufl.core.terminal.Terminal

    count()
    is_cellwise_constant()
    ufl_domains()
        Return tuple of domains related to this terminal object.

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

```
class ufl.variable.Variable(expression, label=None)
    Bases: ufl.core.operator.Operator
```

A Variable is a representative for another expression.

It will be used by the end-user mainly for defining a quantity to differentiate w.r.t. using diff. Example:

```
e = <...>
e = variable(e)
f = exp(e**2)
df = diff(f, e)

evaluate(x, mapping, component, index_values)
expression()
label()
ufl_domains()
ufl_free_indices = ()
ufl_index_dimensions = ()
ufl_shape
```

Module contents

The Unified Form Language is an embedded domain specific language for definition of variational forms intended for finite element discretization. More precisely, it defines a fixed interface for choosing finite element spaces and defining expressions for weak forms in a notation close to the mathematical one.

This Python module contains the language as well as algorithms to work with it.

- To import the language, type

```
from ufl import *
```

- To import the underlying classes an UFL expression tree is built from, type

```
from ufl.classes import *
```

- Various algorithms for working with UFL expression trees can be accessed by

```
from ufl.algorithms import *
```

Classes and algorithms are considered implementation details and should not be used in form definitions.

For more details on the language, see

<http://www.fenicsproject.org>

and

<http://arxiv.org/abs/1211.4047>

The development version can be found in the repository at

<https://www.bitbucket.org/fenics-project/ufl>

A very brief overview of the language contents follows:

- Cells:

```
- AbstractCell
- Cell
- TensorProductCell
- vertex
- interval
- triangle
- tetrahedron
- quadrilateral
- hexahedron
```

- Domains:

```
- AbstractDomain
- Mesh
- MeshView
- TensorProductMesh
```

- Sobolev spaces:

```
- L2
- H1
- H2
- HDiv
- HCurl
```

- Elements:

```
- FiniteElement
- MixedElement
- VectorElement
- TensorElement
- EnrichedElement
- NodalEnrichedElement
- RestrictedElement
- TensorProductElement
- HDivElement
- HCurlElement
- BrokenElement
- FacetElement
- InteriorElement
```

- Function spaces:

- FunctionSpace

- Arguments:

- Argument
- TestFunction
- TrialFunction
- Arguments
- TestFunctions
- TrialFunctions

- Coefficients:

- Coefficient
- Constant
- VectorConstant
- TensorConstant

- Splitting form arguments in mixed spaces:

- split

- Literal constants:

- Identity
- PermutationSymbol

- Geometric quantities:

- SpatialCoordinate
- FacetNormal
- CellNormal
- CellVolume
- Circumradius
- MinCellEdgeLength
- MaxCellEdgeLength
- FacetArea
- MinFacetEdgeLength
- MaxFacetEdgeLength
- Jacobian
- JacobianDeterminant
- JacobianInverse

- Indices:

- Index
- indices
- i, j, k, l
- p, q, r, s

- Scalar to tensor expression conversion:

- as_tensor
- as_vector
- as_matrix

- Unit vectors and matrices:

```
- unit_vector
- unit_vectors
- unit_matrix
- unit_matrices
```

- Tensor algebra operators:

```
- outer, inner, dot, cross, perp
- det, inv, cofac
- transpose, tr, diag, diag_vector
- dev, skew, sym
```

- Elementwise tensor operators:

```
- elem_mult
- elem_div
- elem_pow
- elem_op
```

- Differential operators:

```
- variable
- diff,
- grad, nabla_grad
- div, nabla_div
- curl, rot
- Dx, Dn
```

- Nonlinear functions:

```
- max_value, min_value
- abs, sign
- sqrt
- exp, ln, erf
- cos, sin, tan
- acos, asin, atan, atan_2
- cosh, sinh, tanh
- bessel_J, bessel_Y, bessel_I, bessel_K
```

- Discontinuous Galerkin operators:

```
- v('+'), v(' - ')
- jump
- avg
- cell_avg, facet_avg
```

- Conditional operators:

```
- eq, ne, le, ge, lt, gt
- <, >, <=, >=
- And, Or, Not
- conditional
```

- Integral measures:

```
- dx, ds, dS, dP
- dc, dC, dO, dI, dX
- ds_b, ds_t, ds_tb, ds_v, dS_h, dS_v
```

- Form transformations:

```
- rhs, lhs
- system
- functional
- replace, replace_integral_domains
- adjoint
- action
- energy_norm,
- sensitivity_rhs
- derivative
```

ufl.product (sequence)

Return the product of all elements in a sequence.

exception ufl.UFLEException

Bases: exceptions.Exception

Base class for UFL exceptions.

ufl.as_cell (cell)

Convert any valid object to a Cell or return cell if it is already a Cell.

Allows an already valid cell, a known cellname string, or a tuple of cells for a product cell.

class ufl.AbstractCell (topological_dimension, geometric_dimension)

Bases: object

Representation of an abstract finite element cell with only the dimensions known.

geometric_dimension ()

Return the dimension of the space this cell is embedded in.

has_simplex_facets ()

Return True if all the facets of this cell are simplex cells.

is_simplex ()

Return True if this is a simplex cell.

topological_dimension ()

Return the dimension of the topology of this cell.

class ufl.Cell (cellname, geometric_dimension=None)

Bases: *ufl.cell.AbstractCell*

Representation of a named finite element cell with known structure.

cellname ()

Return the cellname of the cell.

has_simplex_facets ()

Return True if all the facets of this cell are simplex cells.

is_simplex ()

Return True if this is a simplex cell.

num_edges ()

The number of cell edges.

```

num_facet_edges()
    The number of facet edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct (geometric_dimension=None)

class ufl.TensorProductCell (*cells, **kwargs)
    Bases: ufl.cell.AbstractCell

cellname()
    Return the cellname of the cell.

has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

num_edges()
    The number of cell edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct (geometric_dimension=None)

sub_cells()
    Return list of cell factors.

ufl.as_domain (domain)
    Convert any valid object to an AbstractDomain type.

class ufl.AbstractDomain (topological_dimension, geometric_dimension)
    Bases: object

    Symbolic representation of a geometric domain with only a geometric and topological dimension.

geometric_dimension()
    Return the dimension of the space this domain is embedded in.

topological_dimension()
    Return the dimension of the topology of this domain.

class ufl.Mesh (coordinate_element, ufl_id=None, cargo=None)
    Bases: ufl.domain.AbstractDomain

    Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cargo()
    Return carried object that will not be used by UFL.

ufl_cell()

ufl_coordinate_element()

```

```
ufl_id()
    Return the ufl_id of this object.

class ufl.MeshView(mesh, topological_dimension, ufl_id=None)
    Bases: ufl.domain.AbstractDomain
        Symbolic representation of a mesh.

    is_piecewise_linear_simplex_domain()

    ufl_cell()

    ufl_id()
        Return the ufl_id of this object.

    ufl_mesh()

class ufl.TensorProductMesh(meshes, ufl_id=None)
    Bases: ufl.domain.AbstractDomain
        Symbolic representation of a mesh.

    is_piecewise_linear_simplex_domain()

    ufl_cell()

    ufl_coordinate_element()

    ufl_id()
        Return the ufl_id of this object.

class ufl.SpatialCoordinate(domain)
    Bases: ufl.geometry.GeometricCellQuantity
        UFL geometry representation: The coordinate in a domain.

        In the context of expression integration, represents the domain coordinate of each quadrature point.

        In the context of expression evaluation in a point, represents the value of that point.

    evaluate(x, mapping, component, index_values)
        Return the value of the coordinate.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = ‘x’

    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.CellVolume(domain)
    Bases: ufl.geometry.GeometricCellQuantity
        UFL geometry representation: The volume of the cell.

    name = ‘volume’

class ufl.Circumradius(domain)
    Bases: ufl.geometry.GeometricCellQuantity
        UFL geometry representation: The circumradius of the cell.

    name = ‘circumradius’
```

```

class ufl.MinCellEdgeLength(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFL geometry representation: The minimum edge length of the cell.
    name = 'mincelledgelength'

class ufl.MaxCellEdgeLength(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFL geometry representation: The maximum edge length of the cell.
    name = 'maxcelledgelength'

class ufl.FacetArea(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
    UFL geometry representation: The area of the facet.
    name = 'facetarea'

class ufl.MinFacetEdgeLength(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
    UFL geometry representation: The minimum edge length of the facet.
    name = 'minfacetedgelenlength'

class ufl.MaxFacetEdgeLength(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
    UFL geometry representation: The maximum edge length of the facet.
    name = 'maxfacetedgelenlength'

class ufl.FacetNormal(domain)
    Bases: ufl.geometry.GeometricFacetQuantity
    UFL geometry representation: The outwards pointing normal vector of the current facet.
    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.
    name = 'n'
    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.CellNormal(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFL geometry representation: The upwards pointing normal vector of the current manifold cell.
    name = 'cell_normal'
    ufl_shape
        Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.Jacobian(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFL geometry representation: The Jacobian of the mapping from reference cell to spatial coordinates.

```

$$J_{ij} = \frac{dx_i}{dX_j}$$

```
is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'J'

ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.JacobianDeterminant(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFC geometry representation: The determinant of the Jacobian.
    Represents the signed determinant of a square Jacobian or the pseudo-determinant of a non-square Jacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'detJ'

class ufl.JacobianInverse(domain)
    Bases: ufl.geometry.GeometricCellQuantity
    UFC geometry representation: The inverse of the Jacobian.
    Represents the inverse of a square Jacobian or the pseudo-inverse of a non-square Jacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'K'

ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.FiniteElementBase(family, cell, degree, quad_scheme, value_shape, reference_value_shape)
    Bases: object
    Base class for all finite elements.

cell()
    Return cell of finite element.

degree(component=None)
    Return polynomial degree of finite element.

extract_component(i)
    Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component(i)
    Recursively extract reference component index relative to a (simple) element and that element for given reference value component index.

extract_subelement_component(i)
    Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component(i)
    Extract direct subelement index and subelement relative reference component index for a given reference component index.

family()
    Return finite element family.
```

is_cellwise_constant (*component=None*)
 Return whether the basis functions of this element is spatially constant over each cell.

mapping()
 Not implemented.

num_sub_elements()
 Return number of sub-elements.

quadrature_scheme()
 Return quadrature scheme of finite element.

reference_value_shape()
 Return the shape of the value space on the reference cell.

reference_value_size()
 Return the integer product of the reference value shape.

sub_elements()
 Return list of sub-elements.

symmetry()
 Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

value_shape()
 Return the shape of the value space on the global domain.

value_size()
 Return the integer product of the value shape.

class ufl.FiniteElement (*family*, *cell=None*, *degree=None*, *form_degree=None*, *quad_scheme=None*, *variant=None*)
 Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*
 The basic finite element class for all simple finite elements.

mapping()

reconstruct (*family=None*, *cell=None*, *degree=None*)
 Construct a new FiniteElement object with some properties replaced with new values.

shortstr()
 Format as string for pretty printing.

sobolev_space()
 Return the underlying Sobolev space.

variant()

class ufl.MixedElement (**elements*, ***kwargs*)
 Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*
 A finite element composed of a nested hierarchy of mixed or simple elements.

degree (*component=None*)
 Return polynomial degree of finite element.

extract_component (*i*)
 Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component (*i*)
 Recursively extract reference_component index relative to a (simple) element and that element for given value reference_component index.

```
extract_subelement_component(i)
    Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component(i)
    Extract direct subelement index and subelement relative reference_component index for a given reference_component index.

is_cellwise_constant(component=None)
    Return whether the basis functions of this element is spatially constant over each cell.

mapping()
num_sub_elements()
    Return number of sub elements.

reconstruct(**kwargs)
reconstruct_from_elements(*elements)
    Reconstruct a mixed element from new subelements.

shortstr()
    Format as string for pretty printing.

sub_elements()
    Return list of sub elements.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.VectorElement(family, cell=None, degree=None, dim=None, form_degree=None,
                       quad_scheme=None)
Bases: ufl.finiteelement.mixedelement.MixedElement
A special case of a mixed finite element where all elements are equal.

reconstruct(**kwargs)
shortstr()
    Format as string for pretty printing.

class ufl.TensorElement(family, cell=None, degree=None, shape=None, symmetry=None,
                       quad_scheme=None)
Bases: ufl.finiteelement.mixedelement.MixedElement
A special case of a mixed finite element where all elements are equal.

extract_subelement_component(i)
    Extract direct subelement index and subelement relative component index for a given component index.

flattened_sub_element_mapping()

mapping()

reconstruct(**kwargs)
shortstr()
    Format as string for pretty printing.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.EnrichedElement(*elements)
Bases: ufl.finiteelement.enrichedelement.EnrichedElementBase
```

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Dual basis is a concatenation of subelements dual bases; primal basis is a concatenation of subelements primal bases; resulting element is not nodal even when subelements are. Structured basis may be exploited in form compilers.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

shortstr()

Format as string for pretty printing.

class ufl.NodalEnrichedElement (*elements)

Bases: *ufl.finiteelement.enrichedelement.EnrichedElementBase*

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Primal basis is reorthogonalized to dual basis which is a concatenation of subelements dual bases; resulting element is nodal.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

shortstr()

Format as string for pretty printing.

class ufl.RestrictedElement (element, restriction_domain)

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

Represents the restriction of a finite element to a type of cell entity.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

mapping()

num_restricted_sub_elements()

Return number of restricted sub elements.

num_sub_elements()

Return number of sub elements.

reconstruct(kwargs)**

restricted_sub_elements()

Return list of restricted sub elements.

restriction_domain()

Return the domain onto which the element is restricted.

shortstr()

Format as string for pretty printing.

sub_element()

Return the element which is restricted.

sub_elements()

Return list of sub elements.

symmetry()

Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

```
class ufl.TensorProductElement(*elements, **kwargs)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
```

The tensor product of d element spaces:

$$V = V_1 \otimes V_2 \otimes \dots \otimes V_d$$

Given bases $\{\phi_{j_i}\}$ of the spaces V_i for $i = 1, \dots, d$, $\{\phi_{j_1} \otimes \phi_{j_2} \otimes \dots \otimes \phi_{j_d}\}$ forms a basis for V .

mapping()**num_sub_elements()**

Return number of subelements.

reconstruct(cell=None)**shortstr()**

Short pretty-print.

sobolev_space()

Return the underlying Sobolev space of the TensorProductElement.

sub_elements()

Return subelements (factors).

```
class ufl.HDivElement(element)
```

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

A div-conforming version of an outer product element, assuming this makes mathematical sense.

mapping()**reconstruct(**kwargs)****shortstr()**

Format as string for pretty printing.

sobolev_space()

Return the underlying Sobolev space.

```
class ufl.HCurlElement(element)
```

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

A curl-conforming version of an outer product element, assuming this makes mathematical sense.

mapping()**reconstruct(**kwargs)****shortstr()**

Format as string for pretty printing.

sobolev_space()

Return the underlying Sobolev space.

```
class ufl.BrokenElement(element)
```

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

The discontinuous version of an existing Finite Element space.

mapping()

```

reconstruct (**kwargs)
shortstr (element)
    Constructs the restriction of a finite element to the facets of the cell.

 (element)
    Constructs the restriction of a finite element to the interior of the cell.

 (family, short_name, value_rank, sobolev_space, mapping, degree_range, cell-
    names)
    Register new finite element family.

 ()
    Shows all registered elements.

class ufl.FunctionSpace (domain, element)
    Bases: ufl.functionspace.AbstractFunctionSpace

    ufl_domain ()
        Return ufl domain.

    ufl_domains ()
        Return ufl domains.

    ufl_element ()
        Return ufl element.

    ufl_sub_spaces ()
        Return ufl sub spaces.

class ufl.Argument (function_space, number, part=None)
    Bases: ufl.core.terminal.FormArgument

    UFL value: Representation of an argument to a form.

    is_cellwise_constant ()
        Return whether this expression is spatially constant over each cell.

    number ()
        Return the Argument number.

    part ()
    ufl_domain ()
        Deprecated, please use .ufl_function_space().ufl_domain() instead.

    ufl_domains ()
        Deprecated, please use .ufl_function_space().ufl_domains() instead.

    ufl_element ()
        Deprecated, please use .ufl_function_space().ufl_element() instead.

    ufl_function_space ()
        Get the function space of this Argument.

    ufl_shape
        Return the associated UFL shape.

 (function_space, part=None)
    UFL value: Create a test function argument to a form.

```

`ufl.TrialFunction(function_space, part=None)`

UFL value: Create a trial function argument to a form.

`ufl.Arguments(function_space, number)`

UFL value: Create an Argument in a mixed space, and return a tuple with the function components corresponding to the subelements.

`ufl.TestFunctions(function_space)`

UFL value: Create a TestFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

`ufl.TrialFunctions(function_space)`

UFL value: Create a TrialFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

`class ufl.Coefficient(function_space, count=None)`

Bases: `ufl.core.terminal.FormArgument`

UFL form argument type: Representation of a form coefficient.

`count()`

`is_cellwise_constant()`

Return whether this expression is spatially constant over each cell.

`ufl_domain()`

Shortcut to get the domain of the function space of this coefficient.

`ufl_domains()`

Return tuple of domains related to this terminal object.

`ufl_element()`

Shortcut to get the finite element of the function space of this coefficient.

`ufl_function_space()`

Get the function space of this coefficient.

`ufl_shape`

Return the associated UFL shape.

`ufl.Coefficients(function_space)`

UFL value: Create a Coefficient in a mixed space, and return a tuple with the function components corresponding to the subelements.

`ufl.Constant(domain, count=None)`

UFL value: Represents a globally constant scalar valued coefficient.

`ufl.VectorConstant(domain, dim=None, count=None)`

UFL value: Represents a globally constant vector valued coefficient.

`ufl.TensorConstant(domain, shape=None, symmetry=None, count=None)`

UFL value: Represents a globally constant tensor valued coefficient.

`ufl.split(v)`

UFL operator: If v is a Coefficient or Argument in a mixed space, returns a tuple with the function components corresponding to the subelements.

`class ufl.PermutationSymbol(dim)`

Bases: `ufl.constantvalue.ConstantValue`

UFL literal type: Representation of a permutation symbol.

This is also known as the Levi-Civita symbol, antisymmetric symbol, or alternating symbol.

```
evaluate(x, mapping, component, index_values)
    Evaluates the permutation symbol.

ufl_shape

class ufl.Identity(dim)
    Bases: ufl.constantvalue.ConstantValue
    UFC literal type: Representation of an identity matrix.

evaluate(x, mapping, component, index_values)
    Evaluates the identity matrix on the given components.

ufl_shape

ufl.zero(*shape)
    UFC literal constant: Return a zero tensor with the given shape.

ufl.as_ufl(expression)
    Converts expression to an Expr if possible.

class ufl.Index(count=None)
    Bases: ufl.core.multiindex.IndexBase
    UFC value: An index with no value assigned.
    Used to represent free indices in Einstein indexing notation.

count()

ufl.indices(n)
    UFC value: Return a tuple of n new Index objects.

ufl.as_tensor(expressions, indices=None)
    UFC operator: Make a tensor valued expression.
    This works in two different ways, by using indices or lists.
    1) Returns A such that  $A[\text{indices}] = \text{expressions}$ . If indices are provided, expressions must be a scalar valued expression with all the provided indices among its free indices. This operator will then map each of these indices to a tensor axis, thereby making a tensor valued expression from a scalar valued expression with free indices.
    2) Returns A such that  $A[k, \dots] = \text{expressions}^*[k]$ . If no indices are provided, *expressions must be a list or tuple of expressions. The expressions can also consist of recursively nested lists to build higher rank tensors.

ufl.as_vector(expressions, index=None)
    UFC operator: As as_tensor(), but limited to rank 1 tensors.

ufl.as_matrix(expressions, indices=None)
    UFC operator: As as_tensor(), but limited to rank 2 tensors.

ufl.relabel(A, indexmap)
    UFC operator: Relabel free indices of A with new indices, using the given mapping.

ufl.unit_vector(i, d)
    UFC value: A constant unit vector in direction i with dimension d.

ufl.unit_vectors(d)
    UFC value: A tuple of constant unit vectors in all directions with dimension d.

ufl.unit_matrix(i, j, d)
    UFC value: A constant unit matrix in direction i, j with dimension d.

ufl.unit_matrices(d)
    UFC value: A tuple of constant unit matrices in all directions with dimension d.
```

`ufl.rank(f)`

UFL operator: The rank of f .

`ufl.shape(f)`

UFL operator: The shape of f .

`ufl.outer(*operands)`

UFL operator: Take the outer product of two or more operands.

`ufl.inner(a, b)`

UFL operator: Take the inner product of a and b .

`ufl.dot(a, b)`

UFL operator: Take the dot product of a and b .

`ufl.cross(a, b)`

UFL operator: Take the cross product of a and b .

`ufl.perp(v)`

UFL operator: Take the perp of v , i.e. $(-v_1, +v_0)$.

`ufl.det(A)`

UFL operator: Take the determinant of A .

`ufl.inv(A)`

UFL operator: Take the inverse of A .

`ufl.cofac(A)`

UFL operator: Take the cofactor of A .

`ufl.transpose(A)`

UFL operator: Take the transposed of tensor A .

`ufl.tr(A)`

UFL operator: Take the trace of A .

`ufl.diag(A)`

UFL operator: Take the diagonal part of rank 2 tensor A **or** make a diagonal rank 2 tensor from a rank 1 tensor.

Always returns a rank 2 tensor. See also `diag_vector`.

`ufl.diag_vector(A)`

UFL operator: Take the diagonal part of rank 2 tensor A and return as a vector.

See also `diag`.

`ufl.dev(A)`

UFL operator: Take the deviatoric part of A .

`ufl.skew(A)`

UFL operator: Take the skew symmetric part of A .

`ufl.sym(A)`

UFL operator: Take the symmetric part of A .

`ufl.sqrt(f)`

UFL operator: Take the square root of f .

`ufl.exp(f)`

UFL operator: Take the exponential of f .

`ufl.ln(f)`

UFL operator: Take the natural logarithm of f .

`ufl.erf(f)`
UFL operator: Take the error function of f .

`ufl.cos(f)`
UFL operator: Take the cosine of f .

`ufl.sin(f)`
UFL operator: Take the sine of f .

`ufl.tan(f)`
UFL operator: Take the tangent of f .

`ufl.acos(f)`
UFL operator: Take the inverse cosine of f .

`ufl.asin(f)`
UFL operator: Take the inverse sine of f .

`ufl.atan(f)`
UFL operator: Take the inverse tangent of f .

`ufl.atan_2(f1,f2)`
UFL operator: Take the inverse tangent with two the arguments $f1$ and $f2$.

`ufl.cosh(f)`
UFL operator: Take the hyperbolic cosine of f .

`ufl.sinh(f)`
UFL operator: Take the hyperbolic sine of f .

`ufl.tanh(f)`
UFL operator: Take the hyperbolic tangent of f .

`ufl.bessel_J(nu,f)`
UFL operator: cylindrical Bessel function of the first kind.

`ufl.bessel_Y(nu,f)`
UFL operator: cylindrical Bessel function of the second kind.

`ufl.bessel_I(nu,f)`
UFL operator: regular modified cylindrical Bessel function.

`ufl.bessel_K(nu,f)`
UFL operator: irregular modified cylindrical Bessel function.

`ufl.eq(left,right)`
UFL operator: A boolean expression ($\text{left} == \text{right}$) for use with `conditional`.

`ufl.ne(left,right)`
UFL operator: A boolean expression ($\text{left} != \text{right}$) for use with `conditional`.

`ufl.le(left,right)`
UFL operator: A boolean expression ($\text{left} \leq \text{right}$) for use with `conditional`.

`ufl.ge(left,right)`
UFL operator: A boolean expression ($\text{left} \geq \text{right}$) for use with `conditional`.

`ufl.lt(left,right)`
UFL operator: A boolean expression ($\text{left} < \text{right}$) for use with `conditional`.

`ufl.gt(left,right)`
UFL operator: A boolean expression ($\text{left} > \text{right}$) for use with `conditional`.

`ufl.And(left, right)`

UFL operator: A boolean expression (left and right) for use with `conditional`.

`ufl.Or(left, right)`

UFL operator: A boolean expression (left or right) for use with `conditional`.

`ufl.Not(condition)`

UFL operator: A boolean expression (not condition) for use with `conditional`.

`ufl.conditional(condition, true_value, false_value)`

UFL operator: A conditional expression, taking the value of `true_value` when `condition` evaluates to `true` and `false_value` otherwise.

`ufl.sign(x)`

UFL operator: Take the sign (+1 or -1) of `x`.

`ufl.max_value(x, y)`

UFL operator: Take the maximum of `x` and `y`.

`ufl.min_value(x, y)`

UFL operator: Take the minimum of `x` and `y`.

`ufl.Max(x, y)`

UFL operator: Take the maximum of `x` and `y`.

`ufl.Min(x, y)`

UFL operator: Take the minimum of `x` and `y`.

`ufl.variable(e)`

UFL operator: Define a variable representing the given expression, see also `diff()`.

`ufl.diff(f, v)`

UFL operator: Take the derivative of `f` with respect to the variable `v`.

If `f` is a form, `diff` is applied to each integrand.

`ufl.Dx(f, *i)`

UFL operator: Take the partial derivative of `f` with respect to spatial variable number `i`. Equivalent to `f.dx(*i)`.

`ufl.grad(f)`

UFL operator: Take the gradient of `f`.

This operator follows the grad convention where

$$\text{grad}(s)[i] = s.\text{dx}(i)$$

$$\text{grad}(v)[i,j] = v[i].\text{dx}(j)$$

$$\text{grad}(T)[:,i] = T[:,i].\text{dx}(i)$$

for scalar expressions `s`, vector expressions `v`, and arbitrary rank tensor expressions `T`.

See also: [nabla_grad\(\)](#)

`ufl.div(f)`

UFL operator: Take the divergence of `f`.

This operator follows the div convention where

$$\text{div}(v) = v[i].\text{dx}(i)$$

$$\text{div}(T)[:,i] = T[:,i].\text{dx}(i)$$

for vector expressions v , and arbitrary rank tensor expressions T .

See also: [nabla_div\(\)](#)

`ufl.curl(f)`

UFL operator: Take the curl of f .

`ufl.rot(f)`

UFL operator: Take the curl of f .

`ufl.nabla_grad(f)`

UFL operator: Take the gradient of f .

This operator follows the grad convention where

$$\text{nabla_grad}(s)[i] = s.dx(i)$$

$$\text{nabla_grad}(v)[i,j] = v[j].dx(i)$$

$$\text{nabla_grad}(T)[i,:] = T[:,i].dx(i)$$

for scalar expressions s , vector expressions v , and arbitrary rank tensor expressions T .

See also: [grad\(\)](#)

`ufl.nabla_div(f)`

UFL operator: Take the divergence of f .

This operator follows the div convention where

$$\text{nabla_div}(v) = v[i].dx(i)$$

$$\text{nabla_div}(T)[:] = T[i,:].dx(i)$$

for vector expressions v , and arbitrary rank tensor expressions T .

See also: [div\(\)](#)

`ufl.Dn(f)`

UFL operator: Take the directional derivative of f in the facet normal direction, $Dn(f) := \text{dot}(\text{grad}(f), n)$.

`ufl.exterior_derivative(f)`

UFL operator: Take the exterior derivative of f .

The exterior derivative uses the element family to determine whether `id`, `grad`, `curl` or `div` should be used.

Note that this uses the `grad` and `div` operators, as opposed to `nabla_grad` and `nabla_div`.

`ufl.jump(v, n=None)`

UFL operator: Take the jump of v across a facet.

`ufl.avg(v)`

UFL operator: Take the average of v across a facet.

`ufl.cell_avg(f)`

UFL operator: Take the average of v over a cell.

`ufl.facet_avg(f)`

UFL operator: Take the average of v over a facet.

`ufl.elem_mult(A, B)`

UFL operator: Take the elementwise multiplication of tensors A and B with the same shape.

`ufl.elem_div(A, B)`

UFL operator: Take the elementwise division of tensors A and B with the same shape.

`ufl.elem_pow(A, B)`

UFL operator: Take the elementwise power of tensors A and B with the same shape.

`ufl.elem_op(op, *args)`

UFL operator: Take the elementwise application of operator op on scalar values from one or more tensor arguments.

`class ufl.Form(integrals)`

Bases: `object`

Description of a weak form consisting of a sum of integrals over subdomains.

`arguments()`

Return all `Argument` objects found in form.

`coefficient_numbering()`

Return a contiguous numbering of coefficients in a mapping `{coefficient:number}`.

`coefficients()`

Return all `Coefficient` objects found in form.

`domain_numbering()`

Return a contiguous numbering of domains in a mapping `{domain:number}`.

`empty()`

Returns whether the form has no integrals.

`equals(other)`

Evaluate `bool(lhs_form == rhs_form)`.

`geometric_dimension()`

Return the geometric dimension shared by all domains and functions in this form.

`integrals()`

Return a sequence of all integrals in form.

`integrals_by_type(integral_type)`

Return a sequence of all integrals with a particular domain type.

`max_subdomain_ids()`

Returns a mapping on the form `{domain:{integral_type:max_subdomain_id}}`.

`signature()`

Signature for use with jit cache (independent of incidental numbering of indices etc.)

`subdomain_data()`

Returns a mapping on the form `{domain:{integral_type: subdomain_data}}`.

`ufl_cell()`

Return the single cell this form is defined on, fails if multiple cells are found.

`ufl_domain()`

Return the single geometric integration domain occurring in the form.

Fails if multiple domains are found.

NB! This does not include domains of coefficients defined on other meshes, look at form data for that additional information.

`ufl_domains()`

Return the geometric integration domains occurring in the form.

NB! This does not include domains of coefficients defined on other meshes.

The return type is a tuple even if only a single domain exists.

```

x_repr_latex_()
x_repr_png_()

class ufl.Integral (integrand, integral_type, domain, subdomain_id, metadata, subdomain_data)
    Bases: object

    An integral over a single domain.

    integral_type()
        Return the domain type of this integral.

    integrand()
        Return the integrand expression, which is an Expr instance.

    metadata()
        Return the compiler metadata this integral has been annotated with.

    reconstruct (integrand=None, integral_type=None, domain=None, subdomain_id=None, metadata=None, subdomain_data=None)
        Construct a new Integral object with some properties replaced with new values.

    Example: <a = Integral instance> b = a.reconstruct(expand_compounds(a.integrand())) c = a.reconstruct(metadata={'quadrature_degree':2})

    subdomain_data()
        Return the domain data of this integral.

    subdomain_id()
        Return the subdomain id of this integral.

    ufl_domain()
        Return the integration domain of this integral.

class ufl.Measure (integral_type, domain=None, subdomain_id='everywhere', metadata=None, subdomain_main_data=None)
    Bases: object

    integral_type()
        Return the domain type.

        Valid domain types are “cell”, “exterior_facet”, “interior_facet”, etc.

    metadata()
        Return the integral metadata. This data is not interpreted by UFL. It is passed to the form compiler which can ignore it or use it to compile each integral of a form in a different way.

    reconstruct (integral_type=None, subdomain_id=None, domain=None, metadata=None, subdomain_main_data=None)
        Construct a new Measure object with some properties replaced with new values.

    Example: <dm = Measure instance> b = dm.reconstruct(subdomain_id=2) c = dm.reconstruct(metadata={"quadrature_degree": 3 })

    Used by the call operator, so this is equivalent: b = dm(2) c = dm(0, {"quadrature_degree": 3 })

    subdomain_data()
        Return the integral subdomain_data. This data is not interpreted by UFL. Its intension is to give a context in which the domain id is interpreted.

    subdomain_id()
        Return the domain id of this measure (integer).

    ufl_domain()
        Return the domain associated with this measure.

```

This may be None or a Domain object.

`ufl.register_integral_type(integral_type, measure_name)`

`ufl.integral_types()`

Return a tuple of all domain type strings.

`ufl.replace(e, mapping)`

Replace terminal objects in expression.

@param e: An Expr or Form.

@param mapping: A dict with from:to replacements to perform.

`ufl.replace_integral_domains(form, common_domain)`

Given a form and a domain, assign a common integration domain to all integrals.

Does not modify the input form (Form should always be immutable). This is to support ill formed forms with no domain specified, sometimes occurring in pydolfin, e.g. `assemble(1*dx, mesh=mesh)`.

`ufl.derivative(form, coefficient, argument=None, coefficient_derivatives=None)`

UFL form operator: Compute the Gateaux derivative of *form* w.r.t. *coefficient* in direction of *argument*.

If the argument is omitted, a new Argument is created in the same space as the coefficient, with argument number one higher than the highest one in the form.

The resulting form has one additional Argument in the same finite element space as the coefficient.

A tuple of Coefficient s may be provided in place of a single Coefficient, in which case the new Argument argument is based on a MixedElement created from this tuple.

An indexed Coefficient from a mixed space may be provided, in which case the argument should be in the corresponding subspace of the coefficient space.

If provided, *coefficient_derivatives* should be a mapping from Coefficient instances to their derivatives w.r.t. *coefficient*.

`ufl.action(form, coefficient=None)`

UFL form operator: Given a bilinear form, return a linear form with an additional coefficient, representing the action of the form on the coefficient. This can be used for matrix-free methods.

`ufl.energy_norm(form, coefficient=None)`

UFL form operator: Given a bilinear form *a* and a coefficient *f*, return the functional *a(f, f)*.

`ufl.rhs(form)`

UFL form operator: Given a combined bilinear and linear form, extract the right hand side (negated linear form part).

Example:

```
a = u*v*dx + f*v*dx
L = rhs(a) -> -f*v*dx
```

`ufl.lhs(form)`

UFL form operator: Given a combined bilinear and linear form, extract the left hand side (bilinear form part).

Example:

```
a = u*v*dx + f*v*dx
a = lhs(a) -> u*v*dx
```

`ufl.block_split(form, ix, iy=0)`

UFL form operator: Given a linear or bilinear form on a mixed space, extract the block corresponding to the indices *ix*, *iy*.

Example:

```
a = inner(grad(u), grad(v))*dx + div(u)*q*dx + div(v)*p*dx
a = block_split(a, 0, 0) -> inner(grad(u),
grad(v))*dx
```

ufl.system(form)

UFL form operator: Split a form into the left hand side and right hand side, see `lhs` and `rhs`.

ufl.functional(form)

UFL form operator: Extract the functional part of form.

ufl.adjoint(form, reordered_arguments=None)

UFL form operator: Given a combined bilinear form, compute the adjoint form by changing the ordering (count) of the test and trial functions.

By default, new `Argument` objects will be created with opposite ordering. However, if the adjoint form is to be added to other forms later, their arguments must match. In that case, the user must provide a tuple `*reordered_arguments*=(u2,v2)`.

ufl.sensitivity_rhs(a, u, L, v)

UFL form operator: Compute the right hand side for a sensitivity calculation system.

The derivation behind this computation is as follows. Assume a, L to be bilinear and linear forms corresponding to the assembled linear system

$$Ax = b.$$

Where x is the vector of the discrete function corresponding to u . Let v be some scalar variable this equation depends on. Then we can write

$$\begin{aligned} 0 &= \frac{d}{dv}(Ax - b) = \frac{dA}{dv}x + A\frac{dx}{dv} - \frac{db}{dv}, \\ A\frac{dx}{dv} &= \frac{db}{dv} - \frac{dA}{dv}x, \end{aligned}$$

and solve this system for $\frac{dx}{dv}$, using the same bilinear form a and matrix A from the original system. Assume the forms are written

```
v = variable(v_expression)
L = IL(v)*dx
a = Ia(v)*dx
```

where `IL` and `Ia` are integrand expressions. Define a `Coefficient` u representing the solution to the equations. Then we can compute $\frac{db}{dv}$ and $\frac{dA}{dv}$ from the forms

```
da = diff(a, v)
dL = diff(L, v)
```

and the action of da on u by

```
dau = action(da, u)
```

In total, we can build the right hand side of the system to compute $\frac{du}{dv}$ with the single line

```
dL = diff(L, v) - action(diff(a, v), u)
```

or, using this function,

```
dL = sensitivity_rhs(a, u, L, v)
```

Release notes

Changes in the next release

Summary of changes

Note: Developers should use this page to track and list changes during development. At the time of release, this page should be published (and renamed) to list the most important changes in the new release.

Detailed changes

Note: At the time of release, make a verbatim copy of the ChangeLog here (and remove this note).

Changes in version 2017.1.0

UFL 2017.1.0 was released on 2017-05-09.

Summary of changes

- Add the `DirectionalSobolevSpace` subclass of `SobolevSpace`. This allows one to use spaces where elements have varying continuity in different spatial directions.
- Add `sobolev_space` methods for `HDiv` and `HCurl` finite elements.
- Add `sobolev_space` methods for `TensorProductElement` and `EnrichedElement`. The smallest shared Sobolev space will be returned for enriched elements. For the tensor product elements, a `DirectionalSobolevSpace` is returned depending on the order of the spaces associated with the component elements.

Changes in version 2016.2.0

UFL 2016.2.0 was released on 2016-11-30.

Summary of changes

- Deprecate `.cell()`, `.domain()`, `.element()` in favour of `.ufl_cell()`, `.ufl_domain()`, `.ufl_element()`, in multiple classes, to allow closer integration with DOLFIN
- Remove deprecated properties `cell.{d,x,n,volume,circumradius,facet_area}`
- Remove ancient `form2ufl` script
- Large reworking of symbolic geometry pipeline
- Implement symbolic Piola mappings
- `OuterProductCell` and `OuterProductElement` are merged into `TensorProductCell` and `TensorProductElement` respectively

- Better degree estimation for quadrilaterals
- Expansion rules for Q, DQ, RTCE, RTCF, NCE and NCF on tensor product cells
- Add discontinuous Taylor elements
- Add support for the mapping double covariant Piola in uflacs
- Add support for the mapping double contravariant Piola in uflacs
- Support for tensor-valued subelements in uflacs fixed
- Replacing Discontinuous Lagrange Trace with HDiv Trace and removing TraceElement
- Assigning Discontinuous Lagrange Trace and DGT as aliases for HDiv Trace

Detailed changes

- Add call operator syntax to Form to replace arguments and coefficients. This makes it easier to e.g. express the norm defined by a bilinear form as a functional. Example usage:

```
# Equivalent to replace(a, {u: f, v: f})
M = a(f, f)
# Equivalent to replace(a, {f:1})
c = a(coefficients={f:1})
```

- **Add call operator syntax to Form to replace arguments and coefficients:** `a(f, g) == replace(a, {u: f, v: g})`
`a(coefficients={f:1}) == replace(a, {f:1})`
- Add @ operator to Form: `form @ f == action(form, f)` (python 3.5+ only)
- Reduce noise in Mesh str such that `print(form)` gets more short and readable
- Fix repeated split(function) for arbitrary nested elements
- **EnrichedElement: Remove +/* warning** In the distant past, `A + B => MixedElement([A, B])`. The change that `A + B => EnrichedElement([A, B])` was made in d622c74 (22 March 2010). A warning was introduced in fcfc5ff (26 March 2010) that the meaning of “+” had changed, and that users wanting a MixedElement should use “**” instead. People have, presumably, been seeing this warning for 6 1/2 years by now, so it’s probably safe to remove.
- Rework TensorProductElement implementation, replaces OuterProductElement
- Rework TensorProductCell implementation, replaces OuterProductCell
- Remove OuterProductVectorElement and OuterProductTensorElement
- Add FacetElement and InteriorElement
- Add Hellan-Herrmann-Johnson element
- Add support for double covariant and contravariant mappings in mixed elements
- Support discontinuous Taylor elements on all simplices
- Some more performance improvements
- Minor bugfixes
- Improve Python 3 support
- More permissive in integer types accepted some places
- Make ufl pass almost all flake8 tests
- Add bitbucket pipelines testing

- Improve documentation

Changes in version 2016.1.0

UFL 2016.1.0 was released on 2016-06-23.

- Add operator $A^{\wedge}(i,j) := \text{as_tensor}(A, (i,j))$
- Updates to old manual for publishing on fenics-ufl.readthedocs.org
- Bugfix for ufl files with utf-8 encoding
- **Bugfix in conditional derivatives to avoid inf/nan values in generated code.** This bugfix may break ffc if uflacs is not used, to get around that the old workaround in ufl can be enabled by setting `ufl.algorithms.apply_derivatives.CONDITIONAL_WORKAROUND = True` at the top of your program.
- Allow `sum([expressions])` where expressions are nonscalar by defining `expr+0==expr`
- Allow `form=0; form -= other;`
- Deprecate `.cell()`, `.domain()`, `.element()` in favour of `.ufl_cell()`, `.ufl_domain()`, `.ufl_element()`, in multiple classes, to allow closer integration with dolfin.
- Remove deprecated properties `cell.{d,x,n,volume,circumradius,facet_area}`.
- Remove ancient `form2ufl` script
- Add new class `Mesh` to replace `Domain`
- Add new class `FunctionSpace(mesh, element)`
- Make `FiniteElement` classes take `Cell`, not `Domain`.
- Large reworking of symbolic geometry pipeline
- Implement symbolic Piola mappings

Changes in version 1.6.0

UFL 1.6.0 was released on 2015-07-28.

- Change approach to attaching `__hash__` implementation to accomodate Python 3
- Implement new non-recursive traversal based hash computation
- Allow `derivative(M, ListTensor(<scalars>), ...)` just like list/tuple works
- Add traits `is_in_reference_frame`, `is_restriction`, `is_evaluation`, `is_differential`
- Add missing linear operators to `ArgumentDependencyExtractor`
- Add `_ufl_is_literal_type` trait
- Add `_ufl_is_terminal_modifier_` type trait and `Expr._ufl_terminal_modifiers_list`
- Add new types `ReferenceDiv` and `ReferenceCurl`
- Outer product element support in degree estimation
- Add `TraceElement`, `InteriorElement`, `FacetElement`, `BrokenElement`
- Add `OuterProductCell` to valid `Real` elements
- Add `_cache` member to `form` for use by external frameworks
- Add Sobolev space `HEin`

- Add measures `dI`, `dO`, `dC` for interface, overlap, cutcell
- Remove `Measure` constants
- Remove `cell2D` and `cell3D`
- Implement `reference_value` in `apply_restrictions`
- Rename point integral to vertex integral and kept `*dP` syntax
- Replace lambda functions in `ufl_type` with named functions for nicer stack traces
- Minor bugfixes, removal of unused code and cleanups

[FIXME: These links don't belong here, should go under API reference somehow.]

- `genindex`
- `modindex`

Python Module Index

U

ufl, 162
ufl.algebra, 95
ufl.algorithms, 69
ufl.algorithms.ad, 46
ufl.algorithms.analysis, 46
ufl.algorithms.apply_algebra_lowering,
 47
ufl.algorithms.apply_derivatives, 48
ufl.algorithms.apply_function_pullbacks,
 52
ufl.algorithms.apply_geometry_lowering,
 52
ufl.algorithms.apply_integral_scaling,
 53
ufl.algorithms.apply_restrictions, 53
ufl.algorithms.change_to_reference, 55
ufl.algorithms.check_arities, 56
ufl.algorithms.check_restrictions, 57
ufl.algorithms.checks, 57
ufl.algorithms.compute_form_data, 58
ufl.algorithms.domain_analysis, 58
ufl.algorithms.elementtransformations,
 59
ufl.algorithms.estimate_degrees, 59
ufl.algorithms.expand_compounds, 62
ufl.algorithms.expand_indices, 62
ufl.algorithms.formdata, 63
ufl.algorithms.formfiles, 63
ufl.algorithms.forms splitter, 64
ufl.algorithms.formtransformations, 64
ufl.algorithms.map_integrands, 66
ufl.algorithms.multifunction, 66
ufl.algorithms.renumbering, 66
ufl.algorithms.replace, 67
ufl.algorithms.signature, 67
ufl.algorithms.transformer, 68
ufl.algorithms.traversal, 69
ufl.argument, 96
ufl.assertions, 97
ufl.cell, 97
ufl.checks, 99
ufl.classes, 99
ufl.coefficient, 128
ufl.compound_expressions, 129
ufl.conditional, 129
ufl.constantvalue, 131
ufl.core, 78
ufl.core.compute_expr_hash, 73
ufl.core.expr, 73
ufl.core.multiindex, 74
ufl.core.operator, 75
ufl.core.terminal, 76
ufl.core.ufl_id, 76
ufl.core.ufl_type, 77
ufl.corealg, 79
ufl.corealg.map_dag, 78
ufl.corealg.monomial, 78
ufl.corealg.traversal, 79
ufl.differentiation, 132
ufl.domain, 134
ufl.equation, 135
ufl.exprcontainers, 135
ufl.exprequals, 136
ufl.exprooperators, 136
ufl.finiteelement, 86
ufl.finiteelement.brokenelement, 79
ufl.finiteelement.elementlist, 80
ufl.finiteelement.enrichedelement, 80
ufl.finiteelement.facetelement, 81
ufl.finiteelement.finiteelement, 81
ufl.finiteelement.finiteelementbase, 81
ufl.finiteelement.hdivcurl, 83
ufl.finiteelement.interiorelement, 83
ufl.finiteelement.mixedelement, 83
ufl.finiteelement.restrictedelement, 85
ufl.finiteelement.tensorproductelement,
 85
ufl.form, 137

ufl.formatting, 92
ufl.formatting.graph, 86
ufl.formatting.latextools, 87
ufl.formatting.printing, 87
ufl.formatting.ufl2dot, 88
ufl.formatting.ufl2latex, 89
ufl.formoperators, 138
ufl.functionspace, 140
ufl.geometry, 140
ufl.index_combination_utils, 146
ufl.indexed, 146
ufl.indexsum, 147
ufl.integral, 147
ufl.log, 147
ufl.mathfunctions, 149
ufl.measure, 150
ufl.objects, 151
ufl.operators, 152
ufl.permutation, 156
ufl.precedence, 156
ufl.protocols, 157
ufl.referencevalue, 157
ufl.restriction, 157
ufl.sobolevspace, 158
ufl.sorting, 158
ufl.split_functions, 158
ufl.tensoralgebra, 158
ufl.tensors, 160
ufl.utils, 95
ufl.utils.counted, 92
ufl.utils.derivativetuples, 92
ufl.utils_dicts, 92
ufl.utils.formatting, 93
ufl.utils.indexflattening, 93
ufl.utils.py23, 94
ufl.utils.sequences, 94
ufl.utils.sorting, 94
ufl.utils.stacks, 95
ufl.utils.ufltypedicts, 95
ufl.variable, 162

Index

A

Abs (class in `ufl.algebra`), 95
Abs (class in `ufl.classes`), 110
`abs()` (`ufl.algorithms.apply_derivatives.GenericDerivativeRuleset` method), 48
`abs()` (`ufl.algorithms.estimate_degrees.SumDegreeEstimator` method), 60
`abs()` (`ufl.formatting.ufl2latex.Expression2LatexHandler` method), 89
`AbstractCell` (class in `ufl`), 166
`AbstractCell` (class in `ufl.cell`), 97
`AbstractCell` (class in `ufl.classes`), 118
`AbstractDomain` (class in `ufl`), 167
`AbstractDomain` (class in `ufl.classes`), 123
`AbstractDomain` (class in `ufl.domain`), 134
`AbstractFunctionSpace` (class in `ufl.classes`), 124
`AbstractFunctionSpace` (class in `ufl.functionspace`), 140
`accumulate_integrands_with_same_metadata()` (in module `ufl.algorithms.domain_analysis`), 58
`Acos` (class in `ufl.classes`), 117
`Acos` (class in `ufl.mathfunctions`), 149
`acos()` (in module `ufl`), 179
`acos()` (in module `ufl.operators`), 152
`acos()` (`ufl.algorithms.apply_derivatives.GenericDerivativeRuleset` method), 49
`acos()` (`ufl.formatting.ufl2latex.Expression2LatexHandler` method), 89
`action()` (in module `ufl`), 184
`action()` (in module `ufl.formoperators`), 138
`add_indent()` (`ufl.log.Logger` method), 147
`add_logfile()` (`ufl.log.Logger` method), 148
`adj_expr()` (in module `ufl.compound_expressions`), 129
`adj_expr_2x2()` (in module `ufl.compound_expressions`), 129
`adj_expr_3x3()` (in module `ufl.compound_expressions`), 129
`adj_expr_4x4()` (in module `ufl.compound_expressions`), 129
`adjoint()` (in module `ufl`), 185
`adjoint()` (in module `ufl.formoperators`), 138
`affine_mesh()` (in module `ufl.domain`), 135
`align()` (in module `ufl.formatting.latextools`), 87
`alternative_dot()` (`ufl.algorithms.apply_algebra_lowering.LowerCompoundA` method), 47
`alternative_inner()` (`ufl.algorithms.apply_algebra_lowering.LowerCompoundA` method), 47
`always_reconstruct()` (`ufl.algorithms.Transformer` method), 70
`always_reconstruct()` (`ufl.algorithms.transformer.Transformer` method), 68
`analyse_key()` (in module `ufl.exproperators`), 136
`And()` (in module `ufl`), 179
`And()` (in module `ufl.operators`), 152
`and_condition()` (`ufl.formatting.ufl2latex.Expression2LatexHandler` method), 89
`and_tuples()` (in module `ufl.utils.sequences`), 94
`AndCondition` (class in `ufl.classes`), 115
`AndCondition` (class in `ufl.conditional`), 129
`apply_algebra_lowering()` (in module `ufl.algorithms.apply_algebra_lowering`), 47
`apply_default_restrictions()` (in module `ufl.algorithms.apply_restrictions`), 55
`apply_derivatives()` (in module `ufl.algorithms.apply_derivatives`), 51
`apply_function_pullbacks()` (in module `ufl.algorithms.apply_function_pullbacks`), 52
`apply_geometry_lowering()` (in module `ufl.algorithms.apply_geometry_lowering`), 53
`apply_integral_scaling()` (in module `ufl.algorithms.apply_integral_scaling`), 53
`apply_restrictions()` (in module `ufl.algorithms.apply_restrictions`), 55
`apply_single_function_pullbacks()` (in module `ufl.algorithms.apply_function_pullbacks`), 52
`apply_transformer()` (in module `ufl.algorithms`), 70

apply_transformer() (in module ufl.algorithms.transformer), 69
Argument (class in ufl), 175
Argument (class in ufl.argument), 96
Argument (class in ufl.classes), 108
argument() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset method), 48
argument() (ufl.algorithms.apply_derivatives.GradRuleset method), 50
argument() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51
argument() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51
argument() (ufl.algorithms.check_arities.ArityChecker method), 56
argument() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
argument() (ufl.algorithms.FormSplitter method), 72
argument() (ufl.algorithms.formsplitter.FormSplitter method), 64
argument() (ufl.algorithms.formtransformations.PartExtractor method), 64
argument() (ufl.formatting.graph.StringDependencyDefiner method), 86
argument() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89
Arguments() (in module ufl), 176
Arguments() (in module ufl.argument), 97
arguments() (ufl.classes.Form method), 127
arguments() (ufl.Form method), 182
arguments() (ufl.form.Form method), 137
ArityChecker (class in ufl.algorithms.check_arities), 56
ArityMismatch, 57
as_bytes() (in module ufl.utils.py23), 94
as_cell() (in module ufl), 166
as_cell() (in module ufl.cell), 98
as_domain() (in module ufl), 167
as_domain() (in module ufl.domain), 135
as_form() (in module ufl.form), 138
as_integral_type() (in module ufl.measure), 151
as_matrix() (in module ufl), 177
as_matrix() (in module ufl.tensors), 160
as_multi_index() (in module ufl.core.multiindex), 75
as_native_str() (in module ufl.utils.py23), 94
as_native_strings() (in module ufl.utils.py23), 94
as_scalar() (in module ufl.tensors), 161
as_scalars() (in module ufl.tensors), 161
as_tensor() (in module ufl), 177
as_tensor() (in module ufl.tensors), 161
as_ufl() (in module ufl), 177
as_ufl() (in module ufl.constantvalue), 132
as_unicode() (in module ufl.utils.py23), 94

module as_vector() (in module ufl), 177
as_vector() (in module ufl.tensors), 161
Asin (class in ufl.classes), 117
Asin (class in ufl.mathfunctions), 149
asin() (in module ufl), 179

asin() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
asin() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89
assign_precedences() (in module ufl.precedence), 156

Atan (class in ufl.classes), 117
Atan (class in ufl.mathfunctions), 149

atan() (in module ufl.operators), 152
atan() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

atan2() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89

Atan2 (class in ufl.classes), 117
Atan2 (class in ufl.mathfunctions), 149

atan2() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89

atan_2() (in module ufl), 179
atan_2() (in module ufl.operators), 152
atan_2() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

atan_2() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
attach_estimated_degrees() (in module ufl.algorithms.compute_form_data), 58
attach_implementations_of_indexing_interface() (in module ufl.core.ufl_type), 77
attach_operators_from_hash_data() (in module ufl.core.ufl_type), 77
attach_ufl_id() (in module ufl.core.ufl_id), 76
avg() (in module ufl), 181
avg() (in module ufl.operators), 152

B

begin() (ufl.log.Logger method), 148
bessel_function() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
bessel_I() (in module ufl), 179
bessel_I() (in module ufl.operators), 152
bessel_i() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
bessel_i() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89
bessel_J() (in module ufl), 179
bessel_J() (in module ufl.operators), 152
bessel_j() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

bessel_j() (ufl.formatting.ufl2latex.Expression2LatexHandleCell (class in ufl.cell), 98
 method), 89

bessel_K() (in module ufl), 179

bessel_K() (in module ufl.operators), 152

bessel_k() (ufl.algorithms.apply_derivatives.GenericDerivativeRulesetmethod), 82
 method), 49

bessel_K() (ufl.formatting.ufl2latex.Expression2LatexHandleCell_avg() (in module ufl), 181
 method), 89

bessel_Y() (in module ufl), 179

bessel_Y() (in module ufl.operators), 152

bessel_y() (ufl.algorithms.apply_derivatives.GenericDerivativeRulesetmethod), 49

bessel_y() (ufl.formatting.ufl2latex.Expression2LatexHandleCell_avg() (ufl.algorithms.apply_derivatives.GradRulesetmethod), 50

BesselFunction (class in ufl.classes), 117

BesselFunction (class in ufl.mathfunctions), 149

BesselII (class in ufl.classes), 117

BesselII (class in ufl.mathfunctions), 149

BesselJ (class in ufl.classes), 117

BesselJ (class in ufl.mathfunctions), 149

BesselK (class in ufl.classes), 117

BesselK (class in ufl.mathfunctions), 149

BesselY (class in ufl.classes), 117

BesselY (class in ufl.mathfunctions), 149

bfnname() (in module ufl.formatting.ufl2latex), 91

binary_condition() (ufl.algorithms.apply_derivatives.GenericDerivativeRulesetmethod), 49

BinaryCondition (class in ufl.classes), 115

BinaryCondition (class in ufl.conditional), 130

block_split() (in module ufl), 184

block_split() (in module ufl.algorithms.formsplitter), 64

block_split() (in module ufl.formoperators), 138

BrokenElement (class in ufl), 174

BrokenElement (class in ufl.classes), 123

BrokenElement (class in ufl.finiteelement.brokenelement), 79

build_component_numbering() (in module ufl.permutation), 156

build_entities() (in module ufl.formatting.ufl2dot), 89

build_graph() (in module ufl.formatting.graph), 86

build_integral_data() (in module ufl.algorithms.domain_analysis), 58

build_precedence_list() (in module ufl.precedence), 156

build_precedence_map() (in module ufl.formatting.ufl2latex), 91

build_precedence_mapping() (in module ufl.precedence), 156

C

camel2underscore() (in module ufl.utils.formatting), 93

canonical_element_description() (in module ufl.finiteelement.elementlist), 80

canonicalize_metadata() (in module ufl.utils.sorting), 94

Cell (class in ufl), 166

Cell (class in ufl.classes), 118

cell() (ufl.classes.FiniteElementBase method), 119

cell() (ufl.finiteelement.finiteelementbase.FiniteElementBase cell() (ufl.FiniteElementBase method), 170

cell_avg() (in module ufl.operators), 152

cell_avg() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset method), 48

cell_avg() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

cell_avg() (ufl.algorithms.apply_derivatives.GradRuleset method), 50

cell_avg() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51

cell_avg() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51

cell_avg() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54

cell_avg() (ufl.algorithms.change_to_reference.NEWChangeToReferenceG method), 55

cell_avg() (ufl.algorithms.check_arities.ArityChecker method), 56

cell_avg() (ufl.algorithms.estimate_degrees.SumDegreeEstimator cell_hex(), 60

cell_avg() (ufl.algorithms.formtransformations.PartExtractor method), 64

cell_avg() (ufl.formatting.ufl2dot.CompactLabeller method), 88

cell_avg() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89

cell_coordinate() (ufl.algorithms.apply_derivatives.GradRuleset method), 50

in cell_coordinate() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51

module cell_coordinate() (ufl.algorithms.apply_geometry_lowering.GeometryLowering method), 52

module cell_coordinate() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60

module cell_normal() (ufl.algorithms.apply_geometry_lowering.GeometryLowering method), 52

module cell_volume() (ufl.algorithms.apply_geometry_lowering.GeometryLowering method), 52

CellAvg (class in ufl.classes), 112

CellAvg (class in ufl.restriction), 157

CellCoordinate (class in ufl.classes), 101

CellCoordinate (class in ufl.geometry), 140

CellEdgeVectors (class in ufl.classes), 103

CellEdgeVectors (class in ufl.geometry), 141

CellFacetJacobian (class in ufl.classes), 102

CellFacetJacobian (class in ufl.geometry), 141

CellFacetJacobianDeterminant (class in ufl.classes), 103

CellFacetJacobianDeterminant (class in ufl.geometry),

141		
CellFacetJacobianInverse (class in ufl.classes), 104		Coefficient (class in ufl), 176
CellFacetJacobianInverse (class in ufl.geometry), 141		Coefficient (class in ufl.classes), 108
CellFacetOrigin (class in ufl.classes), 102		Coefficient (class in ufl.coefficient), 128
CellFacetOrigin (class in ufl.geometry), 141		coefficient() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset method), 48
cellname() (ufl.Cell method), 166		coefficient() (ufl.algorithms.apply_derivatives.GradRuleset method), 50
cellname() (ufl.cell.Cell method), 98		coefficient() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51
cellname() (ufl.cell.TensorProductCell method), 98		coefficient() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51
cellname() (ufl.classes.Cell method), 118		coefficient() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
cellname() (ufl.classes.TensorProductCell method), 118		coefficient() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
cellname() (ufl.TensorProductCell method), 167		coefficient() (ufl.formatting.graph.StringDependencyDefiner method), 86
CellNormal (class in ufl), 169		coefficient() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89
CellNormal (class in ufl.classes), 104		coefficient_derivative() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48
CellNormal (class in ufl.geometry), 141		coefficient_derivative() (ufl.algorithms.change_to_reference.NEWChangeToReference method), 55
CellOrientation (class in ufl.classes), 105		coefficient_derivative() (ufl.algorithms.change_to_reference.OLDChangeToReference method), 56
CellOrientation (class in ufl.geometry), 141		coefficient_derivative() (ufl.algorithms.replace.Replacer method), 67
CellOrigin (class in ufl.classes), 102		coefficient_derivative() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89
CellOrigin (class in ufl.geometry), 142		coefficient_numbering() (ufl.classes.Form method), 127
CellVolume (class in ufl), 168		coefficient_numbering() (ufl.Form method), 182
CellVolume (class in ufl.classes), 105		coefficient_numbering() (ufl.form.Form method), 137
CellVolume (class in ufl.geometry), 142		CoefficientDerivative (class in ufl.classes), 113
cfname() (in module ufl.formatting.ufl2latex), 91		CoefficientDerivative (class in ufl.differentiation), 132
change_integrand_geometry_representation() (in module ufl.algorithms.change_to_reference), 56		Coefficients() (in module ufl), 176
change_to_reference_grad() (in module ufl.algorithms), 72		Coefficients() (in module ufl.coefficient), 128
change_to_reference_grad() (in module ufl.algorithms.change_to_reference), 56		coefficients() (ufl.classes.Form method), 127
check_abstract_trait_consistency() (in module ufl.core.ufl_type), 77		coefficients() (ufl.Form method), 182
check_form_arity() (in module ufl.algorithms.check_arities), 57		coefficients() (ufl.form.Form method), 137
check_has_slots() (in module ufl.core.ufl_type), 77		cofac() (in module ufl), 178
check_implements_required_methods() (in module ufl.core.ufl_type), 77		cofac() (in module ufl.operators), 152
check_implements_required_properties() (in module ufl.core.ufl_type), 77		Cofactor (class in ufl.classes), 111
check_integrand_arity() (in module ufl.algorithms.check_arities), 57		Cofactor (class in ufl.tensoralgebra), 158
check_is_terminal_consistency() (in module ufl.core.ufl_type), 77		cofactor() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
check_restrictions() (in module ufl.algorithms.check_restrictions), 57		cofactor() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
check_type_traits_consistency() (in module ufl.core.ufl_type), 77		cofactor() (ufl.formatting.ufl2latex.Expression2LatexHandler GeometryLoweringApplier)
Circumradius (class in ufl), 168		cofactor_expr() (in module ufl.compound_expressions), 129
Circumradius (class in ufl.classes), 105		cofactor_expr_2x2() (in module ufl.compound_expressions), 129
Circumradius (class in ufl.geometry), 142		cofactor_expr_3x3() (in module ufl.compound_expressions), 129
circumradius() (ufl.algorithms.apply_geometry_lowering method), 52		
cmp_expr() (in module ufl.sorting), 158		
code2latex() (in module ufl.formatting.ufl2latex), 91		
codeterminant_expr_nxn() (in module ufl.compound_expressions), 129		

ufl.compound_expressions), 129
 cofactor_expr_4x4() (in module ufl.compound_expressions), 129
 CompactLabeller (class in ufl.formatting.ufl2dot), 88
 component() (ufl.algorithms.expand_indices.IndexExpander.compute_form_lhs() (in module ufl.algorithms), 73
 method), 62
 component_tensor() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleSet.compute_form_rhs() (in module ufl.algorithms.formtransformations), 66
 method), 49
 component_tensor() (ufl.algorithms.check_arities.ArityChecker.compute_form_rhs() (in module ufl.algorithms.formtransformations), 66
 method), 56
 component_tensor() (ufl.algorithms.estimate_degrees.SumDegreeEstimator.compute_form_signature() (in module ufl.algorithms), 73
 method), 60
 component_tensor() (ufl.algorithms.expand_indices.IndexExpander.compute_form_with_arity() (in module ufl.algorithms.formtransformations), 67
 method), 62
 component_tensor() (ufl.algorithms.formtransformations.PartExtractor.compute_form_with_arity() (in module ufl.algorithms.formtransformations), 66
 method), 64
 component_tensor() (ufl.formatting.ufl2dot.CompactLabeller.compute_form_with_arity() (in module ufl.algorithms.formtransformations), 67
 method), 88
 component_tensor() (ufl.formatting.ufl2latex.Expression2LatexHandler.compute_form_with_arity() (in module ufl.algorithms.formtransformations), 53
 method), 89
 ComponentTensor (class in ufl.classes), 108
 ComponentTensor (class in ufl.tensors), 160
 compound_derivative() (ufl.algorithms.estimate_degrees.SumDegreeEstimator.compute_order_tuples() (in module ufl.permutation), 156
 method), 60
 compound_tensor_operator() (ufl.algorithms.estimate_degrees.SumDegreeEstimator.compute_order_tuples() (in module ufl.permutation), 156
 method), 60
 CompoundDerivative (class in ufl.classes), 114
 CompoundDerivative (class in ufl.differentiation), 132
 CompoundTensorOperator (class in ufl.classes), 110
 CompoundTensorOperator (class in ufl.tensoralgebra), 159
 compute_derivative_tuples() (in module ufl.utils.derivativetuples), 92
 compute_energy_norm() (in module ufl.algorithms), 72
 compute_energy_norm() (in module ufl.algorithms.formtransformations), 65
 compute_expr_hash() (in module ufl.core.compute_expr_hash), 73
 compute_expression_hashdata() (in module ufl.algorithms.signature), 67
 compute_expression_signature() (in module ufl.algorithms.signature), 67
 compute_form_action() (in module ufl.algorithms), 72
 compute_form_action() (in module ufl.algorithms.formtransformations), 65
 compute_form_adjoint() (in module ufl.algorithms), 72
 compute_form_adjoint() (in module ufl.algorithms.formtransformations), 66
 compute_form_arities() (in module ufl.algorithms.formtransformations), 66
 compute_form_data() (in module ufl.algorithms), 70
 compute_form_data() (in module ufl.algorithms.compute_form_data), 58
 compute_form_functional() (in module ufl.algorithms), 73
 compute_form_functional() (in module ufl.algorithms.formtransformations), 66
 compute_form_lhs() (in module ufl.algorithms.formtransformations), 66
 compute_form_rhs() (in module ufl.algorithms), 73
 compute_form_rhs() (in module ufl.algorithms.formtransformations), 66
 compute_form_signature() (in module ufl.algorithms), 73
 compute_integrand_scaling_factor() (in module ufl.algorithms.formtransformations), 66
 compute_multiindex_hashdata() (in module ufl.algorithms.signature), 67
 compute_order_tuples() (in module ufl.permutation), 156
 compute_order_tuples() (in module ufl.permutation), 156
 compute_permutations() (in module ufl.permutation), 156
 compute_sign() (in module ufl.permutation), 156
 compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 Condition (class in ufl.classes), 115
 Condition (class in ufl.conditional), 130
 condition() (ufl.algorithms.estimate_degrees.SumDegreeEstimator.compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 method), 60
 Conditional (class in ufl.classes), 116
 Conditional (class in ufl.conditional), 130
 conditional() (in module ufl), 180
 conditional() (in module ufl.operators), 152
 conditional() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset.compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 method), 49
 conditional() (ufl.algorithms.check_arities.ArityChecker.compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 method), 56
 conditional() (ufl.algorithms.estimate_degrees.SumDegreeEstimator.compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 method), 60
 conditional() (ufl.algorithms.expand_indices.IndexExpander.compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 method), 62
 conditional() (ufl.formatting.ufl2latex.Expression2LatexHandler.compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 method), 89
 Constant() (in module ufl), 176
 Constant() (in module ufl.coefficient), 128
 constant() (ufl.formatting.ufl2latex.Expression2LatexHandler.constant_value() (in module ufl.algorithms.apply_derivatives.GenericDerivativeRuleset.compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 method), 49
 constant_value() (ufl.algorithms.apply_restrictions.RestrictionPropagator.compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 method), 54

constant_value() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 ConstantValue (class in ufl.classes), 106
 ConstantValue (class in ufl.constantvalue), 131
 contraction() (in module ufl.operators), 153
 CopyTransformer (class in ufl.algorithms.transformer), 68
 Cos (class in ufl.classes), 117
 Cos (class in ufl.mathfunctions), 149
 cos() (in module ufl), 179
 cos() (in module ufl.operators), 153
 cos() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 cos() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89
 Cosh (class in ufl.classes), 117
 Cosh (class in ufl.mathfunctions), 149
 cosh() (in module ufl), 179
 cosh() (in module ufl.operators), 153
 cosh() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 cosh() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89
 count() (ufl.classes.Coefficient method), 109
 count() (ufl.classes.Index method), 125
 count() (ufl.classes.Label method), 109
 count() (ufl.Coefficient method), 176
 count() (ufl.coefficient.Coefficient method), 128
 count() (ufl.core.multiindex.Index method), 75
 count() (ufl.Index method), 177
 count() (ufl.utils.counted.ExampleCounted method), 92
 count() (ufl.variable.Label method), 162
 counted_init() (in module ufl.utils.counted), 92
 create_nested_lists() (in module ufl.algorithms.apply_function_pullbacks), 52
 create_slice_indices() (in module ufl.index_combination_utils), 146
 Cross (class in ufl.classes), 111
 Cross (class in ufl.tensoralgebra), 159
 cross() (in module ufl), 178
 cross() (in module ufl.operators), 153
 cross() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
 cross() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 cross() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 89
 cross_expr() (in module ufl.compound_expressions), 129
 Curl (class in ufl.classes), 115
 Curl (class in ufl.differentiation), 132
 curl() (in module ufl), 181
 curl() (in module ufl.operators), 153

curl() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 47
 curl() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 curl() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 curl() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 cutoff_post_traversal() (in module ufl.corealg.traversal), 79
 cutoff_unique_post_traversal() (in module ufl.corealg.traversal), 79

D

debug() (ufl.log.Logger method), 148
 default_domain() (in module ufl.domain), 135
 DefaultRestrictionApplier (class in ufl.algorithms.apply_restrictions), 53
 degree() (ufl.classes.FiniteElementBase method), 119
 degree() (ufl.classes.MixedElement method), 120
 degree() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
 degree() (ufl.finiteelement.mixedelement.MixedElement method), 83
 degree() (ufl.FiniteElementBase method), 170
 degree() (ufl.MixedElement method), 171
 dependency_sorting() (in module ufl.formatting.ufl2latex), 91
 deprecate() (ufl.log.Logger method), 148
 deps2latex() (in module ufl.formatting.ufl2latex), 91
 depth_first_ordering() (in module ufl.formatting.graph), 87
 Derivative (class in ufl.classes), 113
 Derivative (class in ufl.differentiation), 133
 derivative() (in module ufl), 184
 derivative() (in module ufl.formoperators), 138
 derivative() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48
 derivative() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 derivative() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 53
 derivative() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 derivative_counts_to_listing() (in module ufl.utils.derivativetuples), 92
 derivative_listing_to_counts() (in module ufl.utils.derivativetuples), 92
 DerivativeRuleDispatcher (class in ufl.algorithms.apply_derivatives), 48
 det() (in module ufl), 178
 det() (in module ufl.operators), 153
 Determinant (class in ufl.classes), 111
 Determinant (class in ufl.tensoralgebra), 159

determinant() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebraHandler method), 47

determinant() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60

determinant() (ufl.formatting.ufl2dot.CompactLabeller method), 88

determinant() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

determinant() (ufl.formatting.ufl2dot.CompactLabeller method), 88

determinant() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

determinant() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

determinant_expr() (in ufl.compound_expressions), 129

determinant_expr_2x2() (in ufl.compound_expressions), 129

determinant_expr_3x3() (in ufl.compound_expressions), 129

determine_num_ops() (in module ufl.core.ufl_type), 77

dev() (in module ufl), 178

dev() (in module ufl.operators), 153

dev() (ufl.formatting.ufl2dot.CompactLabeller method), 88

Deviatoric (class in ufl.classes), 112

Deviatoric (class in ufl.tensoralgebra), 159

deviatoric() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebraHandler method), 47

deviatoric() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60

deviatoric() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

deviatoric_expr() (in module ufl.compound_expressions), 129

deviatoric_expr_2x2() (in ufl.compound_expressions), 129

deviatoric_expr_3x3() (in ufl.compound_expressions), 129

diag() (in module ufl), 178

diag() (in module ufl.operators), 153

diag_vector() (in module ufl), 178

diag_vector() (in module ufl.operators), 153

dict_sum() (in module ufl.utils_dicts), 93

dicts_lt() (in module ufl.algorithms.domain_analysis), 59

diff() (in module ufl), 180

diff() (in module ufl.operators), 153

diff() (ufl.formatting.ufl2dot.CompactLabeller method), 88

dimension() (ufl.classes.IndexSum method), 112

dimension() (ufl.indexsum.IndexSum method), 147

DirectionalSobolevSpace (class in ufl.sobolevspace), 158

Div (class in ufl.classes), 114

Div (class in ufl.differentiation), 133

div() (in module ufl), 180

div() (in module ufl.operators), 153

div() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebraHandler method), 47

div() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60

dim() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60

Division (class in ufl.algebra), 96

Division (class in ufl.classes), 110

division() (ufl.algorithms.expand_indices.IndexExpander method), 62

division() (ufl.algorithms.formtransformations.PartExtractor method), 64

division() (ufl.formatting.ufl2dot.CompactLabeller method), 88

division() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

Dn() (in module ufl), 181

document() (in module ufl.formatting.latextools), 87

domain (ufl.algorithms.domain_analysis.IntegralData attribute), 58

domain_numbering() (ufl.classes.Form method), 127

domain_numbering() (ufl.Form method), 182

domain_numbering() (ufl.form.Form method), 137

Dot (class in ufl.classes), 111

Dot (class in ufl.tensoralgebra), 159

dot() (in module ufl), 178

dot() (in module ufl.operators), 153

dot() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47

dot() (ufl.algorithms.check_arities.ArityChecker method), 56

dot() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

dot() (ufl.algorithms.formtransformations.PartExtractor method), 64

dot() (ufl.formatting.ufl2dot.CompactLabeller method), 88

dot() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

dstr() (in module ufl.utils_formatting), 93

Dt() (in module ufl.operators), 152

Dx() (in module ufl), 180

Dx() (in module ufl.operators), 152

dx() (ufl.classes.Expr method), 100

dx() (ufl.core.expr.Expr method), 74

dydtx() (in module ufl.tensors), 161

E

E() (ufl.formatting.graph.Graph method), 86

Ein() (ufl.formatting.graph.Graph method), 86
elem_div() (in module ufl), 181
elem_div() (in module ufl.operators), 153
elem_mult() (in module ufl), 181
elem_mult() (in module ufl.operators), 153
elem_op() (in module ufl), 182
elem_op() (in module ufl.operators), 153
elem_op_items() (in module ufl.operators), 153
elem_pow() (in module ufl), 181
elem_pow() (in module ufl.operators), 154
element2latex() (in module ufl.formatting.ufl2latex), 91
empty() (ufl.classes.Form method), 127
empty() (ufl.Form method), 182
empty() (ufl.form.Form method), 137
EmptyDictType (class in ufl.utils_dicts), 92
enabled_coefficients (ufl.algorithms.domain_analysis.Integral attribute), 58
end() (ufl.log.Logger method), 148
energy_norm() (in module ufl), 184
energy_norm() (in module ufl.formoperators), 138
EnrichedElement (class in ufl), 172
EnrichedElement (class in ufl.classes), 121
EnrichedElement (class ufl.finiteelement.enrichedelement), 80
EnrichedElementBase (class ufl.finiteelement.enrichedelement), 80
Eout() (ufl.formatting.graph.Graph method), 86
EQ (class in ufl.classes), 115
EQ (class in ufl.conditional), 130
eq() (in module ufl), 179
eq() (in module ufl.operators), 154
eq() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
equals() (ufl.classes.Form method), 127
equals() (ufl.Form method), 182
equals() (ufl.form.Form method), 137
Equation (class in ufl.classes), 128
Equation (class in ufl.equation), 135
Erf (class in ufl.classes), 117
Erf (class in ufl.mathfunctions), 150
erf() (in module ufl), 178
erf() (in module ufl.operators), 154
erf() (ufl.algorithms.apply_derivatives.GenericDerivativeRule method), 49
erf() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
error() (ufl.log.Logger method), 148
estimate_total_polynomial_degree() (in ufl.algorithms), 69
estimate_total_polynomial_degree() (in ufl.algorithms.estimate_degrees), 62
estr() (in module ufl.utils.formatting), 93
evaluate() (ufl.algebra.Abs method), 95
evaluate() (ufl.algebra.Division method), 96
evaluate() (ufl.algebra.Power method), 96
evaluate() (ufl.algebra.Product method), 96
evaluate() (ufl.algebra.Sum method), 96
evaluate() (ufl.classes.Abs method), 110
evaluate() (ufl.classes.AndCondition method), 115
evaluate() (ufl.classes.Atan2 method), 117
evaluate() (ufl.classes.BesselFunction method), 117
evaluate() (ufl.classes.CellAvg method), 112
evaluate() (ufl.classes.ComponentTensor method), 108
evaluate() (ufl.classes.Conditional method), 116
evaluate() (ufl.classes.Division method), 110
evaluate() (ufl.classes.EQ method), 115
evaluate() (ufl.classes.Erf method), 117
evaluate() (ufl.classes.Expr method), 100
evaluate() (ufl.classes.FacetAvg method), 113
evaluate() (ufl.classes.GE method), 115
evaluate() (ufl.classes.Grad method), 114
evaluate() (ufl.classes.GT method), 115
evaluate() (ufl.classes.Identity method), 107
evaluate() (ufl.classes.Indexed method), 108
evaluate() (ufl.classes.IndexSum method), 112
evaluate() (ufl.classes.LE method), 115
in evaluate() (ufl.classes.ListTensor method), 108
evaluate() (ufl.classes.Ln method), 116
in evaluate() (ufl.classes.LT method), 115
evaluate() (ufl.classes.MathFunction method), 116
evaluate() (ufl.classes.MaxValue method), 116
evaluate() (ufl.classes.MinValue method), 116
evaluate() (ufl.classes.MultiIndex method), 106
evaluate() (ufl.classes.NE method), 115
evaluate() (ufl.classes.NotCondition method), 116
evaluate() (ufl.classes.OrCondition method), 116
evaluate() (ufl.classes.PermutationSymbol method), 107
evaluate() (ufl.classes.Power method), 110
evaluate() (ufl.classes.Product method), 110
evaluate() (ufl.classes.ReferenceGrad method), 114
evaluate() (ufl.classes.ReferenceValue method), 118
evaluate() (ufl.classes.Restricted method), 112
evaluate() (ufl.classes.ScalarValue method), 107
evaluate() (ufl.classes.SpatialCoordinate method), 101
evaluate() (ufl.classes.Sum method), 110
evaluate() (ufl.classes.Terminal method), 100
evaluate() (ufl.classes.Variable method), 109
evaluate() (ufl.classes.Zero method), 107
evaluate() (ufl.conditional.AndCondition method), 129
evaluate() (ufl.conditional.Conditional method), 130
evaluate() (ufl.conditional.EQ method), 130
evaluate() (ufl.conditional.GE method), 130
evaluate() (ufl.conditional.GT method), 130
evaluate() (ufl.conditional.LE method), 130
evaluate() (ufl.conditional.LT method), 130
evaluate() (ufl.conditional.MaxValue method), 130
evaluate() (ufl.conditional.MinValue method), 130
evaluate() (ufl.conditional.NE method), 131

evaluate() (ufl.conditional.NotCondition method), 131
 evaluate() (ufl.conditional.OrCondition method), 131
 evaluate() (ufl.constantvalue.Identity method), 131
 evaluate() (ufl.constantvalue.PermutationSymbol method), 131
 evaluate() (ufl.constantvalue.ScalarValue method), 132
 evaluate() (ufl.constantvalue.Zero method), 132
 evaluate() (ufl.core.expr.Expr method), 74
 evaluate() (ufl.core.multiindex.MultiIndex method), 75
 evaluate() (ufl.core.terminal.Terminal method), 76
 evaluate() (ufl.differentiation.Grad method), 133
 evaluate() (ufl.differentiation.ReferenceGrad method), 133
 evaluate() (ufl.geometry.SpatialCoordinate method), 146
 evaluate() (ufl.Identity method), 177
 evaluate() (ufl.indexed.Indexed method), 146
 evaluate() (ufl.indexsum.IndexSum method), 147
 evaluate() (ufl.mathfunctions.Atan2 method), 149
 evaluate() (ufl.mathfunctions.BesselFunction method), 149
 evaluate() (ufl.mathfunctions.Erf method), 150
 evaluate() (ufl.mathfunctions.Ln method), 150
 evaluate() (ufl.mathfunctions.MathFunction method), 150
 evaluate() (ufl.PermutationSymbol method), 176
 evaluate() (ufl.referencevalue.ReferenceValue method), 157
 evaluate() (ufl.restriction.CellAvg method), 157
 evaluate() (ufl.restriction.FacetAvg method), 157
 evaluate() (ufl.restriction.Restricted method), 158
 evaluate() (ufl.SpatialCoordinate method), 168
 evaluate() (ufl.tensors.ComponentTensor method), 160
 evaluate() (ufl.tensors.ListTensor method), 160
 evaluate() (ufl.variable.Variable method), 162
 ExampleCounted (class in ufl.utils.counted), 92
 execute_ufl_code() (in module ufl.algorithms.formfiles), 63
 Exp (class in ufl.classes), 116
 Exp (class in ufl.mathfunctions), 150
 exp() (in module ufl), 178
 exp() (in module ufl.operators), 154
 exp() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 exp() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 expand_compounds() (in module ufl.algorithms), 72
 expand_compounds() (in module ufl.algorithms.expand_compounds), 62
 expand_derivatives() (in module ufl.algorithms), 72
 expand_derivatives() (in module ufl.algorithms.ad), 46
 expand_indices() (in module ufl.algorithms), 71
 expand_indices() (in module ufl.algorithms.expand_indices), 63
 expecting_expr() (in module ufl.assertions), 97
 expecting_instance() (in module ufl.assertions), 97
 expecting_python_scalar() (in module ufl.assertions), 97
 expecting_terminal() (in module ufl.assertions), 97
 expecting_true_ufl_scalar() (in module ufl.assertions), 97
 Expr (class in ufl.classes), 99
 Expr (class in ufl.core.expr), 73
 expr() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
 expr() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48
 expr() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 expr() (ufl.algorithms.apply_function_pullbacks.FunctionPullbackApplier method), 52
 expr() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier method), 52
 expr() (ufl.algorithms.change_to_reference.NEWChangeToReferenceGrad method), 55
 expr() (ufl.algorithms.change_to_reference.OLDChangeToReferenceGrad method), 56
 expr() (ufl.algorithms.check_arities.ArityChecker method), 56
 expr() (ufl.algorithms.check_restrictions.RestrictionChecker method), 57
 expr() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 expr() (ufl.algorithms.FormSplitter method), 72
 expr() (ufl.algorithms.formsplitter.FormSplitter method), 64
 expr() (ufl.algorithms.formtransformations.PartExtractor method), 64
 expr() (ufl.algorithms.MultiFunction method), 71
 expr() (ufl.algorithms.replace.Replacer method), 67
 expr() (ufl.algorithms.ReuseTransformer method), 70
 expr() (ufl.algorithms.Transformer method), 70
 expr() (ufl.algorithms.transformer.CopyTransformer method), 68
 expr() (ufl.algorithms.transformer.ReuseTransformer method), 68
 expr() (ufl.algorithms.transformer.Transformer method), 68
 expr() (ufl.corealg.multiplication.MultiFunction method), 78
 expr() (ufl.formatting.graph.StringDependencyDefiner method), 86
 expr() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 expr_equals() (in module ufl.exprequals), 136
 ExprData (class in ufl.algorithms.formdata), 63
 expression() (ufl.classes.Variable method), 109
 expression() (ufl.variable.Variable method), 162
 expression2latex() (in module ufl.formatting.ufl2latex), 91
 Expression2LatexHandler (class in ufl.formatting.ufl2latex), 89

ExprList (class in ufl.classes), 113
ExprList (class in ufl.exprcontainers), 135
ExprMapping (class in ufl.classes), 113
ExprMapping (class in ufl.exprcontainers), 136
ExprTupleKey (class in ufl.algorithms.domain_analysis), 58
exterior_derivative() (in module ufl), 181
exterior_derivative() (in module ufl.operators), 154
extract_arguments() (in module ufl.algorithms), 72
extract_arguments() (in module ufl.algorithms.analysis), 46
extract_arguments_and_coefficients() (in module ufl.algorithms.analysis), 46
extract_coefficients() (in module ufl.algorithms), 72
extract_coefficients() (in module ufl.algorithms.analysis), 46
extract_component() (ufl.classes.FiniteElementBase method), 119
extract_component() (ufl.classes.MixedElement method), 120
extract_component() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
extract_component() (ufl.finiteelement.mixedelement.MixedElement method), 83
extract_component() (ufl.FiniteElementBase method), 170
extract_component() (ufl.MixedElement method), 171
extract_domains() (in module ufl.domain), 135
extract_elements() (in module ufl.algorithms), 71
extract_elements() (in module ufl.algorithms.analysis), 46
extract_incoming_edges() (in module ufl.formatting.graph), 87
extract_incoming_vertex_connections() (in module ufl.formatting.graph), 87
extract_outgoing_edges() (in module ufl.formatting.graph), 87
extract_outgoing_vertex_connections() (in module ufl.formatting.graph), 87
extract_reference_component() (ufl.classes.FiniteElementBase method), 119
extract_reference_component() (ufl.classes.MixedElement method), 120
extract_reference_component() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
extract_reference_component() (ufl.finiteelement.mixedelement.MixedElement method), 83
extract_reference_component() (ufl.FiniteElementBase method), 170
extract_reference_component() (ufl.MixedElement method), 171
extract_sub_elements() (in module ufl.algorithms), 71
extract_sub_elements() (in module ufl.algorithms.analysis), 46
extract_subelement_component() (ufl.classes.FiniteElementBase method), 119
extract_subelement_component() (ufl.classes.MixedElement method), 120
extract_subelement_component() (ufl.classes.TensorElement method), 121
extract_subelement_component() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
extract_subelement_component() (ufl.finiteelement.mixedelement.MixedElement method), 83
extract_subelement_component() (ufl.finiteelement.mixedelement.TensorElement method), 84
extract_subelement_component() (ufl.FiniteElementBase method), 170
~~extract_subelement_component()~~ (ufl.MixedElement method), 172
~~extract_subelement_component()~~ (ufl.TensorElement method), 172
extract_subelement_reference_component() (ufl.classes.FiniteElementBase method), 119
extract_subelement_reference_component() (ufl.classes.MixedElement method), 120
extract_subelement_reference_component() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
extract_subelement_reference_component() (ufl.finiteelement.mixedelement.MixedElement method), 83
extract_subelement_reference_component() (ufl.FiniteElementBase method), 170
extract_subelement_reference_component() (ufl.MixedElement method), 172
extract_type() (in module ufl.algorithms), 71
extract_type() (in module ufl.algorithms.analysis), 46
extract_unique_domain() (in module ufl.domain), 135
extract_unique_elements() (in module ufl.algorithms), 71
extract_unique_elements() (in module ufl.algorithms.analysis), 46

F

facet_area() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringA method), 52
facet_area() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 53
facet_avg() (in module ufl), 181
facet_avg() (in module ufl.operators), 154

facet_avg() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset class in ufl.geometry), 142
 method), 48
 facet_avg() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset class in ufl.classes), 113
 method), 49
 facet_avg() (ufl.algorithms.apply_derivatives.GradRuleset class in ufl.restriction), 157
 method), 50
 facet_avg() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset class in ufl.geometry), 142
 method), 51
 facet_avg() (ufl.algorithms.apply_derivatives.VariableRuleset class in ufl.classes), 123
 method), 51
 facet_avg() (ufl.algorithms.apply_restrictions.RestrictionPropagator class in ufl.finiteelement.facetelement), 81
 method), 54
 facet_avg() (ufl.algorithms.change_to_reference.NEWChangeToReferenceGrad class in ufl.geometry), 143
 method), 55
 facet_avg() (ufl.algorithms.check_arities.ArityChecker class in ufl.classes), 143
 method), 56
 facet_avg() (ufl.algorithms.estimate_degrees.SumDegreeEstimator class in ufl.geometry), 143
 method), 61
 facet_avg() (ufl.algorithms.formtransformations.PartExtractor class in ufl.classes), 104
 method), 64
 facet_avg() (ufl.formatting.ufl2dot.CompactLabeller class in ufl.core.multiindex), 143
 method), 88
 facet_cell_coordinate() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier class in ufl.core.multiindex), 102
 method), 52
 facet_coordinate() (ufl.algorithms.apply_restrictions.RestrictionPropagator class in ufl.classes.FiniteElementBase method), 119
 method), 54
 facet_jacobian() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier class in ufl.core.multiindex), 102
 method), 53
 facet_jacobian() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier class in ufl.formatting.ufl2dot), 89
 method), 53
 facet_jacobian_determinant()
 (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier class in ufl.core.multiindex), 63
 method), 53
 facet_jacobian_determinant()
 (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier class in ufl.core.multiindex), 120
 method), 53
 facet_jacobian_inverse() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier class in ufl.core.multiindex), 170
 method), 53
 facet_jacobian_inverse() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier class in ufl.core.multiindex), 119
 method), 53
 facet_normal() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier class in ufl.core.multiindex), 81
 method), 53
 facet_normal() (ufl.algorithms.apply_restrictions.RestrictionPropagator class in ufl.core.multiindex), 74
 method), 54
 facet_normal() (ufl.algorithms.check_restrictions.RestrictionChecker class in ufl.core.multiindex), 49
 method), 57
 facet_normal() (ufl.formatting.graph.StringDependencyDefiner class in ufl.core.multiindex), 93
 method), 86
 facet_normal() (ufl.formatting.ufl2latex.Expression2LatexHandler class in ufl.core.multiindex), 121
 method), 90
 facet_origin() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier class in ufl.finiteelement.mixedelement.TensorElement method), 84
 method), 54
 FacetArea (class in ufl), 169
 FacetArea (class in ufl.classes), 105

FloatValue (class in ufl.classes), 107
 FloatValue (class in ufl.constantvalue), 131
 Form (class in ufl), 182
 Form (class in ufl.classes), 127
 Form (class in ufl.form), 137
 form2code2latex() (in module ufl.formatting.ufl2latex), 91
 form2latex() (in module ufl.formatting.ufl2latex), 91
 form_argument() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 form_argument() (ufl.algorithms.apply_function_pullbacks.FunctionPullbackApplier method), 52
 form_argument() (ufl.algorithms.change_to_reference.NEWChangeToRefinement) method), 55
 form_argument() (ufl.algorithms.check_restrictions.RestrictionPropagator method), 57
 form_argument() (ufl.algorithms.expand_indices.IndexExpansion method), 63
 form_argument() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 form_info() (in module ufl.formatting.printing), 87
 FormArgument (class in ufl.classes), 100
 FormArgument (class in ufl.core.terminal), 76
 format_entities() (in module ufl.formatting.ufl2dot), 89
 format_float() (in module ufl.constantvalue), 132
 format_index() (in module ufl.formatting.ufl2latex), 91
 format_multi_index() (in module ufl.formatting.ufl2latex), 91
 FormData (class in ufl.algorithms.formdata), 63
 formdata2latex() (in module ufl.formatting.ufl2latex), 91
 forms2latexdocument() (in module ufl.formatting.ufl2latex), 91
 FormSplitter (class in ufl.algorithms), 72
 FormSplitter (class in ufl.algorithms.forms splitter), 64
 free_indices() (ufl.classes.ExprList method), 113
 free_indices() (ufl.classes.ExprMapping method), 113
 free_indices() (ufl.exprcontainers.ExprList method), 135
 free_indices() (ufl.exprcontainers.ExprMapping method), 136
 from_numpy_to_lists() (in module ufl.tensors), 161
 functional() (in module ufl), 185
 functional() (in module ufl.formoperators), 138
 FunctionPullbackApplier (class in ufl.algorithms.apply_function_pullbacks), 52
 FunctionSpace (class in ufl), 175
 FunctionSpace (class in ufl.classes), 124
 FunctionSpace (class in ufl.functionspace), 140
G
 GateauxDerivativeRuleset (class in ufl.algorithms.apply_derivatives), 48
 GE (class in ufl.classes), 115
 GE (class in ufl.conditional), 130
 ge() (in module ufl), 179
 ge() (in module ufl.operators), 154
 ge() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 generic_pseudo_determinant_expr() (in module ufl.compound_expressions), 129
 generic_pseudo_inverse_expr() (in module ufl.compound_expressions), 129
 GenericDerivativeRuleset (class in ufl.algorithms.apply_derivatives), 48
 genericpullbackapply() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 56
 geometric_dimension() (ufl.AbstractCell method), 166
 geometric_dimension() (ufl.Domain method), 167
 geometric_dimension() (ufl.cell.AbstractCell method), 97
 geometric_dimension() (ufl.classes.AbstractCell method), 118
 geometric_dimension() (ufl.classes.AbstractDomain method), 124
 geometric_dimension() (ufl.classes.Expr method), 100
 geometric_dimension() (ufl.classes.Form method), 127
 geometric_dimension() (ufl.core.expr.Expr method), 74
 geometric_dimension() (ufl.domain.AbstractDomain method), 134
 geometric_dimension() (ufl.Form method), 182
 geometric_dimension() (ufl.form.Form method), 137
 geometric_facet_quantity() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
 geometric_quantity() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset method), 48
 geometric_quantity() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 geometric_quantity() (ufl.algorithms.apply_derivatives.GradRuleset method), 50
 geometric_quantity() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51
 geometric_quantity() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51
 geometric_quantity() (ufl.algorithms.change_to_reference.NEWChangeToRefinement method), 55
 geometric_quantity() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 geometric_quantity() (ufl.formatting.graph.StringDependencyDefiner method), 86
 geometric_quantity() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 GeometricCellQuantity (class in ufl.classes), 101
 GeometricCellQuantity (class in ufl.geometry), 144
 GeometricFacetQuantity (class in ufl.classes), 101
 GeometricFacetQuantity (class in ufl.geometry), 144
 GeometricQuantity (class in ufl.classes), 100

GeometricQuantity (class in ufl.geometry), 144
 GeometryLoweringApplier (class in ufl.algorithms.apply_geometry_lowering), 52
 get_base_attr() (in module ufl.core.ufl_type), 77
 get_handler() (ufl.log.Logger method), 148
 get_logfile_handler() (ufl.log.Logger method), 148
 get_logger() (ufl.log.Logger method), 148
 get_num_args() (in module ufl.corealg.monomialfunction), 78
 Grad (class in ufl.classes), 114
 Grad (class in ufl.differentiation), 133
 grad() (in module ufl), 180
 grad() (in module ufl.operators), 154
 grad() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48
 grad() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset method), 48
 grad() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 grad() (ufl.algorithms.apply_derivatives.GradRuleset method), 50
 grad() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51
 grad() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51
 grad() (ufl.algorithms.apply_restrictions.RestrictionPropagation method), 54
 grad() (ufl.algorithms.change_to_reference.NEWChangeToReferenceGrad method), 55
 grad() (ufl.algorithms.change_to_reference.OLDChangeToReferenceGrad method), 56
 grad() (ufl.algorithms.check_arities.ArityChecker method), 56
 grad() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 grad() (ufl.algorithms.expand_indices.IndexExpander method), 63
 grad() (ufl.algorithms.formtransformations.PartExtractor method), 64
 grad() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 grad() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 GradRuleset (class in ufl.algorithms.apply_derivatives), 50
 Graph (class in ufl.formatting.graph), 86
 group_form_integrals() (in module ufl.algorithms.domain_analysis), 59
 group_integrals_by_domain_and_type() (in module ufl.algorithms.domain_analysis), 59
 GT (class in ufl.classes), 115
 GT (class in ufl.conditional), 130
 gt() (in module ufl), 179
 gt() (in module ufl.operators), 154
 gt() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

H

has_exact_type() (in module ufl.algorithms.analysis), 46
 has_simplex_facets() (ufl.AbstractCell method), 166
 has_simplex_facets() (ufl.Cell method), 166
 has_simplex_facets() (ufl.cell.AbstractCell method), 97
 has_simplex_facets() (ufl.cell.Cell method), 98
 has_simplex_facets() (ufl.cell.TensorProductCell method), 98
 has_simplex_facets() (ufl.classes.AbstractCell method), 118
 has_simplex_facets() (ufl.classes.Cell method), 118
 has_simplex_facets() (ufl.classes.TensorProductCell method), 119
 has_simplex_facets() (ufl.TensorProductCell method), 167
 has_type() (in module ufl.algorithms.analysis), 46
 HCurlElement (class in ufl), 174
 HCurlElement (class in ufl.classes), 123
 HCurlElement (class in ufl.finiteelement.hdivcurl), 83
 HDivElement (class in ufl), 174
 HDivElement (class in ufl.classes), 123
 HDivElement (class in ufl.finiteelement.hdivcurl), 83
 heapItem (class in ufl.formatting.graph), 86
 hypercube() (in module ufl.cell), 99

I

id_of_none() (in module ufl.protocols), 157
 Identity (class in ufl), 177
 Identity (class in ufl.classes), 107
 Identity (class in ufl.constantvalue), 131
 identity() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 identity() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 increase_order() (in module ufl.algorithms.elementtransformations), 59
 independent_operator() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 independent_terminal() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 Index (class in ufl), 177
 Index (class in ufl.classes), 125
 Index (class in ufl.core.multiindex), 75
 index() (ufl.algorithms.renumbering.IndexRenumberingTransformer method), 67
 index() (ufl.classes.IndexSum method), 112
 index() (ufl.indexsum.IndexSum method), 147
 index_dimensions() (ufl.classes.ExprList method), 113
 index_dimensions() (ufl.classes.ExprMapping method), 113

index_dimensions() (ufl.exprcontainers.ExprList method), 135
index_dimensions() (ufl.exprcontainers.ExprMapping method), 136
index_sum() (ufl.algorithms.apply_derivatives.GenericDerivativeRule) (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 49
index_sum() (ufl.algorithms.check_arities.ArityChecker method), 56
index_sum() (ufl.algorithms.estimate_degrees.SumDegreeEstimator) (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
index_sum() (ufl.algorithms.expand_indices.IndexExpander) (ufl.algorithms.formtransformations.PartExtractor method), 63
index_sum() (ufl.algorithms.formtransformations.PartExtractor) (ufl.formatting.ufl2dot.CompactLabeller method), 64
index_sum() (ufl.formatting.ufl2dot.CompactLabeller method), 88
index_sum() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
index_sum() (ufl.formatting.ufl2latex.Expression2LatexHandler) (ufl.integral.Integral class in ufl), 183
IndexBase (class in ufl.classes), 125
IndexBase (class in ufl.core.multiindex), 75
Indexed (class in ufl.classes), 107
Indexed (class in ufl.indexed), 146
indexed() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher) (ufl.algorithms.domain_analysis.IntegralData subdomain_ids() (in module ufl.algorithms.domain_analysis), 59
indexed() (ufl.algorithms.apply_derivatives.GenericDerivativeRule) (ufl.algorithms.domain_analysis.IntegralData method), 49
indexed() (ufl.algorithms.check_arities.ArityChecker method), 56
indexed() (ufl.algorithms.estimate_degrees.SumDegreeEstimator) (ufl.integral.Integral class in ufl), 183
indexed() (ufl.algorithms.expand_indices.IndexExpander method), 63
indexed() (ufl.algorithms.formtransformations.PartExtractor) (ufl.integral.Integral class in ufl), 184
indexed() (ufl.formatting.ufl2dot.CompactLabeller method), 88
indexed() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
IndexExpander (class in ufl.algorithms.expand_indices), 62
IndexRenumberingTransformer (class in ufl.algorithms.renumbering), 66
IndexSum (class in ufl.classes), 112
IndexSum (class in ufl.indexsum), 147
indices() (in module ufl), 177
indices() (in module ufl.core.multiindex), 75
indices() (ufl.classes.ComponentTensor method), 108
indices() (ufl.classes.MultiIndex method), 106
indices() (ufl.core.multiindex.MultiIndex method), 75
indices() (ufl.tensors.ComponentTensor method), 160
info() (ufl.log.Logger method), 148
info_blue() (ufl.log.Logger method), 148
info_green() (ufl.log.Logger method), 148
info_red() (ufl.log.Logger method), 148
inner() (class in ufl.classes), 111
inner() (class in ufl.tensoralgebra), 159
inner() (in module ufl), 178
inner() (in module ufl.operators), 154
inner() (ufl.algorithms.estimate_degrees.SumDegreeEstimator) (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
inner() (ufl.algorithms.formtransformations.PartExtractor) (ufl.algorithms.formtransformations.PartExtractor method), 65
inner() (ufl.formatting.ufl2dot.CompactLabeller) (ufl.formatting.ufl2dot.CompactLabeller method), 88
inner() (ufl.formatting.ufl2latex.Expression2LatexHandler) (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
Integral (class in ufl), 126
Integral (class in ufl.integral), 147
integral_coefficients (ufl.algorithms.domain_analysis.IntegralData attribute), 58
integral_info() (in module ufl.formatting.printing), 87
integral_type() (ufl.algorithms.domain_analysis.IntegralData attribute), 58
integral_type() (ufl.classes.Integral method), 126
integral_type() (ufl.classes.Measure method), 125
integral_type() (ufl.integral.Integral method), 147
integral_type() (ufl.Measure method), 183
integral_type() (ufl.measure.Measure method), 150
integral_types() (in module ufl), 184
integral_types() (in module ufl.measure), 151
IntegralData (class in ufl.algorithms.domain_analysis), 58
integrals (ufl.algorithms.domain_analysis.IntegralData attribute), 58
integrals() (ufl.classes.Form method), 127
integrals() (ufl.Form method), 182
integrals() (ufl.form.Form method), 137
integrals_by_type() (ufl.classes.Form method), 127
integrals_by_type() (ufl.Form method), 182
integrals_by_type() (ufl.form.Form method), 137
integrand() (ufl.classes.Integral method), 126
integrand() (ufl.Integral method), 183
integrand() (ufl.integral.Integral method), 147
integrand2code() (in module ufl.formatting.ufl2latex), 91
InteriorElement() (in module ufl), 175
InteriorElement() (in module ufl.classes), 123
InteriorElement() (in module ufl.finiteelement.interiorelement), 83
interpret_ufl_namespace() (in module ufl.algorithms.formfiles), 63
IntValue (class in ufl.classes), 107

IntValue (class in ufl.constantvalue), 131
 inv() (in module ufl), 178
 inv() (in module ufl.operators), 154
 Inverse (class in ufl.classes), 111
 Inverse (class in ufl.tensoralgebra), 159
 inverse() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgorithm), 104
 method), 47
 inverse() (ufl.algorithms.estimate_degrees.SumDegreeEstimator), 61
 inverse() (ufl.formatting.ufl2latex.Expression2LatexHandler), 90
 inverse_expr() (in module ufl.compound_expressions), 129
 IrreducibleInt (class in ufl.algorithms.estimate_degrees), 59
 is_cellwise_constant() (in module ufl.checks), 99
 is_cellwise_constant() (ufl.Argument method), 175
 is_cellwise_constant() (ufl.argument.Argument method), 96
 is_cellwise_constant() (ufl.classes.Argument method), 108
 is_cellwise_constant() (ufl.classes.CellCoordinate method), 101
 is_cellwise_constant() (ufl.classes.CellEdgeVectors method), 103
 is_cellwise_constant() (ufl.classes.CellFacetJacobian method), 103
 is_cellwise_constant() (ufl.classes.CellFacetJacobianDeterminant method), 103
 is_cellwise_constant() (ufl.classes.CellFacetJacobianDeterminant method), 104
 is_cellwise_constant() (ufl.classes.CellOrigin method), 102
 is_cellwise_constant() (ufl.classes.Coefficient method), 109
 is_cellwise_constant() (ufl.classes.ConstantValue method), 107
 is_cellwise_constant() (ufl.classes.EnrichedElement method), 121
 is_cellwise_constant() (ufl.classes.FacetCoordinate method), 101
 is_cellwise_constant() (ufl.classes.FacetEdgeVectors method), 103
 is_cellwise_constant() (ufl.classes.FacetJacobian method), 102
 is_cellwise_constant() (ufl.classes.FacetJacobianDeterminant), 103
 is_cellwise_constant() (ufl.classes.FacetJacobianInverse method), 104
 is_cellwise_constant() (ufl.classes.FacetNormal method), 104
 is_cellwise_constant() (ufl.classes.FiniteElementBase method), 119
 is_cellwise_constant() (ufl.classes.GeometricQuantity

 method), 101
 is_cellwise_constant() (ufl.classes.Jacobian method), 102
 is_cellwise_constant() (ufl.classes.JacobianDeterminant method), 103
 is_cellwise_constant() (ufl.classes.JacobianInverse method), 104
 is_cellwise_constant() (ufl.classes.Label method), 109
 is_cellwise_constant() (ufl.classes.MixedElement method), 120
 is_cellwise_constant() (ufl.classes.MultiIndex method), 106
 is_cellwise_constant() (ufl.classes.NodalEnrichedElement method), 122
 is_cellwise_constant() (ufl.classes.QuadratureWeight method), 106
 is_cellwise_constant() (ufl.classes.RestrictedElement method), 122
 is_cellwise_constant() (ufl.classes.SpatialCoordinate method), 101
 is_cellwise_constant() (ufl.Coefficient method), 176
 is_cellwise_constant() (ufl.coefficient.Coefficient method), 128
 is_cellwise_constant() (ufl.constantvalue.ConstantValue method), 131
 is_cellwise_constant() (ufl.core.multiindex.MultiIndex method), 75
 is_cellwise_constant() (ufl.EnrichedElement method), 173
 is_cellwise_constant() (ufl.FacetNormal method), 169
 is_cellwise_constant() (ufl.finiteelement.enrichedelement.EnrichedElement method), 80
 is_cellwise_constant() (ufl.finiteelement.enrichedelement.NodalEnrichedElement method), 81
 is_cellwise_constant() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
 is_cellwise_constant() (ufl.finiteelement.mixedelement.MixedElement method), 84
 is_cellwise_constant() (ufl.finiteelement.restrictedelement.RestrictedElement method), 85
 is_cellwise_constant() (ufl.FiniteElementBase method), 170
 is_cellwise_constant() (ufl.geometry.CellCoordinate method), 140
 is_cellwise_constant() (ufl.geometry.CellEdgeVectors method), 141
 is_cellwise_constant() (ufl.geometry.CellFacetJacobian method), 141
 is_cellwise_constant() (ufl.geometry.CellFacetJacobianDeterminant method), 141
 is_cellwise_constant() (ufl.geometry.CellFacetJacobianInverse method), 141
 is_cellwise_constant() (ufl.geometry.CellOrigin method), 142
 is_cellwise_constant() (ufl.geometry.FacetCoordinate

method), 142
is_cellwise_constant() (ufl.geometry.FacetEdgeVectors method), 142
is_cellwise_constant() (ufl.geometry.FacetJacobian method), 143
is_cellwise_constant() (ufl.geometry.FacetJacobianDeterminant method), 143
is_cellwise_constant() (ufl.geometry.FacetJacobianInverse method), 143
is_cellwise_constant() (ufl.geometry.FacetNormal method), 143
is_cellwise_constant() (ufl.geometry.GeometricQuantity method), 144
is_cellwise_constant() (ufl.geometry.Jacobian method), 144
is_cellwise_constant() (ufl.geometry.JacobianDeterminant method), 144
is_cellwise_constant() (ufl.geometry.JacobianInverse method), 144
is_cellwise_constant() (ufl.geometry.QuadratureWeight method), 145
is_cellwise_constant() (ufl.geometry.SpatialCoordinate method), 146
is_cellwise_constant() (ufl.Jacobian method), 169
is_cellwise_constant() (ufl.JacobianDeterminant method), 170
is_cellwise_constant() (ufl.JacobianInverse method), 170
is_cellwise_constant() (ufl.MixedElement method), 172
is_cellwise_constant() (ufl.NodalEnrichedElement method), 173
is_cellwise_constant() (ufl.RestrictedElement method), 173
is_cellwise_constant() (ufl.SpatialCoordinate method), 168
is_cellwise_constant() (ufl.variable.Label method), 162
is_globally_constant() (in module ufl.checks), 99
is_piecewise_linear_simplex_domain() (ufl.classes.Mesh method), 124
is_piecewise_linear_simplex_domain() (ufl.classes.MeshView method), 124
is_piecewise_linear_simplex_domain() (ufl.classes.TensorProductMesh method), 124
is_piecewise_linear_simplex_domain() (ufl.domain.Mesh method), 134
is_piecewise_linear_simplex_domain() (ufl.domain.MeshView method), 134
is_piecewise_linear_simplex_domain() (ufl.domain.TensorProductMesh method), 135
is_piecewise_linear_simplex_domain() (ufl.Mesh method), 167
is_piecewise_linear_simplex_domain() (ufl.MeshView method), 168
is_piecewise_linear_simplex_domain() (ufl.TensorProductMesh method), 168
is_post_handler() (in module ufl.algorithms.transformer), 69
is_python_scalar() (in module ufl.checks), 99
is_scalar_constant_expression() (in module ufl.checks), 99
is_simplex() (ufl.AbstractCell method), 166
is_simplex() (ufl.Cell method), 166
is_simplex() (ufl.cell.AbstractCell method), 98
is_simplex() (ufl.cell.Cell method), 98
is_simplex() (ufl.cell.TensorProductCell method), 98
is_simplex() (ufl.classes.AbstractCell method), 118
is_simplex() (ufl.classes.Cell method), 118
is_simplex() (ufl.classes.TensorProductCell method), 119
is_simplex() (ufl.TensorProductCell method), 167
is_true_ufl_scalar() (in module ufl.checks), 99
is_ufl_scalar() (in module ufl.checks), 99
istr() (in module ufl.utils.formatting), 93
itemize() (in module ufl.formatting.latextools), 87
iter_expressions() (in module ufl.algorithms.traversal), 69
iter_tree() (in module ufl.utils.sequences), 94

J

Jacobian (class in ufl), 169
Jacobian (class in ufl.classes), 102
Jacobian (class in ufl.geometry), 144
jacobian() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringAp method), 53
jacobian_determinant() (ufl.algorithms.apply_geometry_lowering.Geometry method), 53
jacobian_inverse() (ufl.algorithms.apply_derivatives.GradRuleset method), 50
jacobian_inverse() (ufl.algorithms.apply_geometry_lowering.GeometryLow method), 53
JacobianDeterminant (class in ufl), 170
JacobianDeterminant (class in ufl.classes), 103
JacobianDeterminant (class in ufl.geometry), 144
JacobianInverse (class in ufl), 170
JacobianInverse (class in ufl.classes), 104
JacobianInverse (class in ufl.geometry), 144
join_domains() (in module ufl.domain), 135
jump() (in module ufl), 181
jump() (in module ufl.operators), 154

L

Label (class in ufl.classes), 109
Label (class in ufl.variable), 162
label() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
label() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
label() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

label() (ufl.classes.Variable method), 109
 label() (ufl.variable.Variable method), 162
 LE (class in ufl.classes), 115
 LE (class in ufl.conditional), 130
 le() (in module ufl), 179
 le() (in module ufl.operators), 154
 le() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 len_items() (in module ufl.formatting.graph), 87
 lhs() (in module ufl), 184
 lhs() (in module ufl.formoperators), 138
 linear_indexed_type() (ufl.algorithms.check_arities.ArityChecker method), 56
 linear_indexed_type() (ufl.algorithms.formtransformations.PartExtractor method), 65
 linear_operator() (ufl.algorithms.check_arities.ArityChecker method), 57
 linear_operator() (ufl.algorithms.formtransformations.PartExtractor method), 65
 list_tensor() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 list_tensor() (ufl.algorithms.check_arities.ArityChecker method), 57
 list_tensor() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 list_tensor() (ufl.algorithms.expand_indices.IndexExpander method), 63
 list_tensor() (ufl.algorithms.formtransformations.PartExtractor method), 65
 list_tensor() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 lists() (in module ufl.formatting.graph), 87
 ListTensor (class in ufl.classes), 108
 ListTensor (class in ufl.tensors), 160
 Ln (class in ufl.classes), 116
 Ln (class in ufl.mathfunctions), 150
 ln() (in module ufl), 178
 ln() (in module ufl.operators), 154
 ln() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 ln() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 load_forms() (in module ufl.algorithms.formfiles), 63
 load_ufl_file() (in module ufl.algorithms), 70
 load_ufl_file() (in module ufl.algorithms.formfiles), 63
 log() (ufl.log.Logger method), 148
 Logger (class in ufl.log), 147
 LowerCompoundAlgebra (class in ufl.algorithms.apply_algebra_lowering), 47
 lstr() (in module ufl.utils.formatting), 93
 LT (class in ufl.classes), 115
 LT (class in ufl.conditional), 130
 lt() (in module ufl), 179
 lt() (in module ufl.operators), 154
 lt() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

M

map_expr_dag() (in module ufl.corealg.map_dag), 78
 map_expr_dags() (in module ufl.corealg.map_dag), 78
 map_integrand_dags() (in module ufl.algorithms.map_integrands), 66
 map_integrands() (in module ufl.algorithms.map_integrands), 66
 mapping() (ufl.BrokenElement method), 174
 mapping() (ufl.classes.BrokenElement method), 123
 mapping() (ufl.classes.FiniteElement method), 120
 mapping() (ufl.classes.FiniteElementBase method), 119
 mapping() (ufl.classes.HCurlElement method), 123
 mapping() (ufl.classes.HDivElement method), 123
 mapping() (ufl.classes.MixedElement method), 120
 mapping() (ufl.classes.RestrictedElement method), 122
 mapping() (ufl.classes.TensorElement method), 121
 mapping() (ufl.classes.TensorProductElement method), 122
 mapping() (ufl.FiniteElement method), 171
 mapping() (ufl.finiteelement.brokenelement.BrokenElement method), 79
 mapping() (ufl.finiteelement.enrichedelement.EnrichedElementBase method), 80
 mapping() (ufl.finiteelement.finiteelement.FiniteElement method), 81
 mapping() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
 mapping() (ufl.finiteelement.hdivcurl.HCurlElement method), 83
 mapping() (ufl.finiteelement.hdivcurl.HDivElement method), 83
 mapping() (ufl.finiteelement.mixedelement.MixedElement method), 84
 mapping() (ufl.finiteelement.mixedelement.TensorElement method), 84
 mapping() (ufl.finiteelement.restrictedelement.RestrictedElement method), 85
 mapping() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 85
 mapping() (ufl.FiniteElementBase method), 171
 mapping() (ufl.HCurlElement method), 174
 mapping() (ufl.HDivElement method), 174
 mapping() (ufl.MixedElement method), 172
 mapping() (ufl.RestrictedElement method), 173
 mapping() (ufl.TensorElement method), 172
 mapping() (ufl.TensorProductElement method), 174
 math_function() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 math_function() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

math_function() (ufl.formatting.ufl2dot.CompactLabeller method), 88
MathFunction (class in ufl.classes), 116
MathFunction (class in ufl.mathfunctions), 150
Max() (in module ufl), 180
Max() (in module ufl.operators), 152
max_cell_edge_length() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplyingApplier method), 53
max_facet_edge_length() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier method), 53
max_facet_edge_length() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
max_subdomain_ids() (ufl.classes.Form method), 127
max_subdomain_ids() (ufl.Form method), 182
max_subdomain_ids() (ufl.form.Form method), 137
max_value() (in module ufl), 180
max_value() (in module ufl.operators), 154
max_value() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
max_value() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
max_value() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
MaxCellEdgeLength (class in ufl), 169
MaxCellEdgeLength (class in ufl.classes), 105
MaxCellEdgeLength (class in ufl.geometry), 145
MaxFacetEdgeLength (class in ufl), 169
MaxFacetEdgeLength (class in ufl.classes), 105
MaxFacetEdgeLength (class in ufl.geometry), 145
MaxValue (class in ufl.classes), 116
MaxValue (class in ufl.conditional), 130
Measure (class in ufl), 183
Measure (class in ufl.classes), 125
Measure (class in ufl.measure), 150
measure_collisions() (in module ufl.exprequals), 136
measure_names() (in module ufl.measure), 151
MeasureProduct (class in ufl.classes), 126
MeasureProduct (class in ufl.measure), 151
MeasureSum (class in ufl.classes), 126
MeasureSum (class in ufl.measure), 151
memoized_handler() (in ufl.corealg.multipfunction), 78
merge_nonoverlapping_indices() (in ufl.index_combination_utils), 146
merge_overlapping_indices() (in ufl.index_combination_utils), 146
merge_unique_indices() (in ufl.index_combination_utils), 146
mergedicts() (in module ufl.utils.dicts), 93
mergedicts2() (in module ufl.utils.dicts), 93
Mesh (class in ufl), 167
Mesh (class in ufl.classes), 124
Mesh (class in ufl.domain), 134
MeshView (class in ufl), 168
MeshView (class in ufl.classes), 124
MeshView (class in ufl.domain), 134
metadata (ufl.algorithms.domain_analysis.IntegralData attribute), 58
metalingege (ufl.algorithms.IntegralApplier method), 126
metadata() (ufl.classes.Measure method), 126
metadata() (ufl.Integral method), 183
myIntegratingApplier (ufl.algorithms.Integral method), 147
metadata() (ufl.Measure method), 183
metadata() (ufl.measure.Measure method), 150
oneApplierEqual() (in module ufl.protocols), 157
metadata_hashdata() (in module ufl.protocols), 157
Min() (in module ufl), 180
Min() (in module ufl.operators), 152
min_cell_edge_length() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier method), 53
min_facet_edge_length() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
min_value() (in module ufl), 180
min_value() (in module ufl.operators), 154
min_value() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
min_value() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
min_value() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
MinCellEdgeLength (class in ufl), 168
MinCellEdgeLength (class in ufl.classes), 105
MinCellEdgeLength (class in ufl.geometry), 145
MinFacetEdgeLength (class in ufl), 169
MinFacetEdgeLength (class in ufl.classes), 105
MinFacetEdgeLength (class in ufl.geometry), 145
MinValue (class in ufl.classes), 116
MinValue (class in ufl.conditional), 130
MixedElement (class in ufl), 171
MixedElement (class in ufl.classes), 120
module MixedElement (class in ufl.finiteelement.mixedelement), 83
module MixedFunctionSpace (class in ufl.classes), 125
MixedFunctionSpace (class in ufl.functionspace), 140
module multi_index() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
module multi_index() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
multi_index() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
multi_index() (ufl.algorithms.expand_indices.IndexExpander method), 63

multi_index() (ufl.algorithms.FormSplitter method), 72
multi_index() (ufl.algorithms.formsplitter.FormSplitter method), 64
multi_index() (ufl.algorithms.renumbering.IndexRenumbering method), 67
multi_index() (ufl.formatting.ufl2dot.CompactLabeller method), 88
multi_index() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
MultiFunction (class in ufl.algorithms), 71
MultiFunction (class in ufl.corealg.monomial), 78
MultiIndex (class in ufl.classes), 106
MultiIndex (class in ufl.core.multiindex), 75

N

nabla_div() (in module ufl), 181
nabla_div() (in module ufl.operators), 155
nabla_div() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
nabla_div() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
nabla_div() (ufl.formatting.ufl2dot.CompactLabeller method), 88
nabla_div() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
nabla_grad() (in module ufl), 181
nabla_grad() (in module ufl.operators), 155
nabla_grad() (ufl.algorithms.apply_algebra_lowering.LowerCompoundGeometry method), 47
nabla_grad() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
nabla_grad() (ufl.formatting.ufl2dot.CompactLabeller method), 88
nabla_grad() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
NablaDiv (class in ufl.classes), 114
NablaDiv (class in ufl.differentiation), 133
NablaGrad (class in ufl.classes), 114
NablaGrad (class in ufl.differentiation), 133
name (ufl.CellNormal attribute), 169
name (ufl.CellVolume attribute), 168
name (ufl.Circumradius attribute), 168
name (ufl.classes.CellCoordinate attribute), 101
name (ufl.classes.CellEdgeVectors attribute), 103
name (ufl.classes.CellFacetJacobian attribute), 103
name (ufl.classes.CellFacetJacobianDeterminant attribute), 103
name (ufl.classes.CellFacetJacobianInverse attribute), 104
name (ufl.classes.CellFacetOrigin attribute), 102
name (ufl.classes.CellNormal attribute), 104
name (ufl.classes.CellOrientation attribute), 106
name (ufl.classes.CellOrigin attribute), 102
name (ufl.classes.CellVolume attribute), 105
name (ufl.classes.Circumradius attribute), 105
name (ufl.classes.FacetArea attribute), 105
name (ufl.classes.FacetCoordinate attribute), 101
name (ufl.classes.FacetEdgeVectors attribute), 103
name (ufl.classes.FacetJacobian attribute), 102
name (ufl.classes.FacetJacobianDeterminant attribute), 103
name (ufl.classes.FacetJacobianInverse attribute), 104
name (ufl.classes.FacetNormal attribute), 104
name (ufl.classes.FacetOrientation attribute), 106
name (ufl.classes.FacetOrigin attribute), 102
name (ufl.classes.Jacobian attribute), 102
name (ufl.classes.JacobianDeterminant attribute), 103
name (ufl.classes.JacobianInverse attribute), 104
name (ufl.classes.MaxCellEdgeLength attribute), 105
name (ufl.classes.MaxFacetEdgeLength attribute), 105
name (ufl.classes.MinCellEdgeLength attribute), 105
name (ufl.classes.MinFacetEdgeLength attribute), 105
name (ufl.classes.QuadratureWeight attribute), 106
name (ufl.classes.ReferenceCellVolume attribute), 105
name (ufl.classes.ReferenceFacetVolume attribute), 105
name (ufl.classes.ReferenceNormal attribute), 105
name (ufl.classes.SpatialCoordinate attribute), 101
name (ufl.FacetArea attribute), 169
name (ufl.FacetNormal attribute), 169
name (ufl.geometry.CellCoordinate attribute), 140
name (ufl.geometry.CellEdgeVectors attribute), 141
name (ufl.geometry.CellFacetJacobian attribute), 141
name (ufl.geometry.CellFacetJacobianDeterminant attribute), 141
name (ufl.geometry.CellFacetJacobianInverse attribute), 141
name (ufl.geometry.CellFacetOrigin attribute), 141
name (ufl.geometry.CellNormal attribute), 141
name (ufl.geometry.CellOrientation attribute), 142
name (ufl.geometry.CellOrigin attribute), 142
name (ufl.geometry.CellVolume attribute), 142
name (ufl.geometry.Circumradius attribute), 142
name (ufl.geometry.FacetArea attribute), 142
name (ufl.geometry.FacetCoordinate attribute), 142
name (ufl.geometry.FacetEdgeVectors attribute), 143
name (ufl.geometry.FacetJacobian attribute), 143
name (ufl.geometry.FacetJacobianDeterminant attribute), 143
name (ufl.geometry.FacetJacobianInverse attribute), 143
name (ufl.geometry.FacetNormal attribute), 143
name (ufl.geometry.FacetOrientation attribute), 143
name (ufl.geometry.FacetOrigin attribute), 144
name (ufl.geometry.Jacobian attribute), 144
name (ufl.geometry.JacobianDeterminant attribute), 144
name (ufl.geometry.JacobianInverse attribute), 144
name (ufl.geometry.MaxCellEdgeLength attribute), 145
name (ufl.geometry.MaxFacetEdgeLength attribute), 145
name (ufl.geometry.MinCellEdgeLength attribute), 145

name (ufl.geometry.MinFacetEdgeLength attribute), 145
name (ufl.geometry.QuadratureWeight attribute), 145
name (ufl.geometry.ReferenceCellVolume attribute), 145
name (ufl.geometry.ReferenceFacetVolume attribute),
 145
name (ufl.geometry.ReferenceNormal attribute), 145
name (ufl.geometry.SpatialCoordinate attribute), 146
name (ufl.Jacobian attribute), 170
name (ufl.JacobianDeterminant attribute), 170
name (ufl.JacobianInverse attribute), 170
name (ufl.MaxCellEdgeLength attribute), 169
name (ufl.MaxFacetEdgeLength attribute), 169
name (ufl.MinCellEdgeLength attribute), 169
name (ufl.MinFacetEdgeLength attribute), 169
name (ufl.SpatialCoordinate attribute), 168
NE (class in ufl.classes), 115
NE (class in ufl.conditional), 131
ne() (in module ufl), 179
ne() (in module ufl.operators), 155
ne() (ufl.formatting.ufl2latex.Expression2LatexHandler
 method), 90
negative_restricted() (ufl.algorithms.check_arities.ArityChecker
 method), 57
negative_restricted() (ufl.algorithms.estimate_degrees.SumDegreeEstimator
 method), 61
negative_restricted() (ufl.algorithms.formtransformations.PartExtract
 method), 65
negative_restricted() (ufl.formatting.ufl2dot.CompactLabeller
 method), 88
negative_restricted() (ufl.formatting.ufl2latex.Expression2LatexHandler
 method), 90
NegativeRestricted (class in ufl.classes), 112
NegativeRestricted (class in ufl.restriction), 157
NEWChangeToReferenceGrad (class
 ufl.algorithms.change_to_reference), 55
NodalEnrichedElement (class in ufl), 173
NodalEnrichedElement (class in ufl.classes), 122
NodalEnrichedElement (class
 ufl.finiteelement.enrichedelement), 81
non_differentiable_terminal()
 (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset
 method), 50
nonlinear_operator() (ufl.algorithms.check_arities.ArityChecker
 method), 57
nonrecursive_expr_equals() (in module ufl.exprquals),
 136
Not() (in module ufl), 180
Not() (in module ufl.operators), 152
not_condition() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset
 method), 50
not_condition() (ufl.formatting.ufl2latex.Expression2LatexHandler
 method), 90
NotCondition (class in ufl.classes), 116
NotCondition (class in ufl.conditional), 131
num_edges() (ufl.Cell method), 166
num_edges() (ufl.cell.Cell method), 98
num_edges() (ufl.cell.TensorProductCell method), 98
num_edges() (ufl.classes.Cell method), 118
num_edges() (ufl.classes.TensorProductCell method),
 119
num_edges() (ufl.TensorProductCell method), 167
num_facet_edges() (ufl.Cell method), 166
num_facet_edges() (ufl.cell.Cell method), 98
num_facet_edges() (ufl.classes.Cell method), 118
num_facets() (ufl.Cell method), 167
num_facets() (ufl.cell.Cell method), 98
num_facets() (ufl.cell.TensorProductCell method), 98
num_facets() (ufl.classes.Cell method), 118
num_facets() (ufl.classes.TensorProductCell method),
 119
num_facets() (ufl.TensorProductCell method), 167
num_restricted_sub_elements()
 (ufl.classes.RestrictedElement method), 122
num_restricted_sub_elements()
 (ufl.finiteelement.restrictedelement.RestrictedElement
 method), 85
num_restricted_sub_elements() (ufl.RestrictedElement
 method), 122
num_sub_elements() (ufl.classes.FiniteElementBase
 method), 173
num_sub_elements() (ufl.classes.MixedElement method),
 121
num_sub_elements() (ufl.classes.RestrictedElement
 method), 122
num_sub_elements() (ufl.classes.TensorProductElement
 method), 123
num_sub_elements() (ufl.finiteelement.finiteelementbase.FiniteElementBase
 method), 82
num_sub_elements() (ufl.finiteelement.mixedelement.MixedElement
 method), 84
num_sub_elements() (ufl.finiteelement.restrictedelement.RestrictedElement
 method), 85
num_sub_elements() (ufl.finiteelement.tensorproductelement.TensorProduct
 method), 85
num_sub_elements() (ufl.FiniteElementBase method),
 171
num_sub_elements() (ufl.MixedElement method), 172
num_sub_elements() (ufl.RestrictedElement method),
 173
num_sub_elements() (ufl.TensorProductElement
 method), 174
num_vertices() (ufl.Cell method), 167
num_vertices() (ufl.cell.Cell method), 98
num_vertices() (ufl.cell.TensorProductCell method), 98
num_vertices() (ufl.classes.Cell method), 118
num_vertices() (ufl.classes.TensorProductCell method),
 119
num_vertices() (ufl.TensorProductCell method), 167

number() (ufl.Argument method), 175
 number() (ufl.argument.Argument method), 96
 number() (ufl.classes.Argument method), 108
 numpy2nestedlists() (in module ufl.tensors), 161

O

old_determinant_expr_3x3() (in module ufl.compound_expressions), 129
 OLDChangeToReferenceGrad (class in ufl.algorithms.change_to_reference), 56

Operator (class in ufl.classes), 106

Operator (class in ufl.core.operator), 75

operator() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54

operator() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55

operator() (ufl.formatting.ufl2dot.ReprLabeller method), 89

Or() (in module ufl), 180

Or() (in module ufl.operators), 152

or_condition() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

or_tuples() (in module ufl.utils.sequences), 94

OrCondition (class in ufl.classes), 115

OrCondition (class in ufl.conditional), 131

Outer (class in ufl.classes), 110

Outer (class in ufl.tensoralgebra), 159

outer() (in module ufl), 178

outer() (in module ufl.operators), 155

outer() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47

outer() (ufl.algorithms.check_arities.ArityChecker method), 57

outer() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

outer() (ufl.algorithms.formtransformations.PartExtractor method), 65

outer() (ufl.formatting.ufl2dot.CompactLabeller method), 88

outer() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90

override() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50

P

par() (in module ufl.formatting.ufl2latex), 91
 parstr() (in module ufl.precedence), 156
 part() (ufl.Argument method), 175
 part() (ufl.argument.Argument method), 96
 part() (ufl.classes.Argument method), 108
 PartExtractor (class in ufl.algorithms.formtransformations), 64
 partition() (in module ufl.formatting.graph), 87
 peek() (ufl.utils.stacks.Stack method), 95

permutation_symbol() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 PermutationSymbol (class in ufl), 176
 PermutationSymbol (class in ufl.classes), 107
 PermutationSymbol (class in ufl.constantvalue), 131
 perp() (in module ufl), 178
 perp() (in module ufl.operators), 155
 pop() (ufl.utils.stacks.StackDict method), 95
 pop_level() (ufl.log.Logger method), 148
 positive_restricted() (ufl.algorithms.check_arities.ArityChecker method), 57
 positive_restricted() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 positive_restricted() (ufl.algorithms.formtransformations.PartExtractor method), 65
 positive_restricted() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 positive_restricted() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 PositiveRestricted (class in ufl.classes), 112
 PositiveRestricted (class in ufl.restriction), 157
 post_traversal() (in module ufl.algorithms), 72
 post_traversal() (in module ufl.corealg.traversal), 79
 Power (class in ufl.algebra), 96
 Power (class in ufl.classes), 110
 power() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 power() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 power() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 power() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 90
 pre_traversal() (in module ufl.corealg.traversal), 79
 print_collisions() (in module ufl.exprequals), 136
 print_visit_stack() (ufl.algorithms.Transformer method), 70
 print_visit_stack() (ufl.algorithms.transformation.Transformer method), 68
 Product (class in ufl.algebra), 96
 Product (class in ufl.classes), 110
 product() (in module ufl), 166
 product() (in module ufl.utils.sequences), 94
 product() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 product() (ufl.algorithms.check_arities.ArityChecker method), 57
 product() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 product() (ufl.algorithms.formtransformations.PartExtractor method), 65
 product() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 product() (ufl.formatting.ufl2latex.Expression2LatexHandler

method), 91
pseudo_determinant_expr() (in module ufl.compound_expressions), 129
pseudo_inverse_expr() (in module ufl.compound_expressions), 129
purge_list_tensors() (in module ufl.algorithms), 70
purge_list_tensors() (in module ufl.algorithms.expand_indices), 63
push() (ufl.utils.stacks.Stack method), 95
push() (ufl.utils.stacks.StackDict method), 95
push_level() (ufl.log.Logger method), 148

Q

quadrature_scheme() (ufl.classes.FiniteElementBase method), 119
quadrature_scheme() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
quadrature_scheme() (ufl.FiniteElementBase method), 171
quadrature_weight() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55
QuadratureWeight (class in ufl.classes), 106
QuadratureWeight (class in ufl.geometry), 145

R

rank() (in module ufl), 177
rank() (in module ufl.operators), 155
read_lines_decoded() (in module ufl.algorithms.formfiles), 63
read_ufl_file() (in module ufl.algorithms.formfiles), 63
rearrange_integrals_by_single_subdomains() (in module ufl.algorithms.domain_analysis), 59
reconstruct() (ufl.BrokenElement method), 174
reconstruct() (ufl.Cell method), 167
reconstruct() (ufl.cell.Cell method), 98
reconstruct() (ufl.cell.TensorProductCell method), 98
reconstruct() (ufl.classes.BrokenElement method), 123
reconstruct() (ufl.classes.Cell method), 118
reconstruct() (ufl.classes.FiniteElement method), 120
reconstruct() (ufl.classes.HCurlElement method), 123
reconstruct() (ufl.classes.HDivElement method), 123
reconstruct() (ufl.classes.Integral method), 127
reconstruct() (ufl.classes.Measure method), 126
reconstruct() (ufl.classes.MixedElement method), 121
reconstruct() (ufl.classes.RestrictedElement method), 122
reconstruct() (ufl.classes.TensorElement method), 121
reconstruct() (ufl.classes.TensorProductCell method), 119
reconstruct() (ufl.classes.TensorProductElement method), 123
reconstruct() (ufl.classes.VectorElement method), 121
reconstruct() (ufl.FiniteElement method), 171
reconstruct() (ufl.finiteelement.brokenelement.BrokenElement method), 79

module reconstruct() (ufl.finiteelement.enrichedelement.EnrichedElementBase method), 81
reconstruct() (ufl.finiteelement.finiteelement.FiniteElement method), 81
reconstruct() (ufl.finiteelement.hcurl.HCurlElement method), 83
reconstruct() (ufl.finiteelement.hdivcurl.HDivElement method), 83
reconstruct() (ufl.finiteelement.mixedelement.MixedElement method), 84
reconstruct() (ufl.finiteelement.mixedelement.TensorElement method), 84
reconstruct() (ufl.finiteelement.mixedelement.VectorElement method), 84
reconstruct() (ufl.finiteelement.restrictedelement.RestrictedElement method), 85
reconstruct() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 85
reconstruct() (ufl.HCurlElement method), 174
reconstruct() (ufl.HDivElement method), 174
reconstruct() (ufl.Integral method), 183
reconstruct() (ufl.integral.Integral method), 147
reconstruct() (ufl.Measure method), 183
reconstruct() (ufl.measure.Measure method), 150
reconstruct() (ufl.MixedElement method), 172
reconstruct() (ufl.RestrictedElement method), 173
reconstruct() (ufl.TensorElement method), 172
reconstruct() (ufl.TensorProductCell method), 167
reconstruct() (ufl.TensorProductElement method), 174
reconstruct() (ufl.VectorElement method), 172
reconstruct_form_from_integral_data() (in module ufl.algorithms.domain_analysis), 59
reconstruct_from_elements() (ufl.classes.MixedElement method), 121
reconstruct_from_elements() (ufl.finiteelement.mixedelement.MixedElement method), 84
reconstruct_from_elements() (ufl.MixedElement method), 172
reconstruct_variable() (ufl.algorithms.Transformer method), 70
reconstruct_variable() (ufl.algorithms.transformer.Transformer method), 68
recursive_chain() (in module ufl.utils.sequences), 94
recursive_expr_equals() (in module ufl.exprequals), 136
reference_cell_volume() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55
reference_curl() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
reference_div() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
reference_facet_volume() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55

reference_grad() (ufl.algorithms.apply_derivatives.DerivativeRuleset method), 48	ReferenceGrad	(class in ufl.algorithms.apply_derivatives), 51	in
reference_grad() (ufl.algorithms.apply_derivatives.Gateaux method), 48	ReferenceGrad	(class in ufl.classes), 104	
reference_grad() (ufl.algorithms.apply_derivatives.GradRule method), 50	ReferenceNormal	(class in ufl.geometry), 145	
reference_grad() (ufl.algorithms.apply_derivatives.Reference method), 51	ReferenceValue	(class in ufl.classes), 118	
	GradRule	(class in ufl.referencevalue), 157	
		(in module ufl.finiteelement.elementlist), 80	
reference_grad() (ufl.algorithms.apply_derivatives.Variable method), 51	Register_element	(in module ufl), 175	module
		register_element() (in module ufl), 175	module
reference_grad() (ufl.algorithms.change_to_reference.NEW method), 55	RefFiniteElement	(in module ufl.finiteelement.elementlist), 80	module
		register_element2() (in module ufl), 175	module
reference_grad() (ufl.algorithms.change_to_reference.OLD method), 56	RefFiniteElement	(in module ufl.finiteelement.elementlist), 80	module
		register_integral_type() (in module ufl), 184	module
reference_grad() (ufl.algorithms.check_arities.ArityChecker method), 57	register_integral_type	(in module ufl.measure), 151	
		relabel() (in module ufl), 177	
reference_grad() (ufl.algorithms.estimate_degrees.SumDegree method), 62	relabel	(in module ufl.tensors), 161	module
		remove_indices() (in module ufl), 161	module
reference_value() (ufl.algorithms.apply_derivatives.Gateaux method), 48	ruleset_combination_utils	(in module ufl.algorithms), 146	module
		renumber_indices() (in module ufl), 146	module
reference_value() (ufl.algorithms.apply_derivatives.GradRuleset method), 50	ruleset_renumbering	(in module ufl.algorithms.renumbering), 67	module
		replace() (in module ufl), 184	module
reference_value() (ufl.algorithms.apply_derivatives.Reference method), 51	replace	(in module ufl.algorithms.replace), 67	module
		replace() (in module ufl.algorithms.replace), 67	module
reference_value() (ufl.algorithms.apply_derivatives.Variable method), 51	Replace_include_statements	(in module ufl.algorithms.formfiles), 63	module
		ufl.algorithms.formfiles), 63	module
reference_value() (ufl.algorithms.apply_restrictions.Restriction method), 55	replace_integral_domains	(in module ufl), 184	module
		replace_integral_domains() (in module ufl.form), 138	module
reference_value() (ufl.algorithms.check_arities.ArityCheck method), 57	Replacer	(class in ufl.algorithms.replace), 67	module
		Replacer (class in ufl.algorithms.replace), 67	module
reference_value() (ufl.algorithms.estimate_degrees.SumDegree method), 62	ReprLabeller	(class in ufl.formatting.ufl2dot), 89	module
		ReprLabeller (class in ufl.formatting.ufl2dot), 89	module
reference_value_shape() (ufl.classes.FiniteElementBase method), 119	restricted	(in module ufl.algorithms.apply_function_pullbacks), 52	module
		Restricted (class in ufl.classes), 112	module
reference_value_shape() (ufl.finiteelement.finiteelementbase method), 82	restricted	(in module ufl.restriction), 157	module
		restricted() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50	module
reference_value_shape() (ufl.FiniteElementBase method), 171	restricted	(ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54	module
reference_value_size() (ufl.classes.FiniteElementBase method), 120	restricted	(ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55	module
reference_value_size() (ufl.finiteelement.finiteelementbase method), 82	restricted	(ufl.algorithms.change_to_reference.NEWChangeToReferenceC method), 55	module
reference_value_size() (ufl.FiniteElementBase method), 171	restricted	(ufl.algorithms.check_restrictions.RestrictionChecker method), 57	module
ReferenceCellVolume (class in ufl.classes), 105	restricted_sub_elements	(ufl.classes.RestrictedElement method), 122	module
ReferenceCellVolume (class in ufl.geometry), 145	restricted_sub_elements	(ufl.finiteelement.restrictedelement.RestrictedElement method), 85	module
ReferenceCurl (class in ufl.classes), 115	restricted_sub_elements	(ufl.RestrictedElement method), 173	module
ReferenceCurl (class in ufl.differentiation), 133	RestrictedElement	(class in ufl), 173	module
ReferenceDiv (class in ufl.classes), 114	RestrictedElement	(class in ufl.classes), 122	module
ReferenceDiv (class in ufl.differentiation), 133			
ReferenceFacetVolume (class in ufl.classes), 105			
ReferenceFacetVolume (class in ufl.geometry), 145			
ReferenceGrad (class in ufl.classes), 114			
ReferenceGrad (class in ufl.differentiation), 133			

RestrictedElement (class in `ufl.finiteelement.restrictedelement`), 85
restriction_domain() (ufl.classes.RestrictedElement method), 122
restriction_domain() (ufl.finiteelement.restrictedelement.RestrictedElement method), 85
restriction_domain() (ufl.RestrictedElement method), 173
RestrictionChecker (class in `ufl.algorithms.check_restrictions`), 57
RestrictionPropagator (class in `ufl.algorithms.apply_restrictions`), 54
reuse() (ufl.algorithms.Transformer method), 70
reuse() (ufl.algorithms.transformer.Transformer method), 68
reuse_if_possible() (ufl.algorithms.Transformer method), 70
reuse_if_possible() (ufl.algorithms.transformer.Transformer method), 68
reuse_if_unouched() (ufl.algorithms.MultiFunction method), 71
reuse_if_unouched() (ufl.algorithms.Transformer method), 71
reuse_if_unouched() (ufl.algorithms.transformer.Transformer method), 68
reuse_if_unouched() (ufl.corealg.multipfunction.MultiFunction method), 78
reuse_variable() (ufl.algorithms.Transformer method), 71
reuse_variable() (ufl.algorithms.transformer.Transformer method), 69
ReuseTransformer (class in `ufl.algorithms`), 70
ReuseTransformer (class in `ufl.algorithms.transformer`), 68
rhs() (in module `ufl`), 184
rhs() (in module `ufl.formoperators`), 139
rot() (in module `ufl`), 181
rot() (in module `ufloperators`), 155

S

scalar_value() (ufl.algorithms.expand_indices.IndexExpander method), 63
scalar_value() (ufl.formatting.uf2dot.CompactLabeller method), 88
scalar_value() (ufl.formatting.uf2latex.Expression2LatexHandler method), 91
ScalarValue (class in `ufl.classes`), 107
ScalarValue (class in `ufl.constantvalue`), 132
section() (in module `ufl.formatting.latextools`), 87
sensitivity_rhs() (in module `ufl`), 185
sensitivity_rhs() (in module `ufl.formoperators`), 139
set_handler() (ufl.log.Logger method), 148
set_indent() (ufl.log.Logger method), 148
set_level() (ufl.log.Logger method), 148
set_list_item() (in module `ufl.formoperators`), 139
set_prefix() (ufl.log.Logger method), 148

in set_trait() (in module `ufl.core.ufl_type`), 77
shape() (in module `ufl`), 178
shape() (in module `ufl.operators`), 155
shape_to_strides() (in module `ufl.utils.indexflattening`),
shortstr() (ufl.BrokenElement method), 175
shortstr() (ufl.classes.BrokenElement method), 123
shortstr() (ufl.classes.EnrichedElement method), 121
shortstr() (ufl.classes.FiniteElement method), 120
shortstr() (ufl.classes.HCurlElement method), 123
shortstr() (ufl.classes.HDivElement method), 123
shortstr() (ufl.classes.MixedElement method), 121
shortstr() (ufl.classes.NodalEnrichedElement method),
122
shortstr() (ufl.classes.RestrictedElement method), 122
shortstr() (ufl.classes.TensorElement method), 121
shortstr() (ufl.classes.TensorProductElement method),
123
shortstr() (ufl.classes.VectorElement method), 121
shortstr() (ufl.EnrichedElement method), 173
shortstr() (ufl.FiniteElement method), 171
shortstr() (ufl.finiteelement.brokenelement.BrokenElement method), 79
shortstr() (ufl.finiteelement.enrichedelement.EnrichedElement method), 80
shortstr() (ufl.finiteelement.enrichedelement.NodalEnrichedElement method), 81
shortstr() (ufl.finiteelement.finiteelement.FiniteElement method), 81
shortstr() (ufl.finiteelement.hdivcurl.HCurlElement method), 83
shortstr() (ufl.finiteelement.hdivcurl.HDivElement method), 83
shortstr() (ufl.finiteelement.mixedelement.MixedElement method), 84
shortstr() (ufl.finiteelement.mixedelement.TensorElement method), 84
shortstr() (ufl.finiteelement.mixedelement.VectorElement method), 84
shortstr() (ufl.finiteelement.restrictedelement.RestrictedElement method), 85
shortstr() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 85
shortstr() (ufl.HCurlElement method), 174
shortstr() (ufl.HDivElement method), 174
shortstr() (ufl.MixedElement method), 172
shortstr() (ufl.NodalEnrichedElement method), 173
shortstr() (ufl.RestrictedElement method), 173
shortstr() (ufl.TensorElement method), 172
shortstr() (ufl.TensorProductElement method), 174
shortstr() (ufl.VectorElement method), 172
show_elements() (in module `ufl`), 175
show_elements() (in module `ufl.finiteelement.elementlist`), 80

side() (ufl.classes.Restricted method), 112
 side() (ufl.restriction.Restricted method), 158
 sign() (in module ufl), 180
 sign() (in module ufl.operators), 155
 signature() (ufl.classes.Form method), 127
 signature() (ufl.Form method), 182
 signature() (ufl.form.Form method), 137
 simplex() (in module ufl.cell), 99
 Sin (class in ufl.classes), 117
 Sin (class in ufl.mathfunctions), 150
 sin() (in module ufl), 179
 sin() (in module ufl.operators), 155
 sin() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 sin() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91
 Sinh (class in ufl.classes), 117
 Sinh (class in ufl.mathfunctions), 150
 sinh() (in module ufl), 179
 sinh() (in module ufl.operators), 155
 sinh() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 sinh() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91
 Skew (class in ufl.classes), 112
 Skew (class in ufl.tensoralgebra), 159
 skew() (in module ufl), 178
 skew() (in module ufl.operators), 155
 skew() (ufl.algorithms.apply_algebra_lowering.LowerCompsplitAlgebra module ufl), 176
 skew() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 skew() (ufl.formatting.ufl2dot.CompactLabeller method), 88
 skew() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91
 slice_dict() (in module ufl.utils.dicts), 93
 sobolev_space() (ufl.classes.FiniteElement method), 120
 sobolev_space() (ufl.classes.HCurlElement method), 123
 sobolev_space() (ufl.classes.HDivElement method), 123
 sobolev_space() (ufl.classes.TensorProductElement method), 123
 sobolev_space() (ufl.FiniteElement method), 171
 sobolev_space() (ufl.finiteelement.enrichedelement.EnrichedFiniteElement method), 81
 sobolev_space() (ufl.finiteelement.finiteelement.FiniteElement method), 81
 sobolev_space() (ufl.finiteelement.hdivcurl.HCurlElement method), 83
 sobolev_space() (ufl.finiteelement.hdivcurl.HDivElement method), 83
 sobolev_space() (ufl.finiteelement.tensorproductelement.TensorProductCell method), 98
 sobolev_space() (ufl.HCurlElement method), 174
 sobolev_space() (ufl.HDivElement method), 174
 sobolev_space() (ufl.TensorProductElement method), 174
 SobolevSpace (class in ufl.sobolevspacespace), 158
 some_key() (in module ufl.utils.dicts), 93
 sort_domains() (in module ufl.domain), 135
 sort_elements() (in module ufl.algorithms), 69
 sort_elements() (in module ufl.algorithms.analysis), 46
 sorted_by_count() (in module ufl.utils.sorting), 94
 sorted_by_key() (in module ufl.utils.sorting), 94
 sorted_by_tuple_key() (in module ufl.utils.sorting), 94
 sorted_by_ufl_id() (in module ufl.utils.sorting), 94
 sorted_expr() (in module ufl.sorting), 158
 sorted_expr_sum() (in module ufl.sorting), 158
 spatial_coordinate() (ufl.algorithms.apply_derivatives.GradRuleset method), 50
 spatial_coordinate() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51
 spatial_coordinate() (ufl.algorithms.apply_geometry_lowering.GeometryLowering method), 53
 spatial_coordinate() (ufl.algorithms.apply_restrictions.DefaultRestrictionApRuleset method), 54
 spatial_coordinate() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 spatial_derivative() (ufl.formatting.graph.StringDependencyDefiner method), 86
 SpatialCoordinate (class in ufl), 168
 SpatialCoordinate (class in ufl.classes), 101
 SpatialCoordinate (class in ufl.geometry), 145
 split() (ufl.split_functions), 158
 split() (ufl.algorithms.FormSplitter method), 72
 split() (ufl.algorithms.forms splitter.FormSplitter method), 64
 split_dict() (in module ufl.utils.dicts), 93
 Sqrt (class in ufl.classes), 116
 Sqrt (class in ufl.mathfunctions), 150
 sqrt() (in module ufl), 178
 sqrt() (in module ufl.operators), 155
 sqrt() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 sqrt() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91
 sstr() (in module ufl.utils.formatting), 93
 StackDict (class in ufl.utils.stack), 95
 setting_set_criteria() (in module ufl.formatting.graph), 87
 StringDependencyDefiner (class in ufl.formatting.graph), 86
 strip_variables() (in module ufl.algorithms), 72
 strip_variables() (in module ufl.algorithms.transformer), 69
 sub_ProductCellTensorProductCell method), 98
 sub_cells() (ufl.classes.TensorProductCell method), 119
 sub_cells() (ufl.TensorProductCell method), 167

sub_element() (ufl.classes.RestrictedElement method), 122
sub_element() (ufl.finiteelement.restrictedelement.RestrictedElement method), 85
sub_element() (ufl.RestrictedElement method), 173
sub_elements() (ufl.classes.FiniteElementBase method), 120
sub_elements() (ufl.classes.MixedElement method), 121
sub_elements() (ufl.classes.RestrictedElement method), 122
sub_elements() (ufl.classes.TensorProductElement method), 123
sub_elements() (ufl.finiteelement.finiteelementbase.FiniteElement method), 82
sub_elements() (ufl.finiteelement.mixedelement.MixedElement method), 84
sub_elements() (ufl.finiteelement.restrictedelement.RestrictedElement method), 85
sub_elements() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 86
sub_elements() (ufl.FiniteElementBase method), 171
sub_elements() (ufl.MixedElement method), 172
sub_elements() (ufl.RestrictedElement method), 173
sub_elements() (ufl.TensorProductElement method), 174
sub_elements_with_mappings() (in module ufl.algorithms.apply_function_pullbacks), 52
sub_measures() (ufl.classes.MeasureProduct method), 126
sub_measures() (ufl.measure.MeasureProduct method), 151
subdict() (in module ufl.utils_dicts), 93
subdomain_data() (ufl.classes.Form method), 127
subdomain_data() (ufl.classes.Integral method), 127
subdomain_data() (ufl.classes.Measure method), 126
subdomain_data() (ufl.Form method), 182
subdomain_data() (ufl.form.Form method), 137
subdomain_data() (ufl.Integral method), 183
subdomain_data() (ufl.integral.Integral method), 147
subdomain_data() (ufl.Measure method), 183
subdomain_data() (ufl.measure.Measure method), 151
subdomain_id (ufl.algorithms.domain_analysis.IntegralDatasystem attribute), 58
subdomain_id() (ufl.classes.Integral method), 127
subdomain_id() (ufl.classes.Measure method), 126
subdomain_id() (ufl.Integral method), 183
subdomain_id() (ufl.integral.Integral method), 147
subdomain_id() (ufl.Measure method), 183
subdomain_id() (ufl.measure.Measure method), 151
subsection() (in module ufl.formatting.latextools), 87
subsubsection() (in module ufl.formatting.latextools), 87
Sum (class in ufl.algebra), 96
Sum (class in ufl.classes), 109
sum() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
sum() (ufl.Element (ufl.algorithms.check_arities.ArityChecker method), 57
sum() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
sum() (ufl.algorithms.formtransformations.PartExtractor method), 65
sum() (ufl.formatting.ufl2dot.CompactLabeller method), 88
sum() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91
SumDegreeEstimator (class in ufl.algorithms.estimate_degrees), 59
Sym (class in ufl.classes), 112
Sym (class in ufl.tensoralgebra), 160
sym() (in module ufl.operators), 155
sym() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
sym() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
sym() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91
symmetry() (ufl.classes.FiniteElementBase method), 120
symmetry() (ufl.classes.MixedElement method), 121
symmetry() (ufl.classes.RestrictedElement method), 122
symmetry() (ufl.classes.TensorElement method), 121
symmetry() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
symmetry() (ufl.finiteelement.mixedelement.MixedElement method), 84
symmetry() (ufl.finiteelement.mixedelement.TensorElement method), 84
symmetry() (ufl.finiteelement.restrictedelement.RestrictedElement method), 85
symmetry() (ufl.FiniteElementBase method), 171
symmetry() (ufl.MixedElement method), 172
symmetry() (ufl.RestrictedElement method), 173
symmetry() (ufl.TensorElement method), 172
system() (in module ufl), 185
system() (in module ufl.formoperators), 139

T

T (ufl.classes.Expr attribute), 100
T (ufl.core.expr.Expr attribute), 74
Tan (class in ufl.classes), 117
Tan (class in ufl.mathfunctions), 150
tan() (in module ufl), 179
tan() (in module ufl.operators), 155
tan() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
tan() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91

Tanh (class in `ufl.classes`), 117
Tanh (class in `ufl.mathfunctions`), 150
`tanh()` (in module `ufl`), 179
`tanh()` (in module `ufl.operators`), 156
`tanh()` (`ufl.algorithms.apply_derivatives.GenericDerivativeRule` method), 50
`tanh()` (`ufl.formatting.ufl2latex.Expression2LatexHandler` method), 91
`tear()` (in module `ufl.algorithms.elementtransformations`), 59
`TensorConstant()` (in module `ufl`), 176
`TensorConstant()` (in module `ufl.coefficient`), 128
`TensorElement` (class in `ufl`), 172
`TensorElement` (class in `ufl.classes`), 121
`TensorElement` (class in `ufl.finiteelement.mixedelement`), 84
`TensorProductCell` (class in `ufl`), 167
`TensorProductCell` (class in `ufl.cell`), 98
`TensorProductCell` (class in `ufl.classes`), 118
`TensorProductElement` (class in `ufl`), 174
`TensorProductElement` (class in `ufl.classes`), 122
`TensorProductElement` (class in `ufl.finiteelement.tensorproductelement`), 85
`TensorProductFunctionSpace` (class in `ufl.classes`), 125
`TensorProductFunctionSpace` (class in `ufl.functionspace`), 140
`TensorProductMesh` (class in `ufl`), 168
`TensorProductMesh` (class in `ufl.classes`), 124
`TensorProductMesh` (class in `ufl.domain`), 134
`Terminal` (class in `ufl.classes`), 100
`Terminal` (class in `ufl.core.terminal`), 76
`terminal()` (`ufl.algorithms.apply_derivatives.DerivativeRule` method), 48
`terminal()` (`ufl.algorithms.apply_function_pullbacks.FunctionRule` method), 52
`terminal()` (`ufl.algorithms.apply_geometry_lowering.GeometryLowering` method), 53
`terminal()` (`ufl.algorithms.apply_restrictions.DefaultRestriction` method), 54
`terminal()` (`ufl.algorithms.apply_restrictions.RestrictionProp` method), 55
`terminal()` (`ufl.algorithms.change_to_reference.NEWChange` method), 55
`terminal()` (`ufl.algorithms.change_to_reference.OLDChange` method), 56
`terminal()` (`ufl.algorithms.check_arities.ArityChecker` method), 57
`terminal()` (`ufl.algorithms.expand_indices.IndexExpander` method), 63
`terminal()` (`ufl.algorithms.formtransformations.PartExtractor` method), 65
`terminal()` (`ufl.algorithms.replace.Replacer` method), 67
`terminal()` (`ufl.algorithms.ReuseTransformer` method), 70
`terminal()` (`ufl.algorithms.Transformer` method), 71
`terminal()` (`ufl.algorithms.transformer.CopyTransformer` method), 68
`terminal()` (`ufl.algorithms.transformer.ReuseTransformer` method), 68
`terminal()` (`ufl.algorithms.transformer.Transformer` method), 69
`terminal()` (`ufl.formatting.ufl2dot.ReprLabeller` method), 89
`testdocument()` (in module `ufl.formatting.latextools`), 87
`TestFunction()` (in module `ufl`), 175
`TestFunction()` (in module `ufl.argument`), 97
`TestFunction()` (in module `ufl.classes`), 125
`TestFunctions()` (in module `ufl`), 176
`TestFunctions()` (in module `ufl.argument`), 97
`TestFunctions()` (in module `ufl.classes`), 125
`topological_dimension()` (`ufl.AbstractCell` method), 166
`topological_dimension()` (`ufl.AbstractDomain` method), 167
`topological_dimension()` (`ufl.cell.AbstractCell` method), 98
`topological_dimension()` (`ufl.classes.AbstractCell` method), 118
`topological_dimension()` (`ufl.classes.AbstractDomain` method), 124
`topological_dimension()` (`ufl.domain.AbstractDomain` method), 134
`topological_sorting()` (in module `ufl.utils.sorting`), 95
`tr()` (in module `ufl`), 178
`tr()` (in module `ufl.operators`), 156
`Trace` (class in `ufl.classes`), 111
`Trace` (class in `ufl.tensoralgebra`), 160
`Diagonal` (`ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra` method), 47
`Diagonal` (`ufl.algorithms.estimate_degrees.SumDegreeEstimator` method), 62
`GeometryLowering` (`ufl2dot.CompactLabeller` method), 88
`DefaultRestriction` (`ufl.formatting.ufl2latex.Expression2LatexHandler` method), 91
`Transformer` (class in `ufl.algorithms`), 70
`Transformer` (class in `ufl.algorithms.Transformer`), 68
`ToRho` (class in `ufl`), 178
`transpose()` (in module `ufl.operators`), 156
`TrResponse` (class in `ufl.classes`), 110
`Transposed` (class in `ufl.tensoralgebra`), 160
`transposed()` (`ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra` method), 47
`transposed()` (`ufl.algorithms.estimate_degrees.SumDegreeEstimator` method), 62
`transposed()` (`ufl.formatting.ufl2dot.CompactLabeller` method), 88
`transposed()` (`ufl.formatting.ufl2latex.Expression2LatexHandler` method), 91
`traverse_terminals()` (in module `ufl.corealg.traversal`), 79

traverse_unique_terminals() (in module ufl.corealg.traversal), 79
tree_format() (in module ufl.algorithms), 73
tree_format() (in module ufl.formatting.printing), 87
TrialFunction() (in module ufl), 175
TrialFunction() (in module ufl.argument), 97
TrialFunction() (in module ufl.classes), 125
TrialFunctions() (in module ufl), 176
TrialFunctions() (in module ufl.argument), 97
TrialFunctions() (in module ufl.classes), 125
tstr() (in module ufl.utils.formatting), 93

U

ufl (module), 162
ufl.algebra (module), 95
ufl.algorithms (module), 69
ufl.algorithms.ad (module), 46
ufl.algorithms.analysis (module), 46
ufl.algorithms.apply_algebra_lowering (module), 47
ufl.algorithms.apply_derivatives (module), 48
ufl.algorithms.apply_function_pullbacks (module), 52
ufl.algorithms.apply_geometry_lowering (module), 52
ufl.algorithms.apply_integral_scaling (module), 53
ufl.algorithms.apply_restrictions (module), 53
ufl.algorithms.change_to_reference (module), 55
ufl.algorithms.check_arities (module), 56
ufl.algorithms.check_restrictions (module), 57
ufl.algorithms.checks (module), 57
ufl.algorithms.compute_form_data (module), 58
ufl.algorithms.domain_analysis (module), 58
ufl.algorithms.elementtransformations (module), 59
ufl.algorithms.estimate_degrees (module), 59
ufl.algorithms.expand_compounds (module), 62
ufl.algorithms.expand_indices (module), 62
ufl.algorithms.formdata (module), 63
ufl.algorithms.formfiles (module), 63
ufl.algorithms.forms splitter (module), 64
ufl.algorithms.formtransformations (module), 64
ufl.algorithms.map_integrands (module), 66
ufl.algorithms.multifunction (module), 66
ufl.algorithms.renumbering (module), 66
ufl.algorithms.replace (module), 67
ufl.algorithms.signature (module), 67
ufl.algorithms.transformer (module), 68
ufl.algorithms.traversal (module), 69
ufl.argument (module), 96
ufl.assertions (module), 97
ufl.cell (module), 97
ufl.checks (module), 99
ufl.classes (module), 99
ufl.coefficient (module), 128
ufl.compound_expressions (module), 129
ufl.conditional (module), 129
ufl.constantvalue (module), 131

module ufl.core (module), 78
ufl.core.compute_expr_hash (module), 73
ufl.core.expr (module), 73
ufl.core.multiindex (module), 74
ufl.core.operator (module), 75
ufl.core.terminal (module), 76
ufl.core.ufl_id (module), 76
ufl.core.ufl_type (module), 77
ufl.corealg (module), 79
ufl.corealg.map_dag (module), 78
ufl.corealg.multifunction (module), 78
ufl.corealg.traversal (module), 79
ufl.differentiation (module), 132
ufl.domain (module), 134
ufl.equation (module), 135
ufl.exprcontainers (module), 135
ufl.exprequals (module), 136
ufl.exproperators (module), 136
ufl.finiteelement (module), 86
ufl.finiteelement.brokenelement (module), 79
ufl.finiteelement.elementlist (module), 80
ufl.finiteelement.enrichedelement (module), 80
ufl.finiteelement.facetelement (module), 81
ufl.finiteelement.finiteelement (module), 81
ufl.finiteelement.finiteelementbase (module), 81
ufl.finiteelement.hdivcurl (module), 83
ufl.finiteelement.interiorelement (module), 83
ufl.finiteelement.mixedelement (module), 83
ufl.finiteelement.restrictedelement (module), 85
ufl.finiteelement.tensorproductelement (module), 85
ufl.form (module), 137
ufl.formatting (module), 92
ufl.formatting.graph (module), 86
ufl.formatting.latextools (module), 87
ufl.formatting.printing (module), 87
ufl.formatting.ufl2dot (module), 88
ufl.formatting.ufl2latex (module), 89
ufl.formoperators (module), 138
ufl.functionspace (module), 140
ufl.geometry (module), 140
ufl.index_combination_utils (module), 146
ufl.indexed (module), 146
ufl.indexsum (module), 147
ufl.integral (module), 147
ufl.log (module), 147
ufl.mathfunctions (module), 149
ufl.measure (module), 150
ufl.objects (module), 151
ufl.operators (module), 152
ufl.permutation (module), 156
ufl.precedence (module), 156
ufl.protocols (module), 157
ufl.referencevalue (module), 157
ufl.restriction (module), 157

ufl.sobolevspace (module), 158
 ufl.sorting (module), 158
 ufl.split_functions (module), 158
 ufl.tensoralgebra (module), 158
 ufl.tensors (module), 160
 ufl.utils (module), 95
 ufl.utils.counted (module), 92
 ufl.utils.derivativetuples (module), 92
 ufl.utils.dicts (module), 92
 ufl.utils.formatting (module), 93
 ufl.utils.indexflattening (module), 93
 ufl.utils.py23 (module), 94
 ufl.utils.sequences (module), 94
 ufl.utils.sorting (module), 94
 ufl.utils.stacks (module), 95
 ufl.utils.ufltypedicts (module), 95
 ufl.variable (module), 162
 ufl2dot() (in module ufl.formatting.ufl2dot), 89
 ufl2latex() (in module ufl.algorithms), 72
 ufl2latex() (in module ufl.formatting.ufl2latex), 91
 ufl2ufl() (in module ufl.algorithms.transformer), 69
 ufl2uflcopy() (in module ufl.algorithms.transformer), 69
 ufl_assert() (in module ufl.assertions), 97
 ufl_cargo() (ufl.classes.Mesh method), 124
 ufl_cargo() (ufl.domain.Mesh method), 134
 ufl_cargo() (ufl.Mesh method), 167
 ufl_cell() (ufl.classes.Form method), 127
 ufl_cell() (ufl.classes.Mesh method), 124
 ufl_cell() (ufl.classes.MeshView method), 124
 ufl_cell() (ufl.classes.TensorProductMesh method), 124
 ufl_cell() (ufl.domain.Mesh method), 134
 ufl_cell() (ufl.domain.MeshView method), 134
 ufl_cell() (ufl.domain.TensorProductMesh method), 135
 ufl_cell() (ufl.Form method), 182
 ufl_cell() (ufl.form.Form method), 137
 ufl_cell() (ufl.Mesh method), 167
 ufl_cell() (ufl.MeshView method), 168
 ufl_cell() (ufl.TensorProductMesh method), 168
 ufl_coordinate_element() (ufl.classes.Mesh method), 124
 ufl_coordinate_element()
 (ufl.classes.TensorProductMesh method), 124
 ufl_coordinate_element() (ufl.domain.Mesh method), 134
 ufl_coordinate_element()
 (ufl.domain.TensorProductMesh method), 135
 ufl_coordinate_element() (ufl.Mesh method), 167
 ufl_coordinate_element() (ufl.TensorProductMesh method), 168
 ufl_disable_profiling() (ufl.classes.Expr static method), 100
 ufl_disable_profiling() (ufl.core.expr.Expr static method), 74
 ufl_domain() (ufl.Argument method), 175
 ufl_domain() (ufl.argument.Argument method), 96
 ufl_domain() (ufl.classes.Argument method), 108
 ufl_domain() (ufl.classes.Coefficient method), 109
 ufl_domain() (ufl.classes.Expr method), 100
 ufl_domain() (ufl.classes.Form method), 127
 ufl_domain() (ufl.classes.FunctionSpace method), 124
 ufl_domain() (ufl.classes.Integral method), 127
 ufl_domain() (ufl.classes.Measure method), 126
 ufl_domain() (ufl.classes.MixedFunctionSpace method), 125
 ufl_domain() (ufl.Coefficient method), 176
 ufl_domain() (ufl.coefficient.Coefficient method), 128
 ufl_domain() (ufl.core.expr.Expr method), 74
 ufl_domain() (ufl.Form method), 182
 ufl_domain() (ufl.form.Form method), 137
 ufl_domain() (ufl.FunctionSpace method), 175
 ufl_domain() (ufl.functionspace.FunctionSpace method), 140
 ufl_domain() (ufl.functionspace.MixedFunctionSpace method), 140
 ufl_domain() (ufl.Integral method), 183
 ufl_domain() (ufl.integral.Integral method), 147
 ufl_domain() (ufl.Measure method), 183
 ufl_domain() (ufl.measure.Measure method), 151
 ufl_domains() (ufl.Argument method), 175
 ufl_domains() (ufl.argument.Argument method), 97
 ufl_domains() (ufl.classes.Argument method), 108
 ufl_domains() (ufl.classes.Coefficient method), 109
 ufl_domains() (ufl.classes.ConstantValue method), 107
 ufl_domains() (ufl.classes.Expr method), 100
 ufl_domains() (ufl.classes.ExprMapping method), 113
 ufl_domains() (ufl.classes.Form method), 128
 ufl_domains() (ufl.classes.FunctionSpace method), 124
 ufl_domains() (ufl.classes.GeometricQuantity method), 101
 ufl_domains() (ufl.classes.Label method), 109
 ufl_domains() (ufl.classes.MixedFunctionSpace method), 125
 ufl_domains() (ufl.classes.MultiIndex method), 106
 ufl_domains() (ufl.classes.Terminal method), 100
 ufl_domains() (ufl.classes.Variable method), 109
 ufl_domains() (ufl.Coefficient method), 176
 ufl_domains() (ufl.coefficient.Coefficient method), 128
 ufl_domains() (ufl.constantvalue.ConstantValue method), 131
 ufl_domains() (ufl.core.expr.Expr method), 74
 ufl_domains() (ufl.core.multiindex.MultiIndex method), 75
 ufl_domains() (ufl.core.terminal.Terminal method), 76
 ufl_domains() (ufl.exprcontainers.ExprMapping method), 136
 ufl_domains() (ufl.Form method), 182
 ufl_domains() (ufl.form.Form method), 137
 ufl_domains() (ufl.FunctionSpace method), 175

ufl_domains() (ufl.functionspace.FunctionSpace method), 140
ufl_domains() (ufl.functionspace.MixedFunctionSpace method), 140
ufl_domains() (ufl.geometry.GeometricQuantity method), 144
ufl_domains() (ufl.variable.Label method), 162
ufl_domains() (ufl.variable.Variable method), 162
ufl_element() (ufl.Argument method), 175
ufl_element() (ufl.argument.Argument method), 97
ufl_element() (ufl.classes.Argument method), 108
ufl_element() (ufl.classes.Coefficient method), 109
ufl_element() (ufl.classes.FunctionSpace method), 124
ufl_element() (ufl.classes.MixedFunctionSpace method), 125
ufl_element() (ufl.Coefficient method), 176
ufl_element() (ufl.coefficient.Coefficient method), 128
ufl_element() (ufl.FunctionSpace method), 175
ufl_element() (ufl.functionspace.FunctionSpace method), 140
ufl_element() (ufl.functionspace.MixedFunctionSpace method), 140
ufl_enable_profiling() (ufl.classes.Expr static method), 100
ufl_enable_profiling() (ufl.core.expr.Expr static method), 74
ufl_err_str() (in module ufl.core.expr), 74
ufl_free_indices (ufl.algebra.Abs attribute), 95
ufl_free_indices (ufl.algebra.Division attribute), 96
ufl_free_indices (ufl.algebra.Power attribute), 96
ufl_free_indices (ufl.algebra.Product attribute), 96
ufl_free_indices (ufl.algebra.Sum attribute), 96
ufl_free_indices (ufl.classes.Abs attribute), 110
ufl_free_indices (ufl.classes.Atan2 attribute), 117
ufl_free_indices (ufl.classes.BesselFunction attribute), 117
ufl_free_indices (ufl.classes.CellAvg attribute), 112
ufl_free_indices (ufl.classes.CoefficientDerivative attribute), 113
ufl_free_indices (ufl.classes.Cofactor attribute), 111
ufl_free_indices (ufl.classes.ComponentTensor attribute), 108
ufl_free_indices (ufl.classes.Condition attribute), 115
ufl_free_indices (ufl.classes.Conditional attribute), 116
ufl_free_indices (ufl.classes.Cross attribute), 111
ufl_free_indices (ufl.classes.Curl attribute), 115
ufl_free_indices (ufl.classes.Determinant attribute), 111
ufl_free_indices (ufl.classes.Deviatoric attribute), 112
ufl_free_indices (ufl.classes.Div attribute), 114
ufl_free_indices (ufl.classes.Division attribute), 110
ufl_free_indices (ufl.classes.Dot attribute), 111
ufl_free_indices (ufl.classes.ExprList attribute), 113
ufl_free_indices (ufl.classes.ExprMapping attribute), 113
ufl_free_indices (ufl.classes.FacetAvg attribute), 113
ufl_free_indices (ufl.classes.Grad attribute), 114
ufl_free_indices (ufl.classes.Indexed attribute), 108
ufl_free_indices (ufl.classes.IndexSum attribute), 112
ufl_free_indices (ufl.classes.Inner attribute), 111
ufl_free_indices (ufl.classes.Inverse attribute), 111
ufl_free_indices (ufl.classes.Label attribute), 109
ufl_free_indices (ufl.classes.ListTensor attribute), 108
ufl_free_indices (ufl.classes.MathFunction attribute), 116
ufl_free_indices (ufl.classes.MaxValue attribute), 116
ufl_free_indices (ufl.classes.MinValue attribute), 116
ufl_free_indices (ufl.classes.MultiIndex attribute), 106
ufl_free_indices (ufl.classes.NablaDiv attribute), 114
ufl_free_indices (ufl.classes.NablaGrad attribute), 114
ufl_free_indices (ufl.classes.Outer attribute), 111
ufl_free_indices (ufl.classes.Power attribute), 110
ufl_free_indices (ufl.classes.Product attribute), 110
ufl_free_indices (ufl.classes.ReferenceCurl attribute), 115
ufl_free_indices (ufl.classes.ReferenceDiv attribute), 114
ufl_free_indices (ufl.classes.ReferenceGrad attribute), 114
ufl_free_indices (ufl.classes.ReferenceValue attribute), 118
ufl_free_indices (ufl.classes.Restricted attribute), 112
ufl_free_indices (ufl.classes.ScalarValue attribute), 107
ufl_free_indices (ufl.classes.Skew attribute), 112
ufl_free_indices (ufl.classes.Sum attribute), 110
ufl_free_indices (ufl.classes.Sym attribute), 112
ufl_free_indices (ufl.classes.Terminal attribute), 100
ufl_free_indices (ufl.classes.Trace attribute), 111
ufl_free_indices (ufl.classes.Transposed attribute), 110
ufl_free_indices (ufl.classes.Variable attribute), 109
ufl_free_indices (ufl.classes.VariableDerivative attribute), 113
ufl_free_indices (ufl.classes.Zero attribute), 107
ufl_free_indices (ufl.conditional.Condition attribute), 130
ufl_free_indices (ufl.conditional.Conditional attribute), 130
ufl_free_indices (ufl.conditional.MaxValue attribute), 130
ufl_free_indices (ufl.conditional.MinValue attribute), 131
ufl_free_indices (ufl.constantvalue.ScalarValue attribute), 132
ufl_free_indices (ufl.constantvalue.Zero attribute), 132
ufl_free_indices (ufl.core.multiindex.MultiIndex attribute), 75
ufl_free_indices (ufl.core.terminal.Terminal attribute), 76
ufl_free_indices (ufl.differentiation.CoefficientDerivative attribute), 132
ufl_free_indices (ufl.differentiation.Curl attribute), 132
ufl_free_indices (ufl.differentiation.Div attribute), 133
ufl_free_indices (ufl.differentiation.Grad attribute), 133
ufl_free_indices (ufl.differentiation.NablaDiv attribute), 133
ufl_free_indices (ufl.differentiation.NablaGrad attribute), 133

ufl_free_indices (ufl.differentiation.ReferenceCurl attribute), 133
 ufl_free_indices (ufl.differentiation.ReferenceDiv attribute), 133
 ufl_free_indices (ufl.differentiation.ReferenceGrad attribute), 134
 ufl_free_indices (ufl.differentiation.VariableDerivative attribute), 134
 ufl_free_indices (ufl.exprcontainers.ExprList attribute), 135
 ufl_free_indices (ufl.exprcontainers.ExprMapping attribute), 136
 ufl_free_indices (ufl.indexed.Indexed attribute), 146
 ufl_free_indices (ufl.indexsum.IndexSum attribute), 147
 ufl_free_indices (ufl.mathfunctions.Atan2 attribute), 149
 ufl_free_indices (ufl.mathfunctions.BesselFunction attribute), 149
 ufl_free_indices (ufl.mathfunctions.MathFunction attribute), 150
 ufl_free_indices (ufl.referencevalue.ReferenceValue attribute), 157
 ufl_free_indices (ufl.restriction.CellAvg attribute), 157
 ufl_free_indices (ufl.restriction.FacetAvg attribute), 157
 ufl_free_indices (ufl.restriction.Restricted attribute), 158
 ufl_free_indices (ufl.tensoralgebra.Cofactor attribute), 158
 ufl_free_indices (ufl.tensoralgebra.Cross attribute), 159
 ufl_free_indices (ufl.tensoralgebra.Determinant attribute), 159
 ufl_free_indices (ufl.tensoralgebra.Deviatoric attribute), 159
 ufl_free_indices (ufl.tensoralgebra.Dot attribute), 159
 ufl_free_indices (ufl.tensoralgebra.Inner attribute), 159
 ufl_free_indices (ufl.tensoralgebra.Inverse attribute), 159
 ufl_free_indices (ufl.tensoralgebra.Outer attribute), 159
 ufl_free_indices (ufl.tensoralgebra.Skew attribute), 160
 ufl_free_indices (ufl.tensoralgebra.Sym attribute), 160
 ufl_free_indices (ufl.tensoralgebra.Trace attribute), 160
 ufl_free_indices (ufl.tensoralgebra.Transposed attribute), 160
 ufl_free_indices (ufl.tensors.ComponentTensor attribute), 160
 ufl_free_indices (ufl.tensors.ListTensor attribute), 160
 ufl_free_indices (ufl.variable.Label attribute), 162
 ufl_free_indices (ufl.variable.Variable attribute), 162
 ufl_function_space() (ufl.Argument method), 175
 ufl_function_space() (ufl.argument.Argument method), 97
 ufl_function_space() (ufl.classes.Argument method), 108
 ufl_function_space() (ufl.classes.Coefficient method), 109
 ufl_function_space() (ufl.Coefficient method), 176
 ufl_function_space() (ufl.coefficient.Coefficient method), 128
 ufl_id() (ufl.classes.Mesh method), 124
 ufl_id() (ufl.classes.MeshView method), 124
 ufl_id() (ufl.classes.TensorProductMesh method), 124
 ufl_id() (ufl.domain.Mesh method), 134
 ufl_id() (ufl.domain.MeshView method), 134
 ufl_id() (ufl.domain.TensorProductMesh method), 135
 ufl_id() (ufl.Mesh method), 167
 ufl_id() (ufl.MeshView method), 168
 ufl_id() (ufl.TensorProductMesh method), 168
 ufl_index_dimensions (ufl.algebra.Abs attribute), 95
 ufl_index_dimensions (ufl.algebra.Division attribute), 96
 ufl_index_dimensions (ufl.algebra.Power attribute), 96
 ufl_index_dimensions (ufl.algebra.Product attribute), 96
 ufl_index_dimensions (ufl.algebra.Sum attribute), 96
 ufl_index_dimensions (ufl.classes.Abs attribute), 110
 ufl_index_dimensions (ufl.classes.Atan2 attribute), 117
 ufl_index_dimensions (ufl.classes.BesselFunction attribute), 117
 ufl_index_dimensions (ufl.classes.CellAvg attribute), 113
 ufl_index_dimensions (ufl.classes.CoefficientDerivative attribute), 113
 ufl_index_dimensions (ufl.classes.Cofactor attribute), 111
 ufl_index_dimensions (ufl.classes.ComponentTensor attribute), 108
 ufl_index_dimensions (ufl.classes.Condition attribute), 115
 ufl_index_dimensions (ufl.classes.Conditional attribute), 116
 ufl_index_dimensions (ufl.classes.Cross attribute), 111
 ufl_index_dimensions (ufl.classes.Curl attribute), 115
 ufl_index_dimensions (ufl.classes.Determinant attribute), 111
 ufl_index_dimensions (ufl.classes.Deviatoric attribute), 112
 ufl_index_dimensions (ufl.classes.Div attribute), 114
 ufl_index_dimensions (ufl.classes.Division attribute), 110
 ufl_index_dimensions (ufl.classes.Dot attribute), 111
 ufl_index_dimensions (ufl.classes.ExprList attribute), 113
 ufl_index_dimensions (ufl.classes.ExprMapping attribute), 113
 ufl_index_dimensions (ufl.classes.FacetAvg attribute), 113
 ufl_index_dimensions (ufl.classes.Grad attribute), 114
 ufl_index_dimensions (ufl.classes.Indexed attribute), 108
 ufl_index_dimensions (ufl.classes.IndexSum attribute), 112
 ufl_index_dimensions (ufl.classes.Inner attribute), 111
 ufl_index_dimensions (ufl.classes.Inverse attribute), 111
 ufl_index_dimensions (ufl.classes.Label attribute), 109
 ufl_index_dimensions (ufl.classes.ListTensor attribute), 108
 ufl_index_dimensions (ufl.classes.MathFunction attribute), 116

ufl_index_dimensions (ufl.classes.MaxValue attribute), 116
ufl_index_dimensions (ufl.classes.MinValue attribute), 116
ufl_index_dimensions (ufl.classes.MultiIndex attribute), 106
ufl_index_dimensions (ufl.classes.NablaDiv attribute), 114
ufl_index_dimensions (ufl.classes.NablaGrad attribute), 114
ufl_index_dimensions (ufl.classes.Outer attribute), 111
ufl_index_dimensions (ufl.classes.Power attribute), 110
ufl_index_dimensions (ufl.classes.Product attribute), 110
ufl_index_dimensions (ufl.classes.ReferenceCurl attribute), 115
ufl_index_dimensions (ufl.classes.ReferenceDiv attribute), 114
ufl_index_dimensions (ufl.classes.ReferenceGrad attribute), 114
ufl_index_dimensions (ufl.classes.ReferenceValue attribute), 118
ufl_index_dimensions (ufl.classes.Restricted attribute), 112
ufl_index_dimensions (ufl.classes.ScalarValue attribute), 107
ufl_index_dimensions (ufl.classes.Skew attribute), 112
ufl_index_dimensions (ufl.classes.Sum attribute), 110
ufl_index_dimensions (ufl.classes.Sym attribute), 112
ufl_index_dimensions (ufl.classes.Terminal attribute), 100
ufl_index_dimensions (ufl.classes.Trace attribute), 111
ufl_index_dimensions (ufl.classes.Transposed attribute), 110
ufl_index_dimensions (ufl.classes.Variable attribute), 109
ufl_index_dimensions (ufl.classes.VariableDerivative attribute), 114
ufl_index_dimensions (ufl.classes.Zero attribute), 107
ufl_index_dimensions (ufl.conditional.Condition attribute), 130
ufl_index_dimensions (ufl.conditional.Conditional attribute), 130
ufl_index_dimensions (ufl.conditional.MaxValue attribute), 130
ufl_index_dimensions (ufl.conditional.MinValue attribute), 131
ufl_index_dimensions (ufl.constantvalue.ScalarValue attribute), 132
ufl_index_dimensions (ufl.constantvalue.Zero attribute), 132
ufl_index_dimensions (ufl.core.multiindex.MultiIndex attribute), 75
ufl_index_dimensions (ufl.core.terminal.Terminal attribute), 76
ufl_index_dimensions (ufl.differentiation.CoefficientDerivative attribute), 132
ufl_index_dimensions (ufl.differentiation.Curl attribute), 132
ufl_index_dimensions (ufl.differentiation.Div attribute), 133
ufl_index_dimensions (ufl.differentiation.Grad attribute), 133
ufl_index_dimensions (ufl.differentiation.NablaDiv attribute), 133
ufl_index_dimensions (ufl.differentiation.NablaGrad attribute), 133
ufl_index_dimensions (ufl.differentiation.ReferenceCurl attribute), 133
ufl_index_dimensions (ufl.differentiation.ReferenceDiv attribute), 133
ufl_index_dimensions (ufl.differentiation.ReferenceGrad attribute), 134
ufl_index_dimensions (ufl.differentiation.VariableDerivative attribute), 134
ufl_index_dimensions (ufl.exprcontainers.ExprList attribute), 136
ufl_index_dimensions (ufl.exprcontainers.ExprMapping attribute), 136
ufl_index_dimensions (ufl.indexed.Indexed attribute), 146
ufl_index_dimensions (ufl.indexsum.IndexSum attribute), 147
ufl_index_dimensions (ufl.mathfunctions.Atan2 attribute), 149
ufl_index_dimensions (ufl.mathfunctions.BesselFunction attribute), 149
ufl_index_dimensions (ufl.mathfunctions.MathFunction attribute), 150
ufl_index_dimensions (ufl.referencevalue.ReferenceValue attribute), 157
ufl_index_dimensions (ufl.restriction.CellAvg attribute), 157
ufl_index_dimensions (ufl.restriction.FacetAvg attribute), 157
ufl_index_dimensions (ufl.restriction.Restricted attribute), 158
ufl_index_dimensions (ufl.tensoralgebra.Cofactor attribute), 158
ufl_index_dimensions (ufl.tensoralgebra.Cross attribute), 159
ufl_index_dimensions (ufl.tensoralgebra.Determinant attribute), 159
ufl_index_dimensions (ufl.tensoralgebra.Deviatoric attribute), 159
ufl_index_dimensions (ufl.tensoralgebra.Dot attribute), 159
ufl_index_dimensions (ufl.tensoralgebra.Inner attribute), 159
ufl_index_dimensions (ufl.tensoralgebra.Inverse attribute), 159

tribute), 159
 (ufl.tensoralgebra.Outer attribute), 159
 (ufl.tensoralgebra.Skew attribute), 160
 (ufl.tensoralgebra.Sym attribute), 160
 (ufl.tensoralgebra.Trace attribute), 160
 (ufl.tensoralgebra.Transposed attribute), 160
 (ufl.tensors.ComponentTensor attribute), 160
 (ufl.tensors.ListTensor attribute), 160
 (ufl.variable.Label attribute), 162
 (ufl.variable.Variable attribute), 162
 (ufl.classes.MeshView method), 124
 (ufl.domain.MeshView method), 134
 (ufl.MeshView method), 168
 (ufl.classes.Operator attribute), 106
 (ufl.classes.Terminal attribute), 100
 (ufl.core.operator.Operator attribute), 75
 (ufl.core.terminal.Terminal attribute), 76
 (ufl.algebra.Abs attribute), 96
 (ufl.algebra.Division attribute), 96
 (ufl.algebra.Power attribute), 96
 (ufl.algebra.Product attribute), 96
 (ufl.algebra.Sum attribute), 96
 (ufl.Argument attribute), 175
 (ufl.argument.Argument attribute), 97
 (ufl.CellNormal attribute), 169
 (ufl.classes.Abs attribute), 110
 (ufl.classes.Argument attribute), 108
 (ufl.classes.Atan2 attribute), 117
 (ufl.classes.BesselFunction attribute), 117
 (ufl.classes.CellAvg attribute), 113
 (ufl.classes.CellCoordinate attribute), 101
 (ufl.classes.CellEdgeVectors attribute), 103
 (ufl.classes.CellFacetJacobian attribute), 103
 (ufl.classes.CellFacetJacobianInverse attribute), 104
 (ufl.classes.CellFacetOrigin attribute), 102
 (ufl.classes.CellNormal attribute), 104
 (ufl.classes.CellOrigin attribute), 102
 (ufl.classes.Coefficient attribute), 109
 (ufl.classes.CoefficientDerivative attribute), 113
 (ufl.classes.Cofactor attribute), 111
 (ufl.classes.ComponentTensor attribute), 108
 (ufl.classes.Condition attribute), 115
 (ufl.classes.Conditional attribute), 116
 (ufl.classes.Cross attribute), 111
 (ufl.classes.Curl attribute), 115
 (ufl.classes.Determinant attribute), 111
 (ufl.classes.Deviatoric attribute), 112
 (ufl.classes.Div attribute), 114
 (ufl.classes.Division attribute), 110
 (ufl.classes.Dot attribute), 111
 (ufl.classes.ExprList attribute), 113
 (ufl.classes.ExprMapping attribute), 113
 (ufl.classes.FacetAvg attribute), 113
 (ufl.classes.FacetCoordinate attribute), 102
 (ufl.classes.FacetEdgeVectors attribute), 103
 (ufl.classes.FacetJacobian attribute), 102
 (ufl.classes.FacetJacobianInverse attribute), 104
 (ufl.classes.FacetNormal attribute), 104
 (ufl.classes.FacetOrigin attribute), 102
 (ufl.classes.GeometricQuantity attribute), 101
 (ufl.classes.Grad attribute), 114
 (ufl.classes.Identity attribute), 107
 (ufl.classes.Indexed attribute), 108
 (ufl.classes.IndexSum attribute), 112
 (ufl.classes.Inner attribute), 111
 (ufl.classes.Inverse attribute), 111
 (ufl.classes.Jacobian attribute), 102
 (ufl.classes.JacobianInverse attribute), 104
 (ufl.classes.Label attribute), 109
 (ufl.classes.ListTensor attribute), 108
 (ufl.classes.MathFunction attribute), 116
 (ufl.classes.MaxValue attribute), 116
 (ufl.classes.MinValue attribute), 116
 (ufl.classes.MultiIndex attribute), 106
 (ufl.classes.NablaDiv attribute), 114
 (ufl.classes.NablaGrad attribute), 114
 (ufl.classes.Outer attribute), 111
 (ufl.classes.PermutationSymbol attribute), 107
 (ufl.classes.Power attribute), 110
 (ufl.classes.Product attribute), 110
 (ufl.classes.ReferenceCurl attribute), 115
 (ufl.classes.ReferenceDiv attribute), 114
 (ufl.classes.ReferenceGrad attribute), 114
 (ufl.classes.ReferenceNormal attribute), 105
 (ufl.classes.ReferenceValue attribute), 118
 (ufl.classes.Restricted attribute), 112
 (ufl.classes.ScalarValue attribute), 107
 (ufl.classes.Skew attribute), 112
 (ufl.classes.SpatialCoordinate attribute), 101
 (ufl.classes.Sum attribute), 110
 (ufl.classes.Sym attribute), 112
 (ufl.classes.Trace attribute), 111
 (ufl.classes.Transposed attribute), 110
 (ufl.classes.Variable attribute), 109
 (ufl.classes.VariableDerivative attribute), 114
 (ufl.classes.Zero attribute), 107
 (ufl.Coefficient attribute), 176

ufl_shape (ufl.coefficient.Coefficient attribute), 128
ufl_shape (ufl.conditional.Condition attribute), 130
ufl_shape (ufl.conditional.Conditional attribute), 130
ufl_shape (ufl.conditional.MaxValue attribute), 130
ufl_shape (ufl.conditional.MinValue attribute), 131
ufl_shape (ufl.constantvalue.Identity attribute), 131
ufl_shape (ufl.constantvalue.PermutationSymbol attribute), 131
ufl_shape (ufl.constantvalue.ScalarValue attribute), 132
ufl_shape (ufl.constantvalue.Zero attribute), 132
ufl_shape (ufl.core.multiindex.MultiIndex attribute), 75
ufl_shape (ufl.differentiation.CoefficientDerivative attribute), 132
ufl_shape (ufl.differentiation.Curl attribute), 132
ufl_shape (ufl.differentiation.Div attribute), 133
ufl_shape (ufl.differentiation.Grad attribute), 133
ufl_shape (ufl.differentiation.NablaDiv attribute), 133
ufl_shape (ufl.differentiation.NablaGrad attribute), 133
ufl_shape (ufl.differentiation.ReferenceCurl attribute), 133
ufl_shape (ufl.differentiation.ReferenceDiv attribute), 133
ufl_shape (ufl.differentiation.ReferenceGrad attribute), 134
ufl_shape (ufl.differentiation.VariableDerivative attribute), 134
ufl_shape (ufl.exprcontainers.ExprList attribute), 136
ufl_shape (ufl.exprcontainers.ExprMapping attribute), 136
ufl_shape (ufl.FacetNormal attribute), 169
ufl_shape (ufl.geometry.CellCoordinate attribute), 140
ufl_shape (ufl.geometry.CellEdgeVectors attribute), 141
ufl_shape (ufl.geometry.CellFacetJacobian attribute), 141
ufl_shape (ufl.geometry.CellFacetJacobianInverse attribute), 141
ufl_shape (ufl.geometry.CellFacetOrigin attribute), 141
ufl_shape (ufl.geometry.CellNormal attribute), 141
ufl_shape (ufl.geometry.CellOrigin attribute), 142
ufl_shape (ufl.geometry.FacetCoordinate attribute), 142
ufl_shape (ufl.geometry.FacetEdgeVectors attribute), 143
ufl_shape (ufl.geometry.FacetJacobian attribute), 143
ufl_shape (ufl.geometry.FacetJacobianInverse attribute), 143
ufl_shape (ufl.geometry.FacetNormal attribute), 143
ufl_shape (ufl.geometry.FacetOrigin attribute), 144
ufl_shape (ufl.geometry.GeometricQuantity attribute), 144
ufl_shape (ufl.geometry.Jacobian attribute), 144
ufl_shape (ufl.geometry.JacobianInverse attribute), 144
ufl_shape (ufl.geometry.ReferenceNormal attribute), 145
ufl_shape (ufl.geometry.SpatialCoordinate attribute), 146
ufl_shape (ufl.Identity attribute), 177
ufl_shape (ufl.indexed.Indexed attribute), 146
ufl_shape (ufl.indexsum.IndexSum attribute), 147
ufl_shape (ufl.Jacobian attribute), 170
ufl_shape (ufl.JacobianInverse attribute), 170
ufl_shape (ufl.mathfunctions.Atan2 attribute), 149
ufl_shape (ufl.mathfunctions.BesselFunction attribute), 149
ufl_shape (ufl.mathfunctions.MathFunction attribute), 150
ufl_shape (ufl.PermutationSymbol attribute), 177
ufl_shape (ufl.referencevalue.ReferenceValue attribute), 157
ufl_shape (ufl.restriction.CellAvg attribute), 157
ufl_shape (ufl.restriction.FacetAvg attribute), 157
ufl_shape (ufl.restriction.Restricted attribute), 158
ufl_shape (ufl.SpatialCoordinate attribute), 168
ufl_shape (ufl.tensoralgebra.Cofactor attribute), 159
ufl_shape (ufl.tensoralgebra.Cross attribute), 159
ufl_shape (ufl.tensoralgebra.Determinant attribute), 159
ufl_shape (ufl.tensoralgebra.Deviatoric attribute), 159
ufl_shape (ufl.tensoralgebra.Dot attribute), 159
ufl_shape (ufl.tensoralgebra.Inner attribute), 159
ufl_shape (ufl.tensoralgebra.Inverse attribute), 159
ufl_shape (ufl.tensoralgebra.Outer attribute), 159
ufl_shape (ufl.tensoralgebra.Skew attribute), 160
ufl_shape (ufl.tensoralgebra.Sym attribute), 160
ufl_shape (ufl.tensoralgebra.Trace attribute), 160
ufl_shape (ufl.tensoralgebra.Transposed attribute), 160
ufl_shape (ufl.tensors.ComponentTensor attribute), 160
ufl_shape (ufl.tensors.ListTensor attribute), 160
ufl_shape (ufl.variable.Label attribute), 162
ufl_shape (ufl.variable.Variable attribute), 162
ufl_sub_spaces() (ufl.classes.AbstractFunctionSpace method), 124
ufl_sub_spaces() (ufl.classes.FunctionSpace method), 125
ufl_sub_spaces() (ufl.classes.MixedFunctionSpace method), 125
ufl_sub_spaces() (ufl.classes.TensorProductFunctionSpace method), 125
ufl_sub_spaces() (ufl.FunctionSpace method), 175
ufl_sub_spaces() (ufl.functionspace.AbstractFunctionSpace method), 140
ufl_sub_spaces() (ufl.functionspace.FunctionSpace method), 140
ufl_sub_spaces() (ufl.functionspace.MixedFunctionSpace method), 140
ufl_sub_spaces() (ufl.functionspace.TensorProductFunctionSpace method), 140
ufl_type() (in module ufl.core.ufl_type), 77
UFLException, 166
UFLTypeDefaultDict (class in ufl.utils.ufltypedicts), 95
UFLTypeDict (class in ufl.utils.ufltypedicts), 95
undefined() (ufl.algorithms.MultiFunction method), 71
undefined() (ufl.algorithms.Transformer method), 71
undefined() (ufl.algorithms.transformer.Transformer method), 69

undefined() (ufl.corealg.multifunction.MultiFunction method), 78
 unexpected() (ufl.algorithms.apply_derivatives.GenericDerivativeRule method), 50
 unflatten_index() (in module ufl.utils.indexflattening), 93
 unique_post_traversal() (in module ufl.corealg.traversal), 79
 unique_pre_traversal() (in module ufl.corealg.traversal), 79
 unique_sorted_indices() (in module ufl.index_combination_utils), 146
 unique_tuple() (in module ufl.algorithms.analysis), 47
 unit_indexed_tensor() (in module ufl.tensors), 161
 unit_list() (in module ufl.tensors), 161
 unit_list2() (in module ufl.tensors), 161
 unit_matrices() (in module ufl), 177
 unit_matrices() (in module ufl.tensors), 161
 unit_matrix() (in module ufl), 177
 unit_matrix() (in module ufl.tensors), 161
 unit_vector() (in module ufl), 177
 unit_vector() (in module ufl.tensors), 161
 unit_vectors() (in module ufl), 177
 unit_vectors() (in module ufl.tensors), 161
 unwrap_list_tensor() (in module ufl.tensors), 161
 unzip() (in module ufl.utils.sequences), 94
 update() (ufl.utils.dicts.EmptyDictType method), 92
 update_global_expr_attributes() (in module ufl.core.ufl_type), 77

V

V() (ufl.formatting.graph.Graph method), 86
 validate_form() (in module ufl.algorithms), 72
 validate_form() (in module ufl.algorithms.checks), 57
 value() (ufl.classes.ScalarValue method), 107
 value() (ufl.constantvalue.ScalarValue method), 132
 value_shape() (ufl.classes.FiniteElementBase method), 120
 value_shape() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
 value_shape() (ufl.FiniteElementBase method), 171
 value_size() (ufl.classes.FiniteElementBase method), 120
 value_size() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 82
 value_size() (ufl.FiniteElementBase method), 171
 Variable (class in ufl.classes), 109
 Variable (class in ufl.variable), 162
 variable() (in module ufl), 180
 variable() (in module ufl.operators), 156
 variable() (ufl.algorithms.apply_derivatives.GenericDerivativeRule method), 50
 variable() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51
 variable() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55

variable() (ufl.algorithms.check_arities.ArityChecker method), 57
 variable() (ufl.algorithms.estimator.SumDegreeEstimator method), 62
 variable() (ufl.algorithms.formtransformations.PartExtractor method), 65
 variable() (ufl.algorithms.renumbering.VariableRenumberingTransformer method), 67
 variable() (ufl.algorithms.ReuseTransformer method), 70
 variable() (ufl.algorithms.transformer.CopyTransformer method), 68
 variable() (ufl.algorithms.transformer.ReuseTransformer method), 68
 variable() (ufl.algorithms.transformer.VariableStripper method), 69
 variable() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91
 variable_derivative() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48
 variable_derivative() (ufl.algorithms.estimator.SumDegreeEstimator method), 62
 variable_derivative() (ufl.formatting.ufl2latex.Expression2LatexHandler method), 91
 VariableDerivative (class in ufl.classes), 113
 VariableDerivative (class in ufl.differentiation), 134
 VariableRenumberingTransformer (class in ufl.algorithms.renumbering), 67
 VariableRuleset (class in ufl.algorithms.apply_derivatives), 51
 VariableStripper (class in ufl.algorithms.transformer), 69
 variant() (ufl.classes.FiniteElement method), 120
 variant() (ufl.FiniteElement method), 171
 variant() (ufl.finiteelement.finiteelement.FiniteElement method), 81
 VectorConstant() (in module ufl), 176
 VectorConstant() (in module ufl.coefficient), 128
 VectorElement (class in ufl), 172
 VectorElement (class in ufl.classes), 121
 VectorElement (class in ufl.finiteelement.mixedelement), 84
 verbatim() (in module ufl.formatting.latextools), 87
 VIn() (ufl.formatting.graph.Graph method), 86
 visit() (ufl.algorithms.Transformer method), 71
 visit() (ufl.algorithms.transformer.Transformer method), 69
 Vout() (ufl.formatting.graph.Graph method), 86

W

warning() (ufl.log.Logger method), 148
 warning_blue() (ufl.log.Logger method), 149
 warning_green() (ufl.log.Logger method), 149
 warning_red() (ufl.log.Logger method), 149

X

x (ufl.algorithms.domain_analysis.ExprTupleKey attribute), [58](#)
x_repr_latex_() (ufl.classes.Form method), [128](#)
x_repr_latex_() (ufl.Form method), [182](#)
x_repr_latex_() (ufl.form.Form method), [137](#)
x_repr_png_() (ufl.classes.Form method), [128](#)
x_repr_png_() (ufl.Form method), [183](#)
x_repr_png_() (ufl.form.Form method), [137](#)
xor() (in module ufl.utils.sequences), [94](#)

Z

Zero (class in ufl.classes), [107](#)
Zero (class in ufl.constantvalue), [132](#)
zero() (in module ufl), [177](#)
zero() (in module ufl.constantvalue), [132](#)
zero() (ufl.algorithms.expand_indices.IndexExpander method), [63](#)
zero() (ufl.algorithms.renumbering.IndexRenumberingTransformer method), [67](#)
zero() (ufl.formatting.ufl2dot.CompactLabeller method), [88](#)
zero() (ufl.formatting.ufl2latex.Expression2LatexHandler method), [91](#)
zero_expr() (in module ufl.algorithms.formtransformations), [66](#)
zero_lists() (in module ufl.formoperators), [139](#)