
Unified Form Language (UFL) Documentation

Release 2018.1.0

FEniCS Project

Jun 14, 2018

Contents

1 Documentation	3
------------------------	----------

Python Module Index	181
----------------------------	------------

The Unified Form Language (UFL) is a domain specific language for declaration of finite element discretizations of variational forms. More precisely, it defines a flexible interface for choosing finite element spaces and defining expressions for weak forms in a notation close to mathematical notation.

UFL is part of the FEniCS Project.

For more information, visit <http://www.fenicsproject.org>

CHAPTER 1

Documentation

1.1 Installation

UFL is normally installed as part of an installation of FEniCS. If you are using UFL as part of the FEniCS software suite, it is recommended that you follow the [installation instructions for FEniCS](#).

To install UFL itself, read on below for a list of requirements and installation instructions.

1.1.1 Requirements and dependencies

UFL requires Python version 3.5 or later and depends on the following Python packages:

- NumPy

These packages will be automatically installed as part of the installation of UFL, if not already present on your system.

1.1.2 Installation instructions

To install UFL, download the source code from the [UFL Bitbucket repository](#), and run the following command:

```
pip install .
```

To install to a specific location, add the `--prefix` flag to the installation command:

```
pip install --prefix=<some directory> .
```

1.2 User manual

1.2.1 Introduction

The Unified Form Language (UFL) is a domain specific language for defining discrete variational forms and functionals in a notation close to pen-and-paper formulation.

UFL is part of the FEniCS Project and is usually used in combination with other components from this project to compute solutions to partial differential equations. The form compiler FFC uses UFL as its end-user interface, producing implementations of the UFC interface as output. See DOLFIN for more details about using UFL in an integrated problem solving environment.

This manual is intended for different audiences. If you are an end-user and all you want to do is to solve your PDEs with the FEniCS framework, you should read [Form language](#), and also [Example forms](#). These two sections explain how to use all operators available in the language and present a number of examples to illustrate the use of the form language in applications.

The remaining chapters contain more technical details intended for developers who need to understand what is happening behind the scenes and modify or extend UFL in the future.

[Internal representation details](#) describes the implementation of the language, in particular how expressions are represented internally by UFL. This can also be useful knowledge to understand error messages and debug errors in your form files.

[Algorithms](#) explains the many algorithms available to work with UFL expressions, mostly intended to aid developers of form compilers. The algorithms include helper functions for easy and efficient iteration over expression trees, formatting tools to present expressions as text or images of different kinds, utilities to analyse properties of expressions or checking their validity, automatic differentiation algorithms, as well as algorithms to work with the computational graphs of expressions.

1.2.2 Form language

UFL consists of a set of operators and atomic expressions that can be used to express variational forms and functionals. Below we will define all these operators and atomic expressions in detail.

UFL is built on top of the Python language, and any Python code is valid in the definition of a form. In particular, comments (lines starting with `#`) and functions (keyword `def`, see [user-defined](#) below) are useful in the definition of a form. However, it is usually a good idea to avoid using advanced Python features in the form definition, to stay close to the mathematical notation.

The entire form language can be imported in Python with the line

```
from ufl import *
```

which is assumed in all examples below and can be omitted in `.ufl` files. This can be useful for experimenting with the language in an interactive Python interpreter.

Forms and integrals

UFL is designed to express forms in the following generalized format:

$$a(\mathbf{v}; \mathbf{w}) = \sum_{k=1}^{n_c} \int_{\Omega_k} I_k^c(\mathbf{v}; \mathbf{w}) dx + \sum_{k=1}^{n_e} \int_{\partial\Omega_k} I_k^e(\mathbf{v}; \mathbf{w}) ds + \sum_{k=1}^{n_i} \int_{\Gamma_k} I_k^i(\mathbf{v}; \mathbf{w}) dS.$$

Here the form a depends on the *form arguments* $\mathbf{v} = (v_1, \dots, v_r)$ and the *form coefficients* $\mathbf{w} = (w_1, \dots, w_n)$, and its expression is a sum of integrals. Each term of a valid form expression must be a scalar-valued expression integrated exactly once. How to define form arguments and integrand expressions is detailed in the rest of this chapter.

Integrals are expressed through multiplication with a measure, representing an integral over either

- the interior of the domain Ω (`dx`, cell integral);
- the boundary $\partial\Omega$ of Ω (`ds`, exterior facet integral);
- the set of interior facets Γ (`dS`, interior facet integral).

(Note that newer versions of UFL support several other integral types currently not documented here). As a basic example, assume v is a scalar-valued expression and consider the integral of v over the interior of Ω . This may be expressed as:

```
a = v*dx
```

and the integral of v over $\partial\Omega$ is written as:

```
a = v*ds.
```

Alternatively, measures can be redefined to represent numbered subsets of a domain, such that a form evaluates to different expressions on different parts of the domain. If c , e_0 and e_1 are scalar-valued expressions, then:

```
a = c*dx + e0*ds(0) + e1*ds(1)
```

represents

$$a = \int_{\Omega} c dx + \int_{\partial\Omega_0} e_0 ds + \int_{\partial\Omega_1} e_1 ds,$$

where

$$\partial\Omega_0 \subset \partial\Omega, \quad \partial\Omega_1 \subset \partial\Omega.$$

Note: The domain Ω , its subdomains and boundaries are not known to UFL. These are defined in a problem solving environment such as DOLFIN, which uses UFL to specify forms.

Finite element spaces

Before defining forms which can be integrated, it is necessary to describe the finite element spaces over which the integration takes place. UFL can represent very flexible general hierarchies of mixed finite elements, and has predefined names for most common element families. A finite element space is defined by an element domain, shape functions and nodal variables. In UFL, the element domain is called a `Cell`.

Cells

A polygonal cell is defined by a shape name and a geometric dimension, written as:

```
cell = Cell(shape, gdim)
```

Valid shapes are “interval”, “triangle”, “tetrahedron”, “quadrilateral”, and “hexahedron”. Some examples:

```
# Regular triangle cell
cell = Cell("triangle")

# Triangle cell embedded in 3D space
cell = Cell("triangle", 3)
```

Objects for regular cells of all basic shapes are predefined:

```
# Predefined linear cells
cell = interval
cell = triangle
cell = tetrahedron
cell = quadrilateral
cell = hexahedron
```

In the rest of this document, a variable name `cell` will be used where any cell is a valid argument, to make the examples dimension-independent wherever possible. Using a variable `cell` to hold the cell type used in a form is highly recommended, since this makes most form definitions dimension-independent.

Element families

UFL predefines a set of names of known element families. When defining a finite element below, the argument `family` is a string and its possible values include

- "Lagrange" or "CG", representing standard scalar Lagrange finite elements (continuous piecewise polynomial functions);
- "Discontinuous Lagrange" or "DG", representing scalar discontinuous Lagrange finite elements (discontinuous piecewise polynomial functions);
- "Crouzeix–Raviart" or "CR", representing scalar Crouzeix–Raviart elements;
- "Brezzi–Douglas–Marini" or "BDM", representing vector-valued Brezzi–Douglas–Marini H(div) elements;
- "Brezzi–Douglas–Fortin–Marini" or "BDFM", representing vector-valued Brezzi–Douglas–Fortin–Marini H(div) elements;
- "Raviart–Thomas" or "RT", representing vector-valued Raviart–Thomas H(div) elements.
- "Nedelec 1st kind H(div)" or "N1div", representing vector-valued Nedelec H(div) elements (of the first kind).
- "Nedelec 2st kind H(div)" or "N2div", representing vector-valued Nedelec H(div) elements (of the second kind).
- "Nedelec 1st kind H(curl)" or "N1curl", representing vector-valued Nedelec H(curl) elements (of the first kind).
- "Nedelec 2st kind H(curl)" or "N2curl", representing vector-valued Nedelec H(curl) elements (of the second kind).
- "Bubble", representing bubble elements, useful for example to build the mini elements.
- "Quadrature" or "Q", representing artificial “finite elements” with degrees of freedom being function evaluations at quadrature points;
- "Boundary Quadrature" or "BQ", representing artificial “finite elements” with degrees of freedom being function evaluations at quadrature points on the boundary.

Note that new versions of UFL also support notation from the Periodic Table of Finite Elements, currently not documented here.

Basic elements

A `FiniteElement`, sometimes called a basic element, represents a finite element from some family on a given cell with a certain polynomial degree. Valid families and cells are explained above. The notation is

```
element = FiniteElement(family, cell, degree)
```

Some examples:

```
element = FiniteElement("Lagrange", interval, 3)
element = FiniteElement("DG", tetrahedron, 0)
element = FiniteElement("BDM", triangle, 1)
```

Vector elements

A `VectorElement` represents a combination of basic elements such that each component of a vector is represented by the basic element. The size is usually omitted, the default size equals the geometry dimension. The notation is

```
element = VectorElement(family, cell, degree[, size])
```

Some examples:

```
# A quadratic "P2" vector element on a triangle
element = VectorElement("CG", triangle, 2)
# A linear 3D vector element on a 1D interval
element = VectorElement("CG", interval, 1, size=3)
# A six-dimensional piecewise constant element on a tetrahedron
element = VectorElement("DG", tetrahedron, 0, size=6)
```

Tensor elements

A `TensorElement` represents a combination of basic elements such that each component of a tensor is represented by the basic element. The shape is usually omitted, the default shape is :math: (d, d) where :math: d is the geometric dimension. The notation is

```
element = TensorElement(family, cell, degree[, shape, symmetry])
```

Any shape tuple consisting of positive integers is valid, and the optional symmetry can either be set to `True` which means standard matrix symmetry (like $A_{ij} = A_{ji}$), or a dict like { (0,1):(1,0), (0,2):(2,0) } where the dict keys are index tuples that are represented by the corresponding dict value.

Examples:

```
element = TensorElement("CG", cell, 2)
element = TensorElement("DG", cell, 0, shape=(6,6))
element = TensorElement("DG", cell, 0, symmetry=True)
element = TensorElement("DG", cell, 0, symmetry={(0,0): (1,1)})
```

Mixed elements

A `MixedElement` represents an arbitrary combination of other elements. `VectorElement` and `TensorElement` are special cases of a `MixedElement` where all sub-elements are equal.

General notation for an arbitrary number of subelements:

```
element = MixedElement(element1, element2[, element3, ...])
```

Shorthand notation for two subelements:

```
element = element1 * element2
```

Note: The `*` operator is left-associative, such that:

```
element = element1 * element2 * element3
```

represents $(e_1 * e_2) * e_3$, i.e. this is a mixed element with two sub-elements $(e_1 * e_2)$ and e_3 .

See [Form arguments](#) for details on how defining functions on mixed spaces can differ from defining functions on other finite element spaces.

Examples:

```
# Taylor-Hood element
V = VectorElement("Lagrange", cell, 2)
P = FiniteElement("Lagrange", cell, 1)
TH = V * P

# A tensor-vector-scalar element
T = TensorElement("Lagrange", cell, 2, symmetry=True)
V = VectorElement("Lagrange", cell, 1)
P = FiniteElement("DG", cell, 0)
ME = MixedElement(T, V, P)
```

EnrichedElement

The data type `EnrichedElement` represents the vector sum of two (or more) finite elements.

Example: The Mini element can be constructed as

```
P1 = VectorElement("Lagrange", "triangle", 1)
B = VectorElement("Bubble", "triangle", 3)
Q = FiniteElement("Lagrange", "triangle", 1)

Mini = (P1 + B) * Q
```

Form arguments

Form arguments are divided in two groups, arguments and coefficients. An `Argument` represents an arbitrary basis function in a given discrete finite element space, while a `Coefficient` represents a function in a discrete finite element space that will be provided by the user at a later stage. The number of `Arguments` that occur in a `Form` equals the “arity” of the form.

Basis functions

The data type `Argument` represents a basis function on a given finite element. An `Argument` must be created for a previously declared finite element (simple or mixed):

```
v = Argument(element)
```

Note that more than one `Argument` can be declared for the same `FiniteElement`. Basis functions are associated with the arguments of a multilinear form in the order of declaration.

For a `MixedElement`, the function `Arguments` can be used to construct tuples of `Arguments`, as illustrated here for a mixed Taylor–Hood element:

```
v, q = Arguments(TH)
u, p = Arguments(TH)
```

For a `Argument` on a `MixedElement` (or `VectorElement` or `TensorElement`), the function `split` can be used to extract basis function values on subspaces, as illustrated here for a mixed Taylor–Hood element:

```
vq = Argument(TH)
v, q = split(up)
```

This is equivalent to the previous use of `Arguments`:

```
v, q = Arguments(TH)
```

For convenience, `TestFunction` and `TrialFunction` are special instances of `Argument` with the property that a `TestFunction` will always be the first argument in a form and `TrialFunction` will always be the second argument in a form (order of declaration does not matter). Their usage is otherwise the same as for `Argument`:

```
v = TestFunction(element)
u = TrialFunction(element)
v, q = TestFunctions(TH)
u, p = TrialFunctions(TH)
```

Meshes and function spaces

Note that newer versions of UFL introduce the concept of a `Mesh` and a `FunctionSpace`. These are currently not documented here.

Coefficient functions

The data type `Coefficient` represents a function belonging to a given finite element space, that is, a linear combination of basis functions of the finite element space. A `Coefficient` must be declared for a previously declared `FiniteElement`:

```
f = Coefficient(element)
```

Note that the order in which `Coefficients` are declared is important, directly reflected in the ordering they have among the arguments to each `Form` they are part of.

`Coefficient` is used to represent user-defined functions, including, e.g., source terms, body forces, variable coefficients and stabilization terms. UFL treats each `Coefficient` as a linear combination of unknown basis functions

with unknown coefficients, that is, UFL knows nothing about the concrete basis functions of the element and nothing about the value of the function.

Note: Note that more than one function can be declared for the same `FiniteElement`. The following example declares two `Arguments` and two `Coefficients` for the same `FiniteElement`:

```
v = Argument(element)
u = Argument(element)
f = Coefficient(element)
g = Coefficient(element)
```

For a `Coefficient` on a `MixedElement` (or `VectorElement` or `TensorElement`), the function `split` can be used to extract function values on subspaces, as illustrated here for a mixed Taylor–Hood element:

```
up = Coefficient(TH)
u, p = split(up)
```

There is a shorthand for this, whose use is similar to `Arguments`, called `Coefficients`:

```
u, p = Coefficients(TH)
```

Spatially constant (or discontinuous piecewise constant) functions can conveniently be represented by `Constant`, `VectorConstant`, and `TensorConstant`:

```
c0 = Constant(cell)
v0 = VectorConstant(cell)
t0 = TensorConstant(cell)
```

These three lines are equivalent with first defining DG0 elements and then defining a `Coefficient` on each, illustrated here:

```
DG0 = FiniteElement("Discontinuous Lagrange", cell, 0)
DG0v = VectorElement("Discontinuous Lagrange", cell, 0)
DG0t = TensorElement("Discontinuous Lagrange", cell, 0)

c1 = Coefficient(DG0)
v1 = Coefficient(DG0v)
t1 = Coefficient(DG0t)
```

Basic Datatypes

UFL expressions can depend on some other quantities in addition to the functions and basis functions described above.

Literals and geometric quantities

Some atomic quantities are derived from the cell. For example, the (global) spatial coordinates are available as a vector valued expression `SpatialCoordinate(cell)`:

```
# Linear form for a load vector with a sin(y) coefficient
v = TestFunction(element)
x = SpatialCoordinate(cell)
L = sin(x[1])*v*dx
```

Another quantity is the (outwards pointing) facet normal `FacetNormal(cell)`. The normal vector is only defined on the boundary, so it can't be used in a cell integral.

Example functional `M`, an integral of the normal component of a function `g` over the boundary:

```
n = FacetNormal(cell)
g = Coefficient(VectorElement("CG", cell, 1))
M = dot(n, g)*ds
```

Python scalars (`int`, `float`) can be used anywhere a scalar expression is allowed. Another literal constant type is `Identity` which represents an $n \times n$ unit matrix of given size n , as in this example:

```
# Geometric dimension
d = cell.geometric_dimension()

# d x d identity matrix
I = Identity(d)

# Kronecker delta
delta_ij = I[i, j]
```

Indexing and tensor components

UFL supports index notation, which is often a convenient way to express forms. The basic principle of index notation is that summation is implicit over indices repeated twice in each term of an expression. The following examples illustrate the index notation, assuming that each of the variables `i` and `j` has been declared as a free `Index`:

- $\mathbf{v}[i] * \mathbf{w}[i]: \sum_{i=0}^{n-1} v_i w_i = \mathbf{v} \cdot \mathbf{w}$
- $\mathbf{Dx}(\mathbf{v}, i) * \mathbf{Dx}(\mathbf{w}, i): \sum_{i=0}^{d-1} \frac{\partial v}{\partial x_i} \frac{\partial w}{\partial x_i} = \nabla \mathbf{v} \cdot \nabla \mathbf{w}$
- $\mathbf{Dx}(\mathbf{v}[i], i): \sum_{i=0}^{d-1} \frac{\partial v_i}{\partial x_i} = \nabla \cdot \mathbf{v}$
- $\mathbf{Dx}(\mathbf{v}[i], j) * \mathbf{Dx}(\mathbf{w}[i], j): \sum_{i=0}^{n-1} \sum_{j=0}^{d-1} \frac{\partial v_i}{\partial x_j} \frac{\partial w_i}{\partial x_j} = \nabla \mathbf{v} : \nabla \mathbf{w}$

Here we will try to very briefly summarize the basic concepts of tensor algebra and index notation, just enough to express the operators in UFL.

Assuming an Euclidean space in d dimensions with $1 \leq d \leq 3$, and a set of orthonormal basis vectors \mathbf{i}_i for $i \in 0, \dots, d - 1$, we can define the dot product of any two basis functions as

$$\mathbf{i}_i \cdot \mathbf{i}_j = \delta_{ij},$$

where δ_{ij} is the Kronecker delta

$$\delta_{ij} \equiv \begin{cases} 1, & i = j, \\ 0, & \text{otherwise.} \end{cases}$$

A rank 1 tensor (vector) quantity \mathbf{v} can be represented in terms of unit vectors and its scalar components in that basis. In tensor algebra it is common to assume implicit summation over indices repeated twice in a product:

$$\mathbf{v} = v_k \mathbf{i}_k \equiv \sum_k v_k \mathbf{i}_k.$$

Similarly, a rank two tensor (matrix) quantity \mathbf{A} can be represented in terms of unit matrices, that is outer products of unit vectors:

$$\mathbf{A} = A_{ij} \mathbf{i}_i \mathbf{i}_j \equiv \sum_i \sum_j A_{ij} \mathbf{i}_i \mathbf{i}_j.$$

This generalizes to tensors of arbitrary rank:

$$\begin{aligned}\mathcal{C} &= C_{\iota} \mathbf{i}_{\iota_0} \otimes \cdots \otimes \mathbf{i}_{\iota_{r-1}} \\ &\equiv \sum_{\iota_0} \cdots \sum_{\iota_{r-1}} C_{\iota} \mathbf{i}_{\iota_0} \otimes \cdots \otimes \mathbf{i}_{\iota_{r-1}},\end{aligned}$$

where \mathcal{C} is a rank r tensor and ι is a multi-index of length r .

When writing equations on paper, a mathematician can easily switch between the \mathbf{v} and v_i representations without stating it explicitly. This is possible because of flexible notation and conventions. In a programming language, we can't use the boldface notation which associates \mathbf{v} and v by convention, and we can't always interpret such conventions unambiguously. Therefore, UFL requires that an expression is explicitly mapped from its tensor representation (\mathbf{v} , \mathbf{A}) to its component representation (v_i , A_{ij}) and back. This is done using `Index` objects, the indexing operator ($\mathbf{v}[\mathbf{i}]$) and the function `as_tensor`. More details on these follow.

In the following descriptions of UFL operator syntax, i -l and p -s are assumed to be predefined indices, and unless otherwise specified the name \mathbf{v} refers to some vector valued expression, and the name \mathbf{A} refers to some matrix valued expression. The name C refers to a tensor expression of arbitrary rank.

Defining indices

A set of indices i , j , k , l and p , q , r , s are predefined, and these should be enough for many applications. Examples will usually use these objects instead of creating new ones to conserve space.

The data type `Index` represents an index used for subscripting derivatives or taking components of non-scalar expressions. To create indices you can either make a single one using `Index()` or make several at once conveniently using `indices(n)`:

```
i = Index()
j, k, l = indices(3)
```

Each of these represents an `index` range determined by the context; if used to subscript a tensor-valued expression, the range is given by the shape of the expression, and if used to subscript a derivative, the range is given by the dimension d of the underlying shape of the finite element space. As we shall see below, indices can be a powerful tool when used to define forms in tensor notation.

Note: Advanced usage

If using UFL inside DOLFIN or another larger programming environment, it is a good idea to define your indices explicitly just before your form uses them, to avoid name collisions. The definition of the predefined indices is simply:

```
i, j, k, l = indices(4)
p, q, r, s = indices(4)
```

Note: Advanced usage

Note that in the old FFC notation, the definition

```
i = Index(0)
```

meant that the value of the index remained constant. This does not mean the same in UFL, and this notation is only meant for internal usage. Fixed indices are simply integers instead:

```
i = 0
```

Taking components of tensors

Basic fixed indexing of a vector valued expression v or matrix valued expression A :

- $v[0]$: component access, representing the scalar value of the first component of v
- $A[0, 1]$: component access, representing the scalar value of the first row, second column of A

Basic indexing:

- $v[i]$: component access, representing the scalar value of some component of v
- $A[i, j]$: component access, representing the scalar value of some component i, j of A

More advanced indexing:

- $A[i, 0]$: component access, representing the scalar value of some component i of the first column of A
- $A[i, :]$: row access, representing some row i of A , i.e. $\text{rank}(A[i,:]) == 1$
- $A[:, j]$: column access, representing some column j of A , i.e. $\text{rank}(A[:,j]) == 1$
- $C[\dots, 0]$: subtensor access, representing the subtensor of A with the last axis fixed, e.g., $A[\dots, 0] == A[:, 0]$
- $C[j, \dots]$: subtensor access, representing the subtensor of A with the first axis fixed, e.g., $A[j, \dots] == A[j, :]$

Making tensors from components

If you have expressions for scalar components of a tensor and wish to convert them to a tensor, there are two ways to do it. If you have a single expression with free indices that should map to tensor axes, like mapping v_k to v or A_{ij} to A , the following examples show how this is done:

```
vk = Identity(cell.geometric_dimension())[0,k]
v = as_tensor(vk, (k,))

Aij = v[i]*u[j]
A = as_tensor(Aij, (i,j))
```

Here v will represent unit vector \mathbf{i}_0 , and A will represent the outer product of v and u .

If you have multiple expressions without indices, you can build tensors from them just as easily, as illustrated here:

```
v = as_vector([1.0, 2.0, 3.0])
A = as_matrix([[u[0], 0], [0, u[1]]])
B = as_matrix([[a+b for b in range(2)] for a in range(2)])
```

Here v , A and B will represent the expressions

$$\begin{aligned} \mathbf{v} &= \mathbf{i}_0 + 2\mathbf{i}_1 + 3\mathbf{i}_2, \\ \mathbf{A} &= \begin{bmatrix} u_0 & 0 \\ 0 & u_1 \end{bmatrix}, \\ \mathbf{B} &= \begin{bmatrix} 0 & 1 \\ 1 & 2 \end{bmatrix}. \end{aligned}$$

Note that the function `as_tensor` generalizes from vectors to tensors of arbitrary rank, while the alternative functions `as_vector` and `as_matrix` work the same way but are only for constructing vectors and matrices. They are included for readability and convenience.

Implicit summation

Implicit summation can occur in only a few situations. A product of two terms that shares the same free index is implicitly treated as a sum over that free index:

- $v[i] * v[i]: \sum_i v_i v_i$
- $A[i, j] * v[i] * v[j]: \sum_j (\sum_i A_{ij} v_i) v_j$

A tensor valued expression indexed twice with the same free index is treated as a sum over that free index:

- $A[i, i]: \sum_i A_{ii}$
- $C[i, j, j, i]: \sum_i \sum_j C_{ijji}$

The spatial derivative, in the direction of a free index, of an expression with the same free index, is treated as a sum over that free index:

- $v[i].dx(i): \sum_i \frac{d(v_i)}{dx_i}$
- $A[i, j].dx(i): \sum_i \frac{d(A_{ij})}{dx_i}$

Note that these examples are sometimes written $v_{i,i}$ and $A_{ij,i}$ in pen-and-paper index notation.

Basic algebraic operators

The basic algebraic operators `+`, `-`, `*`, `/` can be used freely on UFL expressions. They do have some requirements on their operands, summarized here:

Addition or subtraction, `a + b` or `a - b`:

- The operands `a` and `b` must have the same shape.
- The operands `a` and `b` must have the same set of free indices.

Division, `a / b`:

- The operand `b` must be a scalar expression.
- The operand `b` must have no free indices.
- The operand `a` can be non-scalar with free indices, in which division represents scalar division of all components with the scalar `b`.

Multiplication, `a * b`:

- The only non-scalar operations allowed is scalar-tensor, matrix-vector and matrix-matrix multiplication.
- If either of the operands have any free indices, both must be scalar.
- If any free indices are repeated, summation is implied.

Basic nonlinear functions

Some basic nonlinear functions are also available, their meaning mostly obvious.

- `abs(f)`: the absolute value of `f`.

- `sign(f)`: the sign of f (+1 or -1).
- `pow(f, g)` or `f**g`: f to the power g , f^g
- `sqrt(f)`: square root, \sqrt{f}
- `exp(f)`: exponential of f
- `ln(f)`: natural logarithm of f
- `cos(f)`: cosine of f
- `sin(f)`: sine of f
- `tan(f)`: tangent of f
- `cosh(f)`: hyperbolic cosine of f
- `sinh(f)`: hyperbolic sine of f
- `tanh(f)`: hyperbolic tangent of f
- `acos(f)`: inverse cosine of f
- `asin(f)`: inverse sine of f
- `atan(f)`: inverse tangent of f
- `atan2(f1, f2)`: inverse tangent of $(f1/f2)$
- `erf(f)`: error function of f , $\frac{2}{\sqrt{\pi}} \int_0^f \exp(-t^2) dt$
- `bessel_J(nu, f)`: Bessel function of the first kind, $J_\nu(f)$
- `bessel_Y(nu, f)`: Bessel function of the second kind, $Y_\nu(f)$
- `bessel_I(nu, f)`: Modified Bessel function of the first kind, $I_\nu(f)$
- `bessel_K(nu, f)`: Modified Bessel function of the second kind, $K_\nu(f)$

These functions do not accept non-scalar operands or operands with free indices or Argument dependencies.

Tensor algebra operators

`transpose`

The transpose of a matrix A can be written as:

```
AT = transpose(A)
AT = A.T
AT = as_matrix(A[i,j], (j,i))
```

The definition of the transpose is

$$\text{AT}[i, j] \leftrightarrow (A^\top)_{ij} = A_{ji}$$

For transposing higher order tensor expressions, index notation can be used:

```
AT = as_tensor(A[i,j,k,l], (l,k,j,i))
```

tr

The trace of a matrix A is the sum of the diagonal entries. This can be written as:

```
t = tr(A)
t = A[i,i]
```

The definition of the trace is

$$\text{tr}(A) \leftrightarrow \text{tr}A = A_{ii} = \sum_{i=0}^{n-1} A_{ii}.$$

dot

The dot product of two tensors a and b can be written:

```
# General tensors
f = dot(a, b)

# Vectors a and b
f = a[i]*b[i]

# Matrices a and b
f = as_matrix(a[i,k]*b[k,j], (i,j))
```

The definition of the dot product of unit vectors is (assuming an orthonormal basis for a Euclidean space):

$$\mathbf{i}_i \cdot \mathbf{i}_j = \delta_{ij}$$

where δ_{ij} is the Kronecker delta function. The dot product of higher order tensors follow from this, as illustrated with the following examples.

An example with two vectors

$$\mathbf{v} \cdot \mathbf{u} = (v_i \mathbf{i}_i) \cdot (u_j \mathbf{i}_j) = v_i u_j (\mathbf{i}_i \cdot \mathbf{i}_j) = v_i u_j \delta_{ij} = v_i u_i$$

An example with a tensor of rank two

$$\begin{aligned} \mathbf{A} \cdot \mathbf{B} &= (A_{ij} \mathbf{i}_i \mathbf{i}_j) \cdot (B_{kl} \mathbf{i}_k \mathbf{i}_l) \\ &= (A_{ij} B_{kl}) \mathbf{i}_i (\mathbf{i}_j \cdot \mathbf{i}_k) \mathbf{i}_l \\ &= (A_{ij} B_{kl} \delta_{jk}) \mathbf{i}_i \mathbf{i}_l \\ &= A_{ik} B_{kl} \mathbf{i}_i \mathbf{i}_l. \end{aligned}$$

This is the same as a matrix-matrix multiplication.

An example with a vector and a tensor of rank two

$$\begin{aligned} \mathbf{v} \cdot \mathbf{A} &= (v_j \mathbf{i}_j) \cdot (A_{kl} \mathbf{i}_k \mathbf{i}_l) \\ &= (v_j A_{kl}) (\mathbf{i}_j \cdot \mathbf{i}_k) \mathbf{i}_l \\ &= (v_j A_{kl} \delta_{jk}) \mathbf{i}_l \\ &= v_k A_{kl} \mathbf{i}_l \end{aligned}$$

This is the same as a vector-matrix multiplication.

This generalizes to tensors of arbitrary rank: the dot product applies to the last axis of a and the first axis of b. The tensor rank of the product is rank(a)+rank(b)-2.

inner

The inner product is a contraction over all axes of \mathbf{a} and \mathbf{b} , that is the sum of all component-wise products. The operands must have exactly the same dimensions. For two vectors it is equivalent to the dot product.

If \mathbf{A} and \mathbf{B} are rank two tensors and \mathcal{C} and \mathcal{D} are rank 3 tensors their inner products are

$$\begin{aligned}\mathbf{A} : \mathbf{B} &= A_{ij} B_{ij} \\ \mathcal{C} : \mathcal{D} &= C_{ijk} D_{ijk}\end{aligned}$$

Using UFL notation, the following sets of declarations are equivalent:

```
# Vectors
f = dot(a, b)
f = inner(a, b)
f = a[i]*b[i]

# Matrices
f = inner(A, B)
f = A[i,j]*B[i,j]

# Rank 3 tensors
f = inner(C, D)
f = C[i,j,k]*D[i,j,k]
```

outer

The outer product of two tensors \mathbf{a} and \mathbf{b} can be written:

```
A = outer(a, b)
```

The general definition of the outer product of two tensors \mathcal{C} of rank r and \mathcal{D} of rank s is

$$\mathcal{C} \otimes \mathcal{D} = C_{t_0^a \dots t_{r-1}^a} D_{t_0^b \dots t_{s-1}^b} \mathbf{i}_{t_0^a} \otimes \dots \otimes \mathbf{i}_{t_{r-2}^a} \otimes \mathbf{i}_{t_1^b} \otimes \dots \otimes \mathbf{i}_{t_{s-1}^b}$$

Some examples with vectors and matrices are easier to understand:

$$\begin{aligned}\mathbf{v} \otimes \mathbf{u} &= v_i u_j \mathbf{i}_i \mathbf{i}_j, \\ \mathbf{v} \otimes \mathbf{B} &= v_i B_{kl} \mathbf{i}_i \mathbf{i}_k \mathbf{i}_l, \\ \mathbf{A} \otimes \mathbf{B} &= A_{ij} B_{kl} \mathbf{i}_i \mathbf{i}_j \mathbf{i}_k \mathbf{i}_l.\end{aligned}$$

The outer product of vectors is often written simply as

$$\mathbf{v} \otimes \mathbf{u} = \mathbf{v}\mathbf{u},$$

which is what we have done with $\mathbf{i}_i \mathbf{i}_j$ above.

The rank of the outer product is the sum of the ranks of the operands.

cross

The operator `cross` accepts as arguments two logically vector-valued expressions and returns a vector which is the cross product (vector product) of the two vectors:

$$\text{cross}(\mathbf{v}, \mathbf{w}) \leftrightarrow \mathbf{v} \times \mathbf{w} = (v_1 w_2 - v_2 w_1, v_2 w_0 - v_0 w_2, v_0 w_1 - v_1 w_0)$$

Note that this operator is only defined for vectors of length three.

det

The determinant of a matrix A can be written as

$$d = \det(A)$$

dev

The deviatoric part of matrix A can be written as

$$B = \text{dev}(A)$$

The definition is

$$\text{dev}A = A - \frac{\mathbf{A}_{ii}}{d}\mathbf{I}$$

where d is the rank of matrix A and \mathbf{I} is the identity matrix.

sym

The symmetric part of A can be written as

$$B = \text{sym}(A)$$

The definition is

$$\text{sym}A = \frac{1}{2}(A + A^T)$$

skew

The skew symmetric part of A can be written as

$$B = \text{skew}(A)$$

The definition is

$$\text{skew}A = \frac{1}{2}(A - A^T)$$

cofac

The cofactor of a matrix A can be written as

$$B = \text{cofac}(A)$$

The definition is

$$\text{cofac}A = \det(A)A^{-1}$$

The implementation of this is currently rather crude, with a hardcoded symbolic expression for the cofactor. Therefore, this is limited to 1x1, 2x2 and 3x3 matrices.

inv

The inverse of matrix A can be written as

```
Ainv = inv(A)
```

The implementation of this is currently rather crude, with a hardcoded symbolic expression for the inverse. Therefore, this is limited to 1x1, 2x2 and 3x3 matrices.

Differential Operators

Three different kinds of derivatives are currently supported: spatial derivatives, derivatives w.r.t. user defined variables, and derivatives of a form or functional w.r.t. a function.

Basic spatial derivatives

Spatial derivatives hold a special physical meaning in partial differential equations and there are several ways to express those. The basic way is:

```
# Derivative w.r.t. x_2
f = Dx(v, 2)
f = v.dx(2)
# Derivative w.r.t. x_i
g = Dx(v, i)
g = v.dx(i)
```

If v is a scalar expression, f here is the scalar derivative of v with respect to spatial direction z . If v has no free indices, g is the scalar derivative in spatial direction x_i , and g has the free index i . This can be expressed compactly as $v_{,i}$:

$$f = \frac{\partial v}{\partial x_2} = v_{,2},$$
$$g = \frac{\partial v}{\partial x_i} = v_{,i}.$$

If the expression to be differentiated w.r.t. x_i has i as a free-index, implicit summation is implied:

```
# Sum of derivatives w.r.t. x_i for all i
g = Dx(v[i], i)
g = v[i].dx(i)
```

Here g will represent the sum of derivatives w.r.t. x_i for all i , that is

$$g = \sum_i \frac{\partial v}{\partial x_i} = v_{i,i}.$$

Note: $v[i].dx(i)$ and $v_{i,i}$ with compact notation denote implicit summation.

Compound spatial derivatives

UFL implements several common differential operators. The notation is simple and their names should be self-explanatory:

```
Df = grad(f)
df = div(f)
cf = curl(v)
rf = rot(f)
```

The operand f can have no free indices.

Gradient

The gradient of a scalar u is defined as

$$\text{grad}(u) \equiv \nabla u = \sum_{k=0}^{d-1} \frac{\partial u}{\partial x_k} \mathbf{i}_k,$$

which is a vector of all spatial partial derivatives of u .

The gradient of a vector \mathbf{v} is defined as

$$\text{grad}(\mathbf{v}) \equiv \nabla \mathbf{v} = \frac{\partial v_i}{\partial x_j} \mathbf{i}_i \mathbf{i}_j,$$

which, written componentwise, reads

$$\mathbf{A} = \nabla \mathbf{v}, \quad A_{ij} = v_{i,j}$$

In general for a tensor \mathbf{A} of rank r the definition is

$$\text{grad}(\mathbf{A}) \equiv \nabla \mathbf{A} = \left(\frac{\partial}{\partial x_i} \right) (A_\iota \mathbf{i}_{\iota_0} \otimes \cdots \otimes \mathbf{i}_{\iota_{r-1}}) \otimes \mathbf{i}_i = \frac{\partial A_\iota}{\partial x_i} \mathbf{i}_{\iota_0} \otimes \cdots \otimes \mathbf{i}_{\iota_{r-1}} \otimes \mathbf{i}_i,$$

where ι is a multi-index of length r .

In UFL, the following pairs of declarations are equivalent:

```
Dfi = grad(f)[i]
Dfi = f.dx(i)

Dvi = grad(v)[i, j]
Dvi = v[i].dx(j)

DAi = grad(A)[..., i]
DAi = A.dx(i)
```

for a scalar expression f , a vector expression v , and a tensor expression A of arbitrary rank.

Divergence

The divergence of any nonscalar (vector or tensor) expression \mathbf{A} is defined as the contraction of the partial derivative over the last axis of the expression.

The divergence of a vector \mathbf{v} is defined as

$$\text{div}(\mathbf{v}) \equiv \nabla \cdot \mathbf{v} = \sum_{k=0}^{d-1} \frac{\partial v_i}{\partial x_i}$$

In UFL, the following declarations are equivalent:

```
dv = div(v)
dv = v[i].dx(i)

dA = div(A)
dA = A[..., i].dx(i)
```

for a vector expression v and a tensor expression A .

Curl and rot

The operator `curl` or `rot` accepts as argument a vector-valued expression and returns its curl

$$\text{curl}(\mathbf{v}) = \nabla \times \mathbf{v} = \left(\frac{\partial v_2}{\partial x_1} - \frac{\partial v_1}{\partial x_2}, \frac{\partial v_0}{\partial x_2} - \frac{\partial v_2}{\partial x_0}, \frac{\partial v_1}{\partial x_0} - \frac{\partial v_0}{\partial x_1} \right).$$

Note: The `curl` or `rot` operator is only defined for vectors of length three.

In UFL, the following declarations are equivalent:

```
omega = curl(v)
omega = rot(v)
```

Variable derivatives

UFL also supports differentiation with respect to user defined variables. A user defined variable can be any expression that is defined as a variable.

The notation is illustrated here:

```
# Define some arbitrary expression
u = Coefficient(element)
w = sin(u**2)

# Annotate expression w as a variable that can be used by "diff"
w = variable(w)

# This expression is a function of w
F = w***2

# The derivative of expression F w.r.t. the variable w
dF = diff(F, w) # == 2*w
```

Note that the variable w still represents the same expression.

This can be useful for example to implement material laws in hyperelasticity where the stress tensor is derived from a Helmholtz strain energy function.

Currently, UFL does not implement time in any particular way, but differentiation w.r.t. time can be done without this support through the use of a constant variable t :

```
t = variable(Constant(cell))
f = sin(x[0])**2 * cos(t)
dfdt = diff(f, t)
```

Functional derivatives

The third and final kind of derivative are derivatives of functionals or forms w.r.t. to a `Coefficient`. This is described in more detail in the section [AD](#) about form transformations.

DG operators

UFL provides operators for implementation of discontinuous Galerkin methods. These include the evaluation of the jump and average of a function (or in general an expression) over the interior facets (edges or faces) of a mesh.

Restriction: `v('+'')` and `v(''-')`

When integrating over interior facets (`*dS`), one may restrict expressions to the positive or negative side of the facet:

```
element = FiniteElement("Discontinuous Lagrange", tetrahedron, 0)

v = TestFunction(element)
u = TrialFunction(element)

f = Coefficient(element)

a = f('+'')*dot(grad(v)('+''), grad(u)(''-'))*dS
```

Restriction may be applied to functions of any finite element space but will only have effect when applied to expressions that are discontinuous across facets.

Jump: `jump(v)`

The operator `jump` may be used to express the jump of a function across a common facet of two cells. Two versions of the `jump` operator are provided.

If called with only one argument, then the `jump` operator evaluates to the difference between the restrictions of the given expression on the positive and negative sides of the facet:

$$\text{jump}(v) \leftrightarrow [[v]] = v^+ - v^-$$

If the expression `v` is scalar, then `jump(v)` will also be scalar, and if `v` is vector-valued, then `jump(v)` will also be vector-valued.

If called with two arguments, `jump(v, n)` evaluates to the jump in `v` weighted by `n`. Typically, `n` will be chosen to represent the unit outward normal of the facet (as seen from each of the two neighboring cells). If `v` is scalar, then `jump(v, n)` is given by

$$\text{jump}(v, n) \leftrightarrow [[v]]_n = v^+ n^+ + v^- n^-$$

If `v` is vector-valued, then `jump(v, n)` is given by

$$\text{jump}(v, n) \leftrightarrow [[v]]_n = v^+ \cdot n^+ + v^- \cdot n^-$$

Thus, if the expression `v` is scalar, then `jump(v, n)` will be vector-valued, and if `v` is vector-valued, then `jump(v, n)` will be scalar.

Average: avg (v)

The operator `avg` may be used to express the average of an expression across a common facet of two cells:

$$\text{avg}(v) \leftrightarrow [[v]] = \frac{1}{2}(v^+ + v^-)$$

The expression `avg (v)` has the same value shape as the expression `v`.

Conditional Operators

Conditional

UFL has limited support for branching, but for some PDEs it is needed. The expression `c` in:

```
c = conditional(condition, true_value, false_value)
```

evaluates to `true_value` at run-time if `condition` evaluates to true, or to `false_value` otherwise.

This corresponds to the C++ syntax (`condition ? true_value : false_value`), or the Python syntax (`true_value if condition else false_value`).

Conditions

- `eq(a, b)` must be used in place of the notation `a == b`
- `ne(a, b)` must be used in place of the notation `a != b`
- `le(a, b)` is equivalent to `a <= b`
- `ge(a, b)` is equivalent to `a >= b`
- `lt(a, b)` is equivalent to `a < b`
- `gt(a, b)` is equivalent to `a > b`

Note: Because of details in the way Python behaves, we cannot overload the `==` operator, hence these named operators.

User-defined operators

A user may define new operators, using standard Python syntax. As an example, consider the strain-rate operator ϵ of linear elasticity, defined by

$$\epsilon(v) = \frac{1}{2}(\nabla v + (\nabla v)^\top).$$

This operator can be implemented as a function using the Python `def` keyword:

```
def epsilon(v):
    return 0.5*(grad(v) + grad(v).T)
```

Alternatively, using the shorthand `lambda` notation, the strain operator may be defined as follows:

```
epsilon = lambda v: 0.5*(grad(v) + grad(v).T)
```

Form Transformations

When you have defined a `Form`, you can derive new related forms from it automatically. UFL defines a set of common form transformations described in this section.

Replacing arguments of a Form

The function `replace` lets you replace terminal objects with other values, using a mapping defined by a Python dictionary. This can be used for example to replace a `Coefficient` with a fixed value for optimized runtime evaluation.

Example:

```
f = Coefficient(element)
g = Coefficient(element)
c = Constant(cell)
a = f*g*v*dx
b = replace(a, { f: 3.14, g: c })
```

The replacement values must have the same basic properties as the original values, in particular value shape and free indices.

Action of a form on a function

The action of a bilinear form a is defined as

$$b(v; w) = a(v, w)$$

The action of a linear form L is defined as

$$f(w) = L(w)$$

This operation is implemented in UFL simply by replacing the rightmost basis function (trial function for a , test function for L) in a `Form`, and is used like this:

```
L = action(a, w)
f = action(L, w)
```

To give a concrete example, these declarations are equivalent:

```
a = inner(grad(u), grad(v)) * dx
L = action(a, w)

a = inner(grad(u), grad(v)) * dx
L = inner(grad(w), grad(v)) * dx
```

If a is a rank 2 form used to assemble the matrix A , L is a rank 1 form that can be used to assemble the vector $b = Ax$ directly. This can be used to define both the form of a matrix and the form of its action without code duplication, and for the action of a Jacobi matrix computed using derivative.

If L is a rank 1 form used to assemble the vector b , f is a functional that can be used to assemble the scalar value $f = b \cdot w$ directly. This operation is sometimes used in, e.g., error control with L being the residual equation and w

being the solution to the dual problem. (However, the discrete vector for the assembled residual equation will typically be available, so doing the dot product using linear algebra would be faster than using this feature.)

Energy norm of a bilinear form

The functional representing the energy norm $|v|_A = v^T A v$ of a matrix A assembled from a form a can be computed with:

```
f = energy_norm(a, w)
```

which is equivalent to:

```
f = action(action(a, w), w)
```

Adjoint of a bilinear form

The adjoint a' of a bilinear form a is defined as

$$a'(u, v) = a(v, u).$$

This operation is implemented in UFL simply by swapping test and trial functions in a `Form`, and is used like this:

```
aprime = adjoint(a)
```

Linear and bilinear parts of a form

Sometimes it is useful to write an equation on the format

$$a(v, u) - L(v) = 0.$$

Before assembly, we need to extract the forms corresponding to the left hand side and right hand side. This corresponds to extracting the bilinear and linear terms of the form respectively, or separating the terms that depend on both a test and a trial function on one side and the terms that depend on only a test function on the other.

This is easily done in UFL using `lhs` and `rhs`:

```
b = u*v*dx - f*v*dx
a, L = lhs(b), rhs(b)
```

Note that `rhs` multiplies the extracted terms by -1, corresponding to moving them from left to right, so this is equivalent to

```
a = u*v*dx
L = f*v*dx
```

As a slightly more complicated example, this formulation:

```
F = v*(u - w)*dx + k*dot(grad(v), grad(0.5*(w + u)))*dx
a, L = lhs(F), rhs(F)
```

is equivalent to

```
a = v*u*dx + k*dot(grad(v), 0.5*grad(u))*dx
L = v*w*dx - k*dot(grad(v), 0.5*grad(w))*dx
```

Automatic functional differentiation

UFL can compute derivatives of functionals or forms w.r.t. to a `Coefficient`. This functionality can be used for example to linearize your nonlinear residual equation automatically, or derive a linear system from a functional, or compute sensitivity vectors w.r.t. some coefficient.

A functional can be differentiated to obtain a linear form,

$$F(v; w) = \frac{d}{dw} f(v; w)$$

and a linear form can be differentiated to obtain the bilinear form corresponding to its Jacobi matrix.

Note: Note that by “linear form” we only mean a form that is linear in its test function, not in the function you differentiate with respect to.

$$J(v, u; w) = \frac{d}{dw} F(v; w).$$

The UFL code to express this is (for a simple functional $f(w) = \int_{\Omega} \frac{1}{2}w^2 dx$)

```
f = (w**2)/2 * dx
F = derivative(f, w, v)
J = derivative(F, w, u)
```

which is equivalent to

```
f = (w**2)/2 * dx
F = w*v*dx
J = u*v*dx
```

Assume in the following examples that

```
v = TestFunction(element)
u = TrialFunction(element)
w = Coefficient(element)
```

The stiffness matrix can be computed from the functional $\int_{\Omega} \nabla w : \nabla w dx$, by

```
f = inner(grad(w), grad(w))/2 * dx
F = derivative(f, w, v)
J = derivative(F, w, u)
```

which is equivalent to

```
f = inner(grad(w), grad(w))/2 * dx
F = inner(grad(w), grad(v)) * dx
J = inner(grad(u), grad(v)) * dx
```

Note that here the basis functions are provided explicitly, which is sometimes necessary, e.g., if part of the form is linearized manually as in

```

g = Coefficient(element)
f = inner(grad(w), grad(w)) * dx
F = derivative(f, w, v) + dot(w-g, v) * dx
J = derivative(F, w, u)

```

Derivatives can also be computed w.r.t. functions in mixed spaces. Consider this example, an implementation of the harmonic map equations using automatic differentiation:

```

X = VectorElement("Lagrange", cell, 1)
Y = FiniteElement("Lagrange", cell, 1)

x = Coefficient(X)
y = Coefficient(Y)

L = inner(grad(x), grad(x)) * dx + dot(x, x) * y * dx

F = derivative(L, (x,y))
J = derivative(F, (x,y))

```

Here L is defined as a functional with two coefficient functions x and y from separate finite element spaces. However, F and J become linear and bilinear forms respectively with basis functions defined on the mixed finite element

```
M = X + Y
```

There is a subtle difference between defining x and y separately and this alternative implementation (reusing the elements X, Y, M):

```

u = Coefficient(M)
x, y = split(u)

L = inner(grad(x), grad(x)) * dx + dot(x, x) * y * dx

F = derivative(L, u)
J = derivative(F, u)

```

The difference is that the forms here have *one* coefficient function u in the mixed space, and the forms above have *two* coefficient functions x and y .

Combining form transformations

Form transformations can be combined freely. Note that, to do this, derivatives are usually evaluated before applying (e.g.) the action of a form, because `derivative` changes the arity of the form:

```

element = FiniteElement("CG", cell, 1)
w = Coefficient(element)
f = w**4/4*dx(0) + inner(grad(w), grad(w)) * dx(1)
F = derivative(f, w)
J = derivative(F, w)
Ja = action(J, w)
Jp = adjoint(J)
Jpa = action(Jp, w)
g = Coefficient(element)
Jnorm = energy_norm(J, g)

```

Form files

UFL forms and elements can be collected in a *form file* with the extension `.ufl`. Form compilers will typically execute this file with the global UFL namespace available, and extract forms and elements that are defined after execution. The compilers do not compile all forms and elements that are defined in file, but only those that are “exported”. A finite element with the variable name `element` is exported by default, as are forms with the names `M`, `L`, and `a`. The default form names are intended for a functional, linear form, and bilinear form respectively.

To export multiple forms and elements or use other names, an explicit list with the forms and elements to export can be defined. Simply write

```
elements = [V, P, TH]
forms = [a, L, F, J, L2, H1]
```

at the end of the file to export the elements and forms held by these variables.

1.2.3 Example forms

The following examples illustrate basic usage of the form language for the definition of a collection of standard multilinear forms. We assume that `dx` has been declared as an integral over the interior of Ω and that both `i` and `j` have been declared as a free Index.

The examples presented below can all be found in the subdirectory `demo/` of the UFL source tree together with numerous other examples.

The mass matrix

As a first example, consider the bilinear form corresponding to a mass matrix,

$$a(v, u) = \int_{\Omega} v u \, dx,$$

which can be implemented in UFL as follows:

```
element = FiniteElement("Lagrange", triangle, 1)

v = TestFunction(element)
u = TrialFunction(element)

a = v*u*dx
```

This example is implemented in the file `Mass.ufl` in the collection of demonstration forms included with the UFL source distribution.

Poisson equation

The bilinear and linear forms form for Poisson’s equation,

$$\begin{aligned} a(v, u) &= \int_{\Omega} \nabla v \cdot \nabla u \, dx, \\ L(v; f) &= \int_{\Omega} v f \, dx, \end{aligned}$$

can be implemented as follows:

```

element = FiniteElement("Lagrange", triangle, 1)

v = TestFunction(element)
u = TrialFunction(element)
f = Coefficient(element)

a = dot(grad(v), grad(u)) * dx
L = v*f*dx

```

Alternatively, index notation can be used to express the scalar product like this:

```
a = Dx(v, i)*Dx(u, i)*dx
```

or like this:

```
a = v.dx(i)*u.dx(i)*dx
```

This example is implemented in the file `Poisson.ufl` in the collection of demonstration forms included with the UFL source distribution.

Vector-valued Poisson

The bilinear and linear forms for a system of (independent) Poisson equations,

$$a(v, u) = \int_{\Omega} \nabla v : \nabla u \, dx,$$

$$L(v; f) = \int_{\Omega} v \cdot f \, dx,$$

with v , u and f vector-valued can be implemented as follows:

```

element = VectorElement("Lagrange", triangle, 1)

v = TestFunction(element)
u = TrialFunction(element)
f = Coefficient(element)

a = inner(grad(v), grad(u)) * dx
L = dot(v, f) * dx

```

Alternatively, index notation may be used like this:

```
a = Dx(v[i], j)*Dx(u[i], j)*dx
L = v[i]*f[i]*dx
```

or like this:

```
a = v[i].dx(j)*u[i].dx(j)*dx
L = v[i]*f[i]*dx
```

This example is implemented in the file `PoissonSystem.ufl` in the collection of demonstration forms included with the UFL source distribution.

The strain-strain term of linear elasticity

The strain-strain term of linear elasticity,

$$a(v, u) = \int_{\Omega} \epsilon(v) : \epsilon(u) dx,$$

where

$$\epsilon(v) = \frac{1}{2}(\nabla v + (\nabla v)^T)$$

can be implemented as follows:

```
element = VectorElement("Lagrange", tetrahedron, 1)

v = TestFunction(element)
u = TrialFunction(element)

def epsilon(v):
    Dv = grad(v)
    return 0.5*(Dv + Dv.T)

a = inner(epsilon(v), epsilon(u))*dx
```

Alternatively, index notation can be used to define the form:

```
a = 0.25*(Dx(v[j], i) + Dx(v[i], j)) * \
(Dx(u[j], i) + Dx(u[i], j)) *dx
```

or like this:

```
a = 0.25*(v[j].dx(i) + v[i].dx(j)) * \
(u[j].dx(i) + u[i].dx(j)) *dx
```

This example is implemented in the file `Elasticity.ufl` in the collection of demonstration forms included with the UFL source distribution.

The nonlinear term of Navier–Stokes

The bilinear form for fixed-point iteration on the nonlinear term of the incompressible Navier–Stokes equations,

$$a(v, u; w) = \int_{\Omega} (w \cdot \nabla u) \cdot v dx,$$

with w the frozen velocity from a previous iteration, can be implemented as follows:

```
element = VectorElement("Lagrange", tetrahedron, 1)

v = TestFunction(element)
u = TrialFunction(element)
w = Coefficient(element)

a = dot(grad(u)*w, v)*dx
```

alternatively using index notation like this:

```
a = v[i]*w[j]*Dx(u[i], j)*dx
```

or like this:

```
a = v[i]*w[j]*u[i].dx(j)*dx
```

This example is implemented in the file `NavierStokes.ufl` in the collection of demonstration forms included with the UFL source distribution.

The heat equation

Discretizing the heat equation,

$$\dot{u} - \nabla \cdot (c \nabla u) = f,$$

in time using the dG(0) method (backward Euler), we obtain the following variational problem for the discrete solution $u_h = u_h(x, t)$: Find $u_h^n = u_h(\cdot, t_n)$ with $u_h^{n-1} = u_h(\cdot, t_{n-1})$ given such that

$$\frac{1}{k_n} \int_{\Omega} v (u_h^n - u_h^{n-1}) dx + \int_{\Omega} c \nabla v \cdot \nabla u_h^n dx = \int_{\Omega} v f^n dx$$

for all test functions v , where $k_n = t_n - t_{n-1}$ denotes the time step. In the example below, we implement this variational problem with piecewise linear test and trial functions, but other choices are possible (just choose another finite element).

Rewriting the variational problem in the standard form $a(v, u_h) = L(v)$ for all v , we obtain the following pair of bilinear and linear forms:

$$a(v, u_h^n; c, k) = \int_{\Omega} v u_h^n dx + k_n \int_{\Omega} c \nabla v \cdot \nabla u_h^n dx,$$

$$L(v; u_h^{n-1}, f, k) = \int_{\Omega} v u_h^{n-1} dx + k_n \int_{\Omega} v f^n dx,$$

which can be implemented as follows:

```
element = FiniteElement("Lagrange", triangle, 1)

v = TestFunction(element) # Test function
u1 = TrialFunction(element) # Value at t_n
u0 = Coefficient(element) # Value at t_{n-1}
c = Coefficient(element) # Heat conductivity
f = Coefficient(element) # Heat source
k = Constant("triangle") # Time step

a = v*u1*dx + k*c*dot(grad(v), grad(u1))*dx
L = v*u0*dx + k*v*f*dx
```

This example is implemented in the file `Heat.ufl` in the collection of demonstration forms included with the UFL source distribution.

Mixed formulation of Stokes

To solve Stokes' equations,

$$-\Delta u + \nabla p = f,$$

$$\nabla \cdot u = 0,$$

we write the variational problem in standard form $a(v, u) = L(v)$ for all v to obtain the following pair of bilinear and linear forms:

$$a((v, q), (u, p)) = \int_{\Omega} \nabla v : \nabla u - (\nabla \cdot v) p + q (\nabla \cdot u) dx,$$

$$L((v, q); f) = \int_{\Omega} v \cdot f dx.$$

Using a mixed formulation with Taylor-Hood elements, this can be implemented as follows:

```
cell = triangle
P2 = VectorElement("Lagrange", cell, 2)
P1 = FiniteElement("Lagrange", cell, 1)
TH = P2 * P1

(v, q) = TestFunctions(TH)
(u, p) = TrialFunctions(TH)

f = Coefficient(P2)

a = (inner(grad(v), grad(u)) - div(v)*p + q*div(u))*dx
L = dot(v, f)*dx
```

This example is implemented in the file `Stokes.ufl` in the collection of demonstration forms included with the UFL source distribution.

Mixed formulation of Poisson

We next consider the following formulation of Poisson's equation as a pair of first order equations for $\sigma \in H(\text{div})$ and $u \in L^2$:

$$\begin{aligned} \sigma + \nabla u &= 0, \\ \nabla \cdot \sigma &= f. \end{aligned}$$

We multiply the two equations by a pair of test functions τ and w and integrate by parts to obtain the following variational problem: Find $(\sigma, u) \in V = H(\text{div}) \times L^2$ such that

$$a((\tau, w), (\sigma, u)) = L((\tau, w)) \quad \forall (\tau, w) \in V,$$

where

$$a((\tau, w), (\sigma, u)) = \int_{\Omega} \tau \cdot \sigma - \nabla \cdot \tau u + w \nabla \cdot \sigma dx,$$

$$L((\tau, w); f) = \int_{\Omega} w \cdot f dx.$$

We may implement the corresponding forms in our form language using first order BDM $H(\text{div})$ -conforming elements for σ and piecewise constant L^2 -conforming elements for u as follows:

```
cell = triangle
BDM1 = FiniteElement("Brezzi-Douglas-Marini", cell, 1)
DGO = FiniteElement("Discontinuous Lagrange", cell, 0)

element = BDM1 * DGO

(tau, w) = TestFunctions(element)
```

(continues on next page)

(continued from previous page)

```
(sigma, u) = TrialFunctions(element)
f = Coefficient(DG0)
a = (dot(tau, sigma) - div(tau)*u + w*div(sigma))*dx
L = w*f*dx
```

This example is implemented in the file `MixedPoisson.ufl` in the collection of demonstration forms included with the UFL source distribution.

Poisson equation with DG elements

We consider again Poisson's equation, but now in an (interior penalty) discontinuous Galerkin formulation: Find $u \in V = L^2$ such that

$$a(v, u) = L(v) \quad \forall v \in V,$$

where

$$\begin{aligned} a(v, u; h) &= \int_{\Omega} \nabla v \cdot \nabla u \, dx \\ &\quad + \sum_S \int_S -\langle \nabla v \rangle \cdot [[u]]_n - [[v]]_n \cdot \langle \nabla u \rangle + (\alpha/h)[[v]]_n \cdot [[u]]_n \, dS \\ &\quad + \int_{\partial\Omega} -\nabla v \cdot [[u]]_n - [[v]]_n \cdot \nabla u + (\gamma/h)v u \, ds \\ L(v; f, g) &= \int_{\Omega} vf \, dx + \int_{\partial\Omega} vg \, ds. \end{aligned}$$

The corresponding finite element variational problem for discontinuous first order elements may be implemented as follows:

```
cell = triangle
DG1 = FiniteElement("Discontinuous Lagrange", cell, 1)

v = TestFunction(DG1)
u = TrialFunction(DG1)

f = Coefficient(DG1)
g = Coefficient(DG1)
h = 2.0*Circumradius(cell)
alpha = 1
gamma = 1

a = dot(grad(v), grad(u))*dx \
- dot(avg(grad(v)), jump(u))*ds \
- dot(jump(v), avg(grad(u)))*ds \
+ alpha/h(^+) *dot(jump(v), jump(u))*ds \
- dot(grad(v), jump(u))*ds \
- dot(jump(v), grad(u))*ds \
+ gamma/h*v*u*ds
L = v*f*dx + v*g*ds
```

This example is implemented in the file `PoissonDG.ufl` in the collection of demonstration forms included with the UFL source distribution.

The Quadrature family

We consider here a nonlinear version of the Poisson's equation to illustrate the main point of the Quadrature finite element family. The strong equation looks as follows:

$$-\nabla \cdot (1 + u^2) \nabla u = f.$$

The linearised bilinear and linear forms for this equation,

$$\begin{aligned} a(v, u; u_0) &= \int_{\Omega} (1 + u_0^2) \nabla v \cdot \nabla u \, dx + \int_{\Omega} 2u_0 u \nabla v \cdot \nabla u_0 \, dx, \\ L(v; u_0, f) &= \int_{\Omega} v f \, dx - \int_{\Omega} (1 + u_0^2) \nabla v \cdot \nabla u_0 \, dx, \end{aligned}$$

can be implemented in a single form file as follows:

```
element = FiniteElement("Lagrange", triangle, 1)

v = TestFunction(element)
u = TrialFunction(element)
u0 = Coefficient(element)
f = Coefficient(element)

a = (1+u0**2)*dot(grad(v), grad(u))*dx + 2*u0*u*dot(grad(v), grad(u0))*dx
L = v*f*dx - (1+u0**2)*dot(grad(v), grad(u0))*dx
```

Here, u_0 represents the solution from the previous Newton-Raphson iteration.

The above form will be denoted REF1 and serves as our reference implementation for linear elements. A similar form (REF2) using quadratic elements will serve as a reference for quadratic elements.

Now, assume that we want to treat the quantities $C = (1 + u_0^2)$ and $\sigma_0 = (1 + u_0^2) \nabla u_0$ as given functions (to be computed elsewhere). Substituting into the bilinear and linear forms, we obtain

$$\begin{aligned} a(v, u) &= \int_{\Omega} C \nabla v \cdot \nabla u \, dx + \int_{\Omega} 2u_0 u \nabla v \cdot \nabla u_0 \, dx, \\ L(v; \sigma_0, f) &= \int_{\Omega} v f \, dx - \int_{\Omega} \nabla v \cdot \sigma_0 \, dx. \end{aligned}$$

Then, two additional forms are created to compute the tangent C and the gradient of u_0 . This situation shows up in plasticity and other problems where certain quantities need to be computed elsewhere (in user-defined functions). The three forms using the standard `FiniteElement` (linear elements) can then be implemented as

```
# NonlinearPoisson.ufl
element = FiniteElement("Lagrange", triangle, 1)
DG = FiniteElement("Discontinuous Lagrange", triangle, 0)
sig = VectorElement("Discontinuous Lagrange", triangle, 0)

v     = TestFunction(element)
u     = TrialFunction(element)
u0    = Coefficient(element)
C     = Coefficient(DG)
sig0 = Coefficient(sig)
f     = Coefficient(element)

a = v.dx(i)*C*u.dx(i)*dx + v.dx(i)*2*u0*u*u0.dx(i)*dx
L = v*f*dx - dot(grad(v), sig0)*dx
```

and

```
# Tangent.ufl
element = FiniteElement("Lagrange", triangle, 1)
DG = FiniteElement("Discontinuous Lagrange", triangle, 0)

v = TestFunction(DG)
u = TrialFunction(DG)
u0= Coefficient(element)

a = v*u*dx
L = v*(1.0 + u0**2)*dx
```

and

```
# Gradient.ufl
element = FiniteElement("Lagrange", triangle, 1)
DG = VectorElement("Discontinuous Lagrange", triangle, 0)

v = TestFunction(DG)
u = TrialFunction(DG)
u0 = Coefficient(element)

a = dot(v, u)*dx
L = dot(v, (1.0 + u0**2)*grad(u0))*dx
```

The three forms can be implemented using the `QuadratureElement` in a similar fashion in which only the element declaration is different:

```
# QE1NonlinearPoisson.ufl
element = FiniteElement("Lagrange", triangle, 1)
QE = FiniteElement("Quadrature", triangle, 2)
sig = VectorElement("Quadrature", triangle, 2)
```

and

```
# QE1Tangent.ufl
element = FiniteElement("Lagrange", triangle, 1)
QE = FiniteElement("Quadrature", triangle, 2)
```

and

```
# QE1Gradient.ufl
element = FiniteElement("Lagrange", triangle, 1)
QE = VectorElement("Quadrature", triangle, 2)
```

Note that we use two points when declaring the `QuadratureElement`. This is because the RHS of `Tangent.form` is second order and therefore we need two points for exact integration. Due to consistency issues, when passing functions around between the forms, we also need to use two points when declaring the `QuadratureElement` in the other forms.

Typical values of the relative residual for each Newton iteration for all three approaches are shown in the table below. It is to be noted that the convergence rate is quadratic as it should be for all three methods.

Relative residuals for each approach for linear elements:

Iteration	REF1	FE1	QE1
=====	====	==	==
1	6.3e-02	6.3e-02	6.3e-02

(continues on next page)

(continued from previous page)

2	5.3e-04	5.3e-04	5.3e-04
3	3.7e-08	3.7e-08	3.7e-08
4	2.9e-16	2.9e-16	2.5e-16

However, if quadratic elements are used to interpolate the unknown field u , the order of all elements in the above forms is increased by 1. This influences the convergence rate as seen in the table below. Clearly, using the standard `FiniteElement` leads to a poor convergence whereas the `QuadratureElement` still leads to quadratic convergence.

Relative residuals for each approach for quadratic elements:

Iteration	REF2	FE2	QE2
1	2.6e-01	3.9e-01	2.6e-01
2	1.1e-02	4.6e-02	1.1e-02
3	1.2e-05	1.1e-02	1.6e-05
4	1.1e-11	7.2e-04	9.1e-09

More examples

Feel free to send additional demo form files for your favourite PDE to the UFL mailing list.

1.2.4 Internal representation details

This chapter explains how UFL forms and expressions are represented in detail. Most operations are mirrored by a representation class, e.g., `Sum` and `Product`, which are subclasses of `Expr`. You can import all of them from the submodule `ufl.classes` by

```
from ufl.classes import *
```

Structure of a form

Each `Form` owns multiple `Integral` instances, each associated with a different `Measure`. An `Integral` owns a `Measure` and an `Expr`, which represents the integrand expression. The `Expr` is the base class of all expressions. It has two direct subclasses `Terminal` and `Operator`.

Subclasses of `Terminal` represent atomic quantities which terminate the expression tree, e.g. they have no subexpressions. Subclasses of `Operator` represent operations on one or more other expressions, which may usually be `Expr` subclasses of arbitrary type. Different `Operators` may have restrictions on some properties of their arguments.

All the types mentioned here are conceptually immutable, i.e. they should never be modified over the course of their entire lifetime. When a modified expression, measure, integral, or form is needed, a new instance must be created, possibly sharing some data with the old one. Since the shared data is also immutable, sharing can cause no problems.

General properties of expressions

Any UFL expression has certain properties, defined by functions that every `Expr` subclass must implement. In the following, u represents an arbitrary UFL expression, i.e. an instance of an arbitrary `Expr` subclass.

operands

`u.operands()` returns a tuple with all the operands of `u`, which should all be `Expr` instances.

reconstruct

`u.reconstruct(operands)` returns a new `Expr` instance representing the same operation as `u` but with other operands. Terminal objects may simply return `self` since all `Expr` instances are immutable. An important invariant is that `u.reconstruct(u.operands()) == u`.

cell

`u.cell()` returns the first `Cell` instance found in `u`. It is currently assumed in UFL that no two different cells are used in a single form. Not all expression define a cell, in which case this returns `None` and `u` is spatially constant. Note that this property is used in some algorithms.

shape

`u.shape()` returns a tuple of integers, which is the tensor shape of `u`.

free_indices

`u.free_indices()` returns a tuple of `Index` objects, which are the unassigned, free indices of `u`.

index_dimensions

`u.index_dimensions()` returns a `dict` mapping from each `Index` instance in `u.free_indices()` to the integer dimension of the value space each index can range over.

str(u)

`str(u)` returns a human-readable string representation of `u`.

repr(u)

`repr(u)` returns a Python string representation of `u`, such that `eval(repr(u)) == u` holds in Python.

hash(u)

`hash(u)` returns a hash code for `u`, which is used extensively (indirectly) in algorithms whenever `u` is placed in a Python `dict` or `set`.

`u == v`

`u == v` returns true if and only if `u` and `v` represents the same expression in the exact same way. This is used extensively (indirectly) in algorithms whenever `u` is placed in a Python `dict` or `set`.

About other relational operators

In general, UFL expressions are not possible to fully evaluate since the cell and the values of form arguments are not available. Implementing relational operators for immediate evaluation is therefore impossible.

Overloading relational operators as a part of the form language is not possible either, since it interferes with the correct use of container types in Python like `dict` or `set`.

Elements

All finite element classes have a common base class `FiniteElementBase`. The class hierarchy looks like this:

TODO: Class figure. ... TODO: Describe all `FiniteElementBase` subclasses here.

Terminals

All `Terminal` subclasses have some non-`Expr` data attached to them. `ScalarValue` has a Python scalar, `Coefficient` has a `FiniteElement`, etc.

Therefore, a unified implementation of `reconstruct` is not possible, but since all `Expr` instances are immutable, `reconstruct` for terminals can simply return `self`. This feature and the immutability property is used extensively in algorithms.

Operators

All instances of `Operator` subclasses are fully specified by their type plus the tuple of `Expr` instances that are the operands. Their constructors should take these operands as the positional arguments, and only that. This way, a unified implementation of `reconstruct` is possible, by simply calling the constructor with new operands. This feature is used extensively in algorithms.

Extending UFL

Adding new types to the UFL class hierarchy must be done with care. If you can get away with implementing a new operator as a combination of existing ones, that is the easiest route. The reason is that only some of the properties of an operator is represented by the `Expr` subclass. Other properties are part of the various algorithms in UFL. One example is derivatives, which are defined in the differentiation algorithm, and how to render a type to the `LaTeX` or dot formats. These properties could be merged into the class hierarchy, but other properties like how to map a UFL type to some `ffc` or `dolfin` type cannot be part of UFL. So before adding a new class, consider that doing so may require changes in multiple algorithms and even other projects.

1.2.5 Algorithms

Algorithms to work with UFL forms and expressions can be found in the submodule `ufl.algorithms`. You can import all of them with the line

```
from ufl.algorithms import *
```

This chapter gives an overview of (most of) the implemented algorithms. The intended audience is primarily developers, but advanced users may find information here useful for debugging.

While domain specific languages introduce notation to express particular ideas more easily, which can reduce the probability of bugs in user code, they also add yet another layer of abstraction which can make debugging more difficult when the need arises. Many of the utilities described here can be useful in that regard.

Formatting expressions

Expressions can be formatted in various ways for inspection, which is particularly useful for debugging. We use the following as an example form for the formatting sections below:

```
element = FiniteElement("CG", triangle, 1)
v = TestFunction(element)
u = TrialFunction(element)
c = Coefficient(element)
f = Coefficient(element)
a = c*u*v*dx + f*v*ds
```

str

Compact, human readable pretty printing. Useful in interactive Python sessions. Example output of `str(a)`:

```
{ v_0 * v_1 * w_0 } * dx(<Mesh #1 with coordinates parameterized by <Lagrange vector
˓→element of degree 1 on a triangle: 2 x <CG1 on a triangle>>>[everywhere], {})
+ { v_0 * w_1 } * ds(<Mesh #1 with coordinates parameterized by <Lagrange vector
˓→element of degree 1 on a triangle: 2 x <CG1 on a triangle>>>[everywhere], {})
```

repr

Accurate description of an expression, with the property that `eval(repr(a)) == a`. Useful to see which representation types occur in an expression, especially if `str(a)` is ambiguous. Example output of `repr(a)`:

```
Form([Integral(Product(Argument(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle,
˓→1, dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 0, None),
˓→Product(Argument(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1, dim=2), -1),
˓→FiniteElement('Lagrange', triangle, 1)), 1, None),
˓→Coefficient(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1, dim=2), -1),
˓→FiniteElement('Lagrange', triangle, 1)), 0))), 'cell', Mesh(VectorElement('Lagrange
˓→', triangle, 1, dim=2), -1), 'everywhere', {}, None),
˓→Integral(Product(Argument(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1,
˓→dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 0, None),
˓→Coefficient(FunctionSpace(Mesh(VectorElement('Lagrange'), triangle, 1, dim=2), -1),
˓→FiniteElement('Lagrange', triangle, 1)), 1), 'exterior_facet', Mesh(VectorElement(
˓→'Lagrange', triangle, 1, dim=2), -1), 'everywhere', {}, None)])
```

Tree formatting

ASCII tree formatting, useful to inspect the tree structure of an expression in interactive Python sessions. Example output of `tree_format(a)`:

```
Form:
Integral:
    integral type: cell
    subdomain id: everywhere
    integrand:
        Product
        (
            Argument(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 0, None)
            Product
            (
                Argument(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 1, None)
                Coefficient(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 0)
            )
        )
    Integral:
        integral type: exterior_facet
        subdomain id: everywhere
        integrand:
            Product
            (
                Argument(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 0, None)
                Coefficient(FunctionSpace(Mesh(VectorElement('Lagrange', triangle, 1, dim=2), -1), FiniteElement('Lagrange', triangle, 1)), 1)
            )

```

Inspecting and manipulating the expression tree

This subsection is mostly for form compiler developers and technically interested users.

Traversing expressions

iter_expressions

Example usage:

```
for e in iter_expressions(a):
    print str(e)
```

outputs:

```
v_0 * v_1 * w_0
v_0 * w_1
```

Transforming expressions

So far we presented algorithms meant to inspect expressions in various ways. Some recurring patterns occur when writing algorithms to modify expressions, either to apply mathematical transformations or to change their representation. Usually, different expression node types need different treatment.

To assist in such algorithms, UFL provides the `Transformer` class. This implements a variant of the Visitor pattern to enable easy definition of transformation rules for the types you wish to handle.

Shown here is maybe the simplest transformer possible:

```
class Printer(Transformer):
    def __init__(self):
        Transformer.__init__(self)

    def expr(self, o, *operands):
        print "Visiting", str(o), "with operands:"
        print ", ".join(map(str,operands))
        return o

element = FiniteElement("CG", triangle, 1)
v = TestFunction(element)
u = TrialFunction(element)
a = u*v

p = Printer()
p.visit(a)
```

The call to `visit` will traverse `a` and call `Printer.expr` on all expression nodes in post-order, with the argument `operands` holding the return values from visits to the operands of `o`. The output is:

```
Visiting v_0 * v_1 with operands:
v_0, v_1
```

$$(v_h^0)(v_h^1)$$

Implementing `expr` above provides a default handler for any expression node type. For each subclass of `Expr` you can define a handler function to override the default by using the name of the type in underscore notation, e.g. `vector_constant` for `VectorConstant`. The constructor of `Transformer` and implementation of `Transformer.visit` handles the mapping from type to handler function automatically.

Here is a simple example to show how to override default behaviour:

```
from ufl.classes import *
class CoefficientReplacer(Transformer):
    def __init__(self):
        Transformer.__init__(self)

    expr = Transformer.reuse_if_possible
    terminal = Transformer.always_reuse

    def coefficient(self, o):
        return FloatValue(3.14)

element = FiniteElement("CG", triangle, 1)
v = TestFunction(element)
f = Coefficient(element)
a = f*v

r = CoefficientReplacer()
b = r.visit(a)
print b
```

which outputs

3.14 * v_0

The output of this code is the transformed expression `b == 3.14*v`. This code also demonstrates how to reuse existing handlers. The handler `Transformer.reuse_if_possible` will return the input object if the operands have not changed, and otherwise reconstruct a new instance of the same type but with the new transformed operands. The handler `Transformer.always_reuse` always reuses the instance without recursing into its children, usually applied to terminals. To set these defaults with less code, inherit `ReuseTransformer` instead of `Transformer`. This ensures that the parts of the expression tree that are not changed by the transformation algorithms will always reuse the same instances.

We have already mentioned the difference between pre-traversal and post-traversal, and some times you need to combine the two. `Transformer` makes this easy by checking the number of arguments to your handler functions to see if they take transformed operands as input or not. If a handler function does not take more than a single argument in addition to `self`, its children are not visited automatically, and the handler function must call `visit` on its operands itself.

Here is an example of mixing pre- and post-traversal:

```
class Traverser(ReuseTransformer):
    def __init__(self):
        ReuseTransformer.__init__(self)

    def sum(self, o):
        operands = o.operands()
        newoperands = []
        for e in operands:
            newoperands.append( self.visit(e) )
        return sum(newoperands)

element = FiniteElement("CG", triangle, 1)
f = Coefficient(element)
g = Coefficient(element)
h = Coefficient(element)
a = f+g+h

r = Traverser()
b = r.visit(a)
print b
```

This code inherits the `ReuseTransformer` as explained above, so the default behaviour is to recurse into children first and then call `Transformer.reuse_if_possible` to reuse or reconstruct each expression node. Since `sum` only takes `self` and the expression node instance `o` as arguments, its children are not visited automatically, and `sum` explicitly calls `self.visit` to do this.

Automatic differentiation implementation

This subsection is mostly for form compiler developers and technically interested users.

First of all, we give a brief explanation of the algorithm. Recall that a `Coefficient` represents a sum of unknown coefficients multiplied with unknown basis functions in some finite element space.

$$w(x) = \sum_k w_k \phi_k(x)$$

Also recall that an `Argument` represents any (unknown) basis function in some finite element space.

$$v(x) = \phi_k(x), \quad \phi_k \in V_h.$$

A form $L(v; w)$ implemented in UFL is intended for discretization like

$$b_i = L(\phi_i; \sum_k w_k \phi_k), \quad \forall \phi_i \in V_h.$$

The Jacobi matrix A_{ij} of this vector can be obtained by differentiation of b_i w.r.t. w_j , which can be written

$$A_{ij} = \frac{db_i}{dw_j} = a(\phi_i, \phi_j; \sum_k w_k \phi_k), \quad \forall \phi_i \in V_h, \quad \forall \phi_j \in V_h,$$

for some form a . In UFL, the form a can be obtained by differentiating L . To manage this, we note that as long as the domain Ω is independent of w_j , \int_Ω commutes with $\frac{d}{dw_j}$, and we can differentiate the integrand expression instead, e.g.,

$$\begin{aligned} L(v; w) &= \int_\Omega I_c(v; w) dx + \int_{\partial\Omega} I_e(v; w) ds, \\ \frac{d}{dw_j} L(v; w) &= \int_\Omega \frac{dI_c}{dw_j} dx + \int_{\partial\Omega} \frac{dI_e}{dw_j} ds. \end{aligned}$$

In addition, we need that

$$\frac{dw}{dw_j} = \phi_j, \quad \forall \phi_j \in V_h,$$

which in UFL can be represented as

$$\begin{aligned} w &= \text{Coefficient(element)}, \\ v &= \text{Argument(element)}, \\ \frac{dw}{dw_j} &= v, \end{aligned}$$

since w represents the sum and v represents any and all basis functions in V_h .

Other operators have well defined derivatives, and by repeatedly applying the chain rule we can differentiate the integrand automatically.

Computational graphs

This section is for form compiler developers and is probably of no interest to end-users.

An expression tree can be seen as a directed acyclic graph (DAG). To aid in the implementation of form compilers, UFL includes tools to build a linearized¹ computational graph from the abstract expression tree.

A graph can be partitioned into subgraphs based on dependencies of subexpressions, such that a quadrature based compiler can easily place subexpressions inside the right sets of loops.

The computational graph

Consider the expression

$$f = (a + b) * (c + d)$$

where a, b, c, d are arbitrary scalar expressions. The *expression tree* for f looks like this:

¹ Linearized as in a linear datastructure, do not confuse this with automatic differentiation.

```

a   b   c   d
\   /   \   /
+   +   +
\   /
*

```

In UFL f is represented like this expression tree. If a, b, c, d are all distinct Coefficient instances, the UFL representation will look like this:

```

Coefficient   Coefficient   Coefficient   Coefficient
      \       /           \       /
      Sum     Sum
      \       /
--- Product ---

```

If we instead have the expression

$$f = (a + b) * (a - b)$$

the tree will in fact look like this, with the functions a and b only represented once:

```

Coefficient   Coefficient
|   \   /   |
|   Sum   Product -- IntValue(-1)
|   |
|   Product   |
|   |
|----- Sum -----|

```

The expression tree is a directed acyclic graph (DAG) where the vertices are Expr instances and each edge represents a direct dependency between two vertices, i.e. that one vertex is among the operands of another. A graph can also be represented in a linearized data structure, consisting of an array of vertices and an array of edges. This representation is convenient for many algorithms. An example to illustrate this graph representation follows:

```

G = V, E
V = [a, b, a+b, c, d, c+d, (a+b)*(c+d)]
E = [(6,2), (6,5), (5,3), (5,4), (2,0), (2,1)]

```

In the following, this representation of an expression will be called the *computational graph*. To construct this graph from a UFL expression, simply do

```

G = Graph(expression)
V, E = G

```

The Graph class can build some useful data structures for use in algorithms:

```

Vin = G.Vin() # Vin[i] = list of vertex indices j such that there is an edge from  $\textcolor{red}{V[j]}$  to  $\textcolor{blue}{V[i]}$ 
Vout = G.Vout() # Vout[i] = list of vertex indices j such that there is an edge from  $\textcolor{blue}{V[i]}$  to  $\textcolor{red}{V[j]}$ 
Ein = G.Ein() # Ein[i] = list of edge indices j such that  $E[j]$  is an edge to  $V[i]$ , e.g.  $E[j][1] == i$ 
Eout = G.Eout() # Eout[i] = list of edge indices j such that  $E[j]$  is an edge from  $V[i]$ , e.g.  $E[j][0] == i$ 

```

The ordering of the vertices in the graph can in principle be arbitrary, but here they are ordered such that

$$v_i \prec v_j, \quad \forall j > i,$$

where $a \prec b$ means that a does not depend on b directly or indirectly.

Another property of the computational graph built by UFL is that no identical expression is assigned to more than one vertex. This is achieved efficiently by inserting expressions in a dict (a hash map) during graph building.

In principle, correct code can be generated for an expression from its computational graph simply by iterating over the vertices and generating code for each one separately. However, we can do better than that.

Partitioning the graph

To help generate better code efficiently, we can partition vertices by their dependencies, which allows us to, e.g., place expressions outside the quadrature loop if they don't depend (directly or indirectly) on the spatial coordinates. This is done simply by

```
P = partition(G)
```

1.2.6 Commandline utilities

See installed version: `ufl-analyse`

Run

```
# ufl-version
```

to see the currently installed version of UFL printed to the terminal.

Validation and debugging: `ufl-analyse`

The command `ufl-analyse` loads all forms found in a `.ufl` file, tries to discover any errors in them, and prints various kinds of information about each form. Basic usage is

```
# ufl-analyse myform.ufl
```

For more information, type

```
# ufl-analyse --help
```

Note: This script is not well maintained, you will likely get more useful information from your form compiler.

Formatting and visualization: `ufl-convert`

The command `ufl-convert` loads all forms found in a `.ufl` file, compiles them into a different form or extracts some information from them, and writes the result in a suitable file format.

To try this tool, go to the `demo/` directory of the UFL source tree. Some of the features to try are basic printing of `str` and `repr` string representations of each form:

```
# ufl-convert --format=str stiffness.ufl
# ufl-convert --format=repr stiffness.ufl
```

compilation of forms to mathematical notation in LaTeX:

```
# ufl-convert --filetype=pdf --format=tex --show=1 stiffness.ufl
```

LaTeX output of forms after processing with UFL compiler utilities:

```
# ufl-convert -tpdf -ftex -s1 --compile=1 stiffness.ufl
```

and visualization of expression trees using graphviz via compilation of forms to the dot format:

```
# ufl-convert -tpdf -fdot -s1 stiffness.ufl
```

Type `ufl-convert --help` for more details.

1.3 ufl package

1.3.1 Subpackages

`ufl.algorithms` package

Submodules

`ufl.algorithms.ad` module

Front-end for AD routines.

`ufl.algorithms.ad.expand_derivatives(form, **kwargs)`
Expand all derivatives of `expr`.

In the returned expression `g` which is mathematically equivalent to `expr`, there are no `VariableDerivative` or `CoefficientDerivative` objects left, and `Grad` objects have been propagated to Terminal nodes.

`ufl.algorithms.analysis` module

Utility algorithms for inspection of and information extraction from UFL objects in various ways.

`ufl.algorithms.analysis.extract_arguments(a)`
Build a sorted list of all arguments in `a`, which can be a Form, Integral or Expr.

`ufl.algorithms.analysis.extract_arguments_and_coefficients(a)`
Build two sorted lists of all arguments and coefficients in `a`, which can be a Form, Integral or Expr.

`ufl.algorithms.analysis.extract_coefficients(a)`
Build a sorted list of all coefficients in `a`, which can be a Form, Integral or Expr.

`ufl.algorithms.analysis.extract_elements(form)`
Build sorted tuple of all elements used in `form`.

`ufl.algorithms.analysis.extract_sub_elements(elements)`
Build sorted tuple of all sub elements (including parent element).

`ufl.algorithms.analysis.extract_type(a, ufl_type)`
Build a set of all objects of class `ufl_type` found in `a`. The argument `a` can be a Form, Integral or Expr.

`ufl.algorithms.analysis.extract_unique_elements(form)`
Build sorted tuple of all unique elements used in `form`.

`ufl.algorithms.analysis.has_exact_type(a, ufl_type)`

Return if an object of class `ufl_type` can be found in `a`. The argument `a` can be a Form, Integral or Expr.

`ufl.algorithms.analysis.has_type(a, ufl_type)`

Return if an object of class `ufl_type` can be found in `a`. The argument `a` can be a Form, Integral or Expr.

`ufl.algorithms.analysis.sort_elements(elements)`

Sort elements so that any sub elements appear before the corresponding mixed elements. This is useful when sub elements need to be defined before the corresponding mixed elements.

The ordering is based on sorting a directed acyclic graph.

`ufl.algorithms.analysis.unique_tuple(objects)`

Return tuple of unique objects, preserving initial ordering.

ufl.algorithms.apply_algebra_lowering module

Algorithm for expanding compound expressions into equivalent representations using basic operators.

`class ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra`

Bases: `ufl.corealg.multifunction.MultiFunction`

Expands high level compound operators (e.g. `inner`) to equivalent representations using basic operators (e.g. index notation).

`alternative_dot(o, a, b)`

`alternative_inner(o, a, b)`

`cofactor(o, A)`

`cross(o, a, b)`

`curl(o, a)`

`determinant(o, A)`

`deviatoric(o, A)`

`div(o, a)`

`dot(o, a, b)`

`expr(o, *ops)`

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_un触ched
```

as a default rule.

`inner(o, a, b)`

`inverse(o, A)`

`nabla_div(o, a)`

`nabla_grad(o, a)`

`outer(o, a, b)`

`skew(o, A)`

`sym(o, A)`

```
trace(o,A)
transposed(o,A)

ufl.algorithms.apply_algebra_lowering.apply_algebra_lowering(expr)
Expands high level compound operators (e.g. inner) to equivalent representations using basic operators (e.g. index notation).
```

ufl.algorithms.apply_derivatives module

This module contains the apply_derivatives algorithm which computes the derivatives of a form or expression.

```
class ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher
```

Bases: ufl.corealg.multifunction.MultiFunction

```
coefficient_derivative(o,f,dummy_w,dummy_v,dummy_cd)
```

```
derivative(o)
```

```
expr(o,*ops)
```

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

```
grad(o,f)
```

```
indexed(o,Ap,ii)
```

```
reference_grad(o,f)
```

```
terminal(o)
```

```
variable_derivative(o,f,dummy_v)
```

```
class ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset(coefficients,
```

arguments,

coeffi-

cient_derivatives)

Bases: *ufl.algorithms.apply_derivatives.GenericDerivativeRuleset*

Apply AFD (Automatic Functional Differentiation) to expression.

Implements rules for the Gateaux derivative $D_w[v](\dots)$ defined as

$D_w[v](e) = d/d\tau e(w+\tau v)|_{\tau=0}$

```
argument(o)
```

Return a zero with the right shape for terminals independent of differentiation variable.

```
cell_avg(o,fp)
```

```
coefficient(o)
```

```
facet_avg(o,fp)
```

```
geometric_quantity(o)
```

Return a zero with the right shape for terminals independent of differentiation variable.

```
grad(g)
```

```
reference_grad(o)
```

```

reference_value(o)

class ufl.algorithms.apply_derivatives.GenericDerivativeRuleset(var_shape)
Bases: ufl.corealg.multifunction.MultiFunction

abs(o, df)
acos(o, fp)
asin(o, fp)
atan(o, fp)
atan_2(o, fp, gp)
bessel_i(o, nup, fp)
bessel_j(o, nup, fp)
bessel_k(o, nup, fp)
bessel_y(o, nup, fp)
binary_condition(o, dl, dr)
cell_avg(o)
component_tensor(o, Ap, ii)
conditional(o, unused_dc, dt, df)
constant_value(o)
    Return a zero with the right shape for terminals independent of differentiation variable.
cos(o, fp)
cosh(o, fp)
derivative(o)
division(o, fp, gp)
erf(o, fp)
exp(o, fp)
expr(o)
    Trigger error for types with missing handlers.
facet_avg(o)
fixme(o)
form_argument(o)
geometric_quantity(o)
grad(o)
independent_operator(o)
    Return a zero with the right shape and indices for operators independent of differentiation variable.
independent_terminal(o)
    Return a zero with the right shape for terminals independent of differentiation variable.
index_sum(o, Ap, i)
indexed(o, Ap, ii)

```

```
label(o)
Labels and indices are not differentiable. It's convenient to return the non-differentiated object.

list_tensor(o, *dops)

ln(o, fp)

math_function(o, df)

max_value(o, df, dg)

min_value(o, df, dg)

multi_index(o)
Labels and indices are not differentiable. It's convenient to return the non-differentiated object.

non_differentiable_terminal(o)
Labels and indices are not differentiable. It's convenient to return the non-differentiated object.

not_condition(o, c)

override(o)

power(o, fp, gp)

product(o, da, db)

restricted(o, fp)

sin(o, fp)

sinh(o, fp)

sqrt(o, fp)

sum(o, da, db)

tan(o, fp)

tanh(o, fp)

unexpected(o)

variable(o, df, unused_l)

class ufl.algorithms.apply_derivatives.GradRuleset(geometric_dimension)
Bases: ufl.algorithms.apply_derivatives.GenericDerivativeRuleset

argument(o)

cell_avg(o)
Return a zero with the right shape and indices for operators independent of differentiation variable.

cell_coordinate(o)
 $dX/dx = \text{inv}(dx/dX) = \text{inv}(J) = K$ 

coefficient(o)

facet_avg(o)
Return a zero with the right shape and indices for operators independent of differentiation variable.

geometric_quantity(o)
Default for geometric quantities is  $dg/dx = 0$  if piecewise constant, otherwise keep  $\text{Grad}(g)$ . Override for specific types if other behaviour is needed.

grad(o)
Represent  $\text{grad}(\text{grad}(f))$  as  $\text{Grad}(\text{Grad}(f))$ .
```

```

jacobian_inverse(o)
reference_grad(o)
reference_value(o)
spatial_coordinate(o)
    dx/dx = I

class ufl.algorithms.apply_derivatives.ReferenceGradRuleset(topological_dimension)
Bases: ufl.algorithms.apply_derivatives.GenericDerivativeRuleset

argument(o)

cell_avg(o)
    Return a zero with the right shape and indices for operators independent of differentiation variable.

cell_coordinate(o)
    dX/dX = I

coefficient(o)

facet_avg(o)
    Return a zero with the right shape and indices for operators independent of differentiation variable.

geometric_quantity(o)
    dg/dX = 0 if piecewise constant, otherwise ReferenceGrad(g)

grad(o)

reference_grad(o)
    Represent ref_grad(ref_grad(f)) as RefGrad(RefGrad(f)).

reference_value(o)

spatial_coordinate(o)
    dx/dX = J

class ufl.algorithms.apply_derivatives.VariableRuleset(var)
Bases: ufl.algorithms.apply_derivatives.GenericDerivativeRuleset

argument(o)
    Return a zero with the right shape for terminals independent of differentiation variable.

cell_avg(o)
    Return a zero with the right shape and indices for operators independent of differentiation variable.

coefficient(o)
    df/dv = Id if v is f else 0.
    Note that if v = variable(f), df/dv is still 0, but if v == f, i.e. isinstance(v, Coefficient) == True, then df/dv == df/f = Id.

facet_avg(o)
    Return a zero with the right shape and indices for operators independent of differentiation variable.

geometric_quantity(o)
    Return a zero with the right shape for terminals independent of differentiation variable.

grad(o)
    Variable derivative of a gradient of a terminal must be 0.

reference_grad(o)
    Variable derivative of a gradient of a terminal must be 0.

reference_value(o)

```

```
variable(o, df, l)
ufl.algorithms.apply_derivatives.apply_derivatives(expression)
```

ufl.algorithms.apply_function_pullbacks module

Algorithm for replacing gradients in an expression with reference gradients and coordinate mappings.

```
class ufl.algorithms.apply_function_pullbacks.FunctionPullbackApplier
Bases: ufl.corealg.multifunction.MultiFunction
```

```
expr(o, *ops)
```

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

```
form_argument(o)
```

```
terminal(t)
```

```
ufl.algorithms.apply_function_pullbacks.apply_function_pullbacks(expr)
```

Change representation of coefficients and arguments in expression by applying Piola mappings where applicable and representing all form arguments in reference value.

@param expr: An Expr.

```
ufl.algorithms.apply_function_pullbacks.apply_single_function_pullbacks(g)
```

```
ufl.algorithms.apply_function_pullbacks.create_nested_lists(shape)
```

```
ufl.algorithms.apply_function_pullbacks.reshape_to_nested_list(components,
shape)
```

```
ufl.algorithms.apply_function_pullbacks.sub_elements_with_mappings(element)
```

Return an ordered list of the largest subelements that have a defined mapping.

ufl.algorithms.apply_geometry_lowering module

Algorithm for lowering abstractions of geometric types.

This means replacing high-level types with expressions of mostly the Jacobian and reference cell data.

```
class ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier(preserve_types=())
Bases: ufl.corealg.multifunction.MultiFunction
```

```
cell_coordinate(o)
```

```
cell_diameter(o)
```

```
cell_normal(o)
```

```
cell_volume(o)
```

```
circumradius(o)
```

```
expr(o, *ops)
```

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

```
facet_area(o)
facet_cell_coordinate(o)
facet_jacobian(o)
facet_jacobian_determinant(o)
facet_jacobian_inverse(o)
facet_normal(o)
jacobian(o)
jacobian_determinant(o)
jacobian_inverse(o)
max_cell_edge_length(o)
max_facet_edge_length(o)
min_cell_edge_length(o)
min_facet_edge_length(o)
spatial_coordinate(o)
terminal(t)

ufl.algorithms.apply_geometry_lowering.apply_geometry_lowering(form,      pre-
                                                               serve_types=())
Change GeometricQuantity objects in expression to the lowest level GeometricQuantity objects.
```

Assumes the expression is preprocessed or at least that derivatives have been expanded.

@param form: An Expr or Form.

ufl.algorithms.apply_integral_scaling module

Algorithm for replacing gradients in an expression with reference gradients and coordinate mappings.

```
ufl.algorithms.apply_integral_scaling.apply_integral_scaling(form)
Multiply integrands by a factor to scale the integral to reference frame.
```

```
ufl.algorithms.apply_integral_scaling.compute_integrand_scaling_factor(integral)
Change integrand geometry to the right representations.
```

ufl.algorithms.apply_restrictions module

This module contains the apply_restrictions algorithm which propagates restrictions in a form towards the terminals.

```
class ufl.algorithms.apply_restrictions.DefaultRestrictionApplier(side=None)
Bases: ufl.corealg.multifunction.MultiFunction

derivative(o)
facet_area(o)
Restrict a continuous quantity to default side if no current restriction is set.
```

facet_jacobian(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

facet_jacobian_determinant(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

facet_jacobian_inverse(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

facet_origin(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

max_facet_edge_length(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

min_facet_edge_length(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

operator(*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

restricted(*o*)**spatial_coordinate**(*o*)

Restrict a continuous quantity to default side if no current restriction is set.

terminal(*o*)

class ufl.algorithms.apply_restrictions.**RestrictionPropagator**(*side=None*)

Bases: ufl.corealg.multifunction.MultiFunction

argument(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

coefficient(*o*)

Allow coefficients to be unrestricted (apply default if so) if the values are fully continuous across the facet.

constant_value(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

facet_coordinate(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

facet_normal(*o*)**geometric_cell_quantity**(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

geometric_facet_quantity(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

grad(*o*)

Restrict a discontinuous quantity to current side, require a side to be set.

label(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

multi_index(*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

operator (*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

quadrature_weight (*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

reference_cell_volume (*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

reference_facet_volume (*o*)

Ignore current restriction, quantity is independent of side also from a computational point of view.

reference_value (*o*)

Reference value of something follows same restriction rule as the underlying object.

restricted (*o*)

When hitting a restricted quantity, visit child with a separate restriction algorithm.

terminal (*o*)**variable** (*o*, *op*, *label*)

Strip variable.

`ufl.algorithms.apply_restrictions.apply_default_restrictions(expression)`

Some terminals can be restricted from either side.

This applies a default restriction to such terminals if unrestricted.

`ufl.algorithms.apply_restrictions.apply_restrictions(expression)`

Propagate restriction nodes to wrap differential terminals directly.

ufl.algorithms.change_to_reference module

Algorithm for replacing gradients in an expression with reference gradients and coordinate mappings.

class `ufl.algorithms.change_to_reference.NEWChangeToReferenceGrad`

Bases: `ufl.corealg.multifunction.MultiFunction`

cell_avg (*o*, **dummy_ops*)**coefficient_derivative** (*o*, **dummy_ops*)**expr** (*o*, **ops*)

Trigger error for types with missing handlers.

facet_avg (*o*, **dummy_ops*)**form_argument** (*t*)**geometric_quantity** (*t*)**grad** (*o*, **dummy_ops*)

Store modifier state.

reference_grad (*o*, **dummy_ops*)**restricted** (*o*, **dummy_ops*)

Store modifier state.

```
terminal(o)
class ufl.algorithms.change_to_reference.OLDChangeToReferenceGrad
Bases: ufl.corealg.multifunction.MultiFunction
```

```
coefficient_derivative(o)
```

```
expr(o, *ops)
```

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_untouched
```

as a default rule.

```
grad(o)
```

```
reference_grad(o)
```

```
terminal(o)
```

```
ufl.algorithms.change_to_reference.change_integrand_geometry_representation(integrand,
scale,
in-
te-
gral_type)
```

Change integrand geometry to the right representations.

```
ufl.algorithms.change_to_reference.change_to_reference_grad(e)
```

Change Grad objects in expression to products of JacobianInverse and ReferenceGrad.

Assumes the expression is preprocessed or at least that derivatives have been expanded.

@param e: An Expr or Form.

ufl.algorithms.check_arities module

```
class ufl.algorithms.check_arities.ArityChecker(arguments)
```

Bases: ufl.corealg.multifunction.MultiFunction

```
argument(o)
```

```
cell_avg(o, a)
```

```
component_tensor(o, a, i)
```

```
conditional(o, c, a, b)
```

```
division(o, a, b)
```

```
dot(o, a, b)
```

```
expr(o)
```

```
facet_avg(o, a)
```

```
grad(o, a)
```

```
index_sum(o, a, i)
```

```
indexed(o, a, i)
```

```
inner(o, a, b)
```

```

linear_indexed_type(o, a, i)
linear_operator(o, a)
list_tensor(o, *ops)
negative_restricted(o, a)
nonlinear_operator(o)
outer(o, a, b)
positive_restricted(o, a)
product(o, a, b)
reference_grad(o, a)
reference_value(o, a)
sum(o, a, b)
terminal(o)
variable(o, f, l)

exception ufl.algorithms.check_arities.ArityMismatch
    Bases: ufl.log.UFLEException

ufl.algorithms.check_arities.check_form_arity(form, arguments)
ufl.algorithms.check_arities.check_integrand_arity(expr, arguments)

```

ufl.algorithms.check_restrictions module

Algorithms related to restrictions.

```

class ufl.algorithms.check_restrictions.RestrictionChecker(require_restriction)
    Bases: ufl.corealg.multifunction.MultiFunction

expr(o)
    Trigger error for types with missing handlers.

facet_normal(o)
form_argument(o)
restricted(o)

ufl.algorithms.check_restrictions.check_restrictions(expression,           re-
    require_restriction)
    Check that types that must be restricted are restricted in expression.

```

ufl.algorithms.checks module

Functions to check the validity of forms.

```

ufl.algorithms.checks.validate_form(form)
    Performs all implemented validations on a form. Raises exception if something fails.

```

ufl.algorithms.compute_form_data module

This module provides the compute_form_data function which form compilers will typically call prior to code generation to preprocess/simplify a raw input form given by a user.

```
ufl.algorithms.compute_form_data.attach_estimated_degrees(form)
```

Attach estimated polynomial degree to a form's integrals.

Parameters `form` – The `Form` to inspect.

Returns A new Form with estimate degrees attached.

```
ufl.algorithms.compute_form_data.compute_form_data(form,
                                                    do_apply_function_pullbacks=False,
                                                    do_apply_integral_scaling=False,
                                                    do_apply_geometry_lowering=False,
                                                    preserve_geometry_types=(),
                                                    do_apply_default_restrictions=True,
                                                    do_apply_restrictions=True,
                                                    do_estimate_degrees=True)
```

ufl.algorithms.domain_analysis module

Algorithms for building canonical data structure for integrals over subdomains.

```
class ufl.algorithms.domain_analysis.ExprTupleKey(x)
```

Bases: object

`x`

```
class ufl.algorithms.domain_analysis.IntegralData(domain, integral_type, subdomain_main_id, integrals, metadata)
```

Bases: object

Utility class with the members (domain, integral_type, subdomain_id, integrals, metadata)

where metadata is an empty dictionary that may be used for associating metadata with each object.

`domain`

`enabled_coefficients`

`integral_coefficients`

`integral_type`

`integrals`

`metadata`

`subdomain_id`

```
ufl.algorithms.domain_analysis.accumulate_integrands_with_same_metadata(integrals)
```

Taking input on the form: `integrals = [integral0, integral1, ...]`

Return result on the form:

```
integrands_by_id = [(integrand0, metadata0), (integrand1, metadata1), ...]
```

where integrand0 < integrand1 by the canonical ufl expression ordering criteria.

```
ufl.algorithms.domain_analysis.build_integral_data(integrals)
```

Build integral data given a list of integrals.

Parameters `integrals` – An iterable of `Integral` objects.

Returns A tuple of `IntegralData` objects.

The integrals you pass in here must have been rearranged and gathered (removing the “everywhere” subdomain_id). To do this, you should call `group_form_integrals()`.

```
ufl.algorithms.domain_analysis.dicts_lt(a, b)
```

```
ufl.algorithms.domain_analysis.group_form_integrals(form, domains)
```

Group integrals by domain and type, performing canonical simplification.

Parameters

- `form` – the `Form` to group the integrals of.
- `domains` – an iterable of `Domains`.

Returns A new `Form` with gathered integrands.

```
ufl.algorithms.domain_analysis.group_integrals_by_domain_and_type(integrals,
                                                               domains)
```

Input: `integrals`: list of `Integral` objects `domains`: list of `AbstractDomain` objects from the parent `Form`

Output: `integrals_by_domain_and_type`: dict: (domain, integral_type) -> list(`Integral`)

```
ufl.algorithms.domain_analysis.integral_subdomain_ids(integral)
```

Get a tuple of integer subdomains or a valid string subdomain from integral.

```
ufl.algorithms.domain_analysis.rearrange_integrals_by_single_subdomains(integrals)
```

Rearrange integrals over multiple subdomains to single subdomain integrals.

Input: `integrals`: list(`Integral`)

Output: `integrals`: dict: subdomain_id -> list(`Integral`) (reconstructed with single subdomain_id)

```
ufl.algorithms.domain_analysis.reconstruct_form_from_integral_data(integral_data)
```

ufl.algorithms.elementtransformations module

This module provides helper functions to - FFC/DOLFIN adaptive chain, - UFL algorithms taking care of underspecified DOLFIN expressions.

```
ufl.algorithms.elementtransformations.increase_order(element)
```

Return element of same family, but a polynomial degree higher.

```
ufl.algorithms.elementtransformations.tear(element)
```

For a finite element, return the corresponding discontinuous element.

ufl.algorithms.estimate_degrees module

Algorithms for estimating polynomial degrees of expressions.

```
class ufl.algorithms.estimate_degrees.IrreducibleInt
```

Bases: int

Degree type used by quadrilaterals.

Unlike int, values of this type are not decremented by `_reduce_degree`.

```
class ufl.algorithms.estimate_degrees.SumDegreeEstimator(default_degree, ele-  
ment_replace_map)
```

Bases: ufl.corealg.multifunction.MultiFunction

This algorithm is exact for a few operators and heuristic for many.

abs (*v, a*)

This is a heuristic, correct if there is no

argument (*v*)

A form argument provides a degree depending on the element, or the default degree if the element has no degree.

atan_2 (*v, a, b*)

Using the heuristic $\text{degree}(\text{atan2}(\text{const}, \text{const})) == 0$ $\text{degree}(\text{atan2}(a, b)) == \max(\text{degree}(a), \text{degree}(b)) + 2$ which can be wildly inaccurate but at least gives a somewhat high integration degree.

bessel_function (*v, nu, x*)

Using the heuristic $\text{degree}(\text{bessel_}*(\text{const})) == 0$ $\text{degree}(\text{bessel_}*(x)) == \text{degree}(x) + 2$ which can be wildly inaccurate but at least gives a somewhat high integration degree.

cell_avg (*v, a*)

Cell average of a function is always cellwise constant.

cell_coordinate (*v*)

A coordinate provides one additional degree.

coefficient (*v*)

A form argument provides a degree depending on the element, or the default degree if the element has no degree.

cofactor (*v, *args*)

component_tensor (*v, A, ii*)

compound_derivative (*v, *args*)

compound_tensor_operator (*v, *args*)

condition (*v, *args*)

conditional (*v, c, t, f*)

Degree of condition does not influence degree of values which conditional takes. So heuristically taking max of true degree and false degree. This will be exact in cells where condition takes single value. For improving accuracy of quadrature near condition transition surface quadrature order must be adjusted manually.

constant_value (*v*)

Constant values are constant.

cross (*v, *ops*)

curl (*v, f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

derivative (*v, *args*)

determinant (*v, *args*)

deviatoric (*v, *args*)

div (*v, f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

division(*v*, **ops*)

Using the sum here is a heuristic. Consider e.g. $(x+1)/(x-1)$.

dot(*v*, **ops*)**expr**(*v*, **ops*)

For most operators we take the max degree of its operands.

facet_avg(*v*, *a*)

Facet average of a function is always cellwise constant.

geometric_quantity(*v*)

Some geometric quantities are cellwise constant. Others are nonpolynomial and thus hard to estimate.

grad(*v*, *f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

index_sum(*v*, *A*, *ii*)**indexed**(*v*, *A*, *ii*)**inner**(*v*, **ops*)**inverse**(*v*, **args*)**label**(*v*)**list_tensor**(*v*, **ops*)**math_function**(*v*, *a*)

Using the heuristic $\text{degree}(\sin(\text{const})) == 0$ $\text{degree}(\sin(a)) == \text{degree}(a)+2$ which can be wildly inaccurate but at least gives a somewhat high integration degree.

max_value(*v*, *l*, *r*)

Same as conditional.

min_value(*v*, *l*, *r*)

Same as conditional.

multi_index(*v*)**nabla_div**(*v*, *f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

nabla_grad(*v*, *f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

negative_restricted(*v*, *a*)**outer**(*v*, **ops*)**positive_restricted**(*v*, *a*)**power**(*v*, *a*, *b*)

If *b* is a positive integer: $\text{degree}(a^{**}b) == \text{degree}(a)*b$ otherwise use the heuristic $\text{degree}(a^{**}b) == \text{degree}(a) + 2$

product(*v*, **ops*)**reference_curl**(*v*, *f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

reference_div(*v,f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

reference_grad(*v,f*)

Reduces the estimated degree by one; used when derivatives are taken. Does not reduce the degree when TensorProduct elements or quadrilateral elements are involved.

reference_value(*rv,f*)**skew**(*v, *args*)**spatial_coordinate**(*v*)

A coordinate provides additional degrees depending on coordinate field of domain.

sum(*v, *ops*)**sym**(*v, *args*)**trace**(*v, *args*)**transposed**(*v, A*)**variable**(*v, e, l*)**variable_derivative**(*v, *args*)

```
ufl.algorithms.estimate_degrees.estimate_total_polynomial_degree(e, fault_degree=1, element_replace_map={}())
```

Estimate total polynomial degree of integrand.

NB! Although some compound types are supported here, some derivatives and compounds must be preprocessed prior to degree estimation. In generic code, this algorithm should only be applied after preprocessing.

For coefficients defined on an element with unspecified degree (None), the degree is set to the given default degree.

ufl.algorithms.expand_compounds module

Algorithm for expanding compound expressions into equivalent representations using basic operators.

```
ufl.algorithms.expand_compounds.expand_compounds(e)
```

ufl.algorithms.expand_indices module

This module defines expression transformation utilities, for expanding free indices in expressions to explicit fixed indices only.

```
class ufl.algorithms.expand_indices.IndexExpander
```

Bases: *ufl.algorithms.transformer.ReuseTransformer*

```
...
```

component()

Return current component tuple.

component_tensor(*x*)**conditional**(*x*)

```

division(x)
form_argument(x)
grad(x)
index_sum(x)
indexed(x)
list_tensor(x)
multi_index(x)
scalar_value(x)
terminal(x)
    Always reuse Expr (ignore children)
zero(x)

ufl.algorithms.expand_indices.expand_indices(e)
ufl.algorithms.expand_indices.purge_list_tensors(expr)
    Get rid of all ListTensor instances by expanding expressions to use their components directly. Will usually
    increase the size of the expression.

```

ufl.algorithms.formdata module

FormData class easy for collecting of various data about a form.

```

class ufl.algorithms.formdata.ExprData
    Bases: object
        Class collecting various information extracted from a Expr by calling preprocess.

class ufl.algorithms.formdata.FormData
    Bases: object
        Class collecting various information extracted from a Form by calling preprocess.

```

ufl.algorithms.formfiles module

A collection of utility algorithms for handling UFL files.

```

class ufl.algorithms.formfiles.FileData
    Bases: object

ufl.algorithms.formfiles.execute_ufl_code(uflcode, filename)
ufl.algorithms.formfiles.interpret_ufl_namespace(namespace)
    Takes a namespace dict from an executed ufl file and converts it to a FileData object.

ufl.algorithms.formfiles.load_forms(filename)
    Return a list of all forms in a file.

ufl.algorithms.formfiles.load_ufl_file(filename)
    Load a .ufl file with elements, coefficients and forms.

ufl.algorithms.formfiles.read_lines_decoded(fn)
ufl.algorithms.formfiles.read_ufl_file(filename)
    Read a .ufl file, handling file extension, file existance, and #include replacement.

```

```
ufl.algorithms.formfiles.replace_include_statements(lines)
    Replace '#include foo.ufl' statements with contents of foo.ufl.
```

ufl.algorithms.formsplitter module

Extract part of a form in a mixed FunctionSpace.

```
class ufl.algorithms.formsplitter.FormSplitter
```

Bases: ufl.corealg.multifunction.MultiFunction

```
argument(obj)
```

```
expr(o, *ops)
```

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_un触ed
```

as a default rule.

```
multi_index(obj)
```

```
split(form, ix, iy=0)
```

```
ufl.algorithms.formsplitter.block_split(form, ix, iy=0)
```

ufl.algorithms.formtransformations module

This module defines utilities for transforming complete Forms into new related Forms.

```
class ufl.algorithms.formtransformations.PartExtractor(arguments)
```

Bases: ufl.algorithms.transformer.Transformer

PartExtractor extracts those parts of a form that contain the given argument(s).

```
argument(x)
```

Return itself unless itself provides too much.

```
cell_avg(x, arg)
```

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

```
component_tensor(x)
```

Return parts of expression belonging to this indexed expression.

```
division(x)
```

Return parts_of_numerator/denominator.

```
dot(x, *ops)
```

Note: Product is a visit-children-first handler. ops are the visited factors.

```
expr(x)
```

The default is a nonlinear operator not accepting any Arguments among its children.

```
facet_avg(x, arg)
```

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

```
grad(x, arg)
```

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

index_sum(*x*)

Return parts of expression belonging to this indexed expression.

indexed(*x*)

Return parts of expression belonging to this indexed expression.

inner(*x, *ops*)

Note: Product is a visit-children-first handler. ops are the visited factors.

linear_indexed_type(*x*)

Return parts of expression belonging to this indexed expression.

linear_operator(*x, arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

list_tensor(*x, *ops*)**negative_restricted**(*x, arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

outer(*x, *ops*)

Note: Product is a visit-children-first handler. ops are the visited factors.

positive_restricted(*x, arg*)

A linear operator with a single operand accepting arity > 0, providing whatever Argument its operand does.

product(*x, *ops*)

Note: Product is a visit-children-first handler. ops are the visited factors.

sum(*x*)

Return the terms that might eventually yield the correct parts(!)

The logic required for sums is a bit elaborate:

A sum may contain terms providing different arguments. We should return (a sum of) a suitable subset of these terms. Those should all provide the same arguments.

For each term in a sum, there are 2 simple possibilities:

1a) The relevant part of the term is zero -> skip. 1b) The term provides more arguments than we want -> skip

2) If all terms fall into the above category, we can just return zero.

Any remaining terms may provide exactly the arguments we want, or fewer. This is where things start getting interesting.

3) Bottom-line: if there are terms with providing different arguments – provide terms that contain the most arguments. If there are terms providing different sets of same size -> throw error (e.g. Argument(-1) + Argument(-2))

terminal(*x*)

The default is a nonlinear operator not accepting any Arguments among its children.

variable(*x*)

Return relevant parts of this variable.

ufl.algorithms.formtransformations.**compute_energy_norm**(*form, coefficient*)

Compute the a-norm of a Coefficient given a form a.

This works simply by replacing the two Arguments with a Coefficient on the same function space (element). The Form returned will thus be a functional with no Arguments, and one additional Coefficient at the end if no coefficient has been provided.

`ufl.algorithms.formtransformations.compute_form_action(form, coefficient)`

Compute the action of a form on a Coefficient.

This works simply by replacing the last Argument with a Coefficient on the same function space (element). The form returned will thus have one Argument less and one additional Coefficient at the end if no Coefficient has been provided.

`ufl.algorithms.formtransformations.compute_form_adjoint(form, re-ordered_arguments=None)`

Compute the adjoint of a bilinear form.

This works simply by swapping the number and part of the two arguments, but keeping their elements and places in the integrand expressions.

`ufl.algorithms.formtransformations.compute_form_arities(form)`

Return set of arities of terms present in form.

`ufl.algorithms.formtransformations.compute_form_functional(form)`

Compute the functional part of a form, that is the terms independent of Arguments.

(Used for testing, not sure if it's useful for anything?)

`ufl.algorithms.formtransformations.compute_form_lhs(form)`

Compute the left hand side of a form.

Example:

$a = u*v*dx + f*v*dx \quad a = \text{lhs}(a) \rightarrow u*v*dx$

`ufl.algorithms.formtransformations.compute_form_rhs(form)`

Compute the right hand side of a form.

Example:

$a = u*v*dx + f*v*dx \quad L = \text{rhs}(a) \rightarrow -f*v*dx$

`ufl.algorithms.formtransformations.compute_form_with_arity(form, arity, arguments=None)`

Compute parts of form of given arity.

`ufl.algorithms.formtransformations.zero_expr(e)`

ufl.algorithms.map_integrands module

Basic algorithms for applying functions to subexpressions.

`ufl.algorithms.map_integrands.map_integrand_dags(function, form, only_integral_type=None, compress=True)`

`ufl.algorithms.map_integrands.map_integrands(function, form, only_integral_type=None)`
Apply transform(expression) to each integrand expression in form, or to form if it is an Expr.

ufl.algorithms.multipfunction module

ufl.algorithms.renumbering module

Algorithms for renumbering of counted objects, currently variables and indices.

```
class ufl.algorithms.renumbering.IndexRenumberingTransformer
Bases: ufl.algorithms.renumbering.VariableRenumberingTransformer

This is a poorly designed algorithm. It is used in some tests, please do not use for anything else.

index(o)
multi_index(o)
zero(o)

class ufl.algorithms.renumbering.VariableRenumberingTransformer
Bases: ufl.algorithms.transformer.ReuseTransformer

variable(o)

ufl.algorithms.renumbering.renumber_indices(expr)
```

ufl.algorithms.replace module

Algorithm for replacing terminals in an expression.

```
class ufl.algorithms.replace.Replacer(mapping)
Bases: ufl.corealg.multifunction.MultiFunction

coefficient_derivative(o)
expr(o, *ops)
    Reuse object if operands are the same objects.
```

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_un触ed
```

as a default rule.

```
terminal(o)
```

```
ufl.algorithms.replace.replace(e, mapping)
Replace terminal objects in expression.

@param e: An Expr or Form.
@param mapping: A dict with from:to replacements to perform.
```

ufl.algorithms.signature module

Signature computation for forms.

```
ufl.algorithms.signature.compute_expression_hashdata(expression, terminal_hashdata)
ufl.algorithms.signature.compute_expression_signature(expr, renumbering)
ufl.algorithms.signature.compute_form_signature(form, renumbering)
ufl.algorithms.signature.compute_multiindex_hashdata(expr, index_numbering)
ufl.algorithms.signature.compute_terminal_hashdata(expressions, renumbering)
```

ufl.algorithms.transformer module

This module defines the Transformer base class and some basic specializations to further base other algorithms upon, as well as some utilities for easier application of such algorithms.

class ufl.algorithms.transformer.**CopyTransformer** (*variable_cache=None*)

Bases: *ufl.algorithms.transformer.Transformer*

expr (*o, *operands*)

Always reconstruct expr.

terminal (*o*)

Always reuse Expr (ignore children)

variable (*o*)

class ufl.algorithms.transformer.**ReuseTransformer** (*variable_cache=None*)

Bases: *ufl.algorithms.transformer.Transformer*

expr (*o, *ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

expr = MultiFunction.reuse_if_untouched

as a default rule.

terminal (*o*)

Always reuse Expr (ignore children)

variable (*o*)

class ufl.algorithms.transformer.**Transformer** (*variable_cache=None*)

Bases: object

Base class for a visitor-like algorithm design pattern used to transform expression trees from one representation to another.

always_reconstruct (*o, *operands*)

Always reconstruct expr.

expr (*o*)

Trigger error.

print_visit_stack()

reconstruct_variable (*o*)

reuse (*o*)

Always reuse Expr (ignore children)

reuse_if_possible (*o, *ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

expr = MultiFunction.reuse_if_untouched

as a default rule.

reuse_if_untouched (*o, *ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```

expr = MultiFunction.reuse_if_unouched
      as a default rule.

reuse_variable(o)
terminal(o)
      Always reuse Expr (ignore children)

undefined(o)
      Trigger error.

visit(o)

class ufl.algorithms.transformer.VariableStripper
  Bases: ufl.algorithms.transformer.ReuseTransformer

variable(o)

ufl.algorithms.transformer.apply_transformer(e, transformer, integral_type=None)
      Apply transformer.visit(expression) to each integrand expression in form, or to form if it is an Expr.

ufl.algorithms.transformer.is_post_handler(function)
      Is this a handler that expects transformed children as input?

ufl.algorithms.transformer.strip_variables(e)
      Replace all Variable instances with the expression they represent.

ufl.algorithms.transformer.ufl2ufl(e)
      Convert an UFL expression to a new UFL expression, with no changes. This is used for testing that objects in the expression behave as expected.

ufl.algorithms.transformer.ufl2uflcopy(e)
      Convert an UFL expression to a new UFL expression. All nonterminal object instances are replaced with identical copies, while terminal objects are kept. This is used for testing that objects in the expression behave as expected.

```

ufl.algorithms.traversal module

This module contains algorithms for traversing expression trees in different ways.

```

ufl.algorithms.traversal.iter_expressions(a)
  Utility function to handle Form, Integral and any Expr the same way when inspecting expressions. Returns an iterable over Expr instances: - a is an Expr: (a,) - a is an Integral: the integrand expression of a - a is a Form: all integrand expressions of all integrals

```

Module contents

This module collects algorithms and utility functions operating on UFL objects.

```

ufl.algorithms.estimate_total_polynomial_degree(e,           default_degree=1,           ele-
                                                ment_replace_map={})
  Estimate total polynomial degree of integrand.

```

NB! Although some compound types are supported here, some derivatives and compounds must be preprocessed prior to degree estimation. In generic code, this algorithm should only be applied after preprocessing.

For coefficients defined on an element with unspecified degree (None), the degree is set to the given default degree.

`ufl.algorithms.sort_elements(elements)`

Sort elements so that any sub elements appear before the corresponding mixed elements. This is useful when sub elements need to be defined before the corresponding mixed elements.

The ordering is based on sorting a directed acyclic graph.

```
ufl.algorithms.compute_form_data(form,
                                  do_apply_function_pullbacks=False,
                                  do_apply_integral_scaling=False,
                                  do_apply_geometry_lowering=False,
                                  preserve_geometry_types=(),
                                  do_apply_default_restrictions=True,
                                  do_apply_restrictions=True, do_estimate_degrees=True)
```

`ufl.algorithms.purge_list_tensors(expr)`

Get rid of all ListTensor instances by expanding expressions to use their components directly. Will usually increase the size of the expression.

`ufl.algorithms.apply_transformer(e, transformer, integral_type=None)`

Apply transformer.visit(expression) to each integrand expression in form, or to form if it is an Expr.

class `ufl.algorithms.ReuseTransformer(variable_cache=None)`

Bases: `ufl.algorithms.transformer.Transformer`

expr (*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

`expr = MultiFunction.reuse_if_un触ed`

as a default rule.

terminal (*o*)

Always reuse Expr (ignore children)

variable (*o*)

`ufl.algorithms.load_ufl_file(filename)`

Load a .ufl file with elements, coefficients and forms.

class `ufl.algorithms.Transformer(variable_cache=None)`

Bases: `object`

Base class for a visitor-like algorithm design pattern used to transform expression trees from one representation to another.

always_reconstruct (*o*, **operands*)

Always reconstruct expr.

expr (*o*)

Trigger error.

print_visit_stack()

reconstruct_variable (*o*)

reuse (*o*)

Always reuse Expr (ignore children)

reuse_if_possible (*o*, **ops*)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

`expr = MultiFunction.reuse_if_un触ed`

as a default rule.

reuse_if_unouched(*o*, **ops*)
Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

reuse_variable(*o*)
terminal(*o*)
Always reuse Expr (ignore children)

undefined(*o*)
Trigger error.

visit(*o*)

class ufl.algorithms.**MultiFunction**
Bases: object

Base class for collections of non-recursive expression node handlers.

Subclass this (remember to call the `__init__` method of this class), and implement handler functions for each Expr type, using the lower case handler name of the type (`exprtype._ufl_handler_name_`).

This class is optimized for efficient type based dispatch in the `__call__` operator via typecode based lookup of the handler function bound to the algorithm object. Of course Python's function call overhead still applies.

expr(*o*, **args*)
Trigger error for types with missing handlers.

reuse_if_unouched(*o*, **ops*)
Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_unouched
```

as a default rule.

undefined(*o*, **args*)
Trigger error for types with missing handlers.

ufl.algorithms.**extract_unique_elements**(*form*)
Build sorted tuple of all unique elements used in form.

ufl.algorithms.**extract_type**(*a*, *ufl_type*)
Build a set of all objects of class *ufl_type* found in *a*. The argument *a* can be a Form, Integral or Expr.

ufl.algorithms.**extract_elements**(*form*)
Build sorted tuple of all elements used in form.

ufl.algorithms.**extract_sub_elements**(*elements*)
Build sorted tuple of all sub elements (including parent element).

ufl.algorithms.**expand_indices**(*e*)

ufl.algorithms.**replace**(*e*, *mapping*)
Replace terminal objects in expression.

@param e: An Expr or Form.

@param mapping: A dict with from:to replacements to perform.

`ufl.algorithms.expand_derivatives (form, **kwargs)`
Expand all derivatives of expr.

In the returned expression g which is mathematically equivalent to expr, there are no VariableDerivative or CoefficientDerivative objects left, and Grad objects have been propagated to Terminal nodes.

`ufl.algorithms.extract_coefficients (a)`
Build a sorted list of all coefficients in a, which can be a Form, Integral or Expr.

`ufl.algorithms.strip_variables (e)`
Replace all Variable instances with the expression they represent.

`ufl.algorithms.post_traversal (expr)`
Yield o for each node o in *expr*, child before parent.

`ufl.algorithms.change_to_reference_grad (e)`
Change Grad objects in expression to products of JacobianInverse and ReferenceGrad.

Assumes the expression is preprocessed or at least that derivatives have been expanded.

@param e: An Expr or Form.

`ufl.algorithms.expand_compounds (e)`

`ufl.algorithms.validate_form (form)`
Performs all implemented validations on a form. Raises exception if something fails.

`ufl.algorithms.ufl2latex (expression)`
Generate LaTeX code for a UFL expression or form (wrapper for form2latex and expression2latex).

class ufl.algorithms.FormSplitter
Bases: `ufl.corealg.multifunction.MultiFunction`

argument (obj)

expr (o, *ops)

Reuse object if operands are the same objects.

Use in your own subclass by setting e.g.

```
expr = MultiFunction.reuse_if_un触ed
```

as a default rule.

multi_index (obj)

split (form, ix, iy=0)

`ufl.algorithms.extract_arguments (a)`

Build a sorted list of all arguments in a, which can be a Form, Integral or Expr.

`ufl.algorithms.compute_form_adjoint (form, reordered_arguments=None)`
Compute the adjoint of a bilinear form.

This works simply by swapping the number and part of the two arguments, but keeping their elements and places in the integrand expressions.

`ufl.algorithms.compute_form_action (form, coefficient)`
Compute the action of a form on a Coefficient.

This works simply by replacing the last Argument with a Coefficient on the same function space (element). The form returned will thus have one Argument less and one additional Coefficient at the end if no Coefficient has been provided.

`ufl.algorithms.compute_energy_norm(form, coefficient)`

Compute the a-norm of a Coefficient given a form a.

This works simply by replacing the two Arguments with a Coefficient on the same function space (element). The Form returned will thus be a functional with no Arguments, and one additional Coefficient at the end if no coefficient has been provided.

`ufl.algorithms.compute_form_lhs(form)`

Compute the left hand side of a form.

Example:

$a = u*v*dx + f*v*dx \quad a = \text{lhs}(a) \rightarrow u*v*dx$

`ufl.algorithms.compute_form_rhs(form)`

Compute the right hand side of a form.

Example:

$a = u*v*dx + f*v*dx \quad L = \text{rhs}(a) \rightarrow -f*v*dx$

`ufl.algorithms.compute_form_functional(form)`

Compute the functional part of a form, that is the terms independent of Arguments.

(Used for testing, not sure if it's useful for anything?)

`ufl.algorithms.compute_form_signature(form, renumbering)`

`ufl.algorithms.tree_format(expression, indentation=0, parentheses=True)`

ufl.finiteelement package

Submodules

ufl.finiteelement.brokenelement module

`class ufl.finiteelement.brokenelement.BrokenElement(element)`

Bases: `ufl.finiteelementFINITEELEMENTbase.FiniteElementBase`

The discontinuous version of an existing Finite Element space.

`mapping()`

Not implemented.

`reconstruct(**kwargs)`

`shortstr()`

Format as string for pretty printing.

ufl.finiteelement.elementlist module

This module provides an extensive list of predefined finite element families. Users or, more likely, form compilers, may register new elements by calling the function `register_element`.

`ufl.finiteelement.elementlist.canonical_element_description(family, cell, order, form_degree)`

Given basic element information, return corresponding element information on canonical form.

Input: family, cell, (polynomial) order, form_degree Output: family (canonical), short_name (for printing), order, value shape, reference value shape, sobolev_space.

This is used by the FiniteElement constructor to vet input data against the element list and aliases defined in ufl.

```
ufl.finiteelement.elementlist.feec_element (family, n, r, k)
    Finite element exterior calculus notation n = topological dimension of domain r = polynomial order k = form_degree
```

```
ufl.finiteelement.elementlist.register_alias (alias, to)
```

```
ufl.finiteelement.elementlist.register_element (family, short_name, value_rank,
                                              sobolev_space, mapping, degree_range,
                                              cellnames)
```

Register new finite element family.

```
ufl.finiteelement.elementlist.register_element2 (family, value_rank, sobolev_space,
                                               mapping, degree_range, cellnames)
```

Register new finite element family.

```
ufl.finiteelement.elementlist.show_elements ()
```

Shows all registered elements.

ufl.finiteelement.enrichedelement module

This module defines the UFL finite element classes.

```
class ufl.finiteelement.enrichedelement.EnrichedElement (*elements)
    Bases: ufl.finiteelement.enrichedelement.EnrichedElementBase
```

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Dual basis is a concatenation of subelements dual bases; primal basis is a concatenation of subelements primal bases; resulting element is not nodal even when subelements are. Structured basis may be exploited in form compilers.

```
is_cellwise_constant ()
```

Return whether the basis functions of this element is spatially constant over each cell.

```
shortstr ()
```

Format as string for pretty printing.

```
class ufl.finiteelement.enrichedelement.EnrichedElementBase (*elements)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
```

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

```
mapping ()
```

Not implemented.

```
reconstruct (**kwargs)
```

```
sobolev_space ()
```

Return the underlying Sobolev space.

```
class ufl.finiteelement.enrichedelement.NodalEnrichedElement (*elements)
    Bases: ufl.finiteelement.enrichedelement.EnrichedElementBase
```

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Primal basis is reorthogonalized to dual basis which is a concatenation of subelements dual bases; resulting element is nodal.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

shortstr()

Format as string for pretty printing.

ufl.finiteelement.facetelement module

ufl.finiteelement.facetelement.FacetElement(element)

Constructs the restriction of a finite element to the facets of the cell.

ufl.finiteelement.finiteelement module

This module defines the UFL finite element classes.

class ufl.finiteelement.finiteelement.FiniteElement(family, cell=None, degree=None, form_degree=None, quad_scheme=None, variant=None)

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

The basic finite element class for all simple finite elements.

mapping()

Not implemented.

reconstruct(family=None, cell=None, degree=None)

Construct a new FiniteElement object with some properties replaced with new values.

shortstr()

Format as string for pretty printing.

sobolev_space()

Return the underlying Sobolev space.

variant()

ufl.finiteelement.finiteelementbase module

This module defines the UFL finite element classes.

class ufl.finiteelement.finiteelementbase.FiniteElementBase(family, cell, degree, quad_scheme, value_shape, reference_value_shape)

Bases: *object*

Base class for all finite elements.

cell()

Return cell of finite element.

degree (*component=None*)
Return polynomial degree of finite element.

extract_component (*i*)
Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component (*i*)
Recursively extract reference component index relative to a (simple) element and that element for given reference value component index.

extract_subelement_component (*i*)
Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component (*i*)
Extract direct subelement index and subelement relative reference component index for a given reference component index.

family ()
Return finite element family.

is_cellwise_constant (*component=None*)
Return whether the basis functions of this element is spatially constant over each cell.

mapping ()
Not implemented.

num_sub_elements ()
Return number of sub-elements.

quadrature_scheme ()
Return quadrature scheme of finite element.

reference_value_shape ()
Return the shape of the value space on the reference cell.

reference_value_size ()
Return the integer product of the reference value shape.

sub_elements ()
Return list of sub-elements.

symmetry ()
Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

value_shape ()
Return the shape of the value space on the global domain.

value_size ()
Return the integer product of the value shape.

ufl.finiteelement.hdivcurl module

class ufl.finiteelement.hdivcurl.**HcurlElement** (*element*)
Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

A curl-conforming version of an outer product element, assuming this makes mathematical sense.

mapping ()
Not implemented.

```

reconstruct (**kwargs)
shortstr()
    Format as string for pretty printing.

sobolev_spaceclass ufl.finiteelement.hdivcurl.HDivElement (element)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
A div-conforming version of an outer product element, assuming this makes mathematical sense.

mappingreconstruct (**kwargs)
shortstr()
    Format as string for pretty printing.

sobolev_space

```

ufl.finiteelement.interiorelement module

```

ufl.finiteelement.interiorelement.InteriorElement (element)
Constructs the restriction of a finite element to the interior of the cell.

```

ufl.finiteelement.mixedelement module

This module defines the UFL finite element classes.

```

class ufl.finiteelement.mixedelement.MixedElement (*elements, **kwargs)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
A finite element composed of a nested hierarchy of mixed or simple elements.

degree (component=None)
    Return polynomial degree of finite element.

extract_component (i)
    Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component (i)
    Recursively extract reference_component index relative to a (simple) element and that element for given value reference_component index.

extract_subelement_component (i)
    Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component (i)
    Extract direct subelement index and subelement relative reference_component index for a given reference_component index.

is_cellwise_constant (component=None)
    Return whether the basis functions of this element is spatially constant over each cell.

```

```
mapping()
    Not implemented.

num_sub_elements()
    Return number of sub elements.

reconstruct(**kwargs)

reconstruct_from_elements(*elements)
    Reconstruct a mixed element from new subelements.

shortstr()
    Format as string for pretty printing.

sub_elements()
    Return list of sub elements.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.finiteelement.mixedelement.TensorElement(family, cell=None, degree=None, shape=None, symmetry=None, quad_scheme=None)
Bases: ufl.finiteelement.mixedelement.MixedElement

A special case of a mixed finite element where all elements are equal.

extract_subelement_component(i)
    Extract direct subelement index and subelement relative component index for a given component index.

flattened_sub_element_mapping()

mapping()
    Not implemented.

reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.finiteelement.mixedelement.VectorElement(family, cell=None, degree=None, dim=None, form_degree=None, quad_scheme=None)
Bases: ufl.finiteelement.mixedelement.MixedElement

A special case of a mixed finite element where all elements are equal.

reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.
```

ufl.finiteelement.restrictedelement module

This module defines the UFL finite element classes.

```
class ufl.finiteelement.restrictedelement.RestrictedElement (element, restriction_domain)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase

Represents the restriction of a finite element to a type of cell entity.

is_cellwise_constant()
    Return whether the basis functions of this element is spatially constant over each cell.

mapping()
    Not implemented.

num_restricted_sub_elements()
    Return number of restricted sub elements.

num_sub_elements()
    Return number of sub elements.

reconstruct(**kwargs)

restricted_sub_elements()
    Return list of restricted sub elements.

restriction_domain()
    Return the domain onto which the element is restricted.

shortstr()
    Format as string for pretty printing.

sub_element()
    Return the element which is restricted.

sub_elements()
    Return list of sub elements.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.
```

ufl.finiteelement.tensorproductelement module

This module defines the UFL finite element classes.

```
class ufl.finiteelement.tensorproductelement.TensorProductElement (*elements, **kwargs)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
```

The tensor product of d element spaces:

$$V = V_1 \otimes V_2 \otimes \dots \otimes V_d$$

Given bases $\{\phi_{j_i}\}$ of the spaces V_i for $i = 1, \dots, d$, $\{\phi_{j_1} \otimes \phi_{j_2} \otimes \dots \otimes \phi_{j_d}\}$ forms a basis for V .

```
mapping()
    Not implemented.

num_sub_elements()
    Return number of subelements.

reconstruct(cell=None)

shortstr()
    Short pretty-print.
```

```
sobolev_space()
    Return the underlying Sobolev space of the TensorProductElement.

sub_elements()
    Return subelements (factors).
```

Module contents

This module defines the UFL finite element classes.

1.3.2 Submodules

1.3.3 ufl.algebra module

Basic algebra operations.

```
class ufl.algebra.Abs(a)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.algebra.Division(a, b)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = ()

class ufl.algebra.Power(a, b)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = ()

class ufl.algebra.Product(a, b)
    Bases: ufl.core.operator.Operator

    The product of two or more UFL objects.

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices
```

```




class ufl.algebra.Sum(a, b)  

Bases: ufl.core.operator.Operator



evaluate (x, mapping, component, index_values)  

Evaluate expression at given coordinate with given values for terminals.



```



```


```

1.3.4 ufl.argument module

This module defines the class Argument and a number of related classes (functions), including TestFunction and TrialFunction.

class ufl.argument.Argument(*function_space, number, part=None*)

Bases: ufl.core.terminal.FormArgument

UFL value: Representation of an argument to a form.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

number()

Return the Argument number.

part()

ufl_domain()

Deprecated, please use .ufl_function_space().ufl_domain() instead.

ufl_domains()

Deprecated, please use .ufl_function_space().ufl_domains() instead.

ufl_element()

Deprecated, please use .ufl_function_space().ufl_element() instead.

ufl_function_space()

Get the function space of this Argument.

ufl_shape

Return the associated UFL shape.

ufl.argument.Arguments(*function_space, number*)

UFL value: Create an Argument in a mixed space, and return a tuple with the function components corresponding to the subelements.

ufl.argument.TestFunction(*function_space, part=None*)

UFL value: Create a test function argument to a form.

ufl.argument.TestFunctions(*function_space*)

UFL value: Create a TestFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

ufl.argument.TrialFunction(*function_space, part=None*)

UFL value: Create a trial function argument to a form.

```
ufl.argument.TrialFunctions(function_space)
```

UFL value: Create a TrialFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

1.3.5 ufl.assertions module

This module provides assertion functions used by the UFL implementation.

```
ufl.assertions.expecting_expr(v)
ufl.assertions.expecting_instance(v, c)
ufl.assertions.expecting_python_scalar(v)
ufl.assertions.expecting_terminal(v)
ufl.assertions.expecting_true_ufl_scalar(v)
ufl.assertions.ufl_assert(condition, *message)
```

Assert that condition is true and otherwise issue an error with given message.

1.3.6 ufl.averaging module

Averaging operations.

```
class ufl.averaging.CellAvg(f)
    Bases: ufl.core.operator.Operator
    evaluate(x, mapping, component, index_values)
        Performs an approximate symbolic evaluation, since we dont have a cell.
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.averaging.FacetAvg(f)
    Bases: ufl.core.operator.Operator
    evaluate(x, mapping, component, index_values)
        Performs an approximate symbolic evaluation, since we dont have a cell.
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

1.3.7 ufl.cell module

Types for representing a cell.

```
class ufl.cell.AbstractCell(topological_dimension, geometric_dimension)
    Bases: object
    Representation of an abstract finite element cell with only the dimensions known.
    geometric_dimension()
        Return the dimension of the space this cell is embedded in.
```

```

has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

topological_dimension()
    Return the dimension of the topology of this cell.

class ufl.cell.Cell(cellname, geometric_dimension=None)
    Bases: ufl.cell.AbstractCell

    Representation of a named finite element cell with known structure.

cellname()
    Return the cellname of the cell.

has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

num_edges()
    The number of cell edges.

num_facet_edges()
    The number of facet edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct(geometric_dimension=None)

class ufl.cell.TensorProductCell(*cells, **kwargs)
    Bases: ufl.cell.AbstractCell

cellname()
    Return the cellname of the cell.

has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

num_edges()
    The number of cell edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct(geometric_dimension=None)

sub_cells()
    Return list of cell factors.


    Convert any valid object to a Cell or return cell if it is already a Cell.

```

Allows an already valid cell, a known cellname string, or a tuple of cells for a product cell.

`ufl.cell.hypercube(topological_dimension, geometric_dimension=None)`
Return a hypercube cell of given dimension.

`ufl.cell.simplex(topological_dimension, geometric_dimension=None)`
Return a simplex cell of given dimension.

1.3.8 ufl.checks module

Utility functions for checking properties of expressions.

`ufl.checks.is_cellwise_constant(expr)`
Return whether expression is constant over a single cell.

`ufl.checks.is_globally_constant(expr)`
Check if an expression is globally constant, which includes spatially independent constant coefficients that are not known before assembly time.

`ufl.checks.is_python_scalar(expression)`
Return True iff expression is of a Python scalar type.

`ufl.checks.is_scalar_constant_expression(expr)`
Check if an expression is a globally constant scalar expression.

`ufl.checks.is_true_ufl_scalar(expression)`
Return True iff expression is scalar-valued, with no free indices.

`ufl.checks.is_ufl_scalar(expression)`
Return True iff expression is scalar-valued, but possibly containing free indices.

1.3.9 ufl.classes module

This file is useful for external code like tests and form compilers, since it enables the syntax “from ufl.classes import CellFacetooBar” for getting implementation details not exposed through the default ufl namespace. It also contains functionality used by algorithms for dealing with groups of classes, and for mapping types to different handler functions.

`class ufl.classes.Expr`

Bases: `object`

Base class for all UFL expression types.

Instance properties Every `Expr` instance will have certain properties. The most important ones are `ufl_operands`, `ufl_shape`, `ufl_free_indices`, and `ufl_index_dimensions` properties. Expressions are immutable and hashable.

Type traits The `Expr` API defines a number of type traits that each subclass needs to provide. Most of these are specified indirectly via the arguments to the `ufl_type` class decorator, allowing UFL to do some consistency checks and automate most of the traits for most types. Type traits are accessed via a class or instance object of the form `obj._ufl_traitname_`. See the source code for description of each type trait.

Operators Some Python special functions are implemented in this class, some are implemented in subclasses, and some are attached to this class in the `ufl_type` class decorator.

Defining subclasses To define a new expression class, inherit from either `Terminal` or `Operator`, and apply the `ufl_type` class decorator with suitable arguments. See the docstring of `ufl_type` for details on its arguments. Looking at existing classes similar to the one you wish to add is a good idea. Looking

through the comments in the `Expr` class and `ufl_type` to understand all the properties that may need to be specified is also a good idea. Note that many algorithms in UFL and form compilers will need handlers implemented for each new type:::

```
@ufl_type()
class MyOperator(Operator):
    pass
```

Type collections All `Expr` subclasses are collected by `ufl_type` in global variables available via `Expr`.

Profiling Object creation statistics can be collected by doing

```
Expr.ufl_enable_profiling()
# ... run some code
initstats, delstats = Expr.ufl_disable_profiling()
```

Giving a list of creation and deletion counts for each typecode.

T

Transpose a rank-2 tensor expression. For more general transpose operations of higher order tensor expressions, use indexing and `Tensor`.

`dx(*ii)`

Return the partial derivative with respect to spatial variable number ii .

`evaluate(x, mapping, component, index_values)`

Evaluate expression at given coordinate with given values for terminals.

`geometric_dimension()`

Return the geometric dimension this expression lives in.

`static ufl_disable_profiling()`

Turn off the object counting mechanism. Return object init and del counts.

`ufl_domain()`

Return the single unique domain this expression is defined on, or throw an error.

`ufl_domains()`

Return all domains this expression is defined on.

`static ufl_enable_profiling()`

Turn on the object counting mechanism and reset counts to zero.

`class ufl.classes.Terminal`

Bases: `ufl.core.expr.Expr`

A terminal node in the UFL expression tree.

`evaluate(x, mapping, component, index_values, derivatives=())`

Get `self` from `mapping` and return the component asked for.

`ufl_domains()`

Return tuple of domains related to this terminal object.

`ufl_free_indices = ()`

`ufl_index_dimensions = ()`

`ufl_operands = ()`

`class ufl.classes.FormArgument`

Bases: `ufl.core.terminal.Terminal`

An abstract class for a form argument.

```
class ufl.classes.GeometricQuantity(domain)
Bases: ufl.core.terminal.Terminal

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell (or over each facet for facet quantities).

ufl_domains()
    Return tuple of domains related to this terminal object.

ufl_shape = ()

class ufl.classes.GeometricCellQuantity(domain)
Bases: ufl.geometry.GeometricQuantity

class ufl.classes.GeometricFacetQuantity(domain)
Bases: ufl.geometry.GeometricQuantity

class ufl.classes.SpatialCoordinate(domain)
Bases: ufl.geometry.GeometricCellQuantity

UFL geometry representation: The coordinate in a domain.

In the context of expression integration, represents the domain coordinate of each quadrature point.

In the context of expression evaluation in a point, represents the value of that point.

evaluate(x, mapping, component, index_values)
    Return the value of the coordinate.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'x'

ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.classes.CellCoordinate(domain)
Bases: ufl.geometry.GeometricCellQuantity

UFL geometry representation: The coordinate in a reference cell.

In the context of expression integration, represents the reference cell coordinate of each quadrature point.

In the context of expression evaluation in a point in a cell, represents that point in the reference coordinate system of the cell.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'x'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.classes.FacetCoordinate(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The coordinate in a reference cell of a facet.

In the context of expression integration over a facet, represents the reference facet coordinate of each quadrature point.
```

In the context of expression evaluation in a point on a facet, represents that point in the reference coordinate system of the facet.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

name = 'x_f'

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

class ufl.classes.CellOrigin(domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The spatial coordinate corresponding to origin of a reference cell.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell (or over each facet for facet quantities).

name = 'x₀'

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

class ufl.classes.FacetOrigin(domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The spatial coordinate corresponding to origin of a reference facet.

name = 'x_{0f}'

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

class ufl.classes.CellFacetOrigin(domain)

Bases: *ufl.geometry.GeometricFacetQuantity*

UFL geometry representation: The reference cell coordinate corresponding to origin of a reference facet.

name = 'X_{0f}'

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

class ufl.classes.Jacobian(domain)

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The Jacobian of the mapping from reference cell to spatial coordinates.

$$J_{ij} = \frac{dx_i}{dX_j}$$

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

name = 'J'

ufl_shape

Return the number of coordinates defined (i.e. the geometric dimension of the domain).

```
class ufl.classes.FacetJacobian(domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The Jacobian of the mapping from reference facet to spatial coordinates.

$$FJ_{ij} = dx_i/dXf_j$$

The FacetJacobian is the product of the Jacobian and CellFacetJacobian:

$$FJ = dx/dXf = dx/dX \cdot dX/dXf = J * CFJ$$

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

```
name = 'FJ'
```

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

```
class ufl.classes.CellFacetJacobian(domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The Jacobian of the mapping from reference facet to reference cell coordinates.

$$CFJ_{ij} = dX_i/dXf_j$$

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

```
name = 'CFJ'
```

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

```
class ufl.classes.ReferenceCellEdgeVectors(domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The vectors between reference cell vertices for each edge in cell.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

```
name = 'RCEV'
```

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

```
class ufl.classes.ReferenceFacetEdgeVectors(domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The vectors between reference cell vertices for each edge in current facet.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

```
name = 'RFEV'
```

ufl_shape
tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
If the argument is a tuple, the return value is the same object.

```
class ufl.classes.CellVertices (domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: Physical cell vertices.

is_cellwise_constant()
Return whether this expression is spatially constant over each cell.

name = 'CV'

ufl_shape
tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
If the argument is a tuple, the return value is the same object.

```
class ufl.classes.CellEdgeVectors (domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The vectors between physical cell vertices for each edge in cell.

is_cellwise_constant()
Return whether this expression is spatially constant over each cell.

name = 'CEV'

ufl_shape
tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
If the argument is a tuple, the return value is the same object.

```
class ufl.classes.FacetEdgeVectors (domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The vectors between physical cell vertices for each edge in current facet.

is_cellwise_constant()
Return whether this expression is spatially constant over each cell.

name = 'FEV'

ufl_shape
tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
If the argument is a tuple, the return value is the same object.

```
class ufl.classes.JacobianDeterminant (domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The determinant of the Jacobian.
Represents the signed determinant of a square Jacobian or the pseudo-determinant of a non-square Jacobian.

is_cellwise_constant()
Return whether this expression is spatially constant over each cell.

name = 'detJ'

```
class ufl.classes.FacetJacobianDeterminant (domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The pseudo-determinant of the FacetJacobian.

```
is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'detFJ'

class ufl.classes.CellFacetJacobianDeterminant(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The pseudo-determinant of the CellFacetJacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'detCFJ'

class ufl.classes.JacobianInverse(domain)
Bases: ufl.geometry.GeometricCellQuantity

UFL geometry representation: The inverse of the Jacobian.

Represents the inverse of a square Jacobian or the pseudo-inverse of a non-square Jacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'K'

ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.classes.FacetJacobianInverse(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The pseudo-inverse of the FacetJacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'FK'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.classes.CellFacetJacobianInverse(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The pseudo-inverse of the CellFacetJacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'CFK'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.classes.FacetNormal(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The outwards pointing normal vector of the current facet.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.
```

```

name = 'n'

ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.classes.CellNormal(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The upwards pointing normal vector of the current manifold cell.

name = 'cell_normal'

ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.classes.ReferenceNormal(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The outwards pointing normal vector of the current facet on the reference cell

name = 'reference_normal'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

    If the argument is a tuple, the return value is the same object.

class ufl.classes.ReferenceCellVolume(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The volume of the reference cell.

name = 'reference_cell_volume'

class ufl.classes.ReferenceFacetVolume(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The volume of the reference cell of the current facet.

name = 'reference_facet_volume'

class ufl.classes.CellVolume(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The volume of the cell.

name = 'volume'

class ufl.classes.Circumradius(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The circumradius of the cell.

name = 'circumradius'

class ufl.classes.CellDiameter(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The diameter of the cell, i.e., maximal distance of two points in the cell.

name = 'diameter'

class ufl.classes.FacetArea(domain)
    Bases: ufl.geometry.GeometricFacetQuantity

    UFL geometry representation: The area of the facet.

name = 'facetarea'

```

```
class ufl.classes.MinCellEdgeLength(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The minimum edge length of the cell.

name = 'mincelledgeLength'

class ufl.classes.MaxCellEdgeLength(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The maximum edge length of the cell.

name = 'maxcelledgeLength'

class ufl.classes.MinFacetEdgeLength(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The minimum edge length of the facet.

name = 'minfacetedgeLength'

class ufl.classes.MaxFacetEdgeLength(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The maximum edge length of the facet.

name = 'maxfacetedgeLength'

class ufl.classes.CellOrientation(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The orientation (+1/-1) of the current cell.

For non-manifold cells (tdim == gdim), this equals the sign of the Jacobian determinant, i.e. +1 if the physical
cell is oriented the same way as the reference cell and -1 otherwise.

For manifold cells of tdim==gdim-1 this is input data belonging to the mesh, used to distinguish between the
sides of the manifold.

name = 'cell_orientation'

class ufl.classes.FacetOrientation(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The orientation (+1/-1) of the current facet relative to the reference cell.

name = 'facet_orientation'

class ufl.classes.QuadratureWeight(domain)
Bases: ufl.geometry.GeometricQuantity
UFL geometry representation: The current quadrature weight.

Only used inside a quadrature context.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'weight'

class ufl.classes.Operator(operands=None)
Bases: ufl.core.expr.Expr
Base class for all operators, i.e. non-terminal expression types.

uf1_operands
```

```
class ufl.classes.MultiIndex (indices)
Bases: ufl.core.terminal.Terminal

Represents a sequence of indices, either fixed or free.

evaluate (x, mapping, component, index_values)
    Evaluate index.

indices ()
    Return tuple of indices.

is_cellwise_constant ()
    Always True.

ufl_domains ()
    Return tuple of domains related to this terminal object.

ufl_free_indices
    This shall not be used.

ufl_index_dimensions
    This shall not be used.

ufl_shape
    This shall not be used.

class ufl.classes.ConstantValue
Bases: ufl.core.terminal.Terminal

is_cellwise_constant ()
    Return whether this expression is spatially constant over each cell.

ufl_domains ()
    Return tuple of domains related to this terminal object.

class ufl.classes.Zero (shape=(), free_indices=(), index_dimensions=None)
Bases: ufl.constantvalue.ConstantValue

UFL literal type: Representation of a zero valued expression.

evaluate (x, mapping, component, index_values)
    Get self from mapping and return the component asked for.

ufl_free_indices
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

ufl_index_dimensions
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

ufl_shape

class ufl.classes.ScalarValue (value)
Bases: ufl.constantvalue.ConstantValue

A constant scalar value.

evaluate (x, mapping, component, index_values)
    Get self from mapping and return the component asked for.

ufl_free_indices = ()
ufl_index_dimensions = ()
```

```
ufl_shape = ()  
value()  
  
class ufl.classes.FloatValue(value)  
Bases: ufl.constantvalue.ScalarValue  
UFL literal type: Representation of a constant scalar floating point value.  
  
class ufl.classes.IntValue(value)  
Bases: ufl.constantvalue.ScalarValue  
UFL literal type: Representation of a constant scalar integer value.  
  
class ufl.classes.Identity(dim)  
Bases: ufl.constantvalue.ConstantValue  
UFL literal type: Representation of an identity matrix.  
  
evaluate(x, mapping, component, index_values)  
Evaluates the identity matrix on the given components.  
  
ufl_shape  
  
class ufl.classes.PermutationSymbol(dim)  
Bases: ufl.constantvalue.ConstantValue  
UFL literal type: Representation of a permutation symbol.  
This is also known as the Levi-Civita symbol, antisymmetric symbol, or alternating symbol.  
  
evaluate(x, mapping, component, index_values)  
Evaluates the permutation symbol.  
  
ufl_shape  
  
class ufl.classes.Indexed(expression, multiindex)  
Bases: ufl.core.operator.Operator  
  
evaluate(x, mapping, component, index_values, derivatives=())  
Evaluate expression at given coordinate with given values for terminals.  
  
ufl_free_indices  
ufl_index_dimensions  
ufl_shape = ()  
  
class ufl.classes.ListTensor(*expressions)  
Bases: ufl.core.operator.Operator  
UFL operator type: Wraps a list of expressions into a tensor valued expression of one higher rank.  
  
evaluate(x, mapping, component, index_values, derivatives=())  
Evaluate expression at given coordinate with given values for terminals.  
  
ufl_free_indices  
ufl_index_dimensions  
ufl_shape  
  
class ufl.classes.ComponentTensor(expression, indices)  
Bases: ufl.core.operator.Operator  
UFL operator type: Maps the free indices of a scalar valued expression to tensor axes.
```

```

evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

indices ()
ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.Argument (function_space, number, part=None)
    Bases: ufl.core.terminal.FormArgument

    UFL value: Representation of an argument to a form.

is_cellwise_constant ()
    Return whether this expression is spatially constant over each cell.

number ()
    Return the Argument number.

part ()
ufl_domain ()
    Deprecated, please use .ufl_function_space().ufl_domain() instead.

ufl_domains ()
    Deprecated, please use .ufl_function_space().ufl_domains() instead.

ufl_element ()
    Deprecated, please use .ufl_function_space().ufl_element() instead.

ufl_function_space ()
    Get the function space of this Argument.

ufl_shape
    Return the associated UFL shape.

class ufl.classes.Coefficient (function_space, count=None)
    Bases: ufl.core.terminal.FormArgument

    UFL form argument type: Representation of a form coefficient.

count ()
is_cellwise_constant ()
    Return whether this expression is spatially constant over each cell.

ufl_domain ()
    Shortcut to get the domain of the function space of this coefficient.

ufl_domains ()
    Return tuple of domains related to this terminal object.

ufl_element ()
    Shortcut to get the finite element of the function space of this coefficient.

ufl_function_space ()
    Get the function space of this coefficient.

ufl_shape
    Return the associated UFL shape.

class ufl.classes.Label (count=None)
    Bases: ufl.core.terminal.Terminal

```

```
count()
is_cellwise_constant()
ufl_domains()
    Return tuple of domains related to this terminal object.

ufl_free_indices
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
        If the argument is a tuple, the return value is the same object.

ufl_index_dimensions
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
        If the argument is a tuple, the return value is the same object.

ufl_shape
```

```
class ufl.classes.Variable(expression, label=None)
Bases: ufl.core.operator.Operator
```

A Variable is a representative for another expression.

It will be used by the end-user mainly for defining a quantity to differentiate w.r.t. using diff. Example:

```
e = <...>
e = variable(e)
f = exp(e**2)
df = diff(f, e)
```

```
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.
```

```
expression()
```

```
label()
```

```
ufl_domains()
    Return all domains this expression is defined on.
```

```
ufl_free_indices = ()
```

```
ufl_index_dimensions = ()
```

```
ufl_shape
```

```
class ufl.classes.Sum(a, b)
Bases: ufl.core.operator.Operator
```

```
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.
```

```
ufl_free_indices
```

```
ufl_index_dimensions
```

```
ufl_shape
```

```
class ufl.classes.Product(a, b)
Bases: ufl.core.operator.Operator
```

The product of two or more UFL objects.

```
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.
```

```
ufl_free_indices
ufl_index_dimensions
ufl_shape = ()

class ufl.classes.Division(a, b)
Bases: ufl.core.operator.Operator

evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

ufl_free_indices
ufl_index_dimensions
ufl_shape = ()

class ufl.classes.Power(a, b)
Bases: ufl.core.operator.Operator

evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

ufl_free_indices
ufl_index_dimensions
ufl_shape = ()

class ufl.classes.Abs(a)
Bases: ufl.core.operator.Operator

evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.CompoundTensorOperator(operands)
Bases: ufl.core.operator.Operator

class ufl.classes.Transposed(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.Outer(a, b)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.Inner(a, b)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices
```

```
ufl_index_dimensions
ufl_shape = ()

class ufl.classes.Dot(a,b)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.Cross(a,b)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices
ufl_index_dimensions
ufl_shape = (3,)

class ufl.classes.Trace(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices
ufl_index_dimensions
ufl_shape = ()

class ufl.classes.Determinant(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices = ()
ufl_index_dimensions = ()
ufl_shape = ()

class ufl.classes.Inverse(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices = ()
ufl_index_dimensions = ()
ufl_shape

class ufl.classes.Cofactor(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices = ()
ufl_index_dimensions = ()
ufl_shape

class ufl.classes.Deviatoric(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.Skew(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator
```

```





class ufl.classes.Sym(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator

    
    
    

class ufl.classes.IndexSum(summand, index)
    Bases: ufl.core.operator.Operator

    dimension()

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    index()

    
    
    

class ufl.classes.Restricted(f)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    side()

    
    
    

class ufl.classes.PositiveRestricted(f)
    Bases: ufl.restriction.Restricted

class ufl.classes.NegativeRestricted(f)
    Bases: ufl.restriction.Restricted

class ufl.classes.ExprList(*operands)
    Bases: ufl.core.operator.Operator

    List of Expr objects. For internal use, never to be created by end users.

    free_indices()

    index_dimensions()

    
    
    

```

```
class ufl.classes.ExprMapping (*operands)
Bases: ufl.core.operator.Operator
Mapping of Expr objects. For internal use, never to be created by end users.

free_indices()
index_dimensions()
ufl_domains()
    Return all domains this expression is defined on.
ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.Derivative (operands)
Bases: ufl.core.operator.Operator
Base class for all derivative types.

class ufl.classes.CoefficientDerivative (integrand, coefficients, arguments, coefficient_derivatives)
Bases: ufl.differentiation.Derivative
Derivative of the integrand of a form w.r.t. the degrees of freedom in a discrete Coefficient.

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.VariableDerivative (f, v)
Bases: ufl.differentiation.Derivative
ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.CompoundDerivative (operands)
Bases: ufl.differentiation.Derivative
Base class for all compound derivative types.

class ufl.classes.Grad (f)
Bases: ufl.differentiation.CompoundDerivative
evaluate (x, mapping, component, index_values, derivatives=())
    Get child from mapping and return the component asked for.

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.ReferenceGrad (f)
Bases: ufl.differentiation.CompoundDerivative
evaluate (x, mapping, component, index_values, derivatives=())
    Get child from mapping and return the component asked for.

ufl_free_indices
```

```
ufl_index_dimensions
ufl_shape

class ufl.classes.Div(f)
Bases: ufl.differentiation.CompoundDerivative

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.ReferenceDiv(f)
Bases: ufl.differentiation.CompoundDerivative

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.NablaGrad(f)
Bases: ufl.differentiation.CompoundDerivative

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.NablaDiv(f)
Bases: ufl.differentiation.CompoundDerivative

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.Curl(f)
Bases: ufl.differentiation.CompoundDerivative

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.ReferenceCurl(f)
Bases: ufl.differentiation.CompoundDerivative

ufl_free_indices
ufl_index_dimensions
ufl_shape

class ufl.classes.Condition(operands)
Bases: ufl.core.operator.Operator

ufl_free_indices = ()
ufl_index_dimensions = ()
ufl_shape = ()

class ufl.classes.BinaryCondition(name, left, right)
Bases: ufl.conditional.Condition
```

```
class ufl.classes.EQ(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.NE(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.LE(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.GE(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.LT(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.GT(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.AndCondition(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.OrCondition(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.NotCondition(condition)
Bases: ufl.conditional.Condition
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.Conditional(condition, true_value, false_value)
Bases: ufl.core.operator.Operator
evaluate(x, mapping, component, index_values)
Evaluate expression at given coordinate with given values for terminals.

ufl_free_indices
ufl_index_dimensions
ufl_shape
```

```

class ufl.classes.MinValue(left, right)
Bases: ufl.core.operator.Operator
UFL operator: Take the minimum of two values.

evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

 = ()
 = ()
 = ()

class ufl.classes.MaxValue(left, right)
Bases: ufl.core.operator.Operator
UFL operator: Take the maximum of two values.

evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

 = ()
 = ()
 = ()

class ufl.classes.MathFunction(name, argument)
Bases: ufl.core.operator.Operator
Base class for all unary scalar math functions.

evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

 = ()
 = ()
 = ()

class ufl.classes.Sqrt(argument)
Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Exp(argument)
Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Ln(argument)
Bases: ufl.mathfunctions.MathFunction

evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.Cos(argument)
Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Sin(argument)
Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Tan(argument)
Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Cosh(argument)
Bases: ufl.mathfunctions.MathFunction

```

```
class ufl.classes.Sinh(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Tanh(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Acos(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Asin(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Atan(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.classes.Atan2(arg1, arg2)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.classes.Erf(argument)
    Bases: ufl.mathfunctions.MathFunction

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

class ufl.classes.BesselFunction(name, classname, nu, argument)
    Bases: ufl.core.operator.Operator

    Base class for all bessel functions

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.classes.BesselJ(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.classes.BesselY(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.classes.BesselI(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.classes.BesselK(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.classes.CellAvg(f)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Performs an approximate symbolic evaluation, since we dont have a cell.

    ufl_free_indices
```

```




class ufl.classes.FacetAvg(f)
    Bases: ufl.core.operator.Operator

    evaluate (x, mapping, component, index_values)
        Performs an approximate symbolic evaluation, since we dont have a cell.





class ufl.classes.ReferenceValue(f)
    Bases: ufl.core.operator.Operator

    Representation of the reference cell value of a form argument.

    evaluate (x, mapping, component, index_values, derivatives=())
        Get child from mapping and return the component asked for.

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape

class ufl.classes.AbstractCell (topological_dimension, geometric_dimension)
    Bases: object

    Representation of an abstract finite element cell with only the dimensions known.

    geometric_dimension ()
        Return the dimension of the space this cell is embedded in.

    has_simplex_facets ()
        Return True if all the facets of this cell are simplex cells.

    is_simplex ()
        Return True if this is a simplex cell.

    topological_dimension ()
        Return the dimension of the topology of this cell.

class ufl.classes.Cell (cellname, geometric_dimension=None)
    Bases: ufl.cell.AbstractCell

    Representation of a named finite element cell with known structure.

    cellname ()
        Return the cellname of the cell.

    has_simplex_facets ()
        Return True if all the facets of this cell are simplex cells.

    is_simplex ()
        Return True if this is a simplex cell.

    num_edges ()
        The number of cell edges.

    num_facet_edges ()
        The number of facet edges.

```

```
num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct (geometric_dimension=None)

class ufl.classes.TensorProductCell (*cells, **kwargs)
Bases: ufl.cell.AbstractCell

cellname()
    Return the cellname of the cell.

has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

num_edges()
    The number of cell edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct (geometric_dimension=None)

sub_cells()
    Return list of cell factors.

class ufl.classes.FiniteElementBase (family, cell, degree, quad_scheme, value_shape, reference_value_shape)
Bases: object

Base class for all finite elements.

cell()
    Return cell of finite element.

degree (component=None)
    Return polynomial degree of finite element.

extract_component (i)
    Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component (i)
    Recursively extract reference component index relative to a (simple) element and that element for given reference value component index.

extract_subelement_component (i)
    Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component (i)
    Extract direct subelement index and subelement relative reference component index for a given reference component index.

family()
    Return finite element family.
```

is_cellwise_constant (*component=None*)
 Return whether the basis functions of this element is spatially constant over each cell.

mapping()
 Not implemented.

num_sub_elements()
 Return number of sub-elements.

quadrature_scheme()
 Return quadrature scheme of finite element.

reference_value_shape()
 Return the shape of the value space on the reference cell.

reference_value_size()
 Return the integer product of the reference value shape.

sub_elements()
 Return list of sub-elements.

symmetry()
 Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

value_shape()
 Return the shape of the value space on the global domain.

value_size()
 Return the integer product of the value shape.

class ufl.classes.FiniteElement (*family*, *cell=None*, *degree=None*, *form_degree=None*,
quad_scheme=None, *variant=None*)
 Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

The basic finite element class for all simple finite elements.

mapping()
 Not implemented.

reconstruct (*family=None*, *cell=None*, *degree=None*)
 Construct a new FiniteElement object with some properties replaced with new values.

shortstr()
 Format as string for pretty printing.

sobolev_space()
 Return the underlying Sobolev space.

variant()

class ufl.classes.MixedElement (**elements*, ***kwargs*)
 Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

A finite element composed of a nested hierarchy of mixed or simple elements.

degree (*component=None*)
 Return polynomial degree of finite element.

extract_component (*i*)
 Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component(*i*)

Recursively extract reference_component index relative to a (simple) element and that element for given value reference_component index.

extract_subelement_component(*i*)

Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component(*i*)

Extract direct subelement index and subelement relative reference_component index for a given reference_component index.

is_cellwise_constant(*component=None*)

Return whether the basis functions of this element is spatially constant over each cell.

mapping()

Not implemented.

num_sub_elements()

Return number of sub elements.

reconstruct(**kwargs)**reconstruct_from_elements**(*elements)

Reconstruct a mixed element from new subelements.

shortstr()

Format as string for pretty printing.

sub_elements()

Return list of sub elements.

symmetry()

Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

class ufl.classes.VectorElement(*family*, *cell=None*, *degree=None*, *dim=None*,
 form_degree=None, *quad_scheme=None*)

Bases: *ufl.finiteelement.mixedelement.MixedElement*

A special case of a mixed finite element where all elements are equal.

reconstruct(**kwargs)**shortstr**()

Format as string for pretty printing.

class ufl.classes.TensorElement(*family*, *cell=None*, *degree=None*, *shape=None*, *symmetry=None*, *quad_scheme=None*)

Bases: *ufl.finiteelement.mixedelement.MixedElement*

A special case of a mixed finite element where all elements are equal.

extract_subelement_component(*i*)

Extract direct subelement index and subelement relative component index for a given component index.

flattened_sub_element_mapping()**mapping**()

Not implemented.

reconstruct(**kwargs)**shortstr**()

Format as string for pretty printing.

symmetry()

Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

class ufl.classes.EnrichedElement(*elements)

Bases: *ufl.finiteelement.enrichedelement.EnrichedElementBase*

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Dual basis is a concatenation of subelements dual bases; primal basis is a concatenation of subelements primal bases; resulting element is not nodal even when subelements are. Structured basis may be exploited in form compilers.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

shortstr()

Format as string for pretty printing.

class ufl.classes.NodalEnrichedElement(*elements)

Bases: *ufl.finiteelement.enrichedelement.EnrichedElementBase*

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Primal basis is reorthogonalized to dual basis which is a concatenation of subelements dual bases; resulting element is nodal.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

shortstr()

Format as string for pretty printing.

class ufl.classes.RestrictedElement(element, restriction_domain)

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

Represents the restriction of a finite element to a type of cell entity.

is_cellwise_constant()

Return whether the basis functions of this element is spatially constant over each cell.

mapping()

Not implemented.

num_restricted_sub_elements()

Return number of restricted sub elements.

num_sub_elements()

Return number of sub elements.

reconstruct(kwargs)****restricted_sub_elements()**

Return list of restricted sub elements.

restriction_domain()

Return the domain onto which the element is restricted.

shortstr()

Format as string for pretty printing.

sub_element()

Return the element which is restricted.

sub_elements()

Return list of sub elements.

symmetry()

Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

class ufl.classes.TensorProductElement(*elements, **kwargs)

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

The tensor product of d element spaces:

$$V = V_1 \otimes V_2 \otimes \dots \otimes V_d$$

Given bases $\{\phi_{j_i}\}$ of the spaces V_i for $i = 1, \dots, d$, $\{\phi_{j_1} \otimes \phi_{j_2} \otimes \dots \otimes \phi_{j_d}\}$ forms a basis for V .

mapping()

Not implemented.

num_sub_elements()

Return number of subelements.

reconstruct(cell=None)

shortstr()

Short pretty-print.

sobolev_space()

Return the underlying Sobolev space of the TensorProductElement.

sub_elements()

Return subelements (factors).

class ufl.classes.HDivElement(element)

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

A div-conforming version of an outer product element, assuming this makes mathematical sense.

mapping()

Not implemented.

reconstruct(kwargs)**

shortstr()

Format as string for pretty printing.

sobolev_space()

Return the underlying Sobolev space.

class ufl.classes.HCurlElement(element)

Bases: *ufl.finiteelement.finiteelementbase.FiniteElementBase*

A curl-conforming version of an outer product element, assuming this makes mathematical sense.

mapping()

Not implemented.

reconstruct(kwargs)**

shortstr()

Format as string for pretty printing.

```

sobolev_space()
    Return the underlying Sobolev space.

class ufl.classes.BrokenElement (element)
    Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
    The discontinuous version of an existing Finite Element space.

mapping()
    Not implemented.

reconstruct (**kwargs)

shortstr()
    Format as string for pretty printing.

ufl.classes.FacetElement (element)
    Constructs the restriction of a finite element to the facets of the cell.

ufl.classes.InteriorElement (element)
    Constructs the restriction of a finite element to the interior of the cell.

class ufl.classes.AbstractDomain (topological_dimension, geometric_dimension)
    Bases: object
    Symbolic representation of a geometric domain with only a geometric and topological dimension.

geometric_dimension()
    Return the dimension of the space this domain is embedded in.

topological_dimension()
    Return the dimension of the topology of this domain.

class ufl.classes.Mesh (coordinate_element, ufl_id=None, cargo=None)
    Bases: ufl.domain.AbstractDomain
    Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cargo()
    Return carried object that will not be used by UFL.

ufl_cell()

ufl_coordinate_element()

ufl_id()
    Return the ufl_id of this object.

class ufl.classes.MeshView (mesh, topological_dimension, ufl_id=None)
    Bases: ufl.domain.AbstractDomain
    Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cell()

ufl_id()
    Return the ufl_id of this object.

ufl_mesh()

class ufl.classes.TensorProductMesh (meshes, ufl_id=None)
    Bases: ufl.domain.AbstractDomain

```

Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cell()

ufl_coordinate_element()

ufl_id()

Return the ufl_id of this object.

class ufl.classes.**AbstractFunctionSpace**

Bases: object

ufl_sub_spaces()

class ufl.classes.**FunctionSpace**(*domain, element*)

Bases: *ufl.functionspace.AbstractFunctionSpace*

ufl_domain()

Return ufl domain.

ufl_domains()

Return ufl domains.

ufl_element()

Return ufl element.

ufl_sub_spaces()

Return ufl sub spaces.

class ufl.classes.**MixedFunctionSpace**(**function_spaces*)

Bases: *ufl.functionspace.AbstractFunctionSpace*

ufl_domain()

Return ufl domain.

ufl_domains()

Return ufl domains.

ufl_element()

Return ufl element.

ufl_sub_spaces()

Return ufl sub spaces.

class ufl.classes.**TensorProductFunctionSpace**(**function_spaces*)

Bases: *ufl.functionspace.AbstractFunctionSpace*

ufl_sub_spaces()

class ufl.classes.**IndexBase**

Bases: object

Base class for all indices.

class ufl.classes.**FixedIndex**(*value*)

Bases: *ufl.core.multiindex.IndexBase*

UFL value: An index with a specific value assigned.

class ufl.classes.**Index**(*count=None*)

Bases: *ufl.core.multiindex.IndexBase*

UFL value: An index with no value assigned.

Used to represent free indices in Einstein indexing notation.

count ()

`ufl.classes.TestFunction(function_space, part=None)`

UFL value: Create a test function argument to a form.

`ufl.classes.TrialFunction(function_space, part=None)`

UFL value: Create a trial function argument to a form.

`ufl.classes.TestFunctions(function_space)`

UFL value: Create a TestFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

`ufl.classes.TrialFunctions(function_space)`

UFL value: Create a TrialFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

class ufl.classes.Measure(integral_type, domain=None, subdomain_id='everywhere', metadata=None, subdomain_data=None)

Bases: object

integral_type ()

Return the domain type.

Valid domain types are “cell”, “exterior_facet”, “interior_facet”, etc.

metadata ()

Return the integral metadata. This data is not interpreted by UFL. It is passed to the form compiler which can ignore it or use it to compile each integral of a form in a different way.

reconstruct (integral_type=None, subdomain_id=None, domain=None, metadata=None, subdomain_main_data=None)

Construct a new Measure object with some properties replaced with new values.

Example: `<dm = Measure instance> b = dm.reconstruct(subdomain_id=2) c = dm.reconstruct(metadata={“quadrature_degree”: 3})`

Used by the call operator, so this is equivalent: `b = dm(2) c = dm(0, {“quadrature_degree”: 3})`

subdomain_data ()

Return the integral subdomain_data. This data is not interpreted by UFL. Its intension is to give a context in which the domain id is interpreted.

subdomain_id ()

Return the domain id of this measure (integer).

ufl_domain ()

Return the domain associated with this measure.

This may be None or a Domain object.

class ufl.classes.MeasureSum(*measures)

Bases: object

Represents a sum of measures.

This is a notational intermediate object to translate the notation

`f*(ds(1)+ds(3))`

into

`f*ds(1) + f*ds(3)`

```
class ufl.classes.MeasureProduct (*measures)
```

Bases: object

Represents a product of measures.

This is a notational intermediate object to handle the notation

```
f*(dm1*dm2)
```

This is work in progress and not functional. It needs support in other parts of ufl and the rest of the code generation chain.

```
sub_measures()
```

Return submeasures.

```
class ufl.classes.Integral(integrand, integral_type, domain, subdomain_id, metadata, subdo-
```

```
main_data)
```

Bases: object

An integral over a single domain.

```
integral_type()
```

Return the domain type of this integral.

```
integrand()
```

Return the integrand expression, which is an Expr instance.

```
metadata()
```

Return the compiler metadata this integral has been annotated with.

```
reconstruct(integrand=None, integral_type=None, domain=None, subdomain_id=None, meta-
```

```
data=None, subdomain_data=None)
```

Construct a new Integral object with some properties replaced with new values.

Example: <a = Integral instance> b = a.reconstruct(expand_compounds(a.integrand())) c = a.reconstruct(metadata={'quadrature_degree':2})

```
subdomain_data()
```

Return the domain data of this integral.

```
subdomain_id()
```

Return the subdomain id of this integral.

```
ufl_domain()
```

Return the integration domain of this integral.

```
class ufl.classes.Form(integrals)
```

Bases: object

Description of a weak form consisting of a sum of integrals over subdomains.

```
arguments()
```

Return all Argument objects found in form.

```
coefficient_numbering()
```

Return a contiguous numbering of coefficients in a mapping {coefficient:number}.

```
coefficients()
```

Return all Coefficient objects found in form.

```
domain_numbering()
```

Return a contiguous numbering of domains in a mapping {domain:number}.

```
empty()
```

Returns whether the form has no integrals.

equals (other)
Evaluate `bool(lhs_form == rhs_form)`.

geometric_dimension ()
Return the geometric dimension shared by all domains and functions in this form.

integrals ()
Return a sequence of all integrals in form.

integrals_by_type (integral_type)
Return a sequence of all integrals with a particular domain type.

max_subdomain_ids ()
Returns a mapping on the form `{domain:{integral_type:max_subdomain_id}}`.

signature ()
Signature for use with jit cache (independent of incidental numbering of indices etc.)

subdomain_data ()
Returns a mapping on the form `{domain:{integral_type: subdomain_data}}`.

ufl_cell ()
Return the single cell this form is defined on, fails if multiple cells are found.

ufl_domain ()
Return the single geometric integration domain occurring in the form.
Fails if multiple domains are found.
NB! This does not include domains of coefficients defined on other meshes, look at form data for that additional information.

ufl_domains ()
Return the geometric integration domains occurring in the form.
NB! This does not include domains of coefficients defined on other meshes.
The return type is a tuple even if only a single domain exists.

x_repr_latex_ ()

x_repr_png_ ()

class ufl.classes.Equation (lhs, rhs)
Bases: object
This class is used to represent equations expressed by the “`==`” operator. Examples include `a == L` and `F == 0` where `a`, `L` and `F` are Form objects.

1.3.10 ufl.coefficient module

This module defines the Coefficient class and a number of related classes, including Constant.

class ufl.coefficient.Coefficient (function_space, count=None)
Bases: `ufl.core.terminal.FormArgument`
UFL form argument type: Representation of a form coefficient.

count ()

is_cellwise_constant ()
Return whether this expression is spatially constant over each cell.

```
ufl_domain()
    Shortcut to get the domain of the function space of this coefficient.

ufl_domains()
    Return tuple of domains related to this terminal object.

ufl_element()
    Shortcut to get the finite element of the function space of this coefficient.

ufl_function_space()
    Get the function space of this coefficient.

ufl_shape
    Return the associated UFL shape.

ufl.coefficient.Coefficients(function_space)
    UFL value: Create a Coefficient in a mixed space, and return a tuple with the function components corresponding to the subelements.

ufl.coefficient.Constant(domain, count=None)
    UFL value: Represents a globally constant scalar valued coefficient.

ufl.coefficient.TensorConstant(domain, shape=None, symmetry=None, count=None)
    UFL value: Represents a globally constant tensor valued coefficient.

ufl.coefficient.VectorConstant(domain, dim=None, count=None)
    UFL value: Represents a globally constant vector valued coefficient.
```

1.3.11 ufl.compound_expressions module

Functions implementing compound expressions as equivalent representations using basic operators.

```
ufl.compound_expressions.adj_expr(A)
ufl.compound_expressions.adj_expr_2x2(A)
ufl.compound_expressions.adj_expr_3x3(A)
ufl.compound_expressions.adj_expr_4x4(A)
ufl.compound_expressions.codeterminant_expr_nxn(A, rows, cols)
ufl.compound_expressions.cofactor_expr(A)
ufl.compound_expressions.cofactor_expr_2x2(A)
ufl.compound_expressions.cofactor_expr_3x3(A)
ufl.compound_expressions.cofactor_expr_4x4(A)
ufl.compound_expressions.cross_expr(a, b)
ufl.compound_expressions.determinant_expr(A)
    Compute the (pseudo-)determinant of A.

ufl.compound_expressions.determinant_expr_2x2(B)
ufl.compound_expressions.determinant_expr_3x3(A)
ufl.compound_expressions.deviatoric_expr(A)
ufl.compound_expressions.deviatoric_expr_2x2(A)
ufl.compound_expressions.deviatoric_expr_3x3(A)
```

```
ufl.compound_expressions.generic_pseudo_determinant_expr(A)
    Compute the pseudo-determinant of A: sqrt(det(A.T*A)).
```

```
ufl.compound_expressions.generic_pseudo_inverse_expr(A)
    Compute the Penrose-Moore pseudo-inverse of A: (A.T*A)^-1 * A.T.
```

```
ufl.compound_expressions.inverse_expr(A)
    Compute the inverse of A.
```

```
ufl.compound_expressions.old_determinant_expr_3x3(A)
```

```
ufl.compound_expressions.pseudo_determinant_expr(A)
    Compute the pseudo-determinant of A.
```

```
ufl.compound_expressions.pseudo_inverse_expr(A)
    Compute the Penrose-Moore pseudo-inverse of A: (A.T*A)^-1 * A.T.
```

1.3.12 ufl.conditional module

This module defines classes for conditional expressions.

```
class ufl.conditional.AndCondition(left, right)
    Bases: ufl.conditional.BinaryCondition

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.
```

```
class ufl.conditional.BinaryCondition(name, left, right)
    Bases: ufl.conditional.Condition
```

```
class ufl.conditional.Condition(operands)
    Bases: ufl.core.operator.Operator

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()
```

```
class ufl.conditional.Conditional(condition, true_value, false_value)
    Bases: ufl.core.operator.Operator

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

```
class ufl.conditional.EQ(left, right)
    Bases: ufl.conditional.BinaryCondition

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.
```

```
class ufl.conditional.GE(left, right)
    Bases: ufl.conditional.BinaryCondition

    evaluate(x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.
```

```
class ufl.conditional.GT(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

class ufl.conditional.LE(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

class ufl.conditional.LT(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

class ufl.conditional.MaxValue(left, right)
Bases: ufl.core.operator.Operator
UFL operator: Take the maximum of two values.
evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

 = ()
 = ()
 = ()

class ufl.conditional.MinValue(left, right)
Bases: ufl.core.operator.Operator
UFL operator: Take the minimum of two values.
evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

 = ()
 = ()
 = ()

class ufl.conditional.NE(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

class ufl.conditional.NotCondition(condition)
Bases: ufl.conditional.Condition
evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

class ufl.conditional.OrCondition(left, right)
Bases: ufl.conditional.BinaryCondition
evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.
```

1.3.13 ufl.constantvalue module

This module defines classes representing constant values.

class `ufl.constantvalue.ConstantValue`

Bases: `ufl.core.terminal.Terminal`

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

ufl_domains()

Return tuple of domains related to this terminal object.

class `ufl.constantvalue.FloatValue(value)`

Bases: `ufl.constantvalue.ScalarValue`

UFL literal type: Representation of a constant scalar floating point value.

class `ufl.constantvalue.Identity(dim)`

Bases: `ufl.constantvalue.ConstantValue`

UFL literal type: Representation of an identity matrix.

evaluate(x, mapping, component, index_values)

Evaluates the identity matrix on the given components.

ufl_shape

class `ufl.constantvalue.IntValue(value)`

Bases: `ufl.constantvalue.ScalarValue`

UFL literal type: Representation of a constant scalar integer value.

class `ufl.constantvalue.PermutationSymbol(dim)`

Bases: `ufl.constantvalue.ConstantValue`

UFL literal type: Representation of a permutation symbol.

This is also known as the Levi-Civita symbol, antisymmetric symbol, or alternating symbol.

evaluate(x, mapping, component, index_values)

Evaluates the permutation symbol.

ufl_shape

class `ufl.constantvalue.ScalarValue(value)`

Bases: `ufl.constantvalue.ConstantValue`

A constant scalar value.

evaluate(x, mapping, component, index_values)

Get `self` from `mapping` and return the component asked for.

ufl_free_indices = ()

ufl_index_dimensions = ()

ufl_shape = ()

value()

class `ufl.constantvalue.Zero(shape=(), free_indices=(), index_dimensions=None)`

Bases: `ufl.constantvalue.ConstantValue`

UFL literal type: Representation of a zero valued expression.

evaluate (*x, mapping, component, index_values*)Get *self* from *mapping* and return the component asked for.**ufl_free_indices**

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

ufl_index_dimensions

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

ufl_shape**ufl.constantvalue.as_ufl** (*expression*)

Converts expression to an Expr if possible.

ufl.constantvalue.format_float (*x*)

Format float value based on global UFL precision.

ufl.constantvalue.zero (**shape*)

UFL literal constant: Return a zero tensor with the given shape.

1.3.14 ufl.differentiation module

Differential operators.

class *ufl.differentiation.CoefficientDerivative* (*integrand, coefficients, arguments, coefficient_derivatives*)Bases: *ufl.differentiation.Derivative*

Derivative of the integrand of a form w.r.t. the degrees of freedom in a discrete Coefficient.

ufl_free_indices**ufl_index_dimensions****ufl_shape****class** *ufl.differentiation.CompoundDerivative* (*operands*)Bases: *ufl.differentiation.Derivative*

Base class for all compound derivative types.

class *ufl.differentiation.Curl* (*f*)Bases: *ufl.differentiation.CompoundDerivative***ufl_free_indices****ufl_index_dimensions****ufl_shape****class** *ufl.differentiation.Derivative* (*operands*)Bases: *ufl.core.operator.Operator*

Base class for all derivative types.

class *ufl.differentiation.Div* (*f*)Bases: *ufl.differentiation.CompoundDerivative***ufl_free_indices****ufl_index_dimensions**

```



class ufl.differentiation.Grad(f)
    Bases: ufl.differentiation.CompoundDerivative
    evaluate (x, mapping, component, index_values, derivatives=())
        Get child from mapping and return the component asked for.





class ufl.differentiation.NablaDiv(f)
    Bases: ufl.differentiation.CompoundDerivative
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.NablaGrad(f)
    Bases: ufl.differentiation.CompoundDerivative
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.ReferenceCurl(f)
    Bases: ufl.differentiation.CompoundDerivative
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.ReferenceDiv(f)
    Bases: ufl.differentiation.CompoundDerivative
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.ReferenceGrad(f)
    Bases: ufl.differentiation.CompoundDerivative
    evaluate (x, mapping, component, index_values, derivatives=())
        Get child from mapping and return the component asked for.

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.differentiation.VariableDerivative(f, v)
    Bases: ufl.differentiation.Derivative
    ufl_free_indices
    ufl_index_dimensions

```

ufl_shape

1.3.15 ufl.domain module

Types for representing a geometric domain.

class `ufl.domain.AbstractDomain` (*topological_dimension*, *geometric_dimension*)

Bases: `object`

Symbolic representation of a geometric domain with only a geometric and topological dimension.

geometric_dimension()

Return the dimension of the space this domain is embedded in.

topological_dimension()

Return the dimension of the topology of this domain.

class `ufl.domain.Mesh` (*coordinate_element*, *ufl_id=None*, *cargo=None*)

Bases: `ufl.domain.AbstractDomain`

Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cargo()

Return carried object that will not be used by UFL.

ufl_cell()

ufl_coordinate_element()

ufl_id()

Return the `ufl_id` of this object.

class `ufl.domain.MeshView` (*mesh*, *topological_dimension*, *ufl_id=None*)

Bases: `ufl.domain.AbstractDomain`

Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cell()

ufl_id()

Return the `ufl_id` of this object.

ufl_mesh()

class `ufl.domain.TensorProductMesh` (*meshes*, *ufl_id=None*)

Bases: `ufl.domain.AbstractDomain`

Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()

ufl_cell()

ufl_coordinate_element()

ufl_id()

Return the `ufl_id` of this object.

`ufl.domain.affine_mesh` (*cell*, *ufl_id=None*)

Create a Mesh over a given cell type with an affine geometric parameterization.

`ufl.domain.as_domain(domain)`
Convert any valid object to an AbstractDomain type.

`ufl.domain.default_domain(cell)`
Create a singular default Mesh from a cell, always returning the same Mesh object for the same cell.

`ufl.domain.extract_domains(expr)`
Return all domains expression is defined on.

`ufl.domain.extract_unique_domain(expr)`
Return the single unique domain expression is defined on or throw an error.

`ufl.domain.find_geometric_dimension(expr)`
Find the geometric dimension of an expression.

`ufl.domain.join_domains(domains)`
Take a list of domains and return a tuple with only unique domain objects.
Checks that domains with the same id are compatible.

`ufl.domain.sort_domains(domains)`
Sort domains in a canonical ordering.

1.3.16 ufl.equation module

The Equation class, used to express equations like $a == L$.

`class ufl.equation.Equation(lhs, rhs)`
Bases: object

This class is used to represent equations expressed by the “ $==$ ” operator. Examples include $a == L$ and $F == 0$ where a , L and F are Form objects.

1.3.17 ufl.exprcontainers module

This module defines special types for representing mapping of expressions to expressions.

`class ufl.exprcontainers.ExprList(*operands)`
Bases: `ufl.core.operator.Operator`

List of Expr objects. For internal use, never to be created by end users.

`free_indices()`
`index_dimensions()`
`ufl_free_indices`
`ufl_index_dimensions`
`ufl_shape`

`class ufl.exprcontainers.ExprMapping(*operands)`
Bases: `ufl.core.operator.Operator`

Mapping of Expr objects. For internal use, never to be created by end users.

`free_indices()`
`index_dimensions()`
`ufl_domains()`
Return all domains this expression is defined on.

```
ufl_free_indices
ufl_index_dimensions
ufl_shape
```

1.3.18 ufl.exprquals module

`ufl.exprquals.expr_equals(self, other)`

Checks whether the two expressions are represented the exact same way. This does not check if the expressions are mathematically equal or equivalent! Used by sets and dicts.

`ufl.exprquals.measure_collisions(equals_func)`

`ufl.exprquals.nonrecursive_expr_equals(self, other)`

Checks whether the two expressions are represented the exact same way. This does not check if the expressions are mathematically equal or equivalent! Used by sets and dicts.

`ufl.exprquals.print_collisions()`

`ufl.exprquals.recursive_expr_equals(self, other)`

Checks whether the two expressions are represented the exact same way. This does not check if the expressions are mathematically equal or equivalent! Used by sets and dicts.

1.3.19 ufl.exprooperators module

This module attaches special functions to Expr. This way we avoid circular dependencies between e.g. Sum and its superclass Expr.

`ufl.exprooperators.analyse_key(ii, rank)`

Takes something the user might input as an index tuple inside [], which could include complete slices (:) and ellipsis (...), and returns tuples of actual UFL index objects.

The return value is a tuple (indices, axis_indices), each being a tuple of IndexBase instances.

The return value ‘indices’ corresponds to all input objects of these types: - Index - FixedIndex - int => Wrapped in FixedIndex

The return value ‘axis_indices’ corresponds to all input objects of these types: - Complete slice (:) => Replaced by a single new index - Ellipsis (...) => Replaced by multiple new indices

1.3.20 ufl.form module

The Form class.

`class ufl.form.Form(integrals)`

Bases: object

Description of a weak form consisting of a sum of integrals over subdomains.

`arguments()`

Return all Argument objects found in form.

`coefficient_numbering()`

Return a contiguous numbering of coefficients in a mapping {coefficient : number}.

`coefficients()`

Return all Coefficient objects found in form.

domain_numbering()
 Return a contiguous numbering of domains in a mapping {domain:number}.

empty()
 Returns whether the form has no integrals.

equals(*other*)
 Evaluate bool(lhs_form == rhs_form).

geometric_dimension()
 Return the geometric dimension shared by all domains and functions in this form.

integrals()
 Return a sequence of all integrals in form.

integrals_by_type(*integral_type*)
 Return a sequence of all integrals with a particular domain type.

max_subdomain_ids()
 Returns a mapping on the form {domain:{integral_type:max_subdomain_id}}.

signature()
 Signature for use with jit cache (independent of incidental numbering of indices etc.)

subdomain_data()
 Returns a mapping on the form {domain:{integral_type: subdomain_data}}.

ufl_cell()
 Return the single cell this form is defined on, fails if multiple cells are found.

ufl_domain()
 Return the single geometric integration domain occurring in the form.
 Fails if multiple domains are found.
 NB! This does not include domains of coefficients defined on other meshes, look at form data for that additional information.

ufl_domains()
 Return the geometric integration domains occurring in the form.
 NB! This does not include domains of coefficients defined on other meshes.
 The return type is a tuple even if only a single domain exists.

x_repr_latex_()

x_repr_png_()

ufl.form.as_form(*form*)
 Convert to form if not a form, otherwise return form.

ufl.form.replace_integral_domains(*form, common_domain*)
 Given a form and a domain, assign a common integration domain to all integrals.
 Does not modify the input form (Form should always be immutable). This is to support ill formed forms with no domain specified, sometimes occurring in pydolfin, e.g. assemble(1*dx, mesh=mesh).

1.3.21 ufl.formoperators module

Various high level ways to transform a complete Form into a new Form.

`ufl.formoperators.action (form, coefficient=None)`

UFL form operator: Given a bilinear form, return a linear form with an additional coefficient, representing the action of the form on the coefficient. This can be used for matrix-free methods.

`ufl.formoperators.adjoint (form, reordered_arguments=None)`

UFL form operator: Given a combined bilinear form, compute the adjoint form by changing the ordering (count) of the test and trial functions.

By default, new `Argument` objects will be created with opposite ordering. However, if the adjoint form is to be added to other forms later, their arguments must match. In that case, the user must provide a tuple `*reordered_arguments*=(u2,v2)`.

`ufl.formoperators.block_split (form, ix, iy=0)`

UFL form operator: Given a linear or bilinear form on a mixed space, extract the block corresponding to the indices `ix, iy`.

Example:

```
a = inner(grad(u), grad(v))*dx + div(u)*q*dx + div(v)*p*dx a = block_split(a, 0, 0) -> inner(grad(u), grad(v))*dx
```

`ufl.formoperators.derivative (form, coefficient, argument=None, coefficient_derivatives=None)`

UFL form operator: Compute the Gateaux derivative of `form` w.r.t. `coefficient` in direction of `argument`.

If the argument is omitted, a new `Argument` is created in the same space as the coefficient, with argument number one higher than the highest one in the form.

The resulting form has one additional `Argument` in the same finite element space as the coefficient.

A tuple of `Coefficient`s may be provided in place of a single `Coefficient`, in which case the new `Argument` argument is based on a `MixedElement` created from this tuple.

An indexed `Coefficient` from a mixed space may be provided, in which case the argument should be in the corresponding subspace of the coefficient space.

If provided, `coefficient_derivatives` should be a mapping from `Coefficient` instances to their derivatives w.r.t. `coefficient`.

`ufl.formoperators.energy_norm (form, coefficient=None)`

UFL form operator: Given a bilinear form `a` and a coefficient `f`, return the functional $a(f, f)$.

`ufl.formoperators.functionals (form)`

UFL form operator: Extract the functional part of form.

`ufl.formoperators.lhs (form)`

UFL form operator: Given a combined bilinear and linear form, extract the left hand side (bilinear form part).

Example:

```
a = u*v*dx + f*v*dx
a = lhs(a) -> u*v*dx
```

`ufl.formoperators.rhs (form)`

UFL form operator: Given a combined bilinear and linear form, extract the right hand side (negated linear form part).

Example:

```
a = u*v*dx + f*v*dx
L = rhs(a) -> -f*v*dx
```

`ufl.formoperators.sensitivity_rhs (a, u, L, v)`

UFL form operator: Compute the right hand side for a sensitivity calculation system.

The derivation behind this computation is as follows. Assume a, L to be bilinear and linear forms corresponding to the assembled linear system

$$Ax = b.$$

Where x is the vector of the discrete function corresponding to u . Let v be some scalar variable this equation depends on. Then we can write

$$\begin{aligned} 0 &= \frac{d}{dv}(Ax - b) = \frac{dA}{dv}x + A\frac{dx}{dv} - \frac{db}{dv}, \\ A\frac{dx}{dv} &= \frac{db}{dv} - \frac{dA}{dv}x, \end{aligned}$$

and solve this system for $\frac{dx}{dv}$, using the same bilinear form a and matrix A from the original system. Assume the forms are written

```
v = variable(v_expression)
L = IL(v)*dx
a = Ia(v)*dx
```

where IL and Ia are integrand expressions. Define a Coefficient u representing the solution to the equations. Then we can compute $\frac{db}{dv}$ and $\frac{dA}{dv}$ from the forms

```
da = diff(a, v)
dL = diff(L, v)
```

and the action of da on u by

```
dau = action(da, u)
```

In total, we can build the right hand side of the system to compute $\frac{du}{dv}$ with the single line

```
dL = diff(L, v) - action(diff(a, v), u)
```

or, using this function,

```
dL = sensitivity_rhs(a, u, L, v)
```

```
ufl.formoperators.set_list_item(li, i, v)
```

```
ufl.formoperators.system(form)
```

UFL form operator: Split a form into the left hand side and right hand side, see `lhs` and `rhs`.

```
ufl.formoperators.zero_lists(shape)
```

1.3.22 ufl.functionspace module

Types for representing function spaces.

```
class ufl.functionspace.AbstractFunctionSpace
```

Bases: object

```
ufl_sub_spaces()
```

```
class ufl.functionspace.FunctionSpace(domain, element)
```

Bases: `ufl.functionspace.AbstractFunctionSpace`

```
ufl_domain()
```

Return ufl domain.

```
ufl_domains()
    Return ufl domains.

ufl_element()
    Return ufl element.

ufl_sub_spaces()
    Return ufl sub spaces.

class ufl.functionspace.MixedFunctionSpace(*function_spaces)
    Bases: ufl.functionspace.AbstractFunctionSpace

    ufl_domain()
        Return ufl domain.

    ufl_domains()
        Return ufl domains.

    ufl_element()
        Return ufl element.

    ufl_sub_spaces()
        Return ufl sub spaces.

class ufl.functionspace.TensorProductFunctionSpace(*function_spaces)
    Bases: ufl.functionspace.AbstractFunctionSpace

    ufl_sub_spaces()
```

1.3.23 ufl.geometry module

Types for representing symbolic expressions for geometric quantities.

```
class ufl.geometry.CellCoordinate(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFC geometry representation: The coordinate in a reference cell.

    In the context of expression integration, represents the reference cell coordinate of each quadrature point.

    In the context of expression evaluation in a point in a cell, represents that point in the reference coordinate system of the cell.

    is_cellwise_constant()
        Return whether this expression is spatially constant over each cell.

    name = 'X'

    ufl_shape
        tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

        If the argument is a tuple, the return value is the same object.

class ufl.geometry.CellDiameter(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFC geometry representation: The diameter of the cell, i.e., maximal distance of two points in the cell.

    name = 'diameter'

class ufl.geometry.CellEdgeVectors(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFC geometry representation: The vectors between physical cell vertices for each edge in cell.
```

```

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'CEV'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.geometry.CellFacetJacobian(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The Jacobian of the mapping from reference facet to reference cell coordinates.

CFJ_ij = dX_i/dXf_j

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'CFJ'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.geometry.CellFacetJacobianDeterminant(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The pseudo-determinant of the CellFacetJacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'detCFJ'

class ufl.geometry.CellFacetJacobianInverse(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The pseudo-inverse of the CellFacetJacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'CFK'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.geometry.CellFacetOrigin(domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The reference cell coordinate corresponding to origin of a reference facet.

name = 'x0f'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.geometry.CellNormal(domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The upwards pointing normal vector of the current manifold cell.

```
name = 'cell_normal'
```

ufl_shape

Return the number of coordinates defined (i.e. the geometric dimension of the domain).

```
class ufl.geometry.CellOrientation(domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The orientation (+1/-1) of the current cell.

For non-manifold cells ($\text{tdim} == \text{gdim}$), this equals the sign of the Jacobian determinant, i.e. +1 if the physical cell is oriented the same way as the reference cell and -1 otherwise.

For manifold cells of $\text{tdim} == \text{gdim}-1$ this is input data belonging to the mesh, used to distinguish between the sides of the manifold.

```
name = 'cell_orientation'
```

```
class ufl.geometry.CellOrigin(domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The spatial coordinate corresponding to origin of a reference cell.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell (or over each facet for facet quantities).

```
name = 'x0'
```

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

```
class ufl.geometry.CellVertices(domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: Physical cell vertices.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

```
name = 'CV'
```

ufl_shape

tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

```
class ufl.geometry.CellVolume(domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The volume of the cell.

```
name = 'volume'
```

```
class ufl.geometry.Circumradius(domain)
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The circumradius of the cell.

```
name = 'circumradius'
```

```
class ufl.geometry.FacetArea(domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The area of the facet.

```
name = 'facetarea'

class ufl.geometry.FacetCoordinate(domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The coordinate in a reference cell of a facet.

In the context of expression integration over a facet, represents the reference facet coordinate of each quadrature point.

In the context of expression evaluation in a point on a facet, represents that point in the reference coordinate system of the facet.

```
is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'Xf'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
        If the argument is a tuple, the return value is the same object.
```

```
class ufl.geometry.FacetEdgeVectors(domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The vectors between physical cell vertices for each edge in current facet.

```
is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'FEV'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
        If the argument is a tuple, the return value is the same object.
```

```
class ufl.geometry.FacetJacobian(domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The Jacobian of the mapping from reference facet to spatial coordinates.

$$FJ_{ij} = dx_i/dXf_j$$

The FacetJacobian is the product of the Jacobian and CellFacetJacobian:

$$FJ = dx/dXf = dx/dX dX/dXf = J * CFJ$$

```
is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'FJ'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
        If the argument is a tuple, the return value is the same object.
```

```
class ufl.geometry.FacetJacobianDeterminant(domain)
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The pseudo-determinant of the FacetJacobian.

```
is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'detFJ'

class ufl.geometry.Facet JacobianInverse (domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The pseudo-inverse of the Facet Jacobian.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'FK'

ufl_shape
tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.geometry.FacetNormal (domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The outwards pointing normal vector of the current facet.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'n'

ufl_shape
Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.geometry.FacetOrientation (domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The orientation (+1/-1) of the current facet relative to the reference cell.

name = 'facet_orientation'

class ufl.geometry.FacetOrigin (domain)
Bases: ufl.geometry.GeometricFacetQuantity

UFL geometry representation: The spatial coordinate corresponding to origin of a reference facet.

name = 'x0f'

ufl_shape
tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
    If the argument is a tuple, the return value is the same object.

class ufl.geometry.GeometricCellQuantity (domain)
Bases: ufl.geometry.GeometricQuantity

class ufl.geometry.GeometricFacetQuantity (domain)
Bases: ufl.geometry.GeometricQuantity

class ufl.geometry.GeometricQuantity (domain)
Bases: ufl.core.terminal.Terminal

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell (or over each facet for facet quantities).

ufl_domains()
    Return tuple of domains related to this terminal object.
```

```
ufl_shape = ()  
  
class ufl.geometry.Jacobian(domain)  
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The Jacobian of the mapping from reference cell to spatial coordinates.

$$J_{ij} = \frac{dx_i}{dX_j}$$

```
is_cellwise_constant()  
Return whether this expression is spatially constant over each cell.  
  
name = 'J'  
  
ufl_shape  
Return the number of coordinates defined (i.e. the geometric dimension of the domain).
```

```
class ufl.geometry.JacobianDeterminant(domain)  
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The determinant of the Jacobian.

Represents the signed determinant of a square Jacobian or the pseudo-determinant of a non-square Jacobian.

```
is_cellwise_constant()  
Return whether this expression is spatially constant over each cell.
```

```
name = 'detJ'
```

```
class ufl.geometry.JacobianInverse(domain)  
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The inverse of the Jacobian.

Represents the inverse of a square Jacobian or the pseudo-inverse of a non-square Jacobian.

```
is_cellwise_constant()  
Return whether this expression is spatially constant over each cell.
```

```
name = 'K'
```

```
ufl_shape  
Return the number of coordinates defined (i.e. the geometric dimension of the domain).
```

```
class ufl.geometry.MaxCellEdgeLength(domain)  
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The maximum edge length of the cell.

```
name = 'maxcelleddgelength'
```

```
class ufl.geometry.MaxFacetEdgeLength(domain)  
Bases: ufl.geometry.GeometricFacetQuantity
```

UFL geometry representation: The maximum edge length of the facet.

```
name = 'maxfacetedgedgelength'
```

```
class ufl.geometry.MinCellEdgeLength(domain)  
Bases: ufl.geometry.GeometricCellQuantity
```

UFL geometry representation: The minimum edge length of the cell.

```
name = 'mincelleddgelength'
```

```
class ufl.geometry.MinFacetEdgeLength(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The minimum edge length of the facet.

name = 'minfacetedgelenlength'

class ufl.geometry.QuadratureWeight(domain)
Bases: ufl.geometry.GeometricQuantity
UFL geometry representation: The current quadrature weight.

Only used inside a quadrature context.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'weight'

class ufl.geometry.ReferenceCellEdgeVectors(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The vectors between reference cell vertices for each edge in cell.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'RCEV'

ufl_shape
tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
If the argument is a tuple, the return value is the same object.

class ufl.geometry.ReferenceCellVolume(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The volume of the reference cell.

name = 'reference_cell_volume'

class ufl.geometry.ReferenceFacetEdgeVectors(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The vectors between reference cell vertices for each edge in current facet.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'RFEV'

ufl_shape
tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
If the argument is a tuple, the return value is the same object.

class ufl.geometry.ReferenceFacetVolume(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The volume of the reference cell of the current facet.

name = 'reference_facet_volume'

class ufl.geometry.ReferenceNormal(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The outwards pointing normal vector of the current facet on the reference cell
```

```

name = 'reference_normal'

ufl_shape
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
        If the argument is a tuple, the return value is the same object.

class ufl.geometry.SpatialCoordinate(domain)
    Bases: ufl.geometry.GeometricCellQuantity

    UFL geometry representation: The coordinate in a domain.

    In the context of expression integration, represents the domain coordinate of each quadrature point.

    In the context of expression evaluation in a point, represents the value of that point.

evaluate (x, mapping, component, index_values)
    Return the value of the coordinate.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'x'

ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

```

1.3.24 ufl.index_combination_utils module

Utilities for analysing and manipulating free index tuples

`ufl.index_combination_utils.create_slice_indices(component, shape, fi)`

`ufl.index_combination_utils.merge_nonoverlapping_indices(a, b)`

Merge non-overlapping free indices into one representation.

Example: $C[i,j,r,s] = \text{outer}(A[i,s], B[j,r])$ A, B -> (i,j,r,s), (idim,jdim,rdim,sdim)

`ufl.index_combination_utils.merge_overlapping_indices(afi, afid, bfi, bfid)`

Merge overlapping free indices into one free and one repeated representation.

Example: $C[j,r] := A[i,j,k] * B[i,r,k]$ A, B -> (j,r), (jdim,rdim), (i,k), (idim,kdim)

`ufl.index_combination_utils.merge_unique_indices(afi, afid, bfi, bfid)`

Merge two pairs of (index ids, index dimensions) sequences into one pair without duplicates.

The id tuples afi, bfi are assumed already sorted by id. Given a list of (id, dim) tuples already sorted by id, return a unique list with duplicates removed. Also checks that the dimensions of duplicates are matching.

`ufl.index_combination_utils.remove_indices(fi, fid, rfi)`

`ufl.index_combination_utils.unique_sorted_indices(indices)`

Given a list of (id, dim) tuples already sorted by id, return a unique list with duplicates removed. Also checks that the dimensions of duplicates are matching.

1.3.25 ufl.indexed module

This module defines the Indexed class.

`class ufl.indexed.Indexed(expression, multiindex)`

Bases: `ufl.core.operator.Operator`

```
evaluate (x, mapping, component, index_values, derivatives=())
    Evaluate expression at given coordinate with given values for terminals.

ufl_free_indices
ufl_index_dimensions
ufl_shape = ()
```

1.3.26 ufl.indexsum module

This module defines the IndexSum class.

```
class ufl.indexsum.IndexSum (summand, index)
    Bases: ufl.core.operator.Operator

    dimension ()

    evaluate (x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    index ()
    ufl_free_indices
    ufl_index_dimensions
    ufl_shape
```

1.3.27 ufl.integral module

The Integral class.

```
class ufl.integral.Integral (integrand, integral_type, domain, subdomain_id, metadata, subdomain_data)
    Bases: object

    An integral over a single domain.

    integral_type ()
        Return the domain type of this integral.

    integrand ()
        Return the integrand expression, which is an Expr instance.

    metadata ()
        Return the compiler metadata this integral has been annotated with.

    reconstruct (integrand=None, integral_type=None, domain=None, subdomain_id=None, metadata=None, subdomain_data=None)
        Construct a new Integral object with some properties replaced with new values.

    Example: <a = Integral instance> b = a.reconstruct(expand_compounds(a.integrand()))
    c = a.reconstruct(metadata={'quadrature_degree':2})

    subdomain_data ()
        Return the domain data of this integral.

    subdomain_id ()
        Return the subdomain id of this integral.

    ufl_domain ()
        Return the integration domain of this integral.
```

1.3.28 ufl.log module

This module provides functions used by the UFL implementation to output messages. These may be redirected by the user of UFL.

```
class ufl.log.Logger(name, exception_type=<class 'Exception'>)
Bases: object

add_indent (increment=1)
    Add to indentation level.

add_logfile (filename=None, mode='a', level=10)
    Add a log file.

begin (*message)
    Begin task: write message and increase indentation level.

debug (*message)
    Write debug message.

deprecate (*message)
    Write deprecation message.

end ()
    End task: write a newline and decrease indentation level.

error (*message)
    Write error message and raise an exception.

get_handler ()
    Get handler for logging.

get_logfile_handler (filename)
    Gets the handler to the file identified by the given file name.

get_logger ()
    Return message logger.

info (*message)
    Write info message.

info_blue (*message)
    Write info message in blue.

info_green (*message)
    Write info message in green.

info_red (*message)
    Write info message in red.

log (level, *message)
    Write a log message on given log level.

pop_level ()
    Pop log level from the level stack, reverting to before the last push_level.

push_level (level)
    Push a log level on the level stack.

set_handler (handler)
    Replace handler for logging. To add additional handlers instead of replacing the existing one, use log.get_logger().addHandler(myhandler). See the logging module for more details.
```

```
set_indent (level)
    Set indentation level.

set_level (level)
    Set log level.

set_prefix (prefix)
    Set prefix for log messages.

warning (*message)
    Write warning message.

warning_blue (*message)
    Write warning message in blue.

warning_green (*message)
    Write warning message in green.

warning_red (*message)
    Write warning message in red.
```

1.3.29 ufl.mathfunctions module

This module provides basic mathematical functions.

```
class ufl.mathfunctions.Acos (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Asin (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Atan (argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Atan2 (arg1, arg2)
    Bases: ufl.core.operator.Operator

    evaluate (x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.mathfunctions.BesselFunction (name, classname, nu, argument)
    Bases: ufl.core.operator.Operator

    Base class for all bessel functions

    evaluate (x, mapping, component, index_values)
        Evaluate expression at given coordinate with given values for terminals.

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.mathfunctions.BesselI (nu, argument)
    Bases: ufl.mathfunctions.BesselFunction
```

```

class ufl.mathfunctions.BesselJ(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.mathfunctions.BesselK(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.mathfunctions.Bessely(nu, argument)
    Bases: ufl.mathfunctions.BesselFunction

class ufl.mathfunctions.Cos(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Cosh(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Erf(argument)
    Bases: ufl.mathfunctions.MathFunction

evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

class ufl.mathfunctions.Exp(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Ln(argument)
    Bases: ufl.mathfunctions.MathFunction

evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

class ufl.mathfunctions.MathFunction(name, argument)
    Bases: ufl.core.operator.Operator

    Base class for all unary scalar math functions.

evaluate (x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

ufl_free_indices = ()
ufl_index_dimensions = ()
ufl_shape = ()

class ufl.mathfunctions.Sin(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Sinh(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Sqrt(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Tan(argument)
    Bases: ufl.mathfunctions.MathFunction

class ufl.mathfunctions.Tanh(argument)
    Bases: ufl.mathfunctions.MathFunction

```

1.3.30 ufl.measure module

The Measure class.

```
class ufl.measure.Measure(integral_type, domain=None, subdomain_id='everywhere', metadata=None, subdomain_data=None)
```

Bases: object

integral_type()

Return the domain type.

Valid domain types are “cell”, “exterior_facet”, “interior_facet”, etc.

metadata()

Return the integral metadata. This data is not interpreted by UFL. It is passed to the form compiler which can ignore it or use it to compile each integral of a form in a different way.

reconstruct(integral_type=None, subdomain_id=None, domain=None, metadata=None, subdomain_main_data=None)

Construct a new Measure object with some properties replaced with new values.

Example: <dm = Measure instance> b = dm.reconstruct(subdomain_id=2) c = dm.reconstruct(metadata={“quadrature_degree”: 3})

Used by the call operator, so this is equivalent: b = dm(2) c = dm(0, {“quadrature_degree”: 3})

subdomain_data()

Return the integral subdomain_data. This data is not interpreted by UFL. Its intension is to give a context in which the domain id is interpreted.

subdomain_id()

Return the domain id of this measure (integer).

ufl_domain()

Return the domain associated with this measure.

This may be None or a Domain object.

```
class ufl.measure.MeasureProduct(*measures)
```

Bases: object

Represents a product of measures.

This is a notational intermediate object to handle the notation

f*(dm1*dm2)

This is work in progress and not functional. It needs support in other parts of ufl and the rest of the code generation chain.

sub_measures()

Return submeasures.

```
class ufl.measure.MeasureSum(*measures)
```

Bases: object

Represents a sum of measures.

This is a notational intermediate object to translate the notation

f*(ds(1)+ds(3))

into

f*ds(1) + f*ds(3)

```
ufl.measure.as_integral_type(integral_type)
```

Map short name to long name and require a valid one.

```
ufl.measure.integral_types()
    Return a tuple of all domain type strings.

ufl.measure.measure_names()
    Return a tuple of all measure name strings.

ufl.measure.register_integral_type(integral_type, measure_name)
```

1.3.31 ufl.objects module

Utility objects for pretty syntax in user code.

1.3.32 ufl.operators module

This module extends the form language with free function operators, which are either already available as member functions on UFL objects or defined as compound operators involving basic operations on the UFL objects.

```
ufl.operators.And(left, right)
    UFL operator: A boolean expression (left and right) for use with conditional.

ufl.operators.Dn(f)
    UFL operator: Take the directional derivative of  $f$  in the facet normal direction,  $Dn(f) := \text{dot}(\text{grad}(f), n)$ .

ufl.operators.Dt(f)
    UFL operator: <Not implemented yet!> The partial derivative of  $f$  with respect to time.

ufl.operators.Dx(f, *i)
    UFL operator: Take the partial derivative of  $f$  with respect to spatial variable number  $i$ . Equivalent to  $f.dx(*i)$ .

ufl.operators.Max(x, y)
    UFL operator: Take the maximum of  $x$  and  $y$ .

ufl.operators.Min(x, y)
    UFL operator: Take the minimum of  $x$  and  $y$ .

ufl.operators.Not(condition)
    UFL operator: A boolean expression (not condition) for use with conditional.

ufl.operators.Or(left, right)
    UFL operator: A boolean expression (left or right) for use with conditional.

ufl.operators.acos(f)
    UFL operator: Take the inverse cosine of  $f$ .

ufl.operators.asin(f)
    UFL operator: Take the inverse sine of  $f$ .

ufl.operators.atan(f)
    UFL operator: Take the inverse tangent of  $f$ .

ufl.operators.atan_2(f1, f2)
    UFL operator: Take the inverse tangent with two the arguments  $f1$  and  $f2$ .

ufl.operators.avg(v)
    UFL operator: Take the average of  $v$  across a facet.

ufl.operators.bessel_I(nu, f)
    UFL operator: regular modified cylindrical Bessel function.
```

`ufl.operators.bessel_J(nu,f)`

UFL operator: cylindrical Bessel function of the first kind.

`ufl.operators.bessel_K(nu,f)`

UFL operator: irregular modified cylindrical Bessel function.

`ufl.operators.bessel_Y(nu,f)`

UFL operator: cylindrical Bessel function of the second kind.

`ufl.operators.cell_avg(f)`

UFL operator: Take the average of *v* over a cell.

`ufl.operators.cofac(A)`

UFL operator: Take the cofactor of *A*.

`ufl.operators.conditional(condition, true_value, false_value)`

UFL operator: A conditional expression, taking the value of *true_value* when *condition* evaluates to `true` and *false_value* otherwise.

`ufl.operators.contraction(a, a_axes, b, b_axes)`

UFL operator: Take the contraction of *a* and *b* over given axes.

`ufl.operators.cos(f)`

UFL operator: Take the cosine of *f*.

`ufl.operators.cosh(f)`

UFL operator: Take the hyperbolic cosine of *f*.

`ufl.operators.cross(a, b)`

UFL operator: Take the cross product of *a* and *b*.

`ufl.operators.curl(f)`

UFL operator: Take the curl of *f*.

`ufl.operators.det(A)`

UFL operator: Take the determinant of *A*.

`ufl.operators.dev(A)`

UFL operator: Take the deviatoric part of *A*.

`ufl.operators.diag(A)`

UFL operator: Take the diagonal part of rank 2 tensor *A* or make a diagonal rank 2 tensor from a rank 1 tensor.

Always returns a rank 2 tensor. See also `diag_vector`.

`ufl.operators.diag_vector(A)`

UFL operator: Take the diagonal part of rank 2 tensor *A* and return as a vector.

See also `diag`.

`ufl.operators.diff(f, v)`

UFL operator: Take the derivative of *f* with respect to the variable *v*.

If *f* is a form, `diff` is applied to each integrand.

`ufl.operators.div(f)`

UFL operator: Take the divergence of *f*

This operator follows the div convention where

$$\text{div}(\mathbf{v}) = \mathbf{v}[i].\text{dx}(i)$$

$$\text{div}(\mathbf{T})[:] = \mathbf{T}[:,i].\text{dx}(i)$$

for vector expressions v , and arbitrary rank tensor expressions T .

See also: [nabla_div\(\)](#)

`ufl.operators.dot(a, b)`

UFL operator: Take the dot product of a and b .

`ufl.operators.elem_div(A, B)`

UFL operator: Take the elementwise division of tensors A and B with the same shape.

`ufl.operators.elem_mult(A, B)`

UFL operator: Take the elementwise multiplication of tensors A and B with the same shape.

`ufl.operators.elem_op(op, *args)`

UFL operator: Take the elementwise application of operator op on scalar values from one or more tensor arguments.

`ufl.operators.elem_op_items(op_ind, indices, *args)`

`ufl.operators.elem_pow(A, B)`

UFL operator: Take the elementwise power of tensors A and B with the same shape.

`ufl.operators.eq(left, right)`

UFL operator: A boolean expression ($left == right$) for use with `conditional`.

`ufl.operators.erf(f)`

UFL operator: Take the error function of f .

`ufl.operators.exp(f)`

UFL operator: Take the exponential of f .

`ufl.operators.exterior_derivative(f)`

UFL operator: Take the exterior derivative of f .

The exterior derivative uses the element family to determine whether `id`, `grad`, `curl` or `div` should be used.

Note that this uses the `grad` and `div` operators, as opposed to `nabla_grad` and `nabla_div`.

`ufl.operators.facet_avg(f)`

UFL operator: Take the average of v over a facet.

`ufl.operators.ge(left, right)`

UFL operator: A boolean expression ($left \geq right$) for use with `conditional`.

`ufl.operators.grad(f)`

UFL operator: Take the gradient of f .

This operator follows the `grad` convention where

$$\text{grad}(s)[i] = s.\text{dx}(i)$$

$$\text{grad}(v)[i,j] = v[i].\text{dx}(j)$$

$$\text{grad}(T)[:,i] = T[:,i].\text{dx}(i)$$

for scalar expressions s , vector expressions v , and arbitrary rank tensor expressions T .

See also: [nabla_grad\(\)](#)

`ufl.operators.gt(left, right)`

UFL operator: A boolean expression ($left > right$) for use with `conditional`.

`ufl.operators.inner(a, b)`

UFL operator: Take the inner product of a and b .

`ufl.operators.inv(A)`

UFL operator: Take the inverse of A .

`ufl.operators.jump(v, n=None)`

UFL operator: Take the jump of v across a facet.

`ufl.operators.le(left, right)`

UFL operator: A boolean expression ($\text{left} \leq \text{right}$) for use with `conditional`.

`ufl.operators.ln(f)`

UFL operator: Take the natural logarithm of f .

`ufl.operators.lt(left, right)`

UFL operator: A boolean expression ($\text{left} < \text{right}$) for use with `conditional`.

`ufl.operators.max_value(x, y)`

UFL operator: Take the maximum of x and y .

`ufl.operators.min_value(x, y)`

UFL operator: Take the minimum of x and y .

`ufl.operators.nabla_div(f)`

UFL operator: Take the divergence of f .

This operator follows the div convention where

$$\text{nabla_div}(v) = v[i].\text{dx}(i)$$

$$\text{nabla_div}(T)[:] = T[i,:].\text{dx}(i)$$

for vector expressions v , and arbitrary rank tensor expressions T .

See also: [`div\(\)`](#)

`ufl.operators.nabla_grad(f)`

UFL operator: Take the gradient of f .

This operator follows the grad convention where

$$\text{nabla_grad}(s)[i] = s.\text{dx}(i)$$

$$\text{nabla_grad}(v)[i,j] = v[j].\text{dx}(i)$$

$$\text{nabla_grad}(T)[i,:] = T[:,i].\text{dx}(i)$$

for scalar expressions s , vector expressions v , and arbitrary rank tensor expressions T .

See also: [`grad\(\)`](#)

`ufl.operators.ne(left, right)`

UFL operator: A boolean expression ($\text{left} \neq \text{right}$) for use with `conditional`.

`ufl.operators.outer(*operands)`

UFL operator: Take the outer product of two or more operands.

`ufl.operators.perp(v)`

UFL operator: Take the perp of v , i.e. $(-v_1, +v_0)$.

`ufl.operators.rank(f)`

UFL operator: The rank of f .

`ufl.operators.rot(f)`

UFL operator: Take the curl of f .

`ufl.operators.shape(f)`

UFL operator: The shape of f .

```
ufl.operators.sign(x)
    UFL operator: Take the sign (+1 or -1) of x.

ufl.operators.sin(f)
    UFL operator: Take the sine of f.

ufl.operators.sinh(f)
    UFL operator: Take the hyperbolic sine of f.

ufl.operators.skew(A)
    UFL operator: Take the skew symmetric part of A.

ufl.operators.sqrt(f)
    UFL operator: Take the square root of f.

ufl.operators.sym(A)
    UFL operator: Take the symmetric part of A.

ufl.operators.tan(f)
    UFL operator: Take the tangent of f.

ufl.operators.tanh(f)
    UFL operator: Take the hyperbolic tangent of f.

ufl.operators.tr(A)
    UFL operator: Take the trace of A.

ufl.operators.transpose(A)
    UFL operator: Take the transposed of tensor A.

ufl.operators.variable(e)
    UFL operator: Define a variable representing the given expression, see also diff().
```

1.3.33 ufl.permutation module

This module provides utility functions for computing permutations and generating index lists.

```
ufl.permutation.build_component_numbering(shape, symmetry)
    Build a numbering of components within the given value shape, taking into consideration a symmetry mapping which leaves the mapping noncontiguous. Returns a dict { component -> numbering } and an ordered list of components [ numbering -> component ]. The dict contains all components while the list only contains the ones not mapped by the symmetry mapping.

ufl.permutation.compute_indices(shape)
    Compute all index combinations for given shape

ufl.permutation.compute_indices2(shape)
    Compute all index combinations for given shape

ufl.permutation.compute_order_tuples(k, n)
    Compute all tuples of n integers such that the sum is k

ufl.permutation.compute_permutation_pairs(j, k)
    Compute all permutations of j + k elements from (0, j + k) in rising order within (0, j) and (j, j + k) respectively.

ufl.permutation.compute_permutations(k, n, skip=None)
    Compute all permutations of k elements from (0, n) in rising order. Any elements that are contained in the list skip are not included.

ufl.permutation.compute_sign(permutation)
    Compute sign by sorting.
```

1.3.34 ufl.precedence module

Precedence handling.

`ufl.precedence.assign_precedences (precedence_list)`

Given a precedence list, assign ints to class._precedence.

`ufl.precedence.build_precedence_list ()`

`ufl.precedence.build_precedence_mapping (precedence_list)`

Given a precedence list, build a dict with class->int mappings. Utility function used by some external code.

`ufl.precedence.parstr (child, parent, pre='(', post=')', format=<class 'str'>)`

1.3.35 ufl.protocols module

`ufl.protocols.id_or_none (obj)`

Returns None if the object is None, obj.ufl_id() if available, or id(obj) if not.

This allows external libraries to implement an alternative to id(obj) in the ufl_id() function, such that ufl can identify objects as the same without knowing about their types.

`ufl.protocols.metadata_equal (a, b)`

`ufl.protocols.metadata_hashdata (md)`

1.3.36 ufl.referencevalue module

Representation of the reference value of a function.

`class ufl.referencevalue.ReferenceValue (f)`

Bases: `ufl.core.operator.Operator`

Representation of the reference cell value of a form argument.

`evaluate (x, mapping, component, index_values, derivatives=())`

Get child from mapping and return the component asked for.

`ufl_free_indices = ()`

`ufl_index_dimensions = ()`

`ufl_shape`

1.3.37 ufl.restriction module

Restriction operations.

`class ufl.restriction.NegativeRestricted (f)`

Bases: `ufl.restriction.Restricted`

`class ufl.restriction.PositiveRestricted (f)`

Bases: `ufl.restriction.Restricted`

`class ufl.restriction.Restricted (f)`

Bases: `ufl.core.operator.Operator`

`evaluate (x, mapping, component, index_values)`

Evaluate expression at given coordinate with given values for terminals.

```
side()
ufl_free_indices
ufl_index_dimensions
ufl_shape
```

1.3.38 ufl.sobolevspaces module

This module defines a symbolic heirarchy of Sobolev spaces to enable symbolic reasoning about the spaces in which finite elements lie.

```
class ufl.sobolevspaces.DirectionalSobolevSpace (orders)
```

Bases: *ufl.sobolevspaces.SobolevSpace*

Symbolic representation of a Sobolev space with varying smoothness in different spatial directions.

```
class ufl.sobolevspaces.SobolevSpace (name, parents=None)
```

Bases: *object*

Symbolic representation of a Sobolev space. This implements a subset of the methods of a Python set so that finite elements and other Sobolev spaces can be tested for inclusion.

1.3.39 ufl.sorting module

This module contains a sorting rule for expr objects that is more robust w.r.t. argument numbering than using repr.

```
ufl.sorting.cmp_expr (a, b)
```

Replacement for cmp(*a*, *b*), removed in Python 3, for Expr objects.

```
ufl.sorting.sorted_expr (sequence)
```

Return a canonically sorted list of Expr objects in sequence.

```
ufl.sorting.sorted_expr_sum (seq)
```

1.3.40 ufl.split_functions module

Algorithm for splitting a Coefficient or Argument into subfunctions.

```
ufl.split_functions.split (v)
```

UFL operator: If *v* is a Coefficient or Argument in a mixed space, returns a tuple with the function components corresponding to the subelements.

1.3.41 ufl.tensoralgebra module

Compound tensor algebra operations.

```
class ufl.tensoralgebra.Cofactor (A)
```

Bases: *ufl.tensoralgebra.CompoundTensorOperator*

```
ufl_free_indices = ()
```

```
ufl_index_dimensions = ()
```

```
ufl_shape
```

```
class ufl.tensoralgebra.CompoundTensorOperator (operands)
```

Bases: *ufl.core.operator.Operator*

```
class ufl.tensoralgebra.Cross(a, b)
Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = (3,)

class ufl.tensoralgebra.Determinant(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape = ()

class ufl.tensoralgebra.Deviatoric(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.tensoralgebra.Dot(a, b)
Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.tensoralgebra.Inner(a, b)
Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape = ()

class ufl.tensoralgebra.Inverse(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices = ()
    ufl_index_dimensions = ()
    ufl_shape

class ufl.tensoralgebra.Outer(a, b)
Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
    ufl_shape

class ufl.tensoralgebra.Skew(A)
Bases: ufl.tensoralgebra.CompoundTensorOperator

    ufl_free_indices
    ufl_index_dimensions
```

```



class ufl.tensoralgebra.Sym(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator

    
    
    

class ufl.tensoralgebra.Trace(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator

    
    
    

class ufl.tensoralgebra.Transposed(A)
    Bases: ufl.tensoralgebra.CompoundTensorOperator

    
    
    

```

1.3.42 ufl.tensors module

Classes used to group scalar expressions into expressions with rank > 0.

```

class ufl.tensors.ComponentTensor(expression, indices)
    Bases: ufl.core.operator.Operator

```

UFL operator type: Maps the free indices of a scalar valued expression to tensor axes.

```

evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.

indices()
ufl_free_indices
ufl_index_dimensions
ufl_shape

```

```

class ufl.tensors.ListTensor(*expressions)
    Bases: ufl.core.operator.Operator

```

UFL operator type: Wraps a list of expressions into a tensor valued expression of one higher rank.

```

evaluate(x, mapping, component, index_values, derivatives=())
    Evaluate expression at given coordinate with given values for terminals.

ufl_free_indices
ufl_index_dimensions
ufl_shape

```

```

ufl.tensors.as_matrix(expressions, indices=None)
    UFL operator: As as_tensor(), but limited to rank 2 tensors.

```

`ufl.tensors.as_scalar(expression)`

Given a scalar or tensor valued expression A , returns either of the tuples:

(a, b) = ($A, ()$)
(a, b) = ($A[\text{indices}]$, indices)

such that a is always a scalar valued expression.

`ufl.tensors.as_scalars(*expressions)`

Given multiple scalar or tensor valued expressions A , returns either of the tuples:

(a, b) = ($A, ()$)
(a, b) = ([$A[0][\text{indices}]$, ..., $A[-1][\text{indices}]$], indices)

such that a is always a list of scalar valued expressions.

`ufl.tensors.as_tensor(expressions, indices=None)`

UFL operator: Make a tensor valued expression.

This works in two different ways, by using indices or lists.

1) Returns A such that $A[\text{indices}] = \text{expressions}$. If indices are provided, expressions must be a scalar valued expression with all the provided indices among its free indices. This operator will then map each of these indices to a tensor axis, thereby making a tensor valued expression from a scalar valued expression with free indices.

2) Returns A such that $A[k, ...] = \text{expressions}^*[k]$. If no indices are provided, *expressions must be a list or tuple of expressions. The expressions can also consist of recursively nested lists to build higher rank tensors.

`ufl.tensors.as_vector(expressions, index=None)`

UFL operator: As `as_tensor()`, but limited to rank 1 tensors.

`ufl.tensors.dyad(d, *iota)`

TODO: Develop this concept, can e.g. write $A[i,j]*\text{dyad}(j,i)$ for the transpose.

`ufl.tensors.from_numpy_to_lists(expressions)`

`ufl.tensors.numpy2nestedlists(arr)`

`ufl.tensors.relabel(A, indexmap)`

UFL operator: Relabel free indices of A with new indices, using the given mapping.

`ufl.tensors.unit_indexed_tensor(shape, component)`

`ufl.tensors.unit_list(i, n)`

`ufl.tensors.unit_list2(i, j, n)`

`ufl.tensors.unit_matrices(d)`

UFL value: A tuple of constant unit matrices in all directions with dimension d .

`ufl.tensors.unit_matrix(i, j, d)`

UFL value: A constant unit matrix in direction $i, *j*$ with dimension d .

`ufl.tensors.unit_vector(i, d)`

UFL value: A constant unit vector in direction i with dimension d .

`ufl.tensors.unit_vectors(d)`

UFL value: A tuple of constant unit vectors in all directions with dimension d .

`ufl.tensors.unwrap_list_tensor(lt)`

1.3.43 ufl.variable module

Defines the Variable and Label classes, used to label expressions as variables for differentiation.

```
class ufl.variable.Label(count=None)
    Bases: ufl.core.terminal.Terminal

    count()
    is_cellwise_constant()

ufl_domains()
    Return tuple of domains related to this terminal object.

ufl_free_indices
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
        If the argument is a tuple, the return value is the same object.

ufl_index_dimensions
    tuple() -> empty tuple tuple(iterable) -> tuple initialized from iterable's items
        If the argument is a tuple, the return value is the same object.

ufl_shape
```

```
class ufl.variable.Variable(expression, label=None)
    Bases: ufl.core.operator.Operator
```

A Variable is a representative for another expression.

It will be used by the end-user mainly for defining a quantity to differentiate w.r.t. using diff. Example:

```
e = <...>
e = variable(e)
f = exp(e**2)
df = diff(f, e)
```

```
evaluate(x, mapping, component, index_values)
    Evaluate expression at given coordinate with given values for terminals.
```

```
expression()
```

```
label()
```

```
ufl_domains()
```

Return all domains this expression is defined on.

```
ufl_free_indices = ()
```

```
ufl_index_dimensions = ()
```

```
ufl_shape
```

1.3.44 Module contents

The Unified Form Language is an embedded domain specific language for definition of variational forms intended for finite element discretization. More precisely, it defines a fixed interface for choosing finite element spaces and defining expressions for weak forms in a notation close to the mathematical one.

This Python module contains the language as well as algorithms to work with it.

- To import the language, type:

```
from ufl import *
```

- To import the underlying classes an UFL expression tree is built from, type

```
from ufl.classes import *
```

- Various algorithms for working with UFL expression trees can be accessed by

```
from ufl.algorithms import *
```

Classes and algorithms are considered implementation details and should not be used in form definitions.

For more details on the language, see

<http://www.fenicsproject.org>

and

<http://arxiv.org/abs/1211.4047>

The development version can be found in the repository at

<https://www.bitbucket.org/fenics-project/ufl>

A very brief overview of the language contents follows:

- Cells:

```
- AbstractCell  
- Cell  
- TensorProductCell  
- vertex  
- interval  
- triangle  
- tetrahedron  
- quadrilateral  
- hexahedron
```

- Domains:

```
- AbstractDomain  
- Mesh  
- MeshView  
- TensorProductMesh
```

- Sobolev spaces:

```
- L2  
- H1  
- H2  
- HDiv  
- HCurl
```

- Elements:

```
- FiniteElement  
- MixedElement  
- VectorElement  
- TensorElement  
- EnrichedElement
```

(continues on next page)

(continued from previous page)

- NodalEnrichedElement
- RestrictedElement
- TensorProductElement
- HDivElement
- HCurlElement
- BrokenElement
- FacetElement
- InteriorElement

- Function spaces:

- FunctionSpace

- Arguments:

- Argument
- TestFunction
- TrialFunction
- Arguments
- TestFunctions
- TrialFunctions

- Coefficients:

- Coefficient
- Constant
- VectorConstant
- TensorConstant

- Splitting form arguments in mixed spaces:

- split

- Literal constants:

- Identity
 - PermutationSymbol

- Geometric quantities:

- SpatialCoordinate
- FacetNormal
- CellNormal
- CellVolume
- CellDiameter
- Circumradius
- MinCellEdgeLength
- MaxCellEdgeLength
- FacetArea
- MinFacetEdgeLength
- MaxFacetEdgeLength
- Jacobian
- JacobianDeterminant
- JacobianInverse

- Indices:

```
- Index  
- indices  
- i, j, k, l  
- p, q, r, s
```

- Scalar to tensor expression conversion:

```
- as_tensor  
- as_vector  
- as_matrix
```

- Unit vectors and matrices:

```
- unit_vector  
- unit_vectors  
- unit_matrix  
- unit_matrices
```

- Tensor algebra operators:

```
- outer, inner, dot, cross, perp  
- det, inv, cofac  
- transpose, tr, diag, diag_vector  
- dev, skew, sym
```

- Elementwise tensor operators:

```
- elem_mult  
- elem_div  
- elem_pow  
- elem_op
```

- Differential operators:

```
- variable  
- diff,  
- grad, nabla_grad  
- div, nabla_div  
- curl, rot  
- Dx, Dn
```

- Nonlinear functions:

```
- max_value, min_value  
- abs, sign  
- sqrt  
- exp, ln, erf  
- cos, sin, tan  
- acos, asin, atan, atan_2  
- cosh, sinh, tanh  
- bessel_J, bessel_Y, bessel_I, bessel_K
```

- Discontinuous Galerkin operators:

```
- v('+'), v(' - ')  
- jump  
- avg  
- cell_avg, facet_avg
```

- Conditional operators:

```
- eq, ne, le, ge, lt, gt
- <, >, <=, >=
- And, Or, Not
- conditional
```

- Integral measures:

```
- dx, ds, dS, dP
- dc, dC, dO, dI, dX
- ds_b, ds_t, ds_tb, ds_v, dS_h, dS_v
```

- Form transformations:

```
- rhs, lhs
- system
- functional
- replace, replace_integral_domains
- adjoint
- action
- energy_norm,
- sensitivity_rhs
- derivative
```

ufl.product (sequence)

Return the product of all elements in a sequence.

exception ufl.UFLEException

Bases: Exception

Base class for UFL exceptions.

ufl.as_cell (cell)

Convert any valid object to a Cell or return cell if it is already a Cell.

Allows an already valid cell, a known cellname string, or a tuple of cells for a product cell.

class ufl.AbstractCell (topological_dimension, geometric_dimension)

Bases: object

Representation of an abstract finite element cell with only the dimensions known.

geometric_dimension ()

Return the dimension of the space this cell is embedded in.

has_simplex_facets ()

Return True if all the facets of this cell are simplex cells.

is_simplex ()

Return True if this is a simplex cell.

topological_dimension ()

Return the dimension of the topology of this cell.

class ufl.Cell (cellname, geometric_dimension=None)

Bases: [ufl.cell.AbstractCell](#)

Representation of a named finite element cell with known structure.

cellname ()

Return the cellname of the cell.

```
has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

num_edges()
    The number of cell edges.

num_facet_edges()
    The number of facet edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct(geometric_dimension=None)

class ufl.TensorProductCell(*cells, **kwargs)
    Bases: ufl.cell.AbstractCell

cellname()
    Return the cellname of the cell.

has_simplex_facets()
    Return True if all the facets of this cell are simplex cells.

is_simplex()
    Return True if this is a simplex cell.

num_edges()
    The number of cell edges.

num_facets()
    The number of cell facets.

num_vertices()
    The number of cell vertices.

reconstruct(geometric_dimension=None)

sub_cells()
    Return list of cell factors.

ufl.as_domain(domain)
    Convert any valid object to an AbstractDomain type.

class ufl.AbstractDomain(topological_dimension, geometric_dimension)
    Bases: object

    Symbolic representation of a geometric domain with only a geometric and topological dimension.

geometric_dimension()
    Return the dimension of the space this domain is embedded in.

topological_dimension()
    Return the dimension of the topology of this domain.

class ufl.Mesh(coordinate_element, ufl_id=None, cargo=None)
    Bases: ufl.domain.AbstractDomain

    Symbolic representation of a mesh.
```

```

is_piecewise_linear_simplex_domain()
ufl_cargo()
    Return carried object that will not be used by UFL.

ufl_cell()
ufl_coordinate_element()
ufl_id()
    Return the ufl_id of this object.

class ufl.MeshView(mesh, topological_dimension, ufl_id=None)
Bases: ufl.domain.AbstractDomain
Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()
ufl_cell()
ufl_id()
    Return the ufl_id of this object.

ufl_mesh()

class ufl.TensorProductMesh(meshes, ufl_id=None)
Bases: ufl.domain.AbstractDomain
Symbolic representation of a mesh.

is_piecewise_linear_simplex_domain()
ufl_cell()
ufl_coordinate_element()
ufl_id()
    Return the ufl_id of this object.

class ufl.SpatialCoordinate(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The coordinate in a domain.

In the context of expression integration, represents the domain coordinate of each quadrature point.

In the context of expression evaluation in a point, represents the value of that point.

evaluate(x, mapping, component, index_values)
    Return the value of the coordinate.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'x'
ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.CellVolume(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The volume of the cell.

name = 'volume'

```

```
class ufl.CellDiameter(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The diameter of the cell, i.e., maximal distance of two points in the cell.

name = 'diameter'

class ufl.Circumradius(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The circumradius of the cell.

name = 'circumradius'

class ufl.MinCellEdgeLength(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The minimum edge length of the cell.

name = 'mincelledgeLength'

class ufl.MaxCellEdgeLength(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The maximum edge length of the cell.

name = 'maxcelledgeLength'

class ufl.FacetArea(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The area of the facet.

name = 'facetarea'

class ufl.MinFacetEdgeLength(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The minimum edge length of the facet.

name = 'minfacetededgeLength'

class ufl.MaxFacetEdgeLength(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The maximum edge length of the facet.

name = 'maxfacetededgeLength'

class ufl.FacetNormal(domain)
Bases: ufl.geometry.GeometricFacetQuantity
UFL geometry representation: The outwards pointing normal vector of the current facet.

is_cellwise_constant()
    Return whether this expression is spatially constant over each cell.

name = 'n'

ufl_shape
    Return the number of coordinates defined (i.e. the geometric dimension of the domain).

class ufl.CellNormal(domain)
Bases: ufl.geometry.GeometricCellQuantity
UFL geometry representation: The upwards pointing normal vector of the current manifold cell.

name = 'cell_normal'
```

ufl_shape

Return the number of coordinates defined (i.e. the geometric dimension of the domain).

```
class ufl.Jacobian(domain)
```

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The Jacobian of the mapping from reference cell to spatial coordinates.

$$J_{ij} = \frac{dx_i}{dX_j}$$

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

```
name = 'J'
```

ufl_shape

Return the number of coordinates defined (i.e. the geometric dimension of the domain).

```
class ufl.JacobianDeterminant(domain)
```

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The determinant of the Jacobian.

Represents the signed determinant of a square Jacobian or the pseudo-determinant of a non-square Jacobian.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

```
name = 'detJ'
```

```
class ufl.JacobianInverse(domain)
```

Bases: *ufl.geometry.GeometricCellQuantity*

UFL geometry representation: The inverse of the Jacobian.

Represents the inverse of a square Jacobian or the pseudo-inverse of a non-square Jacobian.

is_cellwise_constant()

Return whether this expression is spatially constant over each cell.

```
name = 'K'
```

ufl_shape

Return the number of coordinates defined (i.e. the geometric dimension of the domain).

```
class ufl.FiniteElementBase(family, cell, degree, quad_scheme, value_shape, reference_value_shape)
```

Bases: *object*

Base class for all finite elements.

cell()

Return cell of finite element.

degree(component=None)

Return polynomial degree of finite element.

extract_component(i)

Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component(*i*)

Recursively extract reference component index relative to a (simple) element and that element for given reference value component index.

extract_subelement_component(*i*)

Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component(*i*)

Extract direct subelement index and subelement relative reference component index for a given reference component index.

family()

Return finite element family.

is_cellwise_constant(*component=None*)

Return whether the basis functions of this element is spatially constant over each cell.

mapping()

Not implemented.

num_sub_elements()

Return number of sub-elements.

quadrature_scheme()

Return quadrature scheme of finite element.

reference_value_shape()

Return the shape of the value space on the reference cell.

reference_value_size()

Return the integer product of the reference value shape.

sub_elements()

Return list of sub-elements.

symmetry()

Return the symmetry dict, which is a mapping $c_0 \rightarrow c_1$ meaning that component c_0 is represented by component c_1 . A component is a tuple of one or more ints.

value_shape()

Return the shape of the value space on the global domain.

value_size()

Return the integer product of the value shape.

class `ufl.FiniteElement`(*family*, *cell=None*, *degree=None*, *form_degree=None*,
 quad_scheme=None, *variant=None*)

Bases: `ufl.finetelement.finetelementbase.FiniteElementBase`

The basic finite element class for all simple finite elements.

mapping()

Not implemented.

reconstruct(*family=None*, *cell=None*, *degree=None*)

Construct a new FiniteElement object with some properties replaced with new values.

shortstr()

Format as string for pretty printing.

sobolev_space()

Return the underlying Sobolev space.

variant()

```
class ufl.MixedElement (*elements, **kwargs)
Bases: ufl.finiteelementFINITEELEMENTbase.FiniteElementBase

A finite element composed of a nested hierarchy of mixed or simple elements.

degree (component=None)
    Return polynomial degree of finite element.

extract_component (i)
    Recursively extract component index relative to a (simple) element and that element for given value component index.

extract_reference_component (i)
    Recursively extract reference_component index relative to a (simple) element and that element for given value reference_component index.

extract_subelement_component (i)
    Extract direct subelement index and subelement relative component index for a given component index.

extract_subelement_reference_component (i)
    Extract direct subelement index and subelement relative reference_component index for a given reference_component index.

is_cellwise_constant (component=None)
    Return whether the basis functions of this element is spatially constant over each cell.

mapping ()
    Not implemented.

num_sub_elements ()
    Return number of sub elements.

reconstruct (**kwargs)

reconstruct_from_elements (*elements)
    Reconstruct a mixed element from new subelements.

shortstr ()
    Format as string for pretty printing.

sub_elements ()
    Return list of sub elements.

symmetry ()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.VectorElement (family, cell=None, degree=None, dim=None, form_degree=None,
                           quad_scheme=None)
Bases: ufl.finiteelement.MixedElement

A special case of a mixed finite element where all elements are equal.

reconstruct (**kwargs)

shortstr ()
    Format as string for pretty printing.

class ufl.TensorElement (family, cell=None, degree=None, shape=None, symmetry=None,
                           quad_scheme=None)
Bases: ufl.finiteelement.MixedElement

A special case of a mixed finite element where all elements are equal.
```

```
extract_subelement_component(i)
    Extract direct subelement index and subelement relative component index for a given component index.

flattened_sub_element_mapping()

mapping()
    Not implemented.

reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

class ufl.EnrichedElement(*elements)
Bases: ufl.finiteelement.enrichedelement.EnrichedElementBase
```

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Dual basis is a concatenation of subelements dual bases; primal basis is a concatenation of subelements primal bases; resulting element is not nodal even when subelements are. Structured basis may be exploited in form compilers.

```
is_cellwise_constant()
    Return whether the basis functions of this element is spatially constant over each cell.

shortstr()
    Format as string for pretty printing.

class ufl.NodalEnrichedElement(*elements)
Bases: ufl.finiteelement.enrichedelement.EnrichedElementBase
```

The vector sum of several finite element spaces:

$$\text{EnrichedElement}(V, Q) = \{v + q | v \in V, q \in Q\}.$$

Primal basis is reorthogonalized to dual basis which is a concatenation of subelements dual bases; resulting element is nodal.

```
is_cellwise_constant()
    Return whether the basis functions of this element is spatially constant over each cell.

shortstr()
    Format as string for pretty printing.
```

```
class ufl.RestrictedElement(element, restriction_domain)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
```

Represents the restriction of a finite element to a type of cell entity.

```
is_cellwise_constant()
    Return whether the basis functions of this element is spatially constant over each cell.

mapping()
    Not implemented.

num_restricted_sub_elements()
    Return number of restricted sub elements.
```

```

num_sub_elements()
    Return number of sub elements.

reconstruct(**kwargs)

restricted_sub_elements()
    Return list of restricted sub elements.

restriction_domain()
    Return the domain onto which the element is restricted.

shortstr()
    Format as string for pretty printing.

sub_element()
    Return the element which is restricted.

sub_elements()
    Return list of sub elements.

symmetry()
    Return the symmetry dict, which is a mapping  $c_0 \rightarrow c_1$  meaning that component  $c_0$  is represented by component  $c_1$ . A component is a tuple of one or more ints.

```

```
class ufl.TensorProductElement(*elements, **kwargs)
Bases: ufl.finiteelementFINITEELEMENTBASE
```

The tensor product of d element spaces:

$$V = V_1 \otimes V_2 \otimes \dots \otimes V_d$$

Given bases $\{\phi_{j_i}\}$ of the spaces V_i for $i = 1, \dots, d$, $\{\phi_{j_1} \otimes \phi_{j_2} \otimes \dots \otimes \phi_{j_d}\}$ forms a basis for V .

```

mapping()
    Not implemented.

num_sub_elements()
    Return number of subelements.

reconstruct(cell=None)

shortstr()
    Short pretty-print.

sobolev_space()
    Return the underlying Sobolev space of the TensorProductElement.

sub_elements()
    Return subelements (factors).

```

```
class ufl.HDivElement(element)
Bases: ufl.finiteelementFINITEELEMENTBASE
```

A div-conforming version of an outer product element, assuming this makes mathematical sense.

```

mapping()
    Not implemented.

reconstruct(**kwargs)

shortstr()
    Format as string for pretty printing.

sobolev_space()
    Return the underlying Sobolev space.

```

```
class ufl.HCurlElement (element)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
A curl-conforming version of an outer product element, assuming this makes mathematical sense.

mapping ()
    Not implemented.

reconstruct (**kwargs)

shortstr ()
    Format as string for pretty printing.

sobolev_space ()
    Return the underlying Sobolev space.

class ufl.BrokenElement (element)
Bases: ufl.finiteelement.finiteelementbase.FiniteElementBase
The discontinuous version of an existing Finite Element space.

mapping ()
    Not implemented.

reconstruct (**kwargs)

shortstr ()
    Format as string for pretty printing.

ufl.FacetElement (element)
Constructs the restriction of a finite element to the facets of the cell.

ufl.InteriorElement (element)
Constructs the restriction of a finite element to the interior of the cell.

ufl.register_element (family, short_name, value_rank, sobolev_space, mapping, degree_range, cell-
names)
Register new finite element family.

ufl.show_elements ()
Shows all registered elements.

class ufl.FunctionSpace (domain, element)
Bases: ufl.functionspace.AbstractFunctionSpace

ufl_domain ()
    Return ufl domain.

ufl_domains ()
    Return ufl domains.

ufl_element ()
    Return ufl element.

ufl_sub_spaces ()
    Return ufl sub spaces.

class ufl.Argument (function_space, number, part=None)
Bases: ufl.core.terminal.FormArgument
UFL value: Representation of an argument to a form.

is_cellwise_constant ()
    Return whether this expression is spatially constant over each cell.
```

number()
Return the Argument number.

part()

ufl_domain()
Deprecated, please use .ufl_function_space().ufl_domain() instead.

ufl_domains()
Deprecated, please use .ufl_function_space().ufl_domains() instead.

ufl_element()
Deprecated, please use .ufl_function_space().ufl_element() instead.

ufl_function_space()
Get the function space of this Argument.

ufl_shape
Return the associated UFL shape.

ufl.TestFunction(function_space, part=None)
UFL value: Create a test function argument to a form.

ufl.TrialFunction(function_space, part=None)
UFL value: Create a trial function argument to a form.

ufl.Arguments(function_space, number)
UFL value: Create an Argument in a mixed space, and return a tuple with the function components corresponding to the subelements.

ufl.TestFunctions(function_space)
UFL value: Create a TestFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

ufl.TrialFunctions(function_space)
UFL value: Create a TrialFunction in a mixed space, and return a tuple with the function components corresponding to the subelements.

class ufl.Coefficient(function_space, count=None)
Bases: ufl.core.terminal.FormArgument

UFL form argument type: Representation of a form coefficient.

count()

is_cellwise_constant()
Return whether this expression is spatially constant over each cell.

ufl_domain()
Shortcut to get the domain of the function space of this coefficient.

ufl_domains()
Return tuple of domains related to this terminal object.

ufl_element()
Shortcut to get the finite element of the function space of this coefficient.

ufl_function_space()
Get the function space of this coefficient.

ufl_shape
Return the associated UFL shape.

`ufl.Coefficients(function_space)`

UFL value: Create a Coefficient in a mixed space, and return a tuple with the function components corresponding to the subelements.

`ufl.Constant(domain, count=None)`

UFL value: Represents a globally constant scalar valued coefficient.

`ufl.VectorConstant(domain, dim=None, count=None)`

UFL value: Represents a globally constant vector valued coefficient.

`ufl.TensorConstant(domain, shape=None, symmetry=None, count=None)`

UFL value: Represents a globally constant tensor valued coefficient.

`ufl.split(v)`

UFL operator: If v is a Coefficient or Argument in a mixed space, returns a tuple with the function components corresponding to the subelements.

`class ufl.PermutationSymbol(dim)`

Bases: `ufl.constantvalue.ConstantValue`

UFL literal type: Representation of a permutation symbol.

This is also known as the Levi-Civita symbol, antisymmetric symbol, or alternating symbol.

`evaluate(x, mapping, component, index_values)`

Evaluates the permutation symbol.

`ufl_shape`

`class ufl.Identity(dim)`

Bases: `ufl.constantvalue.ConstantValue`

UFL literal type: Representation of an identity matrix.

`evaluate(x, mapping, component, index_values)`

Evaluates the identity matrix on the given components.

`ufl_shape`

`ufl.zero(*shape)`

UFL literal constant: Return a zero tensor with the given shape.

`ufl.as_ufl(expression)`

Converts expression to an Expr if possible.

`class ufl.Index(count=None)`

Bases: `ufl.core.multiindex.IndexBase`

UFL value: An index with no value assigned.

Used to represent free indices in Einstein indexing notation.

`count()`

`ufl.indices(n)`

UFL value: Return a tuple of n new Index objects.

`ufl.as_tensor(expressions, indices=None)`

UFL operator: Make a tensor valued expression.

This works in two different ways, by using indices or lists.

1) Returns A such that $A[\text{indices}] = \text{expressions}$. If `indices` are provided, `expressions` must be a scalar valued expression with all the provided indices among its free indices. This operator will then map each of these indices to a tensor axis, thereby making a tensor valued expression from a scalar valued expression with free indices.

2) Returns A such that $A[k, \dots] = \text{expressions}*[k]$. If no indices are provided, *expressions must be a list or tuple of expressions. The expressions can also consist of recursively nested lists to build higher rank tensors.

`ufl.as_vector(expressions, index=None)`

UFL operator: As `as_tensor()`, but limited to rank 1 tensors.

`ufl.as_matrix(expressions, indices=None)`

UFL operator: As `as_tensor()`, but limited to rank 2 tensors.

`ufl.relabel(A, indexmap)`

UFL operator: Relabel free indices of A with new indices, using the given mapping.

`ufl.unit_vector(i, d)`

UFL value: A constant unit vector in direction i with dimension d .

`ufl.unit_vectors(d)`

UFL value: A tuple of constant unit vectors in all directions with dimension d .

`ufl.unit_matrix(i, j, d)`

UFL value: A constant unit matrix in direction $i, *j*$ with dimension d .

`ufl.unit_matrices(d)`

UFL value: A tuple of constant unit matrices in all directions with dimension d .

`ufl.rank(f)`

UFL operator: The rank of f .

`ufl.shape(f)`

UFL operator: The shape of f .

`ufl.outer(*operands)`

UFL operator: Take the outer product of two or more operands.

`ufl.inner(a, b)`

UFL operator: Take the inner product of a and b .

`ufl.dot(a, b)`

UFL operator: Take the dot product of a and b .

`ufl.cross(a, b)`

UFL operator: Take the cross product of a and b .

`ufl.perp(v)`

UFL operator: Take the perp of v , i.e. $(-v_1, +v_0)$.

`ufl.det(A)`

UFL operator: Take the determinant of A .

`ufl.inv(A)`

UFL operator: Take the inverse of A .

`ufl.cofac(A)`

UFL operator: Take the cofactor of A .

`ufl.transpose(A)`

UFL operator: Take the transposed of tensor A .

`ufl.tr(A)`

UFL operator: Take the trace of A .

`ufl.diag(A)`

UFL operator: Take the diagonal part of rank 2 tensor A or make a diagonal rank 2 tensor from a rank 1 tensor.

Always returns a rank 2 tensor. See also `diag_vector`.

`ufl.diag_vector(A)`

UFL operator: Take the diagonal part of rank 2 tensor A and return as a vector.

See also `diag`.

`ufl.dev(A)`

UFL operator: Take the deviatoric part of A .

`ufl.skew(A)`

UFL operator: Take the skew symmetric part of A .

`ufl.sym(A)`

UFL operator: Take the symmetric part of A .

`ufl.sqrt(f)`

UFL operator: Take the square root of f .

`ufl.exp(f)`

UFL operator: Take the exponential of f .

`ufl.ln(f)`

UFL operator: Take the natural logarithm of f .

`ufl.erf(f)`

UFL operator: Take the error function of f .

`ufl.cos(f)`

UFL operator: Take the cosine of f .

`ufl.sin(f)`

UFL operator: Take the sine of f .

`ufl.tan(f)`

UFL operator: Take the tangent of f .

`ufl.acos(f)`

UFL operator: Take the inverse cosine of f .

`ufl.asin(f)`

UFL operator: Take the inverse sine of f .

`ufl.atan(f)`

UFL operator: Take the inverse tangent of f .

`ufl.atan_2(f1,f2)`

UFL operator: Take the inverse tangent with two the arguments $f1$ and $f2$.

`ufl.cosh(f)`

UFL operator: Take the hyperbolic cosine of f .

`ufl.sinh(f)`

UFL operator: Take the hyperbolic sine of f .

`ufl.tanh(f)`

UFL operator: Take the hyperbolic tangent of f .

`ufl.bessel_J(nu,f)`

UFL operator: cylindrical Bessel function of the first kind.

`ufl.bessel_Y(nu,f)`

UFL operator: cylindrical Bessel function of the second kind.

`ufl.bessel_I(nu,f)`

UFL operator: regular modified cylindrical Bessel function.

ufl.bessel_K(*nu,f*)

UFL operator: irregular modified cylindrical Bessel function.

ufl.eq(*left,right*)UFL operator: A boolean expression (*left == right*) for use with `conditional`.**ufl.ne**(*left,right*)UFL operator: A boolean expression (*left != right*) for use with `conditional`.**ufl.le**(*left,right*)UFL operator: A boolean expression (*left <= right*) for use with `conditional`.**ufl.ge**(*left,right*)UFL operator: A boolean expression (*left >= right*) for use with `conditional`.**ufl.lt**(*left,right*)UFL operator: A boolean expression (*left < right*) for use with `conditional`.**ufl.gt**(*left,right*)UFL operator: A boolean expression (*left > right*) for use with `conditional`.**ufl.And**(*left,right*)UFL operator: A boolean expression (*left and right*) for use with `conditional`.**ufl.Or**(*left,right*)UFL operator: A boolean expression (*left or right*) for use with `conditional`.**ufl.Not**(*condition*)UFL operator: A boolean expression (*not condition*) for use with `conditional`.**ufl.conditional**(*condition,true_value,false_value*)UFL operator: A conditional expression, taking the value of *true_value* when *condition* evaluates to `true` and *false_value* otherwise.**ufl.sign**(*x*)UFL operator: Take the sign (+1 or -1) of *x*.**ufl.max_value**(*x,y*)UFL operator: Take the maximum of *x* and *y*.**ufl.min_value**(*x,y*)UFL operator: Take the minimum of *x* and *y*.**ufl.Max**(*x,y*)UFL operator: Take the maximum of *x* and *y*.**ufl.Min**(*x,y*)UFL operator: Take the minimum of *x* and *y*.**ufl.variable**(*e*)UFL operator: Define a variable representing the given expression, see also `diff()`.**ufl.diff**(*f,v*)UFL operator: Take the derivative of *f* with respect to the variable *v*.If *f* is a form, `diff` is applied to each integrand.**ufl.Dx**(*f,*i*)UFL operator: Take the partial derivative of *f* with respect to spatial variable number *i*. Equivalent to `f.dx(*i)`.**ufl.grad**(*f*)UFL operator: Take the gradient of *f*.

This operator follows the grad convention where

$$\begin{aligned}\text{grad}(s)[i] &= s.\text{dx}(i) \\ \text{grad}(v)[i,j] &= v[i].\text{dx}(j) \\ \text{grad}(T)[:,i] &= T[:,i].\text{dx}(i)\end{aligned}$$

for scalar expressions s , vector expressions v , and arbitrary rank tensor expressions T .

See also: [nabla_grad\(\)](#)

`ufl.div(f)`

UFL operator: Take the divergence of f .

This operator follows the div convention where

$$\begin{aligned}\text{div}(v) &= v[i].\text{dx}(i) \\ \text{div}(T)[:,i] &= T[:,i].\text{dx}(i)\end{aligned}$$

for vector expressions v , and arbitrary rank tensor expressions T .

See also: [nabla_div\(\)](#)

`ufl.curl(f)`

UFL operator: Take the curl of f .

`ufl.rot(f)`

UFL operator: Take the curl of f .

`ufl.nabla_grad(f)`

UFL operator: Take the gradient of f .

This operator follows the grad convention where

$$\begin{aligned}\text{nabla_grad}(s)[i] &= s.\text{dx}(i) \\ \text{nabla_grad}(v)[i,j] &= v[j].\text{dx}(i) \\ \text{nabla_grad}(T)[i,:] &= T[:,i].\text{dx}(i)\end{aligned}$$

for scalar expressions s , vector expressions v , and arbitrary rank tensor expressions T .

See also: [grad\(\)](#)

`ufl.nabla_div(f)`

UFL operator: Take the divergence of f .

This operator follows the div convention where

$$\begin{aligned}\text{nabla_div}(v) &= v[i].\text{dx}(i) \\ \text{nabla_div}(T)[:,i] &= T[i,:].\text{dx}(i)\end{aligned}$$

for vector expressions v , and arbitrary rank tensor expressions T .

See also: [div\(\)](#)

`ufl.Dn(f)`

UFL operator: Take the directional derivative of f in the facet normal direction, $\text{Dn}(f) := \text{dot}(\text{grad}(f), n)$.

`ufl.exterior_derivative(f)`

UFL operator: Take the exterior derivative of f .

The exterior derivative uses the element family to determine whether `id`, `grad`, `curl` or `div` should be used.

Note that this uses the `grad` and `div` operators, as opposed to `nabla_grad` and `nabla_div`.

`ufl.jump(v, n=None)`
UFL operator: Take the jump of v across a facet.

`ufl.avg(v)`
UFL operator: Take the average of v across a facet.

`ufl.cell_avg(f)`
UFL operator: Take the average of v over a cell.

`ufl.facet_avg(f)`
UFL operator: Take the average of v over a facet.

`ufl.elem_mult(A, B)`
UFL operator: Take the elementwise multiplication of tensors A and B with the same shape.

`ufl.elem_div(A, B)`
UFL operator: Take the elementwise division of tensors A and B with the same shape.

`ufl.elem_pow(A, B)`
UFL operator: Take the elementwise power of tensors A and B with the same shape.

`ufl.elem_op(op, *args)`
UFL operator: Take the elementwise application of operator op on scalar values from one or more tensor arguments.

class ufl.Form(integrals)
Bases: `object`

Description of a weak form consisting of a sum of integrals over subdomains.

arguments()
Return all Argument objects found in form.

coefficient_numbering()
Return a contiguous numbering of coefficients in a mapping `{coefficient: number}`.

coefficients()
Return all Coefficient objects found in form.

domain_numbering()
Return a contiguous numbering of domains in a mapping `{domain: number}`.

empty()
Returns whether the form has no integrals.

equals(other)
Evaluate `bool(lhs_form == rhs_form)`.

geometric_dimension()
Return the geometric dimension shared by all domains and functions in this form.

integrals()
Return a sequence of all integrals in form.

integrals_by_type(integral_type)
Return a sequence of all integrals with a particular domain type.

max_subdomain_ids()
Returns a mapping on the form `{domain: {integral_type: max_subdomain_id}}`.

signature()
Signature for use with jit cache (independent of incidental numbering of indices etc.)

```
subdomain_data()
    Returns a mapping on the form {domain:{integral_type: subdomain_data}}.

uf1_cell()
    Return the single cell this form is defined on, fails if multiple cells are found.

uf1_domain()
    Return the single geometric integration domain occuring in the form.
    Fails if multiple domains are found.

    NB! This does not include domains of coefficients defined on other meshes, look at form data for that
    additional information.

uf1_domains()
    Return the geometric integration domains occuring in the form.
    NB! This does not include domains of coefficients defined on other meshes.
    The return type is a tuple even if only a single domain exists.

x_repr_latex_()
x_repr_png_()

class ufl.Integral(integrand, integral_type, domain, subdomain_id, metadata, subdomain_data)
    Bases: object

    An integral over a single domain.

integral_type()
    Return the domain type of this integral.

integrand()
    Return the integrand expression, which is an Expr instance.

metadata()
    Return the compiler metadata this integral has been annotated with.

reconstruct(integrand=None, integral_type=None, domain=None, subdomain_id=None, meta-
data=None, subdomain_data=None)
    Construct a new Integral object with some properties replaced with new values.

    Example: <a = Integral instance> b = a.reconstruct(expand_compounds(a.integrand())) c =
        a.reconstruct(metadata={'quadrature_degree':2})

subdomain_data()
    Return the domain data of this integral.

subdomain_id()
    Return the subdomain id of this integral.

uf1_domain()
    Return the integration domain of this integral.

class ufl.Measure(integral_type, domain=None, subdomain_id='everywhere', metadata=None, subdo-
main_data=None)
    Bases: object

integral_type()
    Return the domain type.

    Valid domain types are "cell", "exterior_facet", "interior_facet", etc.
```

metadata()

Return the integral metadata. This data is not interpreted by UFL. It is passed to the form compiler which can ignore it or use it to compile each integral of a form in a different way.

reconstruct (integral_type=None, subdomain_id=None, domain=None, metadata=None, subdomain_main_data=None)

Construct a new Measure object with some properties replaced with new values.

Example: <dm = Measure instance> b = dm.reconstruct(subdomain_id=2) c = dm.reconstruct(metadata={"quadrature_degree": 3})

Used by the call operator, so this is equivalent: b = dm(2) c = dm(0, {"quadrature_degree": 3})

subdomain_data()

Return the integral subdomain_data. This data is not interpreted by UFL. Its intension is to give a context in which the domain id is interpreted.

subdomain_id()

Return the domain id of this measure (integer).

ufl_domain()

Return the domain associated with this measure.

This may be None or a Domain object.

ufl.register_integral_type (integral_type, measure_name)**ufl.integral_types()**

Return a tuple of all domain type strings.

ufl.replace (e, mapping)

Replace terminal objects in expression.

@param e: An Expr or Form.

@param mapping: A dict with from:to replacements to perform.

ufl.replace_integral_domains (form, common_domain)

Given a form and a domain, assign a common integration domain to all integrals.

Does not modify the input form (Form should always be immutable). This is to support ill formed forms with no domain specified, sometimes occurring in pydolfin, e.g. assemble(1*dx, mesh=mesh).

ufl.derivative (form, coefficient, argument=None, coefficient_derivatives=None)

UFL form operator: Compute the Gateaux derivative of *form* w.r.t. *coefficient* in direction of *argument*.

If the argument is omitted, a new Argument is created in the same space as the coefficient, with argument number one higher than the highest one in the form.

The resulting form has one additional Argument in the same finite element space as the coefficient.

A tuple of Coefficient s may be provided in place of a single Coefficient, in which case the new Argument argument is based on a MixedElement created from this tuple.

An indexed Coefficient from a mixed space may be provided, in which case the argument should be in the corresponding subspace of the coefficient space.

If provided, *coefficient_derivatives* should be a mapping from Coefficient instances to their derivatives w.r.t. *coefficient*.

ufl.action (form, coefficient=None)

UFL form operator: Given a bilinear form, return a linear form with an additional coefficient, representing the action of the form on the coefficient. This can be used for matrix-free methods.

ufl.energy_norm (*form, coefficient=None*)

UFL form operator: Given a bilinear form a and a coefficient f , return the functional $a(f, f)$.

ufl.rhs (*form*)

UFL form operator: Given a combined bilinear and linear form, extract the right hand side (negated linear form part).

Example:

```
a = u*v*dx + f*v*dx
L = rhs(a) -> -f*v*dx
```

ufl.lhs (*form*)

UFL form operator: Given a combined bilinear and linear form, extract the left hand side (bilinear form part).

Example:

```
a = u*v*dx + f*v*dx
a = lhs(a) -> u*v*dx
```

ufl.block_split (*form, ix, iy=0*)

UFL form operator: Given a linear or bilinear form on a mixed space, extract the block corresponding to the indices ix, iy .

Example:

```
a = inner(grad(u), grad(v))*dx + div(u)*q*dx + div(v)*p*dx
a = block_split(a, 0, 0) -> inner(grad(u),
grad(v))*dx
```

ufl.system (*form*)

UFL form operator: Split a form into the left hand side and right hand side, see `lhs` and `rhs`.

ufl.functional (*form*)

UFL form operator: Extract the functional part of form.

ufl.adjoint (*form, reordered_arguments=None*)

UFL form operator: Given a combined bilinear form, compute the adjoint form by changing the ordering (count) of the test and trial functions.

By default, new Argument objects will be created with opposite ordering. However, if the adjoint form is to be added to other forms later, their arguments must match. In that case, the user must provide a tuple `*reordered_arguments*=(u2,v2)`.

ufl.sensitivity_rhs (*a, u, L, v*)

UFL form operator: Compute the right hand side for a sensitivity calculation system.

The derivation behind this computation is as follows. Assume a, L to be bilinear and linear forms corresponding to the assembled linear system

$$Ax = b.$$

Where x is the vector of the discrete function corresponding to u . Let v be some scalar variable this equation depends on. Then we can write

$$\begin{aligned} 0 &= \frac{d}{dv}(Ax - b) = \frac{dA}{dv}x + A\frac{dx}{dv} - \frac{db}{dv}, \\ A\frac{dx}{dv} &= \frac{db}{dv} - \frac{dA}{dv}x, \end{aligned}$$

and solve this system for $\frac{dx}{dv}$, using the same bilinear form a and matrix A from the original system. Assume the forms are written

```
v = variable(v_expression)
L = IL(v)*dx
a = Ia(v)*dx
```

where IL and Ia are integrand expressions. Define a `Coefficient` u representing the solution to the equations. Then we can compute $\frac{db}{dv}$ and $\frac{dA}{dv}$ from the forms

```
da = diff(a, v)
dL = diff(L, v)
```

and the action of da on u by

```
dau = action(da, u)
```

In total, we can build the right hand side of the system to compute $\frac{du}{dv}$ with the single line

```
dL = diff(L, v) - action(diff(a, v), u)
```

or, using this function,

```
dL = sensitivity_rhs(a, u, L, v)
```

1.4 Release notes

1.4.1 Changes in the next release

Summary of changes

- Remove Python 2 support. Now requires Python 3.5 or above.

Note: Developers should use this page to track and list changes during development. At the time of release, this page should be published (and renamed) to list the most important changes in the new release.

Detailed changes

Note: At the time of release, make a verbatim copy of the ChangeLog here (and remove this note).

1.4.2 Changes in version 2018.1.0

UFL 2018.1.0 was released on 2018-06-14.

Summary of changes

- Remove python2 support.

1.4.3 Changes in version 2017.2.0

UFL 2017.2.0 was released on 2017-12-05.

Summary of changes

- Add `CellDiameter` expression giving diameter of a cell, i.e., maximal distance between any two points of the cell. Implemented for all simplices and quads/hexes.
- Make `(Min|Max) (Cell|Facet) EdgeLength` working for quads/hexes

Detailed changes

- Add geometric quantity `CellDiameter` defined as a set diameter of the cell, i.e., maximal distance between any two points of the cell; implemented on simplices and quads/hexes
- Rename internally used reference quantities `(Cell|Facet) EdgeVectors` to `Reference (Cell|Facet) EdgeVectors`
- Add internally used quantities `CellVertices`, `(Cell|Facet) EdgeVectors` which are physical-coordinates-valued; will be useful for further geometry lowering implementations for quads/hexes
- Implement geometry lowering of `(Min|Max) (Cell|Facet) EdgeLength` for quads and hexes

1.4.4 Changes in version 2017.1.0.post1

UFL 2017.1.0.post1 was released on 2017-09-12.

Summary of changes

- Change PyPI package name to `fenics-ufl`.

1.4.5 Changes in version 2017.1.0

UFL 2017.1.0 was released on 2017-05-09.

Summary of changes

- Add the `DirectionalSobolevSpace` subclass of `SobolevSpace`. This allows one to use spaces where elements have varying continuity in different spatial directions.
- Add `sobolev_space` methods for `HDiv` and `HCurl` finite elements.
- Add `sobolev_space` methods for `TensorProductElement` and `EnrichedElement`. The smallest shared Sobolev space will be returned for enriched elements. For the tensor product elements, a `DirectionalSobolevSpace` is returned depending on the order of the spaces associated with the component elements.

1.4.6 Changes in version 2016.2.0

UFL 2016.2.0 was released on 2016-11-30.

Summary of changes

- Deprecate `.cell()`, `.domain()`, `.element()` in favour of `.ufl_cell()`, `.ufl_domain()`, `.ufl_element()`, in multiple classes, to allow closer integration with DOLFIN
- Remove deprecated properties `cell.{d, x, n, volume, circumradius, facet_area}`
- Remove ancient `form2ufl` script
- Large reworking of symbolic geometry pipeline
- Implement symbolic Piola mappings
- `OuterProductCell` and `OuterProductElement` are merged into `TensorProductCell` and `TensorProductElement` respectively
- Better degree estimation for quadrilaterals
- Expansion rules for Q, DQ, RTCE, RTCF, NCE and NCF on tensor product cells
- Add discontinuous Taylor elements
- Add support for the mapping double covariant Piola in `uflacs`
- Add support for the mapping double contravariant Piola in `uflacs`
- Support for tensor-valued subelements in `uflacs` fixed
- Replacing `Discontinuous Lagrange Trace` with `HDiv Trace` and removing `TraceElement`
- Assigning `Discontinuous Lagrange Trace` and `DGT` as aliases for `HDiv Trace`

Detailed changes

- Add call operator syntax to Form to replace arguments and coefficients. This makes it easier to e.g. express the norm defined by a bilinear form as a functional. Example usage:

```
# Equivalent to replace(a, {u: f, v: f})
M = a(f, f)
# Equivalent to replace(a, {f:1})
c = a(coefficients={f:1})
```

- **Add call operator syntax to Form to replace arguments and coefficients::** `a(f, g) == replace(a, {u: f, v: g})`
`a(coefficients={f:1}) == replace(a, {f:1})`
- Add @ operator to Form: `form @ f == action(form, f)` (python 3.5+ only)
- Reduce noise in Mesh str such that `print(form)` gets more short and readable
- Fix repeated split(function) for arbitrary nested elements
- **EnrichedElement: Remove +/* warning** In the distant past, `A + B => MixedElement([A, B])`. The change that `A + B => EnrichedElement([A, B])` was made in d622c74 (22 March 2010). A warning was introduced in fcfc5ff (26 March 2010) that the meaning of “+” had changed, and that users wanting a `MixedElement` should use “*” instead. People have, presumably, been seeing this warning for 6 1/2 years by now, so it’s probably safe to remove.
- Rework `TensorProductElement` implementation, replaces `OuterProductElement`
- Rework `TensorProductCell` implementation, replaces `OuterProductCell`
- Remove `OuterProductVectorElement` and `OuterProductTensorElement`
- Add `FacetElement` and `InteriorElement`

- Add Hellan-Herrmann-Johnson element
- Add support for double covariant and contravariant mappings in mixed elements
- Support discontinuous Taylor elements on all simplices
- Some more performance improvements
- Minor bugfixes
- Improve Python 3 support
- More permissive in integer types accepted some places
- Make ufl pass almost all flake8 tests
- Add bitbucket pipelines testing
- Improve documentation

1.4.7 Changes in version 2016.1.0

UFL 2016.1.0 was released on 2016-06-23.

- Add operator $A^{(i,j)} := \text{as_tensor}(A, (i,j))$
- Updates to old manual for publishing on fenics-ufl.readthedocs.org
- Bugfix for ufl files with utf-8 encoding
- **Bugfix in conditional derivatives to avoid inf/nan values in generated code.** This bugfix may break ffc if uflacs is not used, to get around that the old workaround in ufl can be enabled by setting `ufl.algorithms.apply_derivatives.CONDITIONAL_WORKAROUND = True` at the top of your program.
- Allow `sum([expressions])` where expressions are nonscalar by defining `expr+0==expr`
- Allow `form=0; form == other;`
- Deprecate `.cell()`, `.domain()`, `.element()` in favour of `.ufl_cell()`, `.ufl_domain()`, `.ufl_element()`, in multiple classes, to allow closer integration with dolfin.
- Remove deprecated properties `cell.{d,x,n,volume,circumradius,facet_area}`.
- Remove ancient `form2ufl` script
- Add new class `Mesh` to replace `Domain`
- Add new class `FunctionSpace(mesh, element)`
- Make `FiniteElement` classes take `Cell`, not `Domain`.
- Large reworking of symbolic geometry pipeline
- Implement symbolic Piola mappings

1.4.8 Changes in version 1.6.0

UFL 1.6.0 was released on 2015-07-28.

- Change approach to attaching `__hash__` implementation to accomodate Python 3
- Implement new non-recursive traversal based hash computation
- Allow `derivative(M, ListTensor(<scalars>), ...)` just like list/tuple works
- Add traits `is_in_reference_frame`, `is_restriction`, `is_evaluation`, `is_differential`

- Add missing linear operators to `ArgumentDependencyExtractor`
- Add `_ufl_is_literal_type` trait
- Add `_ufl_is_terminal_modifier_type` trait and `Expr._ufl_terminal_modifiers_list`
- Add new types `ReferenceDiv` and `ReferenceCurl`
- Outer product element support in degree estimation
- Add `TraceElement`, `InteriorElement`, `FacetElement`, `BrokenElement`
- Add `OuterProductCell` to valid `Real` elements
- Add `_cache` member to form for use by external frameworks
- Add Sobolev space `HEin`
- Add measures `dI`, `dO`, `dC` for interface, overlap, cutcell
- Remove `Measure` constants
- Remove `cell2D` and `cell3D`
- Implement `reference_value` in `apply_restrictions`
- Rename point integral to vertex integral and kept `*dP` syntax
- Replace lambda functions in `ufl_type` with named functions for nicer stack traces
- Minor bugfixes, removal of unused code and cleanups

[FIXME: These links don't belong here, should go under API reference somehow.]

- `genindex`
- `modindex`

Python Module Index

U

ufl, 151
ufl.algebra, 80
ufl.algorithms, 69
ufl.algorithms.ad, 46
ufl.algorithms.analysis, 46
ufl.algorithms.apply_algebra_lowering,
 47
ufl.algorithms.apply_derivatives, 48
ufl.algorithms.apply_function_pullbacks,
 52
ufl.algorithms.apply_geometry_lowering,
 52
ufl.algorithms.apply_integral_scaling,
 53
ufl.algorithms.apply_restrictions, 53
ufl.algorithms.change_to_reference, 55
ufl.algorithms.check_arities, 56
ufl.algorithms.check_restrictions, 57
ufl.algorithms.checks, 57
ufl.algorithms.compute_form_data, 58
ufl.algorithms.domain_analysis, 58
ufl.algorithms.elementtransformations,
 59
ufl.algorithms.estimate_degrees, 59
ufl.algorithms.expand_compounds, 62
ufl.algorithms.expand_indices, 62
ufl.algorithms.formdata, 63
ufl.algorithms.formfiles, 63
ufl.algorithms.forms splitter, 64
ufl.algorithms.formtransformations, 64
ufl.algorithms.map_integrands, 66
ufl.algorithms.multifunction, 66
ufl.algorithms.renumbering, 66
ufl.algorithms.replace, 67
ufl.algorithms.signature, 67
ufl.algorithms.transformer, 68
ufl.algorithms.traversal, 69
ufl.argument, 81
ufl.assertions, 82
ufl.averaging, 82
ufl.cell, 82
ufl.checks, 84
ufl.classes, 84
ufl.coefficient, 115
ufl.compound_expressions, 116
ufl.conditional, 117
ufl.constantvalue, 119
ufl.differentiation, 120
ufl.domain, 122
ufl.equation, 123
ufl.exprcontainers, 123
ufl.exprequals, 124
ufl.exprooperators, 124
ufl.finiteelement, 80
ufl.finiteelement.brokenelement, 73
ufl.finiteelement.elementlist, 73
ufl.finiteelement.enrichedelement, 74
ufl.finiteelement.facetelement, 75
ufl.finiteelement.finiteelement, 75
ufl.finiteelement.finiteelementbase, 75
ufl.finiteelement.hdivcurl, 76
ufl.finiteelement.interiorelement, 77
ufl.finiteelement.mixedelement, 77
ufl.finiteelement.restrictedelement, 78
ufl.finiteelement.tensorproductelement,
 79
ufl.form, 124
ufl.formoperators, 125
ufl.functionspace, 127
ufl.geometry, 128
ufl.index_combination_utils, 135
ufl.indexed, 135
ufl.indexsum, 136
ufl.integral, 136
ufl.log, 137
ufl.mathfunctions, 138
ufl.measure, 139
ufl.objects, 141

ufl.operators, 141
ufl.permutation, 145
ufl.precedence, 146
ufl.protocols, 146
ufl.referencevalue, 146
ufl.restriction, 146
ufl.sobolevspace, 147
ufl.sorting, 147
ufl.split_functions, 147
ufl.tensoralgebra, 147
ufl.tensors, 149
ufl.variable, 151

Index

A

Abs (class in `ufl.algebra`), 80
Abs (class in `ufl.classes`), 97
`abs()` (`ufl.algorithms.apply_derivatives.GenericDerivativeRuleset` method), 49
`abs()` (`ufl.algorithms.estimate_degrees.SumDegreeEstimator` method), 60
`AbstractCell` (class in `ufl`), 155
`AbstractCell` (class in `ufl.cell`), 82
`AbstractCell` (class in `ufl.classes`), 105
`AbstractDomain` (class in `ufl`), 156
`AbstractDomain` (class in `ufl.classes`), 111
`AbstractDomain` (class in `ufl.domain`), 122
`AbstractFunctionSpace` (class in `ufl.classes`), 112
`AbstractFunctionSpace` (class in `ufl.functionspace`), 127
`accumulate_integrands_with_same_metadata()` (in module `ufl.algorithms.domain_analysis`), 58
`Acos` (class in `ufl.classes`), 104
`Acos` (class in `ufl.mathfunctions`), 138
`acos()` (in module `ufl`), 168
`acos()` (in module `ufloperators`), 141
`acos()` (`ufl.algorithms.apply_derivatives.GenericDerivativeRuleset` method), 49
`action()` (in module `ufl`), 173
`action()` (in module `ufl.formoperators`), 125
`add_indent()` (`ufl.log.Logger` method), 137
`add_logfile()` (`ufl.log.Logger` method), 137
`adj_expr()` (in module `ufl.compound_expressions`), 116
`adj_expr_2x2()` (in module `ufl.compound_expressions`), 116
`adj_expr_3x3()` (in module `ufl.compound_expressions`), 116
`adj_expr_4x4()` (in module `ufl.compound_expressions`), 116
`adjoint()` (in module `ufl`), 174
`adjoint()` (in module `ufl.formoperators`), 126
`affine_mesh()` (in module `ufl.domain`), 122
`altenative_dot()` (`ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra` method), 47
`alternative_inner()` (`ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra` method), 47
`always_reconstruct()` (`ufl.algorithms.Transformer` method), 70
`always_reconstruct()` (`ufl.algorithms.transformer.Transformer` method), 68
`analyse_key()` (in module `ufl.exproperators`), 124
`And()` (in module `ufl`), 169
`And()` (in module `ufl.operators`), 141
`AndCondition` (class in `ufl.classes`), 102
`AndCondition` (class in `ufl.conditional`), 117
`apply_algebra_lowering()` (in module `ufl.algorithms.apply_algebra_lowering`), 48
`apply_default_restrictions()` (in module `ufl.algorithms.apply_restrictions`), 55
`apply_derivatives()` (in module `ufl.algorithms.apply_derivatives`), 52
`apply_function_pullbacks()` (in module `ufl.algorithms.apply_function_pullbacks`), 52
`apply_geometry_lowering()` (in module `ufl.algorithms.apply_geometry_lowering`), 53
`apply_integral_scaling()` (in module `ufl.algorithms.apply_integral_scaling`), 53
`apply_restrictions()` (in module `ufl.algorithms.apply_restrictions`), 55
`apply_single_function_pullbacks()` (in module `ufl.algorithms.apply_function_pullbacks`), 52
`apply_transformer()` (in module `ufl.algorithms`), 70
`apply_transformer()` (in module `ufl.algorithms.transformer`), 69
`Argument` (class in `ufl`), 164
`Argument` (class in `ufl.argument`), 81
`Argument` (class in `ufl.classes`), 95
`argument()` (`ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset` method), 48
`argument()` (`ufl.algorithms.apply_derivatives.GradRuleset`

method), 50
argument() (ufl.algorithms.apply_derivatives.ReferenceGradRule method), 51
argument() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51
argument() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
argument() (ufl.algorithms.check_arities.ArityChecker method), 56
argument() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
argument() (ufl.algorithms.FormSplitter method), 72
argument() (ufl.algorithms.formsplitter.FormSplitter method), 64
argument() (ufl.algorithms.formtransformations.PartExtractor method), 64
Arguments() (in module ufl), 165
Arguments() (in module ufl.argument), 81
arguments() (ufl.classes.Form method), 114
arguments() (ufl.Form method), 171
arguments() (ufl.form.Form method), 124
ArityChecker (class in ufl.algorithms.check_arities), 56
ArityMismatch, 57
as_cell() (in module ufl), 155
as_cell() (in module ufl.cell), 83
as_domain() (in module ufl), 156
as_domain() (in module ufl.domain), 122
as_form() (in module ufl.form), 125
as_integral_type() (in module ufl.measure), 140
as_matrix() (in module ufl), 167
as_matrix() (in module ufl.tensors), 149
as_scalar() (in module ufl.tensors), 149
as_scalars() (in module ufl.tensors), 150
as_tensor() (in module ufl), 166
as_tensor() (in module ufl.tensors), 150
as_ufl() (in module ufl), 166
as_ufl() (in module ufl.constantvalue), 120
as_vector() (in module ufl), 167
as_vector() (in module ufl.tensors), 150
Asin (class in ufl.classes), 104
Asin (class in ufl.mathfunctions), 138
asin() (in module ufl), 168
asin() (in module ufl.operators), 141
asin() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
assign_precedences() (in module ufl.precedence), 146
Atan (class in ufl.classes), 104
Atan (class in ufl.mathfunctions), 138
atan() (in module ufl), 168
atan() (in module ufl.operators), 141
atan() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
Atan2 (class in ufl.classes), 104
Atan2 (class in ufl.mathfunctions), 138
atan_2() (in module ufl), 168
ReferenceGradRule (in module ufl.operators), 141
atan_2() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
atan_2() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
attach_estimated_degrees() (in module ufl.algorithms.compute_form_data), 58
avg() (in module ufl), 171
SumDegreeEstimator (in module ufl.operators), 141

B

begin() (ufl.log.Logger method), 137
bessel_function() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
bessel_I() (in module ufl), 168
bessel_I() (in module ufl.operators), 141
bessel_i() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
bessel_J() (in module ufl), 168
bessel_J() (in module ufl.operators), 141
bessel_j() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
bessel_K() (in module ufl), 168
bessel_K() (in module ufl.operators), 142
bessel_k() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
bessel_Y() (in module ufl), 168
bessel_Y() (in module ufl.operators), 142
bessel_y() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
BesselFunction (class in ufl.classes), 104
BesselFunction (class in ufl.mathfunctions), 138
BesselI (class in ufl.classes), 104
BesselII (class in ufl.mathfunctions), 138
BesselJ (class in ufl.classes), 104
BesselJ (class in ufl.mathfunctions), 138
BesselK (class in ufl.classes), 104
BesselK (class in ufl.mathfunctions), 139
BesselY (class in ufl.classes), 104
BesselY (class in ufl.mathfunctions), 139
binary_condition() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
BinaryCondition (class in ufl.classes), 101
BinaryCondition (class in ufl.conditional), 117
block_split() (in module ufl), 174
block_split() (in module ufl.algorithms.formsplitter), 64
block_split() (in module ufl.formoperators), 126
BrokenElement (class in ufl), 164
BrokenElement (class in ufl.classes), 111
BrokenElement (class in ufl.finiteelement.brokenelement), 73
build_component_numbering() (in module ufl.permutation), 145

build_integral_data() (in module ufl.algorithms.domain_analysis), 58	CellDiameter (class in ufl), 157
build_precedence_list() (in module ufl.precedence), 146	CellDiameter (class in ufl.classes), 91
build_precedence_mapping() (in module ufl.precedence), 146	CellDiameter (class in ufl.geometry), 128
	CellEdgeVectors (class in ufl.classes), 89
	CellEdgeVectors (class in ufl.geometry), 128
	CellFacetJacobian (class in ufl.classes), 88
	CellFacetJacobian (class in ufl.geometry), 129
	CellFacetJacobianDeterminant (class in ufl.classes), 90
	CellFacetJacobianDeterminant (class in ufl.geometry), 129
C	CellFacetOrigin (class in ufl.classes), 87
canonical_element_description() (in module ufl.finiteelement.elementlist), 73	CellFacetOrigin (class in ufl.geometry), 129
Cell (class in ufl), 155	cellname() (ufl.Cell method), 155
Cell (class in ufl.cell), 83	cellname() (ufl.cell.Cell method), 83
Cell (class in ufl.classes), 105	cellname() (ufl.cell.TensorProductCell method), 83
cell() (ufl.classes.FiniteElementBase method), 106	cellname() (ufl.classes.Cell method), 105
cell() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 75	cellname() (ufl.classes.TensorProductCell method), 106
cell() (ufl.FiniteElementBase method), 159	cellname() (ufl.TensorProductCell method), 156
cell_avg() (in module ufl), 171	CellNormal (class in ufl), 158
cell_avg() (in module ufl.operators), 142	CellNormal (class in ufl.classes), 91
cell_avg() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset method), 48	CellNormal (class in ufl.geometry), 129
cell_avg() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49	CellOrientation (class in ufl.classes), 92
cell_avg() (ufl.algorithms.apply_derivatives.GradRuleset method), 50	CellOrientation (class in ufl.geometry), 130
cell_avg() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51	CellOrigin (class in ufl.classes), 87
cell_avg() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51	CellOrigin (class in ufl.geometry), 130
cell_avg() (ufl.algorithms.change_to_reference.NEWChangeToReferenceGradRuleset method), 55	CellVertices (class in ufl.classes), 89
cell_avg() (ufl.algorithms.check_arities.ArityChecker method), 56	CellVolume (class in ufl), 157
cell_avg() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60	CellVolume (class in ufl.classes), 91
cell_avg() (ufl.algorithms.formtransformations.PartExtractor method), 64	CellVolume (class in ufl.geometry), 130
cell_coordinate() (ufl.algorithms.apply_derivatives.GradRuleset method), 50	change_integrand_geometry_representation() (in module ufl.algorithms.change_to_reference), 56
cell_coordinate() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51	change_to_reference_grad() (in module ufl.algorithms.change_to_reference), 56
cell_coordinate() (ufl.algorithms.apply_geometry_lowering.CheckIntegratingApplier method), 52	check_arities() (in module ufl.algorithms.check_arities), 57
cell_coordinate() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60	check_restriction() (in module ufl.algorithms.check_restrictions), 57
cell_diameter() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier method), 52	GeometryLoweringApplied (class in ufl), 158
cell_normal() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier method), 52	Circumradius (class in ufl.classes), 91
cell_volume() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier method), 52	GeometryLoweringApplied (class in ufl.geometry), 130
CellAvg (class in ufl.averaging), 82	circumradius() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier), 158
CellAvg (class in ufl.classes), 104	cmp_expr() (in module ufl.sorting), 147
CellCoordinate (class in ufl.classes), 86	codeterminant_expr_nxn() (in module ufl.compound_expressions), 116
CellCoordinate (class in ufl.geometry), 128	Coefficient (class in ufl), 165
	Coefficient (class in ufl.classes), 95

Coefficient (class in ufl.coefficient), 115
coefficient() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset) (ufl.algorithms.expand_indices.IndexExpander method), 48
coefficient() (ufl.algorithms.apply_derivatives.GradRuleset component_tensor) (ufl.algorithms.formtransformations.PartExtractor method), 50
coefficient() (ufl.algorithms.apply_derivatives.ReferenceGradientTensor (class in ufl.classes), 94 ComponentTensor (class in ufl.tensors), 149
method), 51
coefficient() (ufl.algorithms.apply_derivatives.VariableRuleset compound_derivative) (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 51
coefficient() (ufl.algorithms.apply_restrictions.RestrictionPropagation tensor_operator) (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 54
coefficient() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60 CompoundDerivative (class in ufl.classes), 100
coefficient_derivative() (ufl.algorithms.apply_derivatives.DefCompoundDerivative (class in ufl.differentiation), 120 CompoundTensorOperator (class in ufl.classes), 97
method), 48 NEW_GradientTensorOperator (class in ufl.tensoralgebra), 147
coefficient_derivative() (ufl.algorithms.change_to_reference OldChangeToReference (class in module ufl.algorithms), 72
method), 55 compute_energy_norm() (in module ufl.algorithms.formtransformations), 65
coefficient_derivative() (ufl.algorithms.change_to_reference method), 56 compute_expression_hashdata() (in module ufl.algorithms.signature), 67
coefficient_derivative() (ufl.algorithms.replace.Replacer compute_expression_signature() (in module ufl.algorithms.signature), 67
method), 67
coefficient_numbering() (ufl.classes.Form method), 114 compute_form_action() (in module ufl.algorithms), 72
coefficient_numbering() (ufl.Form method), 171 compute_form_action() (in module ufl.algorithms.formtransformations), 65
coefficient_numbering() (ufl.form.Form method), 124 compute_form_adjoint() (in module ufl.algorithms), 72
CoefficientDerivative (class in ufl.classes), 100 compute_form_adjoint() (in module ufl.algorithms.formtransformations), 66
CoefficientDerivative (class in ufl.differentiation), 120 compute_form_arities() (in module ufl.algorithms.formtransformations), 66
Coefficients() (in module ufl), 165 compute_form_data() (in module ufl.algorithms), 70
Coefficients() (in module ufl.coefficient), 116 compute_form_data() (in module ufl.algorithms.compute_form_data), 58
coefficients() (ufl.classes.Form method), 114 compute_form_functional() (in module ufl.algorithms), 73
coefficients() (ufl.Form method), 171 compute_form_functional() (in module ufl.algorithms.formtransformations), 66
coefficients() (ufl.form.Form method), 124 compute_form_lhs() (in module ufl.algorithms), 73
cofac() (in module ufl), 167 compute_form_lhs() (in module ufl.algorithms.formtransformations), 66
cofac() (in module ufl.operators), 142 compute_form_rhs() (in module ufl.algorithms), 73
Cofactor (class in ufl.classes), 98 compute_form_rhs() (in module ufl.algorithms.formtransformations), 66
Cofactor (class in ufl.tensoralgebra), 147 compute_form_signature() (in module ufl.algorithms), 73
cofactor() (ufl.algorithms.apply_algebra_lowering.LowerComputeAlgebrafunctional (in module ufl.algorithms),
method), 47
cofactor() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60 compute_form_signature() (in module ufl.algorithms.signature), 67
cofactor_expr() (in module ufl.compound_expressions), 116 compute_form_with_arity() (in module ufl.algorithms)
cofactor_expr_2x2() (in module ufl.compound_expressions), 116 module
cofactor_expr_3x3() (in module ufl.compound_expressions), 116 compute_form_with_arity() (in module ufl.algorithms.formtransformations), 66
cofactor_expr_4x4() (in module ufl.compound_expressions), 116 compute_form_with_arity() (in module ufl.algorithms.formtransformations), 66
component() (ufl.algorithms.expand_indices.IndexExpander compute_form_with_arity() (in module ufl.algorithms.formtransformations), 66
method), 62 compute_form_with_arity() (in module ufl.algorithms.formtransformations), 66
component_tensor() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49 compute_indices() (in module ufl.permutation), 145
component_tensor() (ufl.algorithms.check_arities.ArityCheck compute_indices2() (in module ufl.permutation), 145
method), 56 compute_integrand_scaling_factor() (in module ufl.algorithms.apply_integral_scaling), 53
component_tensor() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60

compute_multiindex_hashdata() (in module ufl.algorithms.signature), 67
 compute_order_tuples() (in module ufl.permutation), 145
 compute_permutation_pairs() (in module ufl.permutation), 145
 compute_permutations() (in module ufl.permutation), 145
 compute_sign() (in module ufl.permutation), 145
 compute_terminal_hashdata() (in module ufl.algorithms.signature), 67
 Condition (class in ufl.classes), 101
 Condition (class in ufl.conditional), 117
 condition() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 Conditional (class in ufl.classes), 102
 Conditional (class in ufl.conditional), 117
 conditional() (in module ufl), 169
 conditional() (in module ufl.operators), 142
 conditional() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 conditional() (ufl.algorithms.check_arities.ArityChecker method), 56
 conditional() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 conditional() (ufl.algorithms.expand_indices.IndexExpandercurl() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 Constant() (in module ufl), 166
 Constant() (in module ufl.coefficient), 116
 constant_value() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 constant_value() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
 constant_value() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 ConstantValue (class in ufl.classes), 93
 ConstantValue (class in ufl.constantvalue), 119
 contraction() (in module ufl.operators), 142
 CopyTransformer (class in ufl.algorithms.transformer), 68
 Cos (class in ufl.classes), 103
 Cos (class in ufl.mathfunctions), 139
 cos() (in module ufl), 168
 cos() (in module ufl.operators), 142
 cos() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 Cosh (class in ufl.classes), 103
 Cosh (class in ufl.mathfunctions), 139
 cosh() (in module ufl), 168
 cosh() (in module ufl.operators), 142
 cosh() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 count() (ufl.classes.Coefficient method), 95
 count() (ufl.classes.Index method), 113
 count() (ufl.classes.Label method), 95
 count() (ufl.Coefficient method), 165
 count() (ufl.coefficient.Coefficient method), 115
 count() (ufl.Index method), 166
 count() (ufl.variable.Label method), 151
 create_nested_lists() (in module ufl.algorithms.apply_function_pullbacks), 52
 create_slice_indices() (in module ufl.index_combination_utils), 135
 Cross (class in ufl.classes), 98
 Cross (class in ufl.tensoralgebra), 148
 cross() (in module ufl), 167
 cross() (in module ufl.operators), 142
 cross() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
 cross() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 cross_expr() (in module ufl.compound_expressions), 116
 Curl (class in ufl.classes), 101
 Curl (class in ufl.differentiation), 120
 curl() (in module ufl), 170
 curl() (in module ufl.operators), 142
 curl() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
 curl() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
D
 Debug (ufl.log.Logger method), 137
 default_domain() (in module ufl.domain), 123
 DefaultRestrictionApplier (class in ufl.algorithms.apply_restrictions), 53
 degree() (ufl.classes.FiniteElementBase method), 106
 degree() (ufl.classes.MixedElement method), 107
 degree() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 75
 degree() (ufl.finiteelement.mixedelement.MixedElement method), 77
 degree() (ufl.FiniteElementBase method), 159
 degree() (ufl.MixedElement method), 161
 deprecate() (ufl.log.Logger method), 137
 Derivative (class in ufl.classes), 100
 Derivative (class in ufl.differentiation), 120
 derivative() (in module ufl), 173
 derivative() (in module ufl.formoperators), 126
 derivative() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48
 derivative() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
 derivative() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 53
 derivative() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60
 DerivativeRuleDispatcher (class in ufl.algorithms.apply_derivatives), 48

<p>det() (in module ufl), 167 det() (in module ufl.operators), 142 Determinant (class in ufl.classes), 98 Determinant (class in ufl.tensoralgebra), 148 determinant() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47 determinant() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60 determinant_expr() (in ufl.compound_expressions), 116 determinant_expr_2x2() (in ufl.compound_expressions), 116 determinant_expr_3x3() (in ufl.compound_expressions), 116 dev() (in module ufl), 168 dev() (in module ufl.operators), 142 Deviatoric (class in ufl.classes), 98 Deviatoric (class in ufl.tensoralgebra), 148 deviatoric() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47 deviatoric() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60 deviatoric_expr() (in module ufl.compound_expressions), 116 deviatoric_expr_2x2() (in ufl.compound_expressions), 116 deviatoric_expr_3x3() (in ufl.compound_expressions), 116 diag() (in module ufl), 167 diag() (in module ufl.operators), 142 diag_vector() (in module ufl), 167 diag_vector() (in module ufl.operators), 142 dicts_lt() (in module ufl.algorithms.domain_analysis), 59 diff() (in module ufl), 169 diff() (in module ufl.operators), 142 dimension() (ufl.classes.IndexSum method), 99 dimension() (ufl.indexsum.IndexSum method), 136 DirectionalSobolevSpace (class in ufl.sobolevspaces), 147 Div (class in ufl.classes), 101 Div (class in ufl.differentiation), 120 div() (in module ufl), 170 div() (in module ufl.operators), 142 div() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47 div() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 60 Division (class in ufl.algebra), 80 Division (class in ufl.classes), 97 division() (ufl.algorithms.apply_derivatives.GenericDerivativeRule method), 49 division() (ufl.algorithms.check_arities.ArityChecker method), 56 division() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61 </p>	<p>division() (ufl.algorithms.expand_indices.IndexExpander method), 62 division() (ufl.algorithms.formtransformations.PartExtractor method), 64 D Dn() (in module ufl.operators), 141 E Estimator (ufl.algorithms.domain_analysis.IntegralData attribute), 58 module domain_numbering() (ufl.classes.Form method), 114 module domain_numbering() (ufl.Form method), 171 module domain_numbering() (ufl.form.Form method), 124 Dot (class in ufl.classes), 98 Dot (class in ufl.tensoralgebra), 148 dot() (in module ufl), 167 dot() (in module ufl.operators), 143 dot() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47 dot() (ufl.algorithms.check_arities.ArityChecker method), 56 dot() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61 dot() (ufl.algorithms.formtransformations.PartExtractor method), 64 Dt() (in module ufl.operators), 141 Dx() (in module ufl), 169 Dx() (in module ufl.operators), 141 dx() (ufl.classes.Expr method), 85 dyad() (in module ufl.tensors), 150 </p>
E	
<p>elem_div() (in module ufl), 171 elem_div() (in module ufl.operators), 143 elem_mult() (in module ufl), 171 elem_mult() (in module ufl.operators), 143 elem_op() (in module ufl), 171 elem_op() (in module ufl.operators), 143 elem_op_items() (in module ufl.operators), 143 elem_pow() (in module ufl), 171 elem_pow() (in module ufl.operators), 143 empty() (ufl.classes.Form method), 114 empty() (ufl.Form method), 171 empty() (ufl.form.Form method), 125 enabled_coefficients (ufl.algorithms.domain_analysis.IntegralData attribute), 58 end() (ufl.log.Logger method), 137 energy_norm() (in module ufl), 173 energy_norm() (in module ufl.formoperators), 126 EnrichedElement (class in ufl), 162 EnrichedElement (class in ufl.classes), 109 EnrichedElement (class ufl.finiteelement.enrichedelement), 74 EnrichedElementBase (class ufl.finiteelement.enrichedelement), 74 EQ (class in ufl.classes), 101 </p>	

EQ (class in `ufl.conditional`), 117
`eq()` (in module `ufl`), 169
`eq()` (in module `ufl.operators`), 143
`equals()` (`ufl.classes.Form` method), 114
`equals()` (`ufl.Form` method), 171
`equals()` (`ufl.form.Form` method), 125
`Equation` (class in `ufl.classes`), 115
`Equation` (class in `ufl.equation`), 123
`Erf` (class in `ufl.classes`), 104
`Erf` (class in `ufl.mathfunctions`), 139
`erf()` (in module `ufl`), 168
`erf()` (in module `ufl.operators`), 143
`erf()` (`ufl.algorithms.apply_derivatives.GenericDerivativeRules` method), 49
`error()` (`ufl.log.Logger` method), 137
`estimate_total_polynomial_degree()` (in module `ufl.algorithms`), 69
`estimate_total_polynomial_degree()` (in module `ufl.algorithms.estimate_degrees`), 62
`evaluate()` (`ufl.algebra.Abs` method), 80
`evaluate()` (`ufl.algebra.Division` method), 80
`evaluate()` (`ufl.algebra.Power` method), 80
`evaluate()` (`ufl.algebra.Product` method), 80
`evaluate()` (`ufl.algebra.Sum` method), 81
`evaluate()` (`ufl.averaging.CellAvg` method), 82
`evaluate()` (`ufl.averaging.FacetAvg` method), 82
`evaluate()` (`ufl.classes.Abs` method), 97
`evaluate()` (`ufl.classes.AndCondition` method), 102
`evaluate()` (`ufl.classes.Atan2` method), 104
`evaluate()` (`ufl.classes.BesselFunction` method), 104
`evaluate()` (`ufl.classes.CellAvg` method), 104
`evaluate()` (`ufl.classes.ComponentTensor` method), 94
`evaluate()` (`ufl.classes.Conditional` method), 102
`evaluate()` (`ufl.classes.Division` method), 97
`evaluate()` (`ufl.classes.EQ` method), 102
`evaluate()` (`ufl.classes.Erf` method), 104
`evaluate()` (`ufl.classes.Expr` method), 85
`evaluate()` (`ufl.classes.FacetAvg` method), 105
`evaluate()` (`ufl.classes.GE` method), 102
`evaluate()` (`ufl.classes.Grad` method), 100
`evaluate()` (`ufl.classes.GT` method), 102
`evaluate()` (`ufl.classes.Identity` method), 94
`evaluate()` (`ufl.classes.Indexed` method), 94
`evaluate()` (`ufl.classes.IndexSum` method), 99
`evaluate()` (`ufl.classes.LE` method), 102
`evaluate()` (`ufl.classes.ListTensor` method), 94
`evaluate()` (`ufl.classes.Ln` method), 103
`evaluate()` (`ufl.classes.LT` method), 102
`evaluate()` (`ufl.classes.MathFunction` method), 103
`evaluate()` (`ufl.classes.MaxValue` method), 103
`evaluate()` (`ufl.classes.MinValue` method), 103
`evaluate()` (`ufl.classes.MultiIndex` method), 93
`evaluate()` (`ufl.classes.NE` method), 102
`evaluate()` (`ufl.classes.NotCondition` method), 102
`evaluate()` (`ufl.classes.OrCondition` method), 102
`evaluate()` (`ufl.classes.PermutationSymbol` method), 94
`evaluate()` (`ufl.classes.Power` method), 97
`evaluate()` (`ufl.classes.Product` method), 96
`evaluate()` (`ufl.classes.ReferenceGrad` method), 100
`evaluate()` (`ufl.classes.ReferenceValue` method), 105
`evaluate()` (`ufl.classes.Restricted` method), 99
`evaluate()` (`ufl.classes.ScalarValue` method), 93
`evaluate()` (`ufl.classes.SpatialCoordinate` method), 86
`evaluate()` (`ufl.classes.Sum` method), 96
`evaluate()` (`ufl.classes.Terminal` method), 85
`evaluate()` (`ufl.classes.Variable` method), 96
`evaluate()` (`ufl.classes.Zero` method), 93
`evaluate()` (`ufl.conditional.AndCondition` method), 117
`evaluate()` (`ufl.conditional.Conditional` method), 117
`evaluate()` (`ufl.conditional.EQ` method), 117
`evaluate()` (`ufl.conditional.GE` method), 117
`evaluate()` (`ufl.conditional.GT` method), 118
`evaluate()` (`ufl.conditional.LE` method), 118
`evaluate()` (`ufl.conditional.LT` method), 118
`evaluate()` (`ufl.conditional.MaxValue` method), 118
`evaluate()` (`ufl.conditional.MinValue` method), 118
`evaluate()` (`ufl.conditional.NE` method), 118
`evaluate()` (`ufl.conditional.NotCondition` method), 118
`evaluate()` (`ufl.conditional.OrCondition` method), 118
`evaluate()` (`ufl.constantvalue.Identity` method), 119
`evaluate()` (`ufl.constantvalue.PermutationSymbol` method), 119
`evaluate()` (`ufl.constantvalue.ScalarValue` method), 119
`evaluate()` (`ufl.constantvalue.Zero` method), 119
`evaluate()` (`ufl.differentiation.Grad` method), 121
`evaluate()` (`ufl.differentiation.ReferenceGrad` method), 121
`evaluate()` (`ufl.geometry.SpatialCoordinate` method), 135
`evaluate()` (`ufl.Identity` method), 166
`evaluate()` (`ufl.indexed.Indexed` method), 135
`evaluate()` (`ufl.indexsum.IndexSum` method), 136
`evaluate()` (`ufl.mathfunctions.Atan2` method), 138
`evaluate()` (`ufl.mathfunctions.BesselFunction` method), 138
`evaluate()` (`ufl.mathfunctions.Erf` method), 139
`evaluate()` (`ufl.mathfunctions.Ln` method), 139
`evaluate()` (`ufl.mathfunctions.MathFunction` method), 139
`evaluate()` (`ufl.PermutationSymbol` method), 166
`evaluate()` (`ufl.referencevalue.ReferenceValue` method), 146
`evaluate()` (`ufl.restriction.Restricted` method), 146
`evaluate()` (`ufl.SpatialCoordinate` method), 157
`evaluate()` (`ufl.tensors.ComponentTensor` method), 149
`evaluate()` (`ufl.tensors.ListTensor` method), 149
`evaluate()` (`ufl.variable.Variable` method), 151
`execute_ufl_code()` (in module `ufl.algorithms.formfiles`), 63
`Exp` (class in `ufl.classes`), 103

Exp (class in ufl.mathfunctions), 139
exp() (in module ufl), 168
exp() (in module ufl.operators), 143
exp() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleDispatcher method), 49
expand_compounds() (in module ufl.algorithms), 72
expand_compounds() (in module ufl.algorithms.expand_compounds), 62
expand_derivatives() (in module ufl.algorithms), 72
expand_derivatives() (in module ufl.algorithms.ad), 46
expand_indices() (in module ufl.algorithms), 71
expand_indices() (in module ufl.algorithms.expand_indices), 63
expecting_expr() (in module ufl.assertions), 82
expecting_instance() (in module ufl.assertions), 82
expecting_python_scalar() (in module ufl.assertions), 82
expecting_terminal() (in module ufl.assertions), 82
expecting_true_ufl_scalar() (in module ufl.assertions), 82
Expr (class in ufl.classes), 84
expr() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
expr() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48
expr() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
expr() (ufl.algorithms.apply_function_pullbacks.FunctionPullbackApplier method), 52
expr() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier method), 52
expr() (ufl.algorithms.change_to_reference.NEWChangeToReferenceGrad method), 55
expr() (ufl.algorithms.change_to_reference.OLDChangeToReferenceGradins() (in module ufl.domain), 123
method), 56
expr() (ufl.algorithms.check_arities.ArityChecker method), 56
expr() (ufl.algorithms.check_restrictions.RestrictionChecker method), 57
expr() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
expr() (ufl.algorithms.FormSplitter method), 72
expr() (ufl.algorithms.formsplitter.FormSplitter method), 64
expr() (ufl.algorithms.formtransformations.PartExtractor method), 64
expr() (ufl.algorithms.MultiFunction method), 71
expr() (ufl.algorithms.replace.Replacer method), 67
expr() (ufl.algorithms.ReuseTransformer method), 70
expr() (ufl.algorithms.Transformer method), 70
expr() (ufl.algorithms.transformer.CopyTransformer method), 68
expr() (ufl.algorithms.transformer.ReuseTransformer method), 68
expr() (ufl.algorithms.transformer.Transformer method), 68
expr_equals() (in module ufl.exprquals), 124
ExprData (class in ufl.algorithms.formdata), 63
expression() (ufl.classes.Variable method), 96
expression() (ufl.variable.Variable method), 151
ExprList (class in ufl.classes), 99
ExprList (class in ufl.exprcontainers), 123
ExprMapping (class in ufl.classes), 99
ExprMapping (class in ufl.exprcontainers), 123
ExprTupleKey (class in ufl.algorithms.domain_analysis), 58
exterior_derivative() (in module ufl), 170
exterior_derivative() (in module ufl.operators), 143
extract_arguments() (in module ufl.algorithms), 72
extract_arguments() (in module ufl.algorithms.analysis), 46
extract_arguments_and_coefficients() (in module ufl.algorithms.analysis), 46
extract_coefficients() (in module ufl.algorithms), 72
extract_coefficients() (in module ufl.algorithms.analysis), 46
extract_component() (ufl.classes.FiniteElementBase method), 106
extract_component() (ufl.classes.MixedElement method), 107
extract_component() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 76
extract_component() (ufl.finiteelement.mixedelement.MixedElement method), 76
extract_element() (ufl.algorithms), 71
extract_elements() (in module ufl.algorithms.analysis), 46
extract_reference_component() (ufl.classes.FiniteElementBase method), 106
extract_reference_component() (ufl.classes.MixedElement method), 107
extract_reference_component() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 76
extract_reference_component() (ufl.finiteelement.mixedelement.MixedElement method), 77
extract_reference_component() (ufl.FiniteElementBase method), 159
extract_reference_component() (ufl.MixedElement method), 161
extract_sub_elements() (in module ufl.algorithms), 71
extract_sub_elements() (in module ufl.algorithms.analysis), 46
extract_subelement_component() (ufl.classes.FiniteElementBase method),

106
extract_subelement_component()
 (ufl.classes.MixedElement method), 108
extract_subelement_component()
 (ufl.classes.TensorElement method), 108
extract_subelement_component()
 (ufl.finiteelement.finiteelementbase.FiniteElement method), 76
extract_subelement_component()
 (ufl.finiteelement.mixedelement.MixedElement method), 77
extract_subelement_component()
 (ufl.finiteelement.mixedelement.TensorElement method), 78
extract_subelement_component() (ufl.FiniteElementBase method), 160
extract_subelement_component() (ufl.MixedElement method), 161
extract_subelement_component() (ufl.TensorElement method), 161
extract_subelement_reference_component()
 (ufl.classes.FiniteElementBase method), 106
extract_subelement_reference_component()
 (ufl.classes.MixedElement method), 108
extract_subelement_reference_component()
 (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 76
extract_subelement_reference_component()
 (ufl.finiteelement.mixedelement.MixedElement method), 77
extract_subelement_reference_component()
 (ufl.FiniteElementBase method), 160
extract_subelement_reference_component()
 (ufl.MixedElement method), 161
extract_type() (in module ufl.algorithms), 71
extract_type() (in module ufl.algorithms.analysis), 46
extract_unique_domain() (in module ufl.domain), 123
extract_unique_elements() (in module ufl.algorithms), 71
extract_unique_elements() (in module ufl.algorithms.analysis), 46

F

facet_area() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplying), 53
facet_area() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 53
facet_avg() (in module ufl), 171
facet_avg() (in module ufl.operators), 143
facet_avg() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset method), 48
facet_avg() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

facet_avg() (ufl.algorithms.apply_derivatives.GradRuleset method), 50
facet_avg() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51
facet_avg() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51
facet_avg() (ufl.algorithms.change_to_reference.NEWChangeToReference method), 55
facet_avg() (ufl.algorithms.check_arities.ArityChecker method), 56
facet_avg() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
facet_avg() (ufl.algorithms.formtransformations.PartExtractor method), 64
facet_cell_coordinate() (ufl.algorithms.apply_geometry_lowering.Geometry method), 53
facet_coordinate() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
facet_jacobian() (ufl.algorithms.apply_geometry_lowering.GeometryLowering method), 53
facet_jacobian_determinant()
 (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplying method), 53
facet_jacobian_determinant()
 (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
facet_jacobian_inverse() (ufl.algorithms.apply_geometry_lowering.Geometry method), 53
facet_jacobian_inverse() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
facet_normal() (ufl.algorithms.apply_geometry_lowering.GeometryLowering method), 53
facet_normal() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
facet_normal() (ufl.algorithms.check_restrictions.RestrictionChecker method), 57
facet_origin() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
FacetArea (class in ufl), 158
FacetArea (class in ufl.classes), 91
FacetArea (class in ufl.geometry), 130
FacetAvg (class in ufl.classes), 105
FacetCoordinate (class in ufl.classes), 86
FacetCoordinate (class in ufl.geometry), 131
FacetEdgeVectors (class in ufl.classes), 89
FacetEdgeVectors (class in ufl.geometry), 131
FacetElement (in module ufl), 164
FacetElement (in module ufl.classes), 111
FacetElement (in module ufl.finiteelement.facetelement), 75
FacetJacobian (class in ufl.classes), 88

FacetJacobian (class in `ufl.geometry`), 131
FacetJacobianDeterminant (class in `ufl.classes`), 89
FacetJacobianDeterminant (class in `ufl.geometry`), 131
FacetJacobianInverse (class in `ufl.classes`), 90
FacetJacobianInverse (class in `ufl.geometry`), 132
FacetNormal (class in `ufl`), 158
FacetNormal (class in `ufl.classes`), 90
FacetNormal (class in `ufl.geometry`), 132
FacetOrientation (class in `ufl.classes`), 92
FacetOrientation (class in `ufl.geometry`), 132
FacetOrigin (class in `ufl.classes`), 87
FacetOrigin (class in `ufl.geometry`), 132
`family()` (`ufl.classes.FiniteElementBase` method), 106
`family()` (`ufl.finiteelement.finiteelementbase.FiniteElementBase` method), 76
`family()` (`ufl.FiniteElementBase` method), 160
`feec_element()` (in module `ufl.finiteelement.elementlist`), 74
`FileData` (class in `ufl.algorithms.formfiles`), 63
`find_geometric_dimension()` (in module `ufl.domain`), 123
`FiniteElement` (class in `ufl`), 160
`FiniteElement` (class in `ufl.classes`), 107
`FiniteElement` (class in `ufl.finiteelement.finiteelement`), 75
`FiniteElementBase` (class in `ufl`), 159
`FiniteElementBase` (class in `ufl.classes`), 106
`FiniteElementBase` (class in `ufl.finiteelement.finiteelementbase`), 75
`FixedIndex` (class in `ufl.classes`), 112
`fixme()` (`ufl.algorithms.apply_derivatives.GenericDerivativeRuleset` method), 49
`flattened_sub_element_mapping()` (`ufl.classes.TensorElement` method), 108
`flattened_sub_element_mapping()` (`ufl.finiteelement.mixedelement.TensorElement` method), 78
`flattened_sub_element_mapping()` (`ufl.TensorElement` method), 162
`FloatValue` (class in `ufl.classes`), 94
`FloatValue` (class in `ufl.constantvalue`), 119
`Form` (class in `ufl`), 171
`Form` (class in `ufl.classes`), 114
`Form` (class in `ufl.form`), 124
`form_argument()` (`ufl.algorithms.apply_derivatives.GenericDerivativeRuleset` method), 49
`form_argument()` (`ufl.algorithms.apply_function_pullbacks.FunctionPullbackApplier` method), 52
`form_argument()` (`ufl.algorithms.change_to_reference.NEWChangeToReferenceGrad` method), 55
`form_argument()` (`ufl.algorithms.check_restrictions.RestrictionChecker` method), 57
`form_argument()` (`ufl.algorithms.expand_indices.IndexExpander` method), 63
`FormArgument` (class in `ufl.classes`), 85
`format_float()` (in module `ufl.constantvalue`), 120
`FormData` (class in `ufl.algorithms.formdata`), 63
`FormSplitter` (class in `ufl.algorithms`), 72
`FormSplitter` (class in `ufl.algorithms.forms splitter`), 64
`free_indices()` (`ufl.classes.ExprList` method), 99
`free_indices()` (`ufl.classes.ExprMapping` method), 100
`free_indices()` (`ufl.exprcontainers.ExprList` method), 123
`free_indices()` (`ufl.exprcontainers.ExprMapping` method), 123
`from_numpy_to_lists()` (in module `ufl.tensors`), 150
`functional()` (in module `ufl`), 174
`functional()` (in module `ufl.formoperators`), 126
`FunctionPullbackApplier` (class in `ufl.algorithms.apply_function_pullbacks`), 52
`FunctionSpace` (class in `ufl`), 164
`FunctionSpace` (class in `ufl.classes`), 112
`FunctionSpace` (class in `ufl.functionspace`), 127

G

`GateauxDerivativeRuleset` (class in `ufl.algorithms.apply_derivatives`), 48
`GE` (class in `ufl.classes`), 102
`GE` (class in `ufl.conditional`), 117
`ge()` (in module `ufl`), 169
`ge()` (in module `ufl.operators`), 143
`generic_pseudo_determinant_expr()` (in module `ufl.compound_expressions`), 116
`generic_pseudo_inverse_expr()` (in module `ufl.compound_expressions`), 117
`GenericDerivativeRuleset` (class in `ufl.algorithms.apply_derivatives`), 49
`geometric_cell_quantity()` (in module `ufl.algorithms.apply_restrictions.RestrictionPropagator` method), 54
`geometric_dimension()` (`ufl.AbstractCell` method), 155
`geometric_dimension()` (`ufl.AbstractDomain` method), 156
`geometric_dimension()` (`ufl.cell.AbstractCell` method), 82
`geometric_dimension()` (in module `ufl.classes.AbstractCell` method), 105
`geometric_dimension()` (in module `ufl.classes.AbstractDomain` method), 111
`geometric_dimension()` (in module `ufl.classes.Expr` method), 85
`geometric_dimension()` (in module `ufl.classes.Form` method), 115
`geometric_dimension()` (in module `ufl.domain.AbstractDomain` method), 122
`geometric_dimension()` (`ufl.Form` method), 171
`geometric_dimension()` (`ufl.form.Form` method), 125
`geometric_facet_quantity()` (in module `ufl.algorithms.apply_restrictions.RestrictionPropagator` method), 54
`geometric_quantity()` (in module `ufl.algorithms.apply_derivatives.GateauxDerivativeR` method), 48

geometric_quantity() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

geometric_quantity() (ufl.algorithms.apply_derivatives.GradRuleset method), 50

geometric_quantity() (ufl.algorithms.apply_derivatives.GradRuleset module), 50

geometric_quantity() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51

geometric_quantity() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51

geometric_quantity() (ufl.algorithms.change_to_reference.NEWChangeToReference method), 55

geometric_quantity() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

GeometricCellQuantity (class in ufl.classes), 86

GeometricCellQuantity (class in ufl.geometry), 132

GeometricFacetQuantity (class in ufl.classes), 86

GeometricFacetQuantity (class in ufl.geometry), 132

GeometricQuantity (class in ufl.classes), 85

GeometricQuantity (class in ufl.geometry), 132

GeometryLoweringApplier (class in ufl.algorithms.apply_geometry_lowering), 52

get_handler() (ufl.log.Logger method), 137

get_logfile_handler() (ufl.log.Logger method), 137

get_logger() (ufl.log.Logger method), 137

Grad (class in ufl.classes), 100

Grad (class in ufl.differentiation), 121

grad() (in module ufl), 169

grad() (in module ufl.operators), 143

grad() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48

grad() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset method), 48

grad() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

grad() (ufl.algorithms.apply_derivatives.GradRuleset method), 50

grad() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51

grad() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51

grad() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54

grad() (ufl.algorithms.change_to_reference.NEWChangeToReference method), 55

grad() (ufl.algorithms.change_to_reference.OLDChangeToReference method), 56

grad() (ufl.algorithms.check_arities.ArityChecker method), 56

grad() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

grad() (ufl.algorithms.expand_indices.IndexExpander method), 63

grad() (ufl.algorithms.formtransformations.PartExtractor method), 64

GradRuleset (in module ufl.algorithms.apply_derivatives), 50

GradRuleset (in module ufl.algorithms.domain_analysis), 59

GradRulesetByDomainAndType (in module ufl.algorithms.domain_analysis), 59

VariableRuleset (in module ufl.classes), 102

GT (class in ufl.conditional), 117

Grad (in module ufl.operators), 143

H

has_exact_type() (in module ufl.algorithms.analysis), 46

has_simplex_facets() (ufl.AbstractCell method), 155

has_simplex_facets() (ufl.Cell method), 155

has_simplex_facets() (ufl.cell.AbstractCell method), 82

has_simplex_facets() (ufl.cell.Cell method), 83

has_simplex_facets() (ufl.cell.TensorProductCell method), 83

has_simplex_facets() (ufl.classes.AbstractCell method), 105

has_simplex_facets() (ufl.classes.Cell method), 105

has_simplex_facets() (ufl.classes.TensorProductCell method), 106

has_simplex_facets() (ufl.TensorProductCell method), 156

has_type() (in module ufl.algorithms.analysis), 47

HCurlElement (class in ufl), 164

HCurlElement (class in ufl), 164

HDivElement (class in ufl), 110

HDivElement (class in ufl), 76

HDivElement (class in ufl), 163

HDivElement (class in ufl), 110

HDivElement (class in ufl), 77

hypercube() (in module ufl.cell), 84

I

id_or_none() (in module ufl.protocols), 146

Identity (class in ufl), 166

Identity (class in ufl.classes), 94

Identity (class in ufl.constantvalue), 119

Increase_order() (in module ufl.algorithms.elementtransformations), 59

IndependentOperator (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

IndependentTerminal (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49

Index (class in ufl), 166

Index (class in ufl.classes), 112

Index() (ufl.algorithms.renumbering.IndexRenumberingTransformer method), 67

index() (ufl.classes.IndexSum method), 99

index() (ufl.indexsum.IndexSum method), 136

index_dimensions() (ufl.classes.ExprList method), 99

index_dimensions() (ufl.classes.ExprMapping method),
 100
index_dimensions() (ufl.exprcontainers.ExprList
 method), 123
index_dimensions() (ufl.exprcontainers.ExprMapping
 method), 123
index_sum() (ufl.algorithms.apply_derivatives.GenericDerivativeRule)
 method), 49
index_sum() (ufl.algorithms.check_arities.ArityChecker
 method), 56
index_sum() (ufl.algorithms.estimate_degrees.SumDegreeEstimator)
 method), 61
index_sum() (ufl.algorithms.expand_indices.IndexExpander
 method), 63
index_sum() (ufl.algorithms.formtransformations.PartExtractor
 method), 64
IndexBase (class in ufl.classes), 112
Indexed (class in ufl.classes), 94
Indexed (class in ufl.indexed), 135
indexed() (ufl.algorithms.apply_derivatives.DerivativeRule)
 method), 48
indexed() (ufl.algorithms.apply_derivatives.GenericDerivativeRule)
 method), 49
indexed() (ufl.algorithms.check_arities.ArityChecker
 method), 56
indexed() (ufl.algorithms.estimate_degrees.SumDegreeEstimator
 method), 61
indexed() (ufl.algorithms.expand_indices.IndexExpander
 method), 63
indexed() (ufl.algorithms.formtransformations.PartExtractor
 method), 65
IndexExpander (class in ufl.algorithms.expand_indices),
 62
IndexRenumberingTransformer (class
 ufl.algorithms.renumbering), 66
IndexSum (class in ufl.classes), 99
IndexSum (class in ufl.indexsum), 136
indices() (in module ufl), 166
indices() (ufl.classes.ComponentTensor method), 95
indices() (ufl.classes.MultiIndex method), 93
indices() (ufl.tensors.ComponentTensor method), 149
info() (ufl.log.Logger method), 137
info_blue() (ufl.log.Logger method), 137
info_green() (ufl.log.Logger method), 137
info_red() (ufl.log.Logger method), 137
Inner (class in ufl.classes), 97
Inner (class in ufl.tensoralgebra), 148
inner() (in module ufl), 167
inner() (in module ufl.operators), 143
inner() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra
 method), 47
inner() (ufl.algorithms.check_arities.ArityChecker
 method), 56
inner() (ufl.algorithms.estimate_degrees.SumDegreeEstimator
 method), 59
inner() (ufl.algorithms.estimate_degrees.SumDegreeEstimator)
 method), 61
inner() (ufl.algorithms.formtransformations.PartExtractor
 method), 65
Integral (class in ufl), 172
Integral (class in ufl.classes), 114
Integral (class in ufl.integral), 136
IntegralRuleCoefficients (ufl.algorithms.domain_analysis.IntegralData
 attribute), 58
integral_subdomain_ids() (in
 ufl.algorithms.domain_analysis), 59
IntegralType (ufl.classes.Measure method), 113
integral_type() (ufl.Integral method), 172
integral_type() (ufl.integral.Integral method), 136
integral_type() (ufl.Measure method), 172
integral_type() (ufl.measure.Measure method), 140
integral_types() (in module ufl), 173
IntegralData (class in ufl.algorithms.domain_analysis), 58
IntegralData (ufl.algorithms.domain_analysis.IntegralData attribute), 58
integrals() (ufl.classes.Form method), 115
integrals() (ufl.Form method), 171
integrals() (ufl.form.Form method), 125
integrals_by_type() (ufl.classes.Form method), 115
integrals_by_type() (ufl.Form method), 171
integrals_by_type() (ufl.form.Form method), 125
integrand() (ufl.classes.Integral method), 114
integrand() (ufl.Integral method), 172
integrand() (ufl.integral.Integral method), 136
InteriorElement() (in module ufl), 164
InteriorElement() (in module ufl.classes), 111
InteriorElement() (in
 ufl.finiteelement.interiorelement), 77
interpret_ufl_namespace() (in
 ufl.algorithms.formfiles), 63
IntValue (class in ufl.classes), 94
IntValue (class in ufl.constantvalue), 119
inv() (in module ufl), 167
inv() (in module ufl.operators), 143
Inverse (class in ufl.classes), 98
Inverse (class in ufl.tensoralgebra), 148
inverse() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra
 method), 47
inverse() (ufl.algorithms.estimate_degrees.SumDegreeEstimator
 method), 61
inverse_expr() (in module ufl.compound_expressions),
 59
IrreducibleInt (class in ufl.algorithms.estimate_degrees),
 is_cellwise_constant() (in module ufl.checks), 84
is_cellwise_constant() (ufl.Argument method), 164

is_cellwise_constant() (ufl.argument.Argument method), 81
 is_cellwise_constant() (ufl.classes.Argument method), 95
 is_cellwise_constant() (ufl.classes.CellCoordinate method), 86
 is_cellwise_constant() (ufl.classes.CellEdgeVectors method), 89
 is_cellwise_constant() (ufl.classes.CellFacetJacobian method), 88
 is_cellwise_constant() (ufl.classes.CellFacetJacobianDeterminant method), 90
 is_cellwise_constant() (ufl.classes.CellFacetJacobianInverse method), 90
 is_cellwise_constant() (ufl.classes.CellOrigin method), 87
 is_cellwise_constant() (ufl.classes.CellVertices method), 89
 is_cellwise_constant() (ufl.classes.Coefficient method), 95
 is_cellwise_constant() (ufl.classes.ConstantValue method), 93
 is_cellwise_constant() (ufl.classes.EnrichedElement method), 109
 is_cellwise_constant() (ufl.classes.FacetCoordinate method), 87
 is_cellwise_constant() (ufl.classes.FacetEdgeVectors method), 89
 is_cellwise_constant() (ufl.classes.FacetJacobian method), 88
 is_cellwise_constant() (ufl.classes.FacetJacobianDeterminant method), 89
 is_cellwise_constant() (ufl.classes.FacetJacobianInverse method), 90
 is_cellwise_constant() (ufl.classes.FacetNormal method), 90
 is_cellwise_constant() (ufl.classes.FiniteElementBase method), 106
 is_cellwise_constant() (ufl.classes.GeometricQuantity method), 86
 is_cellwise_constant() (ufl.classes.Jacobian method), 87
 is_cellwise_constant() (ufl.classes.JacobianDeterminant method), 89
 is_cellwise_constant() (ufl.classes.JacobianInverse method), 90
 is_cellwise_constant() (ufl.classes.Label method), 96
 is_cellwise_constant() (ufl.classes.MixedElement method), 108
 is_cellwise_constant() (ufl.classes.MultiIndex method), 93
 is_cellwise_constant() (ufl.classes.NodalEnrichedElement method), 109
 is_cellwise_constant() (ufl.classes.QuadratureWeight method), 92
 is_cellwise_constant() (ufl.classes.ReferenceCellEdgeVector method), 88
 is_cellwise_constant() (ufl.classes.ReferenceFacetEdgeVectors method), 88
 is_cellwise_constant() (ufl.classes.RestrictedElement method), 109
 is_cellwise_constant() (ufl.classes.SpatialCoordinate method), 86
 is_cellwise_constant() (ufl.Coefficient method), 165
 is_cellwise_constant() (ufl.coefficient.Coefficient method), 115
 is_cellwise_constant() (ufl.constantvalue.ConstantValue method), 119
 is_cellwise_constant() (ufl.EnrichedElement method), 162
 is_cellwise_constant() (ufl.FacetNormal method), 158
 is_cellwise_constant() (ufl.finiteelement.enrichedelement.EnrichedElement method), 74
 is_cellwise_constant() (ufl.finiteelement.enrichedelement.NodalEnrichedElement method), 75
 is_cellwise_constant() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 76
 is_cellwise_constant() (ufl.finiteelement.mixedelement.MixedElement method), 77
 is_cellwise_constant() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79
 is_cellwise_constant() (ufl.FiniteElementBase method), 160
 is_cellwise_constant() (ufl.geometry.CellCoordinate method), 128
 is_cellwise_constant() (ufl.geometry.CellEdgeVectors method), 128
 is_cellwise_constant() (ufl.geometry.CellFacetJacobian method), 129
 is_cellwise_constant() (ufl.geometry.CellFacetJacobianDeterminant method), 129
 is_cellwise_constant() (ufl.geometry.CellFacetJacobianInverse method), 129
 is_cellwise_constant() (ufl.geometry.CellOrigin method), 130
 is_cellwise_constant() (ufl.geometry.CellVertices method), 130
 is_cellwise_constant() (ufl.geometry.FacetCoordinate method), 131
 is_cellwise_constant() (ufl.geometry.FacetEdgeVectors method), 131
 is_cellwise_constant() (ufl.geometry.FacetJacobian method), 131
 is_cellwise_constant() (ufl.geometry.FacetJacobianDeterminant method), 131
 is_cellwise_constant() (ufl.geometry.FacetJacobianInverse method), 132
 is_cellwise_constant() (ufl.geometry.FacetNormal method), 132
 is_cellwise_constant() (ufl.geometry.GeometricQuantity method), 132

method), 132
is_cellwise_constant() (ufl.geometry.Jacobian method), 133
is_cellwise_constant() (ufl.geometry.JacobianDeterminant method), 133
is_cellwise_constant() (ufl.geometry.JacobianInverse method), 133
is_cellwise_constant() (ufl.geometry.QuadratureWeight method), 134
is_cellwise_constant() (ufl.geometry.ReferenceCellEdgeVectors method), 134
is_cellwise_constant() (ufl.geometry.ReferenceFacetEdgeVectors method), 134
is_cellwise_constant() (ufl.geometry.SpatialCoordinate method), 135
is_cellwise_constant() (ufl.Jacobian method), 159
is_cellwise_constant() (ufl.JacobianDeterminant method), 159
is_cellwise_constant() (ufl.JacobianInverse method), 159
is_cellwise_constant() (ufl.MixedElement method), 161
is_cellwise_constant() (ufl.NodalEnrichedElement method), 162
is_cellwise_constant() (ufl.RestrictedElement method), 162
is_cellwise_constant() (ufl.SpatialCoordinate method), 157
is_cellwise_constant() (ufl.variable.Label method), 151
is_globally_constant() (in module ufl.checks), 84
is_piecewise_linear_simplex_domain() (ufl.classes.Mesh method), 111
is_piecewise_linear_simplex_domain() (ufl.classes.MeshView method), 111
is_piecewise_linear_simplex_domain() (ufl.classes.TensorProductMesh method), 112
is_piecewise_linear_simplex_domain() (ufl.domain.Mesh method), 122
is_piecewise_linear_simplex_domain() (ufl.domain.MeshView method), 122
is_piecewise_linear_simplex_domain() (ufl.domain.TensorProductMesh method), 122
is_piecewise_linear_simplex_domain() (ufl.Mesh method), 156
is_piecewise_linear_simplex_domain() (ufl.MeshView method), 157
is_piecewise_linear_simplex_domain() (ufl.TensorProductMesh method), 157
is_post_handler() (in module ufl.algorithms.transformer), 69
is_python_scalar() (in module ufl.checks), 84
is_scalar_constant_expression() (in module ufl.checks), 84
is_simplex() (ufl.AbstractCell method), 155
is_simplex() (ufl.Cell method), 156
is_simplex() (ufl.cell.AbstractCell method), 83
is_simplex() (ufl.cell.Cell method), 83
is_simplex() (ufl.cell.TensorProductCell method), 83
is_simplex() (ufl.classes.AbstractCell method), 105
is_simplex() (ufl.classes.Cell method), 105
is_simplex() (ufl.classes.TensorProductCell method), 106
is_simplex() (ufl.TensorProductCell method), 156
is_true_ufl_scalar() (in module ufl.checks), 84
iter_expressions() (in module ufl.algorithms.traversal), 69

J

Jacobian (class in ufl), 159
Jacobian (class in ufl.classes), 87
Jacobian (class in ufl.geometry), 133
jacobian() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringAp method), 53
jacobian_determinant() (ufl.algorithms.apply_geometry_lowering.Geometry method), 53
jacobian_inverse() (ufl.algorithms.apply_derivatives.GradRuleset method), 50
jacobian_inverse() (ufl.algorithms.apply_geometry_lowering.GeometryLow method), 53
JacobianDeterminant (class in ufl), 159
JacobianDeterminant (class in ufl.classes), 89
JacobianDeterminant (class in ufl.geometry), 133
JacobianInverse (class in ufl), 159
JacobianInverse (class in ufl.classes), 90
JacobianInverse (class in ufl.geometry), 133
join_domains() (in module ufl.domain), 123
jump() (in module ufl), 170
jump() (in module ufl.operators), 144

L

Label (class in ufl.classes), 95
Label (class in ufl.variable), 151
label() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 49
label() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
label() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
label() (ufl.classes.Variable method), 96
label() (ufl.variable.Variable method), 151
LE (class in ufl.classes), 102
LE (class in ufl.conditional), 118
le() (in module ufl), 169
le() (in module ufl.operators), 144
lhs() (in module ufl), 174
lhs() (in module ufl.formoperators), 126
linear_indexed_type() (ufl.algorithms.check_arities.ArityChecker method), 56

linear_indexed_type() (ufl.algorithms.formtransformations.PartExtrapping) (ufl.finiteelement.brokenelement.BrokenElement method), 65
 linear_operator() (ufl.algorithms.check_arities.ArityCheckermapping) (ufl.finiteelement.enrichedelement.EnrichedElementBase method), 57
 linear_operator() (ufl.algorithms.formtransformations.PartExtrapping) (ufl.finiteelement.finiteelement.FiniteElement method), 65
 list_tensor() (ufl.algorithms.apply_derivatives.GenericDerivativeRulesetmapping) (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 50
 list_tensor() (ufl.algorithms.check_arities.ArityChecker mapping) (ufl.finiteelement.hdivcurl.HCurlElement method), 57
 list_tensor() (ufl.algorithms.estimate_degrees.SumDegreeEstimatormapping) (ufl.finiteelement.hdivcurl.HDivElement method), 61
 list_tensor() (ufl.algorithms.expand_indices.IndexExpander mapping) (ufl.finiteelement.mixedelement.MixedElement method), 63
 list_tensor() (ufl.algorithms.formtransformations.PartExtractormapping) (ufl.finiteelement.mixedelement.TensorElement method), 65
 ListTensor (class in ufl.classes), 94
 ListTensor (class in ufl.tensors), 149
 Ln (class in ufl.classes), 103
 Ln (class in ufl.mathfunctions), 139
 ln() (in module ufl), 168
 ln() (in module ufl.operators), 144
 ln() (ufl.algorithms.apply_derivatives.GenericDerivativeRulesetmapping) (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 load_forms() (in module ufl.algorithms.formfiles), 63
 load_ufl_file() (in module ufl.algorithms), 70
 load_ufl_file() (in module ufl.algorithms.formfiles), 63
 log() (ufl.log.Logger method), 137
 Logger (class in ufl.log), 137
 LowerCompoundAlgebra (class in ufl.algorithms.apply_algebra_lowering), 47
 LT (class in ufl.classes), 102
 LT (class in ufl.conditional), 118
 lt() (in module ufl), 169
 lt() (in module ufl.operators), 144

M

map_integrand_dags() (in module ufl.algorithms.map_integrands), 66
 map_integrands() (in module ufl.algorithms.map_integrands), 66
 mapping() (ufl.BrokenElement method), 164
 mapping() (ufl.classes.BrokenElement method), 111
 mapping() (ufl.classes.FiniteElement method), 107
 mapping() (ufl.classes.FiniteElementBase method), 107
 mapping() (ufl.classes.HCurlElement method), 110
 mapping() (ufl.classes.HDivElement method), 110
 mapping() (ufl.classes.MixedElement method), 108
 mapping() (ufl.classes.RestrictedElement method), 109
 mapping() (ufl.classes.TensorElement method), 108
 mapping() (ufl.classes.TensorProductElement method), 110
 mapping() (ufl.FiniteElement method), 160

module
 max_cell_edge_length() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApp method), 53
 max_facet_edge_length() (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApp method), 53
 max_facet_edge_length() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
 max_subdomain_ids() (ufl.classes.Form method), 115
 max_subdomain_ids() (ufl.Form method), 171
 max_subdomain_ids() (ufl.form.Form method), 125
 max_value() (in module ufl), 169
 max_value() (in module ufl.operators), 144
 max_value() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 max_value() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 MaxCellEdgeLength (class in ufl), 158
 MaxCellEdgeLength (class in ufl.classes), 92

MaxCellEdgeLength (class in ufl.geometry), 133
MaxFacetEdgeLength (class in ufl), 158
MaxFacetEdgeLength (class in ufl.classes), 92
MaxFacetEdgeLength (class in ufl.geometry), 133
MaxValue (class in ufl.classes), 103
MaxValue (class in ufl.conditional), 118
Measure (class in ufl), 172
Measure (class in ufl.classes), 113
Measure (class in ufl.measure), 139
measure_collisions() (in module ufl.exprequals), 124
measure_names() (in module ufl.measure), 141
MeasureProduct (class in ufl.classes), 113
MeasureProduct (class in ufl.measure), 140
MeasureSum (class in ufl.classes), 113
MeasureSum (class in ufl.measure), 140
merge_nonoverlapping_indices() (in ufl.index_combination_utils), 135
merge_overlapping_indices() (in ufl.index_combination_utils), 135
merge_unique_indices() (in ufl.index_combination_utils), 135
Mesh (class in ufl), 156
Mesh (class in ufl.classes), 111
Mesh (class in ufl.domain), 122
MeshView (class in ufl), 157
MeshView (class in ufl.classes), 111
MeshView (class in ufl.domain), 122
metadata (ufl.algorithms.domain_analysis.IntegralData attribute), 58
metadata() (ufl.classes.Integral method), 114
metadata() (ufl.classes.Measure method), 113
metadata() (ufl.Integral method), 172
metadata() (ufl.integral.Integral method), 136
metadata() (ufl.Measure method), 172
metadata() (ufl.measure.Measure method), 140
metadata_equal() (in module ufl.protocols), 146
metadata_hashdata() (in module ufl.protocols), 146
Min() (in module ufl), 169
Min() (in module ufl.operators), 141
min_cell_edge_length() (ufl.algorithms.apply_geometry method), 53
min_facet_edge_length()
 (ufl.algorithms.apply_geometry_lowering.GeometryLoweringApplier method), 53
min_facet_edge_length()
 (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
min_value() (in module ufl), 169
min_value() (in module ufl.operators), 144
min_value() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
min_value() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
MinCellEdgeLength (class in ufl), 158
MinCellEdgeLength (class in ufl.classes), 91
MinCellEdgeLength (class in ufl.geometry), 133
MinFacetEdgeLength (class in ufl), 158
MinFacetEdgeLength (class in ufl.classes), 92
MinFacetEdgeLength (class in ufl.geometry), 133
MinValue (class in ufl.classes), 102
MinValue (class in ufl.conditional), 118
MixedElement (class in ufl), 160
MixedElement (class in ufl.classes), 107
MixedElement (class in ufl.finiteelement.mixedelement), 77
MixedFunctionSpace (class in ufl.classes), 112
MixedFunctionSpace (class in ufl.functionspace), 128
multi_index() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
module multi_index() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 54
module multi_index() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
module multi_index() (ufl.algorithms.expand_indices.IndexExpander method), 63
multi_index() (ufl.algorithms.FormSplitter method), 72
multi_index() (ufl.algorithms.formsplitter.FormSplitter method), 64
multi_index() (ufl.algorithms.renumbering.IndexRenumberingTransformer method), 67
MultiFunction (class in ufl.algorithms), 71
MultiIndex (class in ufl.classes), 92

N

nabla_div() (in module ufl), 170
nabla_div() (in module ufl.operators), 144
nabla_div() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
nabla_div() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
nabla_grad() (in module ufl), 170
nabla_grad() (in module ufl.operators), 144
nabla_grad() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
nabla_grad() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
NablaLoweringApplier (ufl.classes), 101
NablaDiv (class in ufl.differentiation), 121
NablaGrad (class in ufl.classes), 101
NablaGrad (class in ufl.differentiation), 121
name (ufl.CellDiameter attribute), 158
name (ufl.CellNormal attribute), 158
name (ufl.CellVolume attribute), 157
NameRules (ufl.Circumradius attribute), 158
name (ufl.classes.CellCoordinate attribute), 86
NameRules (ufl.classes.CellDiameter attribute), 91
name (ufl.classes.CellEdgeVectors attribute), 89
name (ufl.classes.CellFacetJacobian attribute), 88

name (`ufl.classes.CellFacetJacobianDeterminant` attribute), 90
 name (`ufl.classes.CellFacetJacobianInverse` attribute), 90
 name (`ufl.classes.CellFacetOrigin` attribute), 87
 name (`ufl.classes.CellNormal` attribute), 91
 name (`ufl.classes.CellOrientation` attribute), 92
 name (`ufl.classes.CellOrigin` attribute), 87
 name (`ufl.classes.CellVertices` attribute), 89
 name (`ufl.classes.CellVolume` attribute), 91
 name (`ufl.classes.Circumradius` attribute), 91
 name (`ufl.classes.FacetArea` attribute), 91
 name (`ufl.classes.FacetCoordinate` attribute), 87
 name (`ufl.classes.FacetEdgeVectors` attribute), 89
 name (`ufl.classes.FacetJacobian` attribute), 88
 name (`ufl.classes.FacetJacobianDeterminant` attribute), 90
 name (`ufl.classes.FacetJacobianInverse` attribute), 90
 name (`ufl.classes.FacetNormal` attribute), 90
 name (`ufl.classes.FacetOrientation` attribute), 92
 name (`ufl.classes.FacetOrigin` attribute), 87
 name (`ufl.classes.Jacobian` attribute), 87
 name (`ufl.classes.JacobianDeterminant` attribute), 89
 name (`ufl.classes.JacobianInverse` attribute), 90
 name (`ufl.classes.MaxCellEdgeLength` attribute), 92
 name (`ufl.classes.MaxFacetEdgeLength` attribute), 92
 name (`ufl.classes.MinCellEdgeLength` attribute), 92
 name (`ufl.classes.MinFacetEdgeLength` attribute), 92
 name (`ufl.classes.QuadratureWeight` attribute), 92
 name (`ufl.classes.ReferenceCellEdgeVectors` attribute), 88
 name (`ufl.classes.ReferenceCellVolume` attribute), 91
 name (`ufl.classes.ReferenceFacetEdgeVectors` attribute), 88
 name (`ufl.classes.ReferenceFacetVolume` attribute), 91
 name (`ufl.classes.ReferenceNormal` attribute), 91
 name (`ufl.classes.SpatialCoordinate` attribute), 86
 name (`ufl.FacetArea` attribute), 158
 name (`ufl.FacetNormal` attribute), 158
 name (`ufl.geometry.CellCoordinate` attribute), 128
 name (`ufl.geometry.CellDiameter` attribute), 128
 name (`ufl.geometry.CellEdgeVectors` attribute), 129
 name (`ufl.geometry.CellFacetJacobian` attribute), 129
 name (`ufl.geometry.CellFacetJacobianDeterminant` attribute), 129
 name (`ufl.geometry.CellFacetJacobianInverse` attribute), 129
 name (`ufl.geometry.CellFacetOrigin` attribute), 129
 name (`ufl.geometry.CellNormal` attribute), 130
 name (`ufl.geometry.CellOrientation` attribute), 130
 name (`ufl.geometry.CellOrigin` attribute), 130
 name (`ufl.geometry.CellVertices` attribute), 130
 name (`ufl.geometry.CellVolume` attribute), 130
 name (`ufl.geometry.Circumradius` attribute), 130
 name (`ufl.geometry.FacetArea` attribute), 131
 name (`ufl.geometry.FacetCoordinate` attribute), 131
 at-
 name (`ufl.geometry.FacetEdgeVectors` attribute), 131
 name (`ufl.geometry.FacetJacobian` attribute), 131
 name (`ufl.geometry.FacetJacobianDeterminant` attribute), 132
 name (`ufl.geometry.FacetJacobianInverse` attribute), 132
 name (`ufl.geometry.FacetNormal` attribute), 132
 name (`ufl.geometry.FacetOrientation` attribute), 132
 name (`ufl.geometry.FacetOrigin` attribute), 132
 name (`ufl.geometry.Jacobian` attribute), 133
 name (`ufl.geometry.JacobianDeterminant` attribute), 133
 name (`ufl.geometry.JacobianInverse` attribute), 133
 name (`ufl.geometry.MaxCellEdgeLength` attribute), 133
 name (`ufl.geometry.MaxFacetEdgeLength` attribute), 133
 name (`ufl.geometry.MinCellEdgeLength` attribute), 133
 name (`ufl.geometry.MinFacetEdgeLength` attribute), 134
 name (`ufl.geometry.QuadratureWeight` attribute), 134
 name (`ufl.geometry.ReferenceCellEdgeVectors` attribute), 134
 name (`ufl.geometry.ReferenceCellVolume` attribute), 134
 name (`ufl.geometry.ReferenceFacetEdgeVectors` attribute), 134
 name (`ufl.geometry.ReferenceFacetVolume` attribute), 134
 name (`ufl.geometry.ReferenceNormal` attribute), 134
 name (`ufl.geometry.SpatialCoordinate` attribute), 135
 name (`ufl.Jacobian` attribute), 159
 name (`ufl.JacobianDeterminant` attribute), 159
 name (`ufl.JacobianInverse` attribute), 159
 name (`ufl.MaxCellEdgeLength` attribute), 158
 name (`ufl.MaxFacetEdgeLength` attribute), 158
 name (`ufl.MinCellEdgeLength` attribute), 158
 name (`ufl.MinFacetEdgeLength` attribute), 158
 name (`ufl.SpatialCoordinate` attribute), 157
 NE (class in `ufl.classes`), 102
 NE (class in `ufl.conditional`), 118
 ne() (in module `ufl`), 169
 ne() (in module `ufl.operators`), 144
 negative_restricted() (`ufl.algorithms.check_arities.ArityChecker` method), 57
 negative_restricted() (`ufl.algorithms.estimate_degrees.SumDegreeEstimator` method), 61
 negative_restricted() (`ufl.algorithms.formtransformations.PartExtractor` method), 65
 NegativeRestricted (class in `ufl.classes`), 99
 NegativeRestricted (class in `ufl.restriction`), 146
 NEWChangeToReferenceGrad (class in `ufl.algorithms.change_to_reference`), 55
 NodalEnrichedElement (class in `ufl`), 162
 NodalEnrichedElement (class in `ufl.classes`), 109
 NodalEnrichedElement (class in `ufl.finiteelement.enrichedelement`), 74
 non_differentiable_terminal() (`ufl.algorithms.apply_derivatives.GenericDerivativeRuleset` method), 50

nonlinear_operator() (ufl.algorithms.check_arities.ArityChecker method), 57
nonrecursive_expr_equals() (in module ufl.exprquals), 124
Not() (in module ufl), 169
Not() (in module ufl.operators), 141
not_condition() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
NotCondition (class in ufl.classes), 102
NotCondition (class in ufl.conditional), 118
num_edges() (ufl.Cell method), 156
num_edges() (ufl.cell.Cell method), 83
num_edges() (ufl.cell.TensorProductCell method), 83
num_edges() (ufl.classes.Cell method), 105
num_edges() (ufl.classes.TensorProductCell method), 106
num_edges() (ufl.TensorProductCell method), 156
num_facet_edges() (ufl.Cell method), 156
num_facet_edges() (ufl.cell.Cell method), 83
num_facet_edges() (ufl.classes.Cell method), 105
num_facets() (ufl.Cell method), 156
num_facets() (ufl.cell.Cell method), 83
num_facets() (ufl.cell.TensorProductCell method), 83
num_facets() (ufl.classes.Cell method), 105
num_facets() (ufl.classes.TensorProductCell method), 106
num_facets() (ufl.TensorProductCell method), 156
num_restricted_sub_elements()
 (ufl.classes.RestrictedElement method), 109
num_restricted_sub_elements()
 (ufl.finiteelement.restrictedelement.RestrictedElement method), 79
num_restricted_sub_elements() (ufl.RestrictedElement method), 162
num_sub_elements() (ufl.classes.FiniteElementBase method), 107
num_sub_elements() (ufl.classes.MixedElement method), 108
num_sub_elements() (ufl.classes.RestrictedElement method), 109
num_sub_elements() (ufl.classes.TensorProductElement method), 110
num_sub_elements() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 76
num_sub_elements() (ufl.finiteelement.mixedelement.MixedElement method), 78
num_sub_elements() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79
num_sub_elements() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 79
num_sub_elements() (ufl.FiniteElementBase method), 160
num_sub_elements() (ufl.MixedElement method), 161
num_sub_elements() (ufl.RestrictedElement method),

162
num_sub_elements() (ufl.TensorProductElement method), 163
num_vertices() (ufl.Cell method), 156
num_vertices() (ufl.cell.Cell method), 83
num_vertices() (ufl.cell.TensorProductCell method), 83
DerivativeRuleset (ufl.classes.Cell method), 106
num_vertices() (ufl.classes.TensorProductCell method), 106
num_vertices() (ufl.TensorProductCell method), 156
number() (ufl.Argument method), 164
number() (ufl.argument.Argument method), 81
number() (ufl.classes.Argument method), 95
numpy2nestedlists() (in module ufl.tensors), 150

O

old_determinant_expr_3x3() (in module ufl.compound_expressions), 117
OLDChangeToReferenceGrad (class in ufl.algorithms.change_to_reference), 56
Operator (class in ufl.classes), 92
operator() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
operator() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55
Or() (in module ufl), 169
Or() (in module ufl.operators), 141
OrCondition (class in ufl.classes), 102
OrCondition (class in ufl.conditional), 118
Outer (class in ufl.classes), 97
Outer (class in ufl.tensoralgebra), 148
outer() (in module ufl), 167
outer() (in module ufl.operators), 144
outer() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
outer() (ufl.algorithms.check_arities.ArityChecker method), 57
outer() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
outer() (ufl.algorithms.formtransformations.PartExtractor method), 65
override() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50

P

parstr() (in module ufl.precedence), 146
part() (ufl.Argument method), 165
part() (ufl.argument.Argument method), 81
part() (ufl.classes.Argument method), 95
PartExtractor (class in ufl.algorithms.formtransformations), 64
PermutationSymbol (class in ufl), 166
PermutationSymbol (class in ufl.classes), 94
PermutationSymbol (class in ufl.constantvalue), 119

perp() (in module ufl), 167

perp() (in module ufl.operators), 144

pop_level() (ufl.log.Logger method), 137

positive_restricted() (ufl.algorithms.check_arities.ArityChecker method), 57

positive_restricted() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

positive_restricted() (ufl.algorithms.formtransformations.PartExtractor method), 65

PositiveRestricted (class in ufl.classes), 99

PositiveRestricted (class in ufl.restriction), 146

post_traversal() (in module ufl.algorithms), 72

Power (class in ufl.algebra), 80

Power (class in ufl.classes), 97

power() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50

power() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

print_collisions() (in module ufl.exprequals), 124

print_visit_stack() (ufl.algorithms.Transformer method), 70

print_visit_stack() (ufl.algorithms.transformer.Transformer method), 68

Product (class in ufl.algebra), 80

Product (class in ufl.classes), 96

product() (in module ufl), 155

product() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50

product() (ufl.algorithms.check_arities.ArityChecker method), 57

product() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61

product() (ufl.algorithms.formtransformations.PartExtractor method), 65

pseudo_determinant_expr() (in module ufl.compound_expressions), 117

pseudo_inverse_expr() (in module ufl.compound_expressions), 117

purge_list_tensors() (in module ufl.algorithms), 70

purge_list_tensors() (in module ufl.algorithms.expand_indices), 63

push_level() (ufl.log.Logger method), 137

Q

quadrature_scheme() (ufl.classes.FiniteElementBase method), 107

quadrature_scheme() (ufl.finiteelement.finiteelementbase.FiniteElementBases), 79

quadrature_scheme() (ufl.FiniteElementBase method), 160

quadrature_weight() (ufl.algorithms.apply_restrictions.RestrictionProperties method), 55

QuadratureWeight (class in ufl.classes), 92

QuadratureWeight (class in ufl.geometry), 134

R

rank() (in module ufl), 167

rank() (in module ufl.operators), 144

read_lines_decoded() (in module ufl.algorithms.formfiles), 63

read_ufl_file() (in module ufl.algorithms.formfiles), 63

rearrange_integrals_by_single_subdomains() (in module ufl.algorithms.domain_analysis), 59

reconstruct() (ufl.BrokenElement method), 164

reconstruct() (ufl.Cell method), 156

reconstruct() (ufl.cell.Cell method), 83

reconstruct() (ufl.cell.TensorProductCell method), 83

reconstruct() (ufl.classes.BrokenElement method), 111

reconstruct() (ufl.classes.Cell method), 106

reconstruct() (ufl.classes.FiniteElement method), 107

reconstruct() (ufl.classes.HCurlElement method), 110

reconstruct() (ufl.classes.HDivElement method), 110

reconstruct() (ufl.classes.Integral method), 114

reconstruct() (ufl.classes.Measure method), 113

reconstruct() (ufl.classes.MixedElement method), 108

reconstruct() (ufl.classes.RestrictedElement method), 109

reconstruct() (ufl.classes.TensorElement method), 108

reconstruct() (ufl.classes.TensorProductCell method), 106

reconstruct() (ufl.classes.TensorProductElement method), 110

reconstruct() (ufl.classes.VectorElement method), 108

reconstruct() (ufl.FiniteElement method), 160

reconstruct() (ufl.finiteelement.brokenelement.BrokenElement method), 73

reconstruct() (ufl.finiteelement.enrichedelement.EnrichedElementBase method), 74

reconstruct() (ufl.finiteelement.finiteelement.FiniteElement method), 75

reconstruct() (ufl.finiteelement.hdivcurl.HCurlElement method), 76

reconstruct() (ufl.finiteelement.hdivcurl.HDivElement method), 77

reconstruct() (ufl.finiteelement.mixedelement.MixedElement method), 78

reconstruct() (ufl.finiteelement.mixedelement.TensorElement method), 78

reconstruct() (ufl.finiteelement.mixedelement.VectorElement method), 78

reconstruct() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79

reconstruct() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 79

reconstruct() (ufl.HCurlElement method), 164

reconstruct() (ufl.HDivElement method), 163

reconstruct() (ufl.Integral method), 172

reconstruct() (ufl.Measure method), 173

reconstruct() (ufl.measure.Measure method), 140

reconstruct() (ufl.MixedElement method), 161

reconstruct() (ufl.RestrictedElement method), 163
 reconstruct() (ufl.TensorElement method), 162
 reconstruct() (ufl.TensorProductCell method), 156
 reconstruct() (ufl.TensorProductElement method), 163
 reconstruct() (ufl.VectorElement method), 161
 reconstruct_form_from_integral_data() (in module ufl.algorithms.domain_analysis), 59
 reconstruct_from_elements() (ufl.classes.MixedElement method), 108
 reconstruct_from_elements() (ufl.finiteelement.mixedelement.MixedElement method), 78
 reconstruct_from_elements() (ufl.MixedElement method), 161
 reconstruct_variable() (ufl.algorithms.Transformer method), 70
 reconstruct_variable() (ufl.algorithms.transformer.Transformer method), 68
 recursive_expr_equals() (in module ufl.exprquals), 124
 reference_cell_volume() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55
 reference_curl() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 reference_div() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 61
 reference_facet_volume()
 (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55
 reference_grad() (ufl.algorithms.apply_derivatives.DerivativeRuleset method), 48
 reference_grad() (ufl.algorithms.apply_derivatives.GateauxGradRule method), 48
 reference_grad() (ufl.algorithms.apply_derivatives.GradRule method), 51
 reference_grad() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51
 reference_grad() (ufl.algorithms.apply_derivatives.VariableGradRule method), 51
 reference_grad() (ufl.algorithms.change_to_reference.NEWChangeToReference module ufl.finiteelement.elementlist), 55
 reference_grad() (ufl.algorithms.change_to_reference.OLDChangeToReference(Grad module ufl), 164
 method), 56
 reference_grad() (ufl.algorithms.check_arities.ArityChecker method), 57
 reference_grad() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 reference_value() (ufl.algorithms.apply_derivatives.GateauxDerivativeRuleset type() (in module ufl.measure), 141
 method), 48
 reference_value() (ufl.algorithms.apply_derivatives.GradRuleset type() (in module ufl.measure), 141
 method), 51
 reference_value() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset type() (in module ufl.referencevalue), 146
 method), 51
 reference_value() (ufl.algorithms.change_to_reference.NEWChangeToReference module ufl.finiteelement.elementlist), 74
 register_element() (in module ufl.finiteelement.elementlist), 74
 register_element2() (in module ufl.finiteelement.elementlist), 74
 register_integral_type() (in module ufl), 173
 register_integral_type() (in module ufl.measure), 141
 relabel() (in module ufl), 167
 relabel() (in module ufl.tensors), 150
 remove_indices() (in module ufl), 150
 reindex_combination_utils() (in module ufl.referencevalue), 135
 renumber_indices() (in module ufl), 150
 replace() (in module ufl), 173

replace() (in module ufl.algorithms), 71
 replace() (in module ufl.algorithms.replace), 67
 replace_include_statements() (in module ufl.algorithms.formfiles), 63
 replace_integral_domains() (in module ufl), 173
 replace_integral_domains() (in module ufl.form), 125
 Replacer (class in ufl.algorithms.replace), 67
 reshape_to_nested_list() (in module ufl.algorithms.apply_function_pullbacks), 52
 Restricted (class in ufl.classes), 99
 Restricted (class in ufl.restriction), 146
 restricted() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 restricted() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
 restricted() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55
 restricted() (ufl.algorithms.change_to_reference.NEWChangeToReferenceGrad method), 55
 restricted() (ufl.algorithms.check_restrictions.RestrictionChecker method), 57
 restricted_sub_elements() (ufl.classes.RestrictedElement method), 109
 restricted_sub_elements() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79
 restricted_sub_elements() (ufl.RestrictedElement method), 163
 RestrictedElement (class in ufl), 162
 RestrictedElement (class in ufl.classes), 109
 RestrictedElement (class in ufl.finiteelement.restrictedelement.RestrictedElement method), 78
 restriction_domain() (ufl.classes.RestrictedElement method), 109
 restriction_domain() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79
 restriction_domain() (ufl.RestrictedElement method), 163
 RestrictionChecker (class in ufl.algorithms.check_restrictions), 57
 RestrictionPropagator (class in ufl.algorithms.apply_restrictions), 54
 reuse() (ufl.algorithms.Transformer method), 70
 reuse() (ufl.algorithms.transformer.Transformer method), 68
 reuse_if_possible() (ufl.algorithms.Transformer method), 70
 reuse_if_possible() (ufl.algorithms.transformer.Transformer method), 68
 reuse_if_unouched() (ufl.algorithms.MultiFunction method), 71
 reuse_if_unouched() (ufl.algorithms.Transformer method), 71
 reuse_if_unouched() (ufl.algorithms.transformer.Transformer method), 71

method), 68
 reuse_variable() (ufl.algorithms.Transformer method), 71
 reuse_variable() (ufl.algorithms.transformer.Transformer method), 69
 ReuseTransformer (class in ufl.algorithms), 70
 ReuseTransformer (class in ufl.algorithms.transformer), 68
 rhs() (in module ufl), 174
 rhs() (in module ufl.formoperators), 126
 rot() (in module ufl), 170
 rot() (in module ufl.operators), 144

S

scalar_value() (ufl.algorithms.expand_indices.IndexExpander method), 63
 ScalarValue (class in ufl.classes), 93
 ScalarValue (class in ufl.constantvalue), 119
 sensitivity_rhs() (in module ufl), 174
 sensitivity_rhs() (in module ufl.formoperators), 126
 set_handler() (ufl.log.Logger method), 137
 set_indent() (ufl.log.Logger method), 137
 set_level() (ufl.log.Logger method), 138
 set_list_item() (in module ufl.formoperators), 127
 set_prefix() (ufl.log.Logger method), 138
 shape() (in module ufl), 167
 shape() (in module ufl.operators), 144
 shortstr() (ufl.BrokenElement method), 164
 shortstr() (ufl.classes.BrokenElement method), 111
 shortstr() (ufl.classes.EnrichedElement method), 109
 shortstr() (ufl.classes.FiniteElement method), 107
 shortstr() (ufl.classes.HCurlElement method), 110
 shortstr() (ufl.classes.HDivElement method), 110
 shortstr() (ufl.classes.MixedElement method), 108
 shortstr() (ufl.classes.NodalEnrichedElement method), 109
 shortstr() (ufl.classes.RestrictedElement method), 109
 shortstr() (ufl.classes.TensorElement method), 108
 shortstr() (ufl.classes.TensorProductElement method), 110
 shortstr() (ufl.classes.VectorElement method), 108
 shortstr() (ufl.EnrichedElement method), 162
 shortstr() (ufl.FiniteElement method), 160
 shortstr() (ufl.finiteelement.brokenelement.BrokenElement method), 73
 shortstr() (ufl.finiteelement.enrichedelement.EnrichedElement method), 74
 shortstr() (ufl.finiteelement.enrichedelement.NodalEnrichedElement method), 75
 shortstr() (ufl.finiteelement.finiteelement.FiniteElement method), 75
 shortstr() (ufl.finiteelement.hdivcurl.HCurlElement method), 77
 shortstr() (ufl.finiteelement.hdivcurl.HDivElement method), 77

shortstr() (ufl.finiteelement.mixedelement.MixedElement method), 78
shortstr() (ufl.finiteelement.mixedelement.TensorElement method), 78
shortstr() (ufl.finiteelement.mixedelement.VectorElement method), 78
shortstr() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79
shortstr() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 79
shortstr() (ufl.HCurlElement method), 164
shortstr() (ufl.HDivElement method), 163
shortstr() (ufl.MixedElement method), 161
shortstr() (ufl.NodalEnrichedElement method), 162
shortstr() (ufl.RestrictedElement method), 163
shortstr() (ufl.TensorElement method), 162
shortstr() (ufl.TensorProductElement method), 163
shortstr() (ufl.VectorElement method), 161
show_elements() (in module ufl), 164
show_elements() (in module ufl.finiteelement.elementlist), 74
side() (ufl.classes.Restricted method), 99
side() (ufl.restriction.Restricted method), 146
sign() (in module ufl), 169
sign() (in module ufl.operators), 144
signature() (ufl.classes.Form method), 115
signature() (ufl.Form method), 171
signature() (ufl.form.Form method), 125
simplex() (in module ufl.cell), 84
Sin (class in ufl.classes), 103
Sin (class in ufl.mathfunctions), 139
sin() (in module ufl), 168
sin() (in module ufl.operators), 145
sin() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
Sinh (class in ufl.classes), 103
Sinh (class in ufl.mathfunctions), 139
sinh() (in module ufl), 168
sinh() (in module ufl.operators), 145
sinh() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
Skew (class in ufl.classes), 98
Skew (class in ufl.tensoralgebra), 148
skew() (in module ufl), 168
skew() (in module ufl.operators), 145
skew() (ufl.algorithms.apply_algebra_lowering.LowerComputationAlgorithms method), 47
skew() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
sobolev_space() (ufl.classes.FiniteElement method), 107
sobolev_space() (ufl.classes.HCurlElement method), 110
sobolev_space() (ufl.classes.HDivElement method), 110
sobolev_space() (ufl.classes.TensorProductElement method), 110
sobolev_space() (ufl.FiniteElement method), 160
sobolev_space() (ufl.finiteelement.enrichedelement.EnrichedElementBase method), 74
sobolev_space() (ufl.finiteelement.finiteelement.FiniteElement method), 75
sobolev_space() (ufl.finiteelement.hdivcurl.HCurlElement method), 77
sobolev_space() (ufl.finiteelement.hdivcurl.HDivElement method), 77
sobolev_space() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 80
sobolev_space() (ufl.HCurlElement method), 164
sobolev_space() (ufl.HDivElement method), 163
sobolev_space() (ufl.TensorProductElement method), 163
SobolevSpace (class in ufl.sobolevspacespace), 147
sort_domains() (in module ufl.domain), 123
sort_elements() (in module ufl.algorithms), 69
sort_elements() (in module ufl.algorithms.analysis), 47
sorted_expr() (in module ufl.sorting), 147
sorted_expr_sum() (in module ufl.sorting), 147
spatial_coordinate() (ufl.algorithms.apply_derivatives.GradRuleset method), 51
spatial_coordinate() (ufl.algorithms.apply_derivatives.ReferenceGradRuleset method), 51
spatial_coordinate() (ufl.algorithms.apply_geometry_lowering.GeometryLowering method), 53
spatial_coordinate() (ufl.algorithms.apply_restrictions.DefaultRestrictionApplier method), 54
spatial_coordinate() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
SpatialCoordinate (class in ufl), 157
SpatialCoordinate (class in ufl.classes), 86
SpatialCoordinate (class in ufl.geometry), 135
split() (in module ufl.split_functions), 147
split() (ufl.algorithms.FormSplitter method), 72
split() (ufl.algorithms.forms splitter.FormSplitter method), 64
Sqrt (class in ufl.classes), 103
Sqrt (class in ufl.mathfunctions), 139
sqrt() (in module ufl), 168
sqrt() (in module ufl.operators), 145
sqrt() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
strip_variables() (in module ufl.algorithms), 72
strip_Algorithms() (in module ufl.algorithms.transformer), 69
sub_cells() (ufl.cell.TensorProductCell method), 83
sub_cells() (ufl.classes.TensorProductCell method), 106
sub_cells() (ufl.TensorProductCell method), 156
sub_element() (ufl.classes.RestrictedElement method), 110
sub_element() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79

sub_element() (ufl.RestrictedElement method), 163
 sub_elements() (ufl.classes.FiniteElementBase method), 107
 sub_elements() (ufl.classes.MixedElement method), 108
 sub_elements() (ufl.classes.RestrictedElement method), 110
 sub_elements() (ufl.classes.TensorProductElement method), 110
 sub_elements() (ufl.finiteelement.finiteelementbase.FiniteElement method), 76
 sub_elements() (ufl.finiteelement.mixedelement.MixedElement method), 78
 sub_elements() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79
 sub_elements() (ufl.finiteelement.tensorproductelement.TensorProductElement method), 80
 sub_elements() (ufl.FiniteElementBase method), 160
 sub_elements() (ufl.MixedElement method), 161
 sub_elements() (ufl.RestrictedElement method), 163
 sub_elements() (ufl.TensorProductElement method), 163
 sub_elements_with_mappings() (in module ufl.algorithms.apply_function_pullbacks), 52
 sub_measures() (ufl.classes.MeasureProduct method), 114
 sub_measures() (ufl.measure.MeasureProduct method), 140
 subdomain_data() (ufl.classes.Form method), 115
 subdomain_data() (ufl.classes.Integral method), 114
 subdomain_data() (ufl.classes.Measure method), 113
 subdomain_data() (ufl.Form method), 171
 subdomain_data() (ufl.form.Form method), 125
 subdomain_data() (ufl.Integral method), 172
 subdomain_data() (ufl.integral.Integral method), 136
 subdomain_data() (ufl.Measure method), 173
 subdomain_data() (ufl.measure.Measure method), 140
 subdomain_id (ufl.algorithms.domain_analysis.IntegralData attribute), 58
 subdomain_id() (ufl.classes.Integral method), 114
 subdomain_id() (ufl.classes.Measure method), 113
 subdomain_id() (ufl.Integral method), 172
 subdomain_id() (ufl.integral.Integral method), 136
 subdomain_id() (ufl.Measure method), 173
 subdomain_id() (ufl.measure.Measure method), 140
 Sum (class in ufl.algebra), 81
 Sum (class in ufl.classes), 96
 sum() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 sum() (ufl.algorithms.check_arities.ArityChecker method), 57
 sum() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 sum() (ufl.algorithms.formtransformations.PartExtractor method), 65
 SumDegreeEstimator (class in ufl.algorithms.estimate_degrees), 59
 Sym (class in ufl.classes), 99
 Sym (class in ufl.tensoralgebra), 149
 sym() (in module ufl), 168
 sym() (in module ufl.operators), 145
 sym() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
 Symmetry (ufl.classes.FiniteElementBase method), 62
 symmetry() (ufl.classes.FiniteElementBase method), 107
 symmetry() (ufl.classes.MixedElement method), 108
 symmetry() (ufl.classes.RestrictedElement method), 110
 symmetry() (ufl.classes.TensorElement method), 108
 SymmetryElement (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 76
 symmetry() (ufl.finiteelement.mixedelement.MixedElement method), 78
 symmetry() (ufl.finiteelement.mixedelement.TensorElement method), 78
 symmetry() (ufl.finiteelement.restrictedelement.RestrictedElement method), 79
 symmetry() (ufl.FiniteElementBase method), 160
 symmetry() (ufl.MixedElement method), 161
 symmetry() (ufl.RestrictedElement method), 163
 symmetry() (ufl.TensorElement method), 162
 system() (in module ufl), 174
 system() (in module ufl.formoperators), 127

T

T (ufl.classes.Expr attribute), 85
 Tan (class in ufl.classes), 103
 Tan (class in ufl.mathfunctions), 139
 tan() (in module ufl), 168
 tan() (in module ufl.operators), 145
 tan() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 Tanh (class in ufl.classes), 104
 Tanh (class in ufl.mathfunctions), 139
 tanh() (in module ufl), 168
 tanh() (in module ufl.operators), 145
 tanh() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 tear() (in module ufl.algorithms.elementtransformations), 59
 TensorConstant() (in module ufl), 166
 TensorConstant() (in module ufl.coefficient), 116
 TensorElement (class in ufl), 161
 TensorElement (class in ufl.classes), 108
 TensorElement (class in ufl.finiteelement.mixedelement), 78
 TensorProductCell (class in ufl), 156
 TensorProductCell (class in ufl.cell), 83
 TensorProductCell (class in ufl.classes), 106

TensorProductElement (class in ufl), 163
 TensorProductElement (class in ufl.classes), 110
 TensorProductElement (class in ufl.finiteelement.tensorproductelement), 79
 TensorProductFunctionSpace (class in ufl.classes), 112
 TensorProductFunctionSpace (class in ufl.functionspace), 128
 TensorProductMesh (class in ufl), 157
 TensorProductMesh (class in ufl.classes), 111
 TensorProductMesh (class in ufl.domain), 122
 Terminal (class in ufl.classes), 85
 terminal() (ufl.algorithms.apply_derivatives.DerivativeRule method), 48
 terminal() (ufl.algorithms.apply_function_pullbacks.Function method), 52
 terminal() (ufl.algorithms.apply_geometry_lowering.Geometry method), 53
 terminal() (ufl.algorithms.apply_restrictions.DefaultRestriction method), 54
 terminal() (ufl.algorithms.apply_restrictions.RestrictionProp method), 55
 terminal() (ufl.algorithms.change_to_reference.NEWChangeToReference method), 55
 terminal() (ufl.algorithms.change_to_reference.OLDChangeToReference method), 56
 terminal() (ufl.algorithms.check_arities.ArityChecker method), 57
 terminal() (ufl.algorithms.expand_indices.IndexExpander method), 63
 terminal() (ufl.algorithms.formtransformations.PartExtractor method), 65
 terminal() (ufl.algorithms.replace.Replacer method), 67
 terminal() (ufl.algorithms.ReuseTransformer method), 70
 terminal() (ufl.algorithms.Transformer method), 71
 terminal() (ufl.algorithms.transformer.CopyTransformer method), 68
 terminal() (ufl.algorithms.transformer.ReuseTransformer method), 68
 terminal() (ufl.algorithms.transformer.Transformer method), 69
 TestFunction() (in module ufl), 165
 TestFunction() (in module ufl.argument), 81
 TestFunction() (in module ufl.classes), 113
 TestFunctions() (in module ufl), 165
 TestFunctions() (in module ufl.argument), 81
 TestFunctions() (in module ufl.classes), 113
 topological_dimension() (ufl.AbstractCell method), 155
 topological_dimension() (ufl.AbstractDomain method), 156
 topological_dimension() (ufl.cell.AbstractCell method), 83
 topological_dimension() (ufl.classes.AbstractCell method), 105
 topological_dimension() (ufl.classes.AbstractDomain method), 111
 topological_dimension() (ufl.domain.AbstractDomain method), 122
 tr() (in module ufl), 167
 tr() (in module ufl.operators), 145
 Trace (class in ufl.classes), 98
 Trace (class in ufl.tensoralgebra), 149
 trace() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 47
 trace() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 Disambiguifier (class in ufl.algorithms), 70
 Transformer (class in ufl.algorithms.transformer), 68
 PushForward (Appl module ufl), 167
 transpose() (in module ufl.operators), 145
 Transposed (class in ufl.tensoralgebra), 149
 Transposed() (ufl.algorithms.apply_algebra_lowering.LowerCompoundAlgebra method), 48
 transpose() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 TrialFunction (in module ufl), 165
 TrialFunctionGrad (in module ufl.argument), 81
 TrialFunction() (in module ufl.classes), 113
 TrialFunctions() (in module ufl), 165
 TrialFunctions() (in module ufl.argument), 81
 TrialFunctions() (in module ufl.classes), 113

U

ufl (module), 151
 ufl.algebra (module), 80
 ufl.algorithms (module), 69
 ufl.algorithms.ad (module), 46
 ufl.algorithms.analysis (module), 46
 ufl.algorithms.apply_algebra_lowering (module), 47
 ufl.algorithms.apply_derivatives (module), 48
 ufl.algorithms.apply_function_pullbacks (module), 52
 ufl.algorithms.apply_geometry_lowering (module), 52
 ufl.algorithms.apply_integral_scaling (module), 53
 ufl.algorithms.apply_restrictions (module), 53
 ufl.algorithms.change_to_reference (module), 55
 ufl.algorithms.check_arities (module), 56
 ufl.algorithms.check_restrictions (module), 57
 ufl.algorithms.checks (module), 57
 ufl.algorithms.compute_form_data (module), 58
 ufl.algorithms.domain_analysis (module), 58
 ufl.algorithms.elementtransformations (module), 59
 ufl.algorithms.estimate_degrees (module), 59
 ufl.algorithms.expand_compounds (module), 62
 ufl.algorithms.expand_indices (module), 62
 ufl.algorithms.formdata (module), 63
 ufl.algorithms.formfiles (module), 63
 ufl.algorithms.formsplitter (module), 64

ufl.algorithms.formtransformations (module), 64
 ufl.algorithms.map_integrands (module), 66
 ufl.algorithms.multifunction (module), 66
 ufl.algorithms.renumbering (module), 66
 ufl.algorithms.replace (module), 67
 ufl.algorithms.signature (module), 67
 ufl.algorithms.transformer (module), 68
 ufl.algorithms.traversal (module), 69
 ufl.argument (module), 81
 ufl.assertions (module), 82
 ufl.averaging (module), 82
 ufl.cell (module), 82
 ufl.checks (module), 84
 ufl.classes (module), 84
 ufl.coefficient (module), 115
 ufl.compound_expressions (module), 116
 ufl.conditional (module), 117
 ufl.constantvalue (module), 119
 ufl.differentiation (module), 120
 ufl.domain (module), 122
 ufl.equation (module), 123
 ufl.exprcontainers (module), 123
 ufl.exprequals (module), 124
 ufl.exproperators (module), 124
 ufl.finiteelement (module), 80
 ufl.finiteelement.brokenelement (module), 73
 ufl.finiteelement.elementlist (module), 73
 ufl.finiteelement.enrichedelement (module), 74
 ufl.finiteelement.facetelement (module), 75
 ufl.finiteelement.finiteelement (module), 75
 ufl.finiteelement.finiteelementbase (module), 75
 ufl.finiteelement.hdivcurl (module), 76
 ufl.finiteelement.interiorelement (module), 77
 ufl.finiteelement.mixedelement (module), 77
 ufl.finiteelement.restrictedelement (module), 78
 ufl.finiteelement.tensorproductelement (module), 79
 ufl.form (module), 124
 ufl.formoperators (module), 125
 ufl.functionspace (module), 127
 ufl.geometry (module), 128
 ufl.index_combination_utils (module), 135
 ufl.indexed (module), 135
 ufl.indexsum (module), 136
 ufl.integral (module), 136
 ufl.log (module), 137
 ufl.mathfunctions (module), 138
 ufl.measure (module), 139
 ufl.objects (module), 141
 ufl.operators (module), 141
 ufl.permutation (module), 145
 ufl.precedence (module), 146
 ufl.protocols (module), 146
 ufl.referencevalue (module), 146
 ufl.restriction (module), 146
 ufl.sobolevspace (module), 147
 ufl.sorting (module), 147
 ufl.split_functions (module), 147
 ufl.tensoralgebra (module), 147
 ufl.tensors (module), 149
 ufl.variable (module), 151
 ufl2latex() (in module ufl.algorithms), 72
 ufl2ufl() (in module ufl.algorithms.transformer), 69
 ufl2uflcopy() (in module ufl.algorithms.transformer), 69
 ufl_assert() (in module ufl.assertions), 82
 ufl_cargo() (ufl.classes.Mesh method), 111
 ufl_cargo() (ufl.domain.Mesh method), 122
 ufl_cargo() (ufl.Mesh method), 157
 ufl_cell() (ufl.classes.Form method), 115
 ufl_cell() (ufl.classes.Mesh method), 111
 ufl_cell() (ufl.classes.MeshView method), 111
 ufl_cell() (ufl.classes.TensorProductMesh method), 112
 ufl_cell() (ufl.domain.Mesh method), 122
 ufl_cell() (ufl.domain.MeshView method), 122
 ufl_cell() (ufl.domain.TensorProductMesh method), 122
 ufl_cell() (ufl.Form method), 172
 ufl_cell() (ufl.form.Form method), 125
 ufl_cell() (ufl.Mesh method), 157
 ufl_cell() (ufl.MeshView method), 157
 ufl_cell() (ufl.TensorProductMesh method), 157
 ufl_coordinate_element() (ufl.classes.Mesh method), 111
 ufl_coordinate_element()
 (ufl.classes.TensorProductMesh method),
 112
 ufl_coordinate_element() (ufl.domain.Mesh method), 122
 ufl_coordinate_element()
 (ufl.domain.TensorProductMesh method),
 122
 ufl_coordinate_element() (ufl.Mesh method), 157
 ufl_coordinate_element()
 (ufl.TensorProductMesh method), 157
 ufl_disable_profiling() (ufl.classes.Expr static method),
 85
 ufl_domain() (ufl.Argument method), 165
 ufl_domain() (ufl.argument.Argument method), 81
 ufl_domain() (ufl.classes.Argument method), 95
 ufl_domain() (ufl.classes.Coefficient method), 95
 ufl_domain() (ufl.classes.Expr method), 85
 ufl_domain() (ufl.classes.Form method), 115
 ufl_domain() (ufl.classes.FunctionSpace method), 112
 ufl_domain() (ufl.classes.Integral method), 114
 ufl_domain() (ufl.classes.Measure method), 113
 ufl_domain() (ufl.classes.MixedFunctionSpace method),
 112
 ufl_domain() (ufl.Coefficient method), 165
 ufl_domain() (ufl.coefficient.Coefficient method), 115
 ufl_domain() (ufl.Form method), 172
 ufl_domain() (ufl.form.Form method), 125
 ufl_domain() (ufl.FunctionSpace method), 164

ufl_domain() (ufl.functionspace.FunctionSpace method), 127
ufl_domain() (ufl.functionspace.MixedFunctionSpace method), 128
ufl_domain() (ufl.integral.Integral method), 172
ufl_domain() (ufl.integral.Integral method), 136
ufl_domain() (ufl.Measure method), 173
ufl_domain() (ufl.measure.Measure method), 140
ufl_domains() (ufl.Argument method), 165
ufl_domains() (ufl.argument.Argument method), 81
ufl_domains() (ufl.classes.Argument method), 95
ufl_domains() (ufl.classes.Coefficient method), 95
ufl_domains() (ufl.classes.ConstantValue method), 93
ufl_domains() (ufl.classes.Expr method), 85
ufl_domains() (ufl.classes.ExprMapping method), 100
ufl_domains() (ufl.classes.Form method), 115
ufl_domains() (ufl.classes.FunctionSpace method), 112
ufl_domains() (ufl.classes.GeometricQuantity method), 86
ufl_domains() (ufl.classes.Label method), 96
ufl_domains() (ufl.classes.MixedFunctionSpace method), 112
ufl_domains() (ufl.classes.MultiIndex method), 93
ufl_domains() (ufl.classes.Terminal method), 85
ufl_domains() (ufl.classes.Variable method), 96
ufl_domains() (ufl.Coefficient method), 165
ufl_domains() (ufl.coefficient.Coefficient method), 116
ufl_domains() (ufl.constantvalue.ConstantValue method), 119
ufl_domains() (ufl.exprcontainers.ExprMapping method), 123
ufl_domains() (ufl.Form method), 172
ufl_domains() (ufl.form.Form method), 125
ufl_domains() (ufl.FunctionSpace method), 164
ufl_domains() (ufl.functionspace.FunctionSpace method), 127
ufl_domains() (ufl.functionspace.MixedFunctionSpace method), 128
ufl_domains() (ufl.geometry.GeometricQuantity method), 132
ufl_domains() (ufl.variable.Label method), 151
ufl_domains() (ufl.variable.Variable method), 151
ufl_element() (ufl.Argument method), 165
ufl_element() (ufl.argument.Argument method), 81
ufl_element() (ufl.classes.Argument method), 95
ufl_element() (ufl.classes.Coefficient method), 95
ufl_element() (ufl.classes.FunctionSpace method), 112
ufl_element() (ufl.classes.MixedFunctionSpace method), 112
ufl_element() (ufl.Coefficient method), 165
ufl_element() (ufl.coefficient.Coefficient method), 116
ufl_element() (ufl.FunctionSpace method), 164
ufl_element() (ufl.functionspace.FunctionSpace method), 128
ufl_element() (ufl.functionspace.MixedFunctionSpace method), 128
ufl_enable_profiling() (ufl.classes.Expr static method), 85
ufl_free_indices (ufl.algebra.Abs attribute), 80
ufl_free_indices (ufl.algebra.Division attribute), 80
ufl_free_indices (ufl.algebra.Power attribute), 80
ufl_free_indices (ufl.algebra.Product attribute), 80
ufl_free_indices (ufl.algebra.Sum attribute), 81
ufl_free_indices (ufl.averaging.CellAvg attribute), 82
ufl_free_indices (ufl.averaging.FacetAvg attribute), 82
ufl_free_indices (ufl.classes.Abs attribute), 97
ufl_free_indices (ufl.classes.Atan2 attribute), 104
ufl_free_indices (ufl.classes.BesselFunction attribute), 104
ufl_free_indices (ufl.classes.CellAvg attribute), 104
ufl_free_indices (ufl.classes.CoefficientDerivative attribute), 100
ufl_free_indices (ufl.classes.Cofactor attribute), 98
ufl_free_indices (ufl.classes.ComponentTensor attribute), 95
ufl_free_indices (ufl.classes.Condition attribute), 101
ufl_free_indices (ufl.classes.Conditional attribute), 102
ufl_free_indices (ufl.classes.Cross attribute), 98
ufl_free_indices (ufl.classes.Curl attribute), 101
ufl_free_indices (ufl.classes.Determinant attribute), 98
ufl_free_indices (ufl.classes.Deviatoric attribute), 98
ufl_free_indices (ufl.classes.Div attribute), 101
ufl_free_indices (ufl.classes.Division attribute), 97
ufl_free_indices (ufl.classes.Dot attribute), 98
ufl_free_indices (ufl.classes.ExprList attribute), 99
ufl_free_indices (ufl.classes.ExprMapping attribute), 100
ufl_free_indices (ufl.classes.FacetAvg attribute), 105
ufl_free_indices (ufl.classes.Grad attribute), 100
ufl_free_indices (ufl.classes.Indexed attribute), 94
ufl_free_indices (ufl.classes.IndexSum attribute), 99
ufl_free_indices (ufl.classes.Inner attribute), 97
ufl_free_indices (ufl.classes.Inverse attribute), 98
ufl_free_indices (ufl.classes.Label attribute), 96
ufl_free_indices (ufl.classes.ListTensor attribute), 94
ufl_free_indices (ufl.classes.MathFunction attribute), 103
ufl_free_indices (ufl.classes.MaxValue attribute), 103
ufl_free_indices (ufl.classes.MinValue attribute), 103
ufl_free_indices (ufl.classes.MultiIndex attribute), 93
ufl_free_indices (ufl.classes.NablaDiv attribute), 101
ufl_free_indices (ufl.classes.NablaGrad attribute), 101
ufl_free_indices (ufl.classes.Outer attribute), 97
ufl_free_indices (ufl.classes.Power attribute), 97
ufl_free_indices (ufl.classes.Product attribute), 96
ufl_free_indices (ufl.classes.ReferenceCurl attribute), 101
ufl_free_indices (ufl.classes.ReferenceDiv attribute), 101
ufl_free_indices (ufl.classes.ReferenceGrad attribute), 100
ufl_free_indices (ufl.classes.ReferenceValue attribute), 105

ufl_free_indices (ufl.classes.Restricted attribute), 99
 ufl_free_indices (ufl.classes.ScalarValue attribute), 93
 ufl_free_indices (ufl.classes.Skew attribute), 98
 ufl_free_indices (ufl.classes.Sum attribute), 96
 ufl_free_indices (ufl.classes.Sym attribute), 99
 ufl_free_indices (ufl.classes.Terminal attribute), 85
 ufl_free_indices (ufl.classes.Trace attribute), 98
 ufl_free_indices (ufl.classes.Transposed attribute), 97
 ufl_free_indices (ufl.classes.Variable attribute), 96
 ufl_free_indices (ufl.classes.VariableDerivative attribute), 100
 ufl_free_indices (ufl.classes.Zero attribute), 93
 ufl_free_indices (ufl.conditional.Condition attribute), 117
 ufl_free_indices (ufl.conditional.Conditional attribute), 117
 ufl_free_indices (ufl.conditional.MaxValue attribute), 118
 ufl_free_indices (ufl.conditional.MinValue attribute), 118
 ufl_free_indices (ufl.constantvalue.ScalarValue attribute), 119
 ufl_free_indices (ufl.constantvalue.Zero attribute), 120
 ufl_free_indices (ufl.differentiation.CoefficientDerivative attribute), 120
 ufl_free_indices (ufl.differentiation.Curl attribute), 120
 ufl_free_indices (ufl.differentiation.Div attribute), 120
 ufl_free_indices (ufl.differentiation.Grad attribute), 121
 ufl_free_indices (ufl.differentiation.NablaDiv attribute), 121
 ufl_free_indices (ufl.differentiation.NablaGrad attribute), 121
 ufl_free_indices (ufl.differentiation.ReferenceCurl attribute), 121
 ufl_free_indices (ufl.differentiation.ReferenceDiv attribute), 121
 ufl_free_indices (ufl.differentiation.ReferenceGrad attribute), 121
 ufl_free_indices (ufl.differentiation.VariableDerivative attribute), 121
 ufl_free_indices (ufl.exprcontainers.ExprList attribute), 123
 ufl_free_indices (ufl.exprcontainers.ExprMapping attribute), 124
 ufl_free_indices (ufl.indexed.Indexed attribute), 136
 ufl_free_indices (ufl.indexsum.IndexSum attribute), 136
 ufl_free_indices (ufl.mathfunctions.Atan2 attribute), 138
 ufl_free_indices (ufl.mathfunctions.BesselFunction attribute), 138
 ufl_free_indices (ufl.mathfunctions.MathFunction attribute), 139
 ufl_free_indices (ufl.referencevalue.ReferenceValue attribute), 146
 ufl_free_indices (ufl.restriction.Restricted attribute), 147
 ufl_free_indices (ufl.tensoralgebra.Cofactor attribute), 147
 ufl_free_indices (ufl.tensoralgebra.Cross attribute), 148
 ufl_free_indices (ufl.tensoralgebra.Determinant attribute), 148
 ufl_free_indices (ufl.tensoralgebra.Deviatoric attribute), 148
 ufl_free_indices (ufl.tensoralgebra.Dot attribute), 148
 ufl_free_indices (ufl.tensoralgebra.Inner attribute), 148
 ufl_free_indices (ufl.tensoralgebra.Inverse attribute), 148
 ufl_free_indices (ufl.tensoralgebra.Outer attribute), 148
 ufl_free_indices (ufl.tensoralgebra.Skew attribute), 148
 ufl_free_indices (ufl.tensoralgebra.Sym attribute), 149
 ufl_free_indices (ufl.tensoralgebra.Trace attribute), 149
 ufl_free_indices (ufl.tensoralgebra.Transposed attribute), 149
 ufl_free_indices (ufl.tensors.ComponentTensor attribute), 149
 ufl_free_indices (ufl.tensors.ListTensor attribute), 149
 ufl_free_indices (ufl.variable.Label attribute), 151
 ufl_free_indices (ufl.variable.Variable attribute), 151
 ufl_function_space() (ufl.Argument method), 165
 ufl_function_space() (ufl.argument.Argument method), 81
 ufl_function_space() (ufl.classes.Argument method), 95
 ufl_function_space() (ufl.classes.Coefficient method), 95
 ufl_function_space() (ufl.Coefficient method), 165
 ufl_function_space() (ufl.coefficient.Coefficient method), 116
 ufl_id() (ufl.classes.Mesh method), 111
 ufl_id() (ufl.classes.MeshView method), 111
 ufl_id() (ufl.classes.TensorProductMesh method), 112
 ufl_id() (ufl.domain.Mesh method), 122
 ufl_id() (ufl.domain.MeshView method), 122
 ufl_id() (ufl.domain.TensorProductMesh method), 122
 ufl_id() (ufl.Mesh method), 157
 ufl_id() (ufl.MeshView method), 157
 ufl_id() (ufl.TensorProductMesh method), 157
 ufl_index_dimensions (ufl.algebra.Abs attribute), 80
 ufl_index_dimensions (ufl.algebra.Division attribute), 80
 ufl_index_dimensions (ufl.algebra.Power attribute), 80
 ufl_index_dimensions (ufl.algebra.Product attribute), 80
 ufl_index_dimensions (ufl.algebra.Sum attribute), 81
 ufl_index_dimensions (ufl.averaging.CellAvg attribute), 82
 ufl_index_dimensions (ufl.averaging.FacetAvg attribute), 82
 ufl_index_dimensions (ufl.classes.Abs attribute), 97
 ufl_index_dimensions (ufl.classes.Atan2 attribute), 104
 ufl_index_dimensions (ufl.classes.BesselFunction attribute), 104
 ufl_index_dimensions (ufl.classes.CellAvg attribute), 104
 ufl_index_dimensions (ufl.classes.CoefficientDerivative attribute), 100
 ufl_index_dimensions (ufl.classes.Cofactor attribute), 98
 ufl_index_dimensions (ufl.classes.ComponentTensor attribute), 95

ufl_index_dimensions (ufl.classes.Condition attribute), 101
ufl_index_dimensions (ufl.classes.Conditional attribute), 102
ufl_index_dimensions (ufl.classes.Cross attribute), 98
ufl_index_dimensions (ufl.classes.Curl attribute), 101
ufl_index_dimensions (ufl.classes.Determinant attribute), 98
ufl_index_dimensions (ufl.classes.Deviatoric attribute), 98
ufl_index_dimensions (ufl.classes.Div attribute), 101
ufl_index_dimensions (ufl.classes.Division attribute), 97
ufl_index_dimensions (ufl.classes.Dot attribute), 98
ufl_index_dimensions (ufl.classes.ExprList attribute), 99
ufl_index_dimensions (ufl.classes.ExprMapping attribute), 100
ufl_index_dimensions (ufl.classes.FacetAvg attribute), 105
ufl_index_dimensions (ufl.classes.Grad attribute), 100
ufl_index_dimensions (ufl.classes.Indexed attribute), 94
ufl_index_dimensions (ufl.classes.IndexSum attribute), 99
ufl_index_dimensions (ufl.classes.Inner attribute), 97
ufl_index_dimensions (ufl.classes.Inverse attribute), 98
ufl_index_dimensions (ufl.classes.Label attribute), 96
ufl_index_dimensions (ufl.classes.ListTensor attribute), 94
ufl_index_dimensions (ufl.classes.MathFunction attribute), 103
ufl_index_dimensions (ufl.classes.MaxValue attribute), 103
ufl_index_dimensions (ufl.classes.MinValue attribute), 103
ufl_index_dimensions (ufl.classes.MultiIndex attribute), 93
ufl_index_dimensions (ufl.classes.NablaDiv attribute), 101
ufl_index_dimensions (ufl.classes.NablaGrad attribute), 101
ufl_index_dimensions (ufl.classes.Outer attribute), 97
ufl_index_dimensions (ufl.classes.Power attribute), 97
ufl_index_dimensions (ufl.classes.Product attribute), 97
ufl_index_dimensions (ufl.classes.ReferenceCurl attribute), 101
ufl_index_dimensions (ufl.classes.ReferenceDiv attribute), 101
ufl_index_dimensions (ufl.classes.ReferenceGrad attribute), 100
ufl_index_dimensions (ufl.classes.ReferenceValue attribute), 105
ufl_index_dimensions (ufl.classes.Restricted attribute), 99
ufl_index_dimensions (ufl.classes.ScalarValue attribute), 93
ufl_index_dimensions (ufl.classes.Skew attribute), 99
ufl_index_dimensions (ufl.classes.Sum attribute), 96
ufl_index_dimensions (ufl.classes.Sym attribute), 99
ufl_index_dimensions (ufl.classes.Terminal attribute), 85
ufl_index_dimensions (ufl.classes.Trace attribute), 98
ufl_index_dimensions (ufl.classes.Transposed attribute), 97
ufl_index_dimensions (ufl.classes.Variable attribute), 96
ufl_index_dimensions (ufl.classes.VariableDerivative attribute), 100
ufl_index_dimensions (ufl.classes.Zero attribute), 93
ufl_index_dimensions (ufl.conditional.Condition attribute), 117
ufl_index_dimensions (ufl.conditional.Conditional attribute), 117
ufl_index_dimensions (ufl.conditional.MaxValue attribute), 118
ufl_index_dimensions (ufl.conditional.MinValue attribute), 118
ufl_index_dimensions (ufl.constantvalue.ScalarValue attribute), 119
ufl_index_dimensions (ufl.constantvalue.Zero attribute), 120
ufl_index_dimensions (ufl.differentiation.CoefficientDerivative attribute), 120
ufl_index_dimensions (ufl.differentiation.Curl attribute), 120
ufl_index_dimensions (ufl.differentiation.Div attribute), 120
ufl_index_dimensions (ufl.differentiation.Grad attribute), 121
ufl_index_dimensions (ufl.differentiation.NablaDiv attribute), 121
ufl_index_dimensions (ufl.differentiation.NablaGrad attribute), 121
ufl_index_dimensions (ufl.differentiation.ReferenceCurl attribute), 121
ufl_index_dimensions (ufl.differentiation.ReferenceDiv attribute), 121
ufl_index_dimensions (ufl.differentiation.ReferenceGrad attribute), 121
ufl_index_dimensions (ufl.differentiation.VariableDerivative attribute), 121
ufl_index_dimensions (ufl.exprcontainers.ExprList attribute), 123
ufl_index_dimensions (ufl.exprcontainers.ExprMapping attribute), 124
ufl_index_dimensions (ufl.indexed.Indexed attribute), 136
ufl_index_dimensions (ufl.indexsum.IndexSum attribute), 136
ufl_index_dimensions (ufl.mathfunctions.Atan2 attribute), 138
ufl_index_dimensions (ufl.mathfunctions.BesselFunction

attribute), 138
`ufl_index_dimensions` (`ufl.mathfunctions.MathFunction` attribute), 139
`ufl_index_dimensions` (`ufl.referencevalue.ReferenceValue` attribute), 146
`ufl_index_dimensions` (`ufl.restriction.Restricted` attribute), 147
`ufl_index_dimensions` (`ufl.tensoralgebra.Cofactor` attribute), 147
`ufl_index_dimensions` (`ufl.tensoralgebra.Cross` attribute), 148
`ufl_index_dimensions` (`ufl.tensoralgebra.Determinant` attribute), 148
`ufl_index_dimensions` (`ufl.tensoralgebra.Deviatoric` attribute), 148
`ufl_index_dimensions` (`ufl.tensoralgebra.Dot` attribute), 148
`ufl_index_dimensions` (`ufl.tensoralgebra.Inner` attribute), 148
`ufl_index_dimensions` (`ufl.tensoralgebra.Inverse` attribute), 148
`ufl_index_dimensions` (`ufl.tensoralgebra.Outer` attribute), 148
`ufl_index_dimensions` (`ufl.tensoralgebra.Skew` attribute), 148
`ufl_index_dimensions` (`ufl.tensoralgebra.Sym` attribute), 149
`ufl_index_dimensions` (`ufl.tensoralgebra.Trace` attribute), 149
`ufl_index_dimensions` (`ufl.tensoralgebra.Transposed` attribute), 149
`ufl_index_dimensions` (`ufl.tensors.ComponentTensor` attribute), 149
`ufl_index_dimensions` (`ufl.tensors.ListTensor` attribute), 149
`ufl_index_dimensions` (`ufl.variable.Label` attribute), 151
`ufl_index_dimensions` (`ufl.variable.Variable` attribute), 151
`ufl_mesh()` (`ufl.classes.MeshView` method), 111
`ufl_mesh()` (`ufl.domain.MeshView` method), 122
`ufl_mesh()` (`ufl.MeshView` method), 157
`ufl_operands` (`ufl.classes.Operator` attribute), 92
`ufl_operands` (`ufl.classes.Terminal` attribute), 85
`ufl_shape` (`ufl.algebra.Abs` attribute), 80
`ufl_shape` (`ufl.algebra.Division` attribute), 80
`ufl_shape` (`ufl.algebra.Power` attribute), 80
`ufl_shape` (`ufl.algebra.Product` attribute), 81
`ufl_shape` (`ufl.algebra.Sum` attribute), 81
`ufl_shape` (`ufl.Argument` attribute), 165
`ufl_shape` (`ufl.argument.Argument` attribute), 81
`ufl_shape` (`ufl.averaging.CellAvg` attribute), 82
`ufl_shape` (`ufl.averaging.FacetAvg` attribute), 82
`ufl_shape` (`ufl.CellNormal` attribute), 158
`ufl_shape` (`ufl.classes.Abs` attribute), 97
`ufl_shape` (`ufl.classes.Argument` attribute), 95
`ufl_shape` (`ufl.classes.Atan2` attribute), 104
`ufl_shape` (`ufl.classes.BesselFunction` attribute), 104
`ufl_shape` (`ufl.classes.CellAvg` attribute), 105
`ufl_shape` (`ufl.classes.CellCoordinate` attribute), 86
`ufl_shape` (`ufl.classes.CellEdgeVectors` attribute), 89
`ufl_shape` (`ufl.classes.CellFacetJacobian` attribute), 88
`ufl_shape` (`ufl.classes.CellFacetJacobianInverse` attribute), 90
`ufl_shape` (`ufl.classes.CellFacetOrigin` attribute), 87
`ufl_shape` (`ufl.classes.CellNormal` attribute), 91
`ufl_shape` (`ufl.classes.CellOrigin` attribute), 87
`ufl_shape` (`ufl.classes.CellVertices` attribute), 89
`ufl_shape` (`ufl.classes.Coefficient` attribute), 95
`ufl_shape` (`ufl.classes.CoefficientDerivative` attribute), 100
`ufl_shape` (`ufl.classes.Cofactor` attribute), 98
`ufl_shape` (`ufl.classes.ComponentTensor` attribute), 95
`ufl_shape` (`ufl.classes.Condition` attribute), 101
`ufl_shape` (`ufl.classes.Conditional` attribute), 102
`ufl_shape` (`ufl.classes.Cross` attribute), 98
`ufl_shape` (`ufl.classes.Curl` attribute), 101
`ufl_shape` (`ufl.classes.Determinant` attribute), 98
`ufl_shape` (`ufl.classes.Deviatoric` attribute), 98
`ufl_shape` (`ufl.classes.Div` attribute), 101
`ufl_shape` (`ufl.classes.Division` attribute), 97
`ufl_shape` (`ufl.classes.Dot` attribute), 98
`ufl_shape` (`ufl.classes.ExprList` attribute), 99
`ufl_shape` (`ufl.classes.ExprMapping` attribute), 100
`ufl_shape` (`ufl.classes.FacetAvg` attribute), 105
`ufl_shape` (`ufl.classes.FacetCoordinate` attribute), 87
`ufl_shape` (`ufl.classes.FacetEdgeVectors` attribute), 89
`ufl_shape` (`ufl.classes.FacetJacobian` attribute), 88
`ufl_shape` (`ufl.classes.FacetJacobianInverse` attribute), 90
`ufl_shape` (`ufl.classes.FacetNormal` attribute), 91
`ufl_shape` (`ufl.classes.FacetOrigin` attribute), 87
`ufl_shape` (`ufl.classes.GeometricQuantity` attribute), 86
`ufl_shape` (`ufl.classes.Grad` attribute), 100
`ufl_shape` (`ufl.classes.Identity` attribute), 94
`ufl_shape` (`ufl.classes.Indexed` attribute), 94
`ufl_shape` (`ufl.classes.IndexSum` attribute), 99
`ufl_shape` (`ufl.classes.Inner` attribute), 98
`ufl_shape` (`ufl.classes.Inverse` attribute), 98
`ufl_shape` (`ufl.classes.Jacobian` attribute), 87
`ufl_shape` (`ufl.classes.JacobianInverse` attribute), 90
`ufl_shape` (`ufl.classes.Label` attribute), 96
`ufl_shape` (`ufl.classes.ListTensor` attribute), 94
`ufl_shape` (`ufl.classes.MathFunction` attribute), 103
`ufl_shape` (`ufl.classes.MaxValue` attribute), 103
`ufl_shape` (`ufl.classes.MinValue` attribute), 103
`ufl_shape` (`ufl.classes.MultiIndex` attribute), 93
`ufl_shape` (`ufl.classes.NablaDiv` attribute), 101
`ufl_shape` (`ufl.classes.NablaGrad` attribute), 101
`ufl_shape` (`ufl.classes.Outer` attribute), 97

ufl_shape (ufl.classes.PermutationSymbol attribute), 94
ufl_shape (ufl.classes.Power attribute), 97
ufl_shape (ufl.classes.Product attribute), 97
ufl_shape (ufl.classes.ReferenceCellEdgeVectors attribute), 88
ufl_shape (ufl.classes.ReferenceCurl attribute), 101
ufl_shape (ufl.classes.ReferenceDiv attribute), 101
ufl_shape (ufl.classes.ReferenceFacetEdgeVectors attribute), 88
ufl_shape (ufl.classes.ReferenceGrad attribute), 101
ufl_shape (ufl.classes.ReferenceNormal attribute), 91
ufl_shape (ufl.classes.ReferenceValue attribute), 105
ufl_shape (ufl.classes.Restricted attribute), 99
ufl_shape (ufl.classes.ScalarValue attribute), 93
ufl_shape (ufl.classes.Skew attribute), 99
ufl_shape (ufl.classes.SpatialCoordinate attribute), 86
ufl_shape (ufl.classes.Sum attribute), 96
ufl_shape (ufl.classes.Sym attribute), 99
ufl_shape (ufl.classes.Trace attribute), 98
ufl_shape (ufl.classes.Transposed attribute), 97
ufl_shape (ufl.classes.Variable attribute), 96
ufl_shape (ufl.classes.VariableDerivative attribute), 100
ufl_shape (ufl.classes.Zero attribute), 93
ufl_shape (ufl.Coefficient attribute), 165
ufl_shape (ufl.coefficient.Coefficient attribute), 116
ufl_shape (ufl.conditional.Condition attribute), 117
ufl_shape (ufl.conditional.Conditional attribute), 117
ufl_shape (ufl.conditional.MaxValue attribute), 118
ufl_shape (ufl.conditional.MinValue attribute), 118
ufl_shape (ufl.constantvalue.Identity attribute), 119
ufl_shape (ufl.constantvalue.PermutationSymbol attribute), 119
ufl_shape (ufl.constantvalue.ScalarValue attribute), 119
ufl_shape (ufl.constantvalue.Zero attribute), 120
ufl_shape (ufl.differentiation.CoefficientDerivative attribute), 120
ufl_shape (ufl.differentiation.Curl attribute), 120
ufl_shape (ufl.differentiation.Div attribute), 120
ufl_shape (ufl.differentiation.Grad attribute), 121
ufl_shape (ufl.differentiation.NablaDiv attribute), 121
ufl_shape (ufl.differentiation.NablaGrad attribute), 121
ufl_shape (ufl.differentiation.ReferenceCurl attribute), 121
ufl_shape (ufl.differentiation.ReferenceDiv attribute), 121
ufl_shape (ufl.differentiation.ReferenceGrad attribute), 121
ufl_shape (ufl.differentiation.VariableDerivative attribute), 121
ufl_shape (ufl.exprcontainers.ExprList attribute), 123
ufl_shape (ufl.exprcontainers.ExprMapping attribute), 124
ufl_shape (ufl.FacetNormal attribute), 158
ufl_shape (ufl.geometry.CellCoordinate attribute), 128
ufl_shape (ufl.geometry.CellEdgeVectors attribute), 129
ufl_shape (ufl.geometry.CellFacetJacobian attribute), 129
ufl_shape (ufl.geometry.CellFacetJacobianInverse attribute), 129
ufl_shape (ufl.geometry.CellFacetOrigin attribute), 129
ufl_shape (ufl.geometry.CellNormal attribute), 130
ufl_shape (ufl.geometry.CellOrigin attribute), 130
ufl_shape (ufl.geometry.CellVertices attribute), 130
ufl_shape (ufl.geometry.FacetCoordinate attribute), 131
ufl_shape (ufl.geometry.FacetEdgeVectors attribute), 131
ufl_shape (ufl.geometry.FacetJacobian attribute), 131
ufl_shape (ufl.geometry.FacetJacobianInverse attribute), 132
ufl_shape (ufl.geometry.FacetNormal attribute), 132
ufl_shape (ufl.geometry.FacetOrigin attribute), 132
ufl_shape (ufl.geometry.GeometricQuantity attribute), 132
ufl_shape (ufl.geometry.Jacobian attribute), 133
ufl_shape (ufl.geometry.JacobianInverse attribute), 133
ufl_shape (ufl.geometry.ReferenceCellEdgeVectors attribute), 134
ufl_shape (ufl.geometry.ReferenceFacetEdgeVectors attribute), 134
ufl_shape (ufl.geometry.ReferenceNormal attribute), 135
ufl_shape (ufl.geometry.SpatialCoordinate attribute), 135
ufl_shape (ufl.Identity attribute), 166
ufl_shape (ufl.indexed.Indexed attribute), 136
ufl_shape (ufl.indexsum.IndexSum attribute), 136
ufl_shape (ufl.Jacobian attribute), 159
ufl_shape (ufl.JacobianInverse attribute), 159
ufl_shape (ufl.mathfunctions.Atan2 attribute), 138
ufl_shape (ufl.mathfunctions.BesselFunction attribute), 138
ufl_shape (ufl.mathfunctions.MathFunction attribute), 139
ufl_shape (ufl.PermutationSymbol attribute), 166
ufl_shape (ufl.referencevalue.ReferenceValue attribute), 146
ufl_shape (ufl.restriction.Restricted attribute), 147
ufl_shape (ufl.SpatialCoordinate attribute), 157
ufl_shape (ufl.tensoralgebra.Cofactor attribute), 147
ufl_shape (ufl.tensoralgebra.Cross attribute), 148
ufl_shape (ufl.tensoralgebra.Determinant attribute), 148
ufl_shape (ufl.tensoralgebra.Deviatoric attribute), 148
ufl_shape (ufl.tensoralgebra.Dot attribute), 148
ufl_shape (ufl.tensoralgebra.Inner attribute), 148
ufl_shape (ufl.tensoralgebra.Inverse attribute), 148
ufl_shape (ufl.tensoralgebra.Outer attribute), 148
ufl_shape (ufl.tensoralgebra.Skew attribute), 148
ufl_shape (ufl.tensoralgebra.Sym attribute), 149
ufl_shape (ufl.tensoralgebra.Trace attribute), 149
ufl_shape (ufl.tensoralgebra.Transposed attribute), 149
ufl_shape (ufl.tensors.ComponentTensor attribute), 149
ufl_shape (ufl.tensors.ListTensor attribute), 149
ufl_shape (ufl.variable.Label attribute), 151

ufl_shape (ufl.variable.Variable attribute), 151
 ufl_sub_spaces() (ufl.classes.AbstractFunctionSpace method), 112
 ufl_sub_spaces() (ufl.classes.FunctionSpace method), 112
 ufl_sub_spaces() (ufl.classes.MixedFunctionSpace method), 112
 ufl_sub_spaces() (ufl.classes.TensorProductFunctionSpace method), 112
 ufl_sub_spaces() (ufl.FunctionSpace method), 164
 ufl_sub_spaces() (ufl.functionspace.AbstractFunctionSpace method), 127
 ufl_sub_spaces() (ufl.functionspace.FunctionSpace method), 128
 ufl_sub_spaces() (ufl.functionspace.MixedFunctionSpace method), 128
 ufl_sub_spaces() (ufl.functionspace.TensorProductFunctionSpace method), 128
 UFLEException, 155
 undefined() (ufl.algorithms.MultiFunction method), 71
 undefined() (ufl.algorithms.Transformer method), 71
 undefined() (ufl.algorithms.transformer.Transformer method), 69
 unexpected() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 unique_sorted_indices() (in module ufl.index_combination_utils), 135
 unique_tuple() (in module ufl.algorithms.analysis), 47
 unit_indexed_tensor() (in module ufl.tensors), 150
 unit_list() (in module ufl.tensors), 150
 unit_list2() (in module ufl.tensors), 150
 unit_matrices() (in module ufl), 167
 unit_matrices() (in module ufl.tensors), 150
 unit_matrix() (in module ufl), 167
 unit_matrix() (in module ufl.tensors), 150
 unit_vector() (in module ufl), 167
 unit_vector() (in module ufl.tensors), 150
 unit_vectors() (in module ufl), 167
 unit_vectors() (in module ufl.tensors), 150
 unwrap_list_tensor() (in module ufl.tensors), 150

V

validate_form() (in module ufl.algorithms), 72
 validate_form() (in module ufl.algorithms.checks), 57
 value() (ufl.classes.ScalarValue method), 94
 value() (ufl.constantvalue.ScalarValue method), 119
 value_shape() (ufl.classes.FiniteElementBase method), 107
 value_shape() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 76
 value_shape() (ufl.FiniteElementBase method), 160
 value_size() (ufl.classes.FiniteElementBase method), 107
 value_size() (ufl.finiteelement.finiteelementbase.FiniteElementBase method), 76

W

warning() (ufl.log.Logger method), 138
 warning_blue() (ufl.log.Logger method), 138

value_size() (ufl.FiniteElementBase method), 160
 Variable (class in ufl.classes), 96
 Variable (class in ufl.variable), 151
 variable() (in module ufl), 169
 variable() (in module ufl.operators), 145
 variable() (ufl.algorithms.apply_derivatives.GenericDerivativeRuleset method), 50
 variable() (ufl.algorithms.apply_derivatives.VariableRuleset method), 51
 variable() (ufl.algorithms.apply_restrictions.RestrictionPropagator method), 55
 variable() (ufl.algorithms.check_arities.ArityChecker method), 57
 variable() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 variable() (ufl.algorithms.formtransformations.PartExtractor method), 65
 variable() (ufl.algorithms.renumbering.VariableRenumberingTransformer method), 67
 variable() (ufl.algorithms.ReuseTransformer method), 70
 variable() (ufl.algorithms.transformer.CopyTransformer method), 68
 variable() (ufl.algorithms.transformer.ReuseTransformer method), 68
 variable() (ufl.algorithms.transformer.VariableStripper method), 69
 variable_derivative() (ufl.algorithms.apply_derivatives.DerivativeRuleDispatcher method), 48
 variable_derivative() (ufl.algorithms.estimate_degrees.SumDegreeEstimator method), 62
 VariableDerivative (class in ufl.classes), 100
 VariableDerivative (class in ufl.differentiation), 121
 VariableRenumberingTransformer (class in ufl.algorithms.renumbering), 67
 VariableRuleset (class in ufl.algorithms.apply_derivatives), 51
 VariableStripper (class in ufl.algorithms.transformer), 69
 variant() (ufl.classes.FiniteElement method), 107
 variant() (ufl.FiniteElement method), 160
 variant() (ufl.finiteelement.finiteelement.FiniteElement method), 75
 VectorConstant() (in module ufl), 166
 VectorConstant() (in module ufl.coefficient), 116
 VectorElement (class in ufl), 161
 VectorElement (class in ufl.classes), 108
 VectorElement (class in ufl.finiteelement.mixedelement), 78
 visit() (ufl.algorithms.Transformer method), 71
 visitBase() (ufl.algorithms.transformer.Transformer method), 69

warning_green() (ufl.log.Logger method), [138](#)
warning_red() (ufl.log.Logger method), [138](#)

X

x (ufl.algorithms.domain_analysis.ExprTupleKey attribute), [58](#)
x_repr_latex_() (ufl.classes.Form method), [115](#)
x_repr_latex_() (ufl.Form method), [172](#)
x_repr_latex_() (ufl.form.Form method), [125](#)
x_repr_png_() (ufl.classes.Form method), [115](#)
x_repr_png_() (ufl.Form method), [172](#)
x_repr_png_() (ufl.form.Form method), [125](#)

Z

Zero (class in ufl.classes), [93](#)
Zero (class in ufl.constantvalue), [119](#)
zero() (in module ufl), [166](#)
zero() (in module ufl.constantvalue), [120](#)
zero() (ufl.algorithms.expand_indices.IndexExpander method), [63](#)
zero() (ufl.algorithms.renumbering.IndexRenumberingTransformer method), [67](#)
zero_expr() (in module ufl.algorithms.formtransformations), [66](#)
zero_lists() (in module ufl.formoperators), [127](#)